

Maximum Permissible Exposure

Equipment	:	Komfy Switch with Camera
Brand Name	:	D-LINK
Model No.	:	DKZ-201S
FCC ID	:	KA2KZ201SA1
Standard	:	ANSI/IEEE C95.1
Applicant	:	D-Link Co. Ltd
Manufacturer		No. 289, Sinhu 3rd Rd., Neihu District, Taipei City 114, Taiwan, R.O.C.

The product sample received on Jun. 30, 2015 and completely tested on Aug. 26, 2015. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI/IEEE C95.1 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Kevin Liang / Assistant Manager



Table of Contents

1	HUMAN EXPOSURE ASSESSMENT	4
1.1	Maximum Permissible Exposure	4

Revision History

[illegible]

1 Human Exposure Assessment

1.1 Maximum Permissible Exposure

1.1.1 Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30
Note 1: f = frequency in MHz ; *Plane-wave equivalent power density				
Note 2: For the applicable limit, see FCC 1.1310				

1.1.2 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

E = Electric field (V/m)

G = EUT Antenna numeric gain (numeric)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

P = RF output power (W)

d = Separation distance between radiator and human body (m)

1.1.3 Result of Maximum Permissible Exposure (2.4G)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	RF Output Power (dBm)
2400-2483.5	b	2412-2462	1-11 [11]	1	20.69
2400-2483.5	g	2412-2462	1-11 [11]	2	26.19
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	26.20
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	2	20.31

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.

Worst Maximum RF Output Power Result							
Exposure Environment		General Population / Uncontrolled Exposure					
Separation Distance (cm)		20					
Condition		RF Output Power (dBm)					
Modulation Mode	N _{TX}	Chain-Port 1	Chain-Port 2	Sum Chain	DG (dBi)	EIRP Power	PD (S) (mW/cm ²)
n (HT20)	2	23.68	22.64	26.20	1.50	27.70	0.11721
Maximum Permissible Exposure Limit (mW/cm ²)							1

Note 1: N_{TX} = Number of Transmit Chains

1.1.4 Result of Maximum Permissible Exposure (Bluetooth)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	RF Output Power (dBm)
2400-2483.5	v4.0 LE	2402-2480	0-39 [40]	1	3.22
Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.					

Worst Maximum RF Output Power Result				
Exposure Environment	General Population / Uncontrolled Exposure			
Separation Distance (cm)	20			
Condition	RF Output Power (dBm)			
Modulation Mode	RF Output Power	Antenna Gain (dBi)	EIRP Power	PD (S) (mW/cm ²)
v4.0 LE	3.22	2.27	5.49	0.00705
Maximum Permissible Exposure Limit (mW/cm ²)				1

1.1.5 Result of Maximum Permissible Exposure (5.2G)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	RF Output Power (dBm)
5150-5250	a	5180-5240	36-48 [4]	2	21.73
5150-5250	n (HT20)	5180-5240	36-48 [4]	2	22.14
5150-5250	n (HT40)	5190-5230	38-46 [2]	2	23.81
Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.					

Worst Maximum RF Output Power Result							
Exposure Environment		General Population / Uncontrolled Exposure					
Separation Distance (cm)		20					
Condition		RF Output Power (dBm)					
Modulation Mode	N _{TX}	Chain-Port 1	Chain-Port 2	Sum Chain	DG (dBi)	EIRP Power	PD (S) (mW/cm ²)
n (HT40)	2	20.79	20.81	23.81	2.08	25.89	0.07725
Maximum Permissible Exposure Limit (mW/cm ²)							1
Note 1: N _{TX} = Number of Transmit Chains							

1.1.6 Result of Maximum Permissible Exposure (5.8G)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	RF Output Power (dBm)
5725-5850	a	5745-5825	149-165 [5]	2	23.16
5725-5850	n (HT20)	5745-5825	149-165 [5]	2	23.28
5725-5850	n (HT40)	5755-5795	151-159 [2]	2	19.88
Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.					

Worst Maximum RF Output Power Result							
Exposure Environment		General Population / Uncontrolled Exposure					
Separation Distance (cm)		20					
Condition		RF Output Power (dBm)					
Modulation Mode	N _{TX}	Chain-Port 1	Chain-Port 2	Sum Chain	DG (dBi)	EIRP Power	PD (S) (mW/cm ²)
n (HT20)	2	20.37	20.18	23.28	2.40	25.68	0.07367
Maximum Permissible Exposure Limit (mW/cm ²)							1
Note 1: N _{TX} = Number of Transmit Chains							