

Project No.: TM-2303000028P
Report No.: TMWK2303000589KR

FCC ID: KA2M30A01

Page: 1 / 249
Rev.: 00

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C


Test Standard	FCC Part 15.247
Product name	AX3000 Dual-Band Wi-Fi 6 Router (Single pack), AX3000 Dual-Band Wi-Fi 6 Mesh System (multi-pack)
Brand Name	D-Link
Model No.	M30
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory)

Approved by:



Sehni Hu
Supervisor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: TMWK2303000589KR

Page: 2 / 249
Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	June 20, 2023	Initial Issue	ALL	Allison Chen

Table of contents

1.	GENERAL INFORMATION.....	4
1.1	EUT INFORMATION.....	4
1.2	EUT CHANNEL INFORMATION.....	5
1.3	ANTENNA INFORMATION.....	6
1.4	MEASUREMENT UNCERTAINTY	7
1.5	FACILITIES AND TEST LOCATION.....	8
1.6	INSTRUMENT CALIBRATION	8
1.7	SUPPORT AND EUT ACCESSORIES EQUIPMENT	10
1.8	TEST METHODOLOGY AND APPLIED STANDARDS.....	10
2.	TEST SUMMARY.....	11
3.	DESCRIPTION OF TEST MODES.....	12
3.1	THE WORST MODE OF OPERATING CONDITION	12
3.2	THE WORST MODE OF MEASUREMENT.....	13
3.3	EUT DUTY CYCLE	14
4.	TEST RESULT.....	16
4.1	AC POWER LINE CONDUCTED EMISSION.....	16
4.2	6DB BANDWIDTH AND OCCUPIED BANDWIDTH (99%).....	19
4.3	OUTPUT POWER MEASUREMENT	46
4.4	POWER SPECTRAL DENSITY	53
4.5	CONDUCTED BANDEDGE AND SPURIOUS EMISSION.....	77
4.6	RADIATION BANDEDGE AND SPURIOUS EMISSION.....	114
	APPENDIX 1 - PHOTOGRAPHS OF EUT	A-1

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	D-Link Corporation 14420 Myford Road Suite 100 Irvine California United States 92606
Manufacturer	D-Link Corporation 14420 Myford Road Suite 100 Irvine California United States 92606
Equipment	AX3000 Dual-Band Wi-Fi 6 Router (Single pack), AX3000 Dual-Band Wi-Fi 6 Mesh System (multi-pack)
Model Name	M30
Model Discrepancy	N/A
Brand Name	D-Link
Received Date	March 25, 2023
Date of Test	March 27 ~ May 18, 2023
Power Supply	Power from Power Adapter AMIGO / AMS159A-1201000FU I/P: 100-240Vac, 50/60Hz, 0.5A O/P: 12Vdc, 1.0A
HW Version	1.00
SW Version	A1

Remark:

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

1.2 EUT CHANNEL INFORMATION

Frequency Range	802.11b/g/n HT20 /ax (HE20): 2412 MHz ~ 2462 MHz 802.11n HT40/ax (HE40): 2422 MHz ~ 2452 MHz
Modulation Type	<ol style="list-style-type: none"> 1. IEEE 802.11b mode: DSSS 2. IEEE 802.11g mode: OFDM 3. IEEE 802.11n HT20 mode: OFDM 4. IEEE 802.11n HT40 mode: OFDM 5. IEEE 802.11ax (HE20) mode: OFDMA 6. IEEE 802.11ax (HE40) mode: OFDMA
Number of channels	<ol style="list-style-type: none"> 1. IEEE 802.11b mode: 11 Channels 2. IEEE 802.11g mode: 11 Channels 3. IEEE 802.11n HT20 mode: 11 Channels 4. IEEE 802.11n HT40 mode: 7 Channels 5. IEEE 802.11ax (HE20) mode: 11 Channels 6. IEEE 802.11ax (HE40) mode: 7 Channels

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
<input type="checkbox"/> 1 MHz or less	1	Middle
<input type="checkbox"/> 1 MHz to 10 MHz	2	1 near top and 1 near bottom
<input checked="" type="checkbox"/> More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Specification	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input checked="" type="checkbox"/> Short Dipole <input type="checkbox"/> Coils										
Antenna Gain	<table border="1"> <thead> <tr> <th>Frequency</th> <th>2G-1 (Chain 0) Gain (dBi)</th> <th>2G-2 (Chain 1) Gain (dBi)</th> <th>Total Gain (dBi)</th> </tr> </thead> <tbody> <tr> <td>2412-2462 MHz</td> <td>2.44</td> <td>1.94</td> <td>5.20</td> </tr> </tbody> </table>	Frequency	2G-1 (Chain 0) Gain (dBi)	2G-2 (Chain 1) Gain (dBi)	Total Gain (dBi)	2412-2462 MHz	2.44	1.94	5.20		
	Frequency	2G-1 (Chain 0) Gain (dBi)	2G-2 (Chain 1) Gain (dBi)	Total Gain (dBi)							
2412-2462 MHz	2.44	1.94	5.20								
Antenna Brand/Model	Chain 0: WIESON / ARY196-0030-014-00 Chain 1: WIESON / ARY196-0030-015-00										
Antenna connector	MHF compatible										

Notes:

1. The antenna(s) of the EUT are permanently attached and there are no provisions for connection to an external antenna. So the EUT complies with the requirements of §15.203.
2. Power Directional Gain = $10 \cdot \log \left\{ \left[10^{(Ant1/20)} + 10^{(Ant2/20)} + \dots + 10^{(Ant N /20)} \right]^2 / N \text{ ANT} \right\}$ dBi

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	± 2.213 dB
Channel Bandwidth	± 2.7 %
RF output power (Power Meter + Power sensor)	± 0.243 dB
Power Spectral density	± 2.739 dB
Conducted Bandedge	± 2.739 dB
Conducted Spurious Emission	± 2.742 dB
Radiated Emission_9kHz-30MHz	± 3.761 dB
Radiated Emission_30MHz-200MHz	± 3.473 dB
Radiated Emission_200MHz-1GHz	± 3.946 dB
Radiated Emission_1GHz-6GHz	± 4.797 dB
Radiated Emission_6GHz-18GHz	± 4.803 dB
Radiated Emission_18GHz-26GHz	± 3.459 dB
Radiated Emission_26GHz-40GHz	± 3.297 dB

Remark:

- 1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

No. 12, Ln. 116, Wugong 3rd Rd., Wugu Dist., New Taipei City, Taiwan 24803

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	Tony Chao	-
Radiation	Ray Li, Tony Chao	-
RF Conducted	David Li	-

Remark: The lab has been recognized as the FCC accredited lab. under the KDB 974614 D01 and is listed in the FCC pubic Access Link (PAL) database, FCC Registration No. :444940, the FCC Designation No.:TW1309.

1.6 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Cal Date	Cal Due
Power Sensor	Anritsu	MA2411B	1911386	2022-08-08	2023-08-07
Power Sensor	Anritsu	MA2411B	1911387	2022-08-08	2023-08-07
EXA Signal Analyzer	Keysight	N9010B	MY60242460	2023-02-02	2024-02-01
Power Meter	Anritsu	ML2496A	2136002	2022-11-24	2023-11-23
Software	Radio Test Software Ver. 21 & E3-Ver: 6.11-20180413				

Remark:

1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R. = No Calibration Required.

3M 966 Chamber Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Cal Date	Cal Due
Loop Antenna	SCHWARZBECK	FMZB 1513_60	1513_60_028	2022-12-27	2023-12-26
Preamplifier	EMEC	EM330	060609	2023-02-22	2024-02-21
Thermo-Hygro Meter	WISEWIND	1206	D07	2022-12-19	2023-12-18
PXA Signal Analyzer	Keysight Technologies	N9030B	MY62291089	2022-10-14	2023-10-13
Preamplifier	HP	8449B	3008A00965	2022-12-23	2023-12-22
Bi-Log Antenna	Sunol Sciences	JB3	A030105	2022-08-03	2023-08-02
Cable	Huber+Suhner	104PEA	20995+11112+182330	2023-02-22	2024-02-21
Coaxial Cable	EMCI	EMC105	190914+33953	2022-06-15	2023-06-14
Horn Antenna	ETC	MCTD 1209	DRH13M02003	2023-01-12	2024-01-11
High Pass Filters	Titan Microwave	T04H30001800070S01	22011402-4	2022-06-29	2023-06-28
Horn Antenna	SCHWARZBECK	BBHA9170	1047	2022-12-30	2023-12-29
Pre-Amplifier	EMCI	EMC184045SE	980860	2022-12-27	2023-12-26
Cable	EMCI	EMC101G	211010+211011+211012	2022-12-12	2023-12-11
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Software	e3 V9-210616c				

AC Conducted Emissions Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Cal Date	Cal Due
EMI Test Receiver	R&S	ESCI	100064	2022-06-17	2023-06-16
LISN	TESEQ	LN2-16N	22012	2023-03-08	2024-03-07
Cable	EMCI	CFD300-NL	CERF	2022-06-27	2023-06-26
Software	EZ-EMC(CCS-3A1-CE-wugu)				

Remark:

1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R. = No Calibration Required.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
	N/A					

Support Equipment						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
1	NB(E)	Lenovo	T460	N/A	N/A	N/A

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, KDB 662911 and KDB 558074.

2. TEST SUMMARY

FCC Standard Section	Report Section	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207(a)	4.1	AC Conducted Emission	Pass
15.247(a)(2)	4.2	6 dB Bandwidth	Pass
-	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)	4.3	Output Power Measurement	Pass
15.247(e)	4.4	Power Spectral Density	Pass
15.247(d)	4.5	Conducted Band Edge	Pass
15.247(d)	4.5	Conducted Spurious Emission	Pass
15.247(d)	4.6	Radiation Band Edge	Pass
15.247(d)	4.6	Radiation Spurious Emission	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

<p>Operation mode</p>	<p>IEEE 802.11b mode:1Mbps IEEE 802.11g mode:6Mbps IEEE 802.11n HT20 mode: MCS0 IEEE 802.11n HT40 mode: MCS0 IEEE 802.11ax (HE20) mode: MCS0 IEEE 802.11ax (HE40) mode: MCS0</p>
<p>Operation Transmitter</p>	<p>IEEE 802.11b mode: 2T2R(SISO) IEEE 802.11g mode: 2T2R(SISO) IEEE 802.11n HT20 mode: 2T2R(MIMO) IEEE 802.11n HT40 mode: 2T2R(MIMO) IEEE 802.11ax (HE20) mode: 2T2R(MIMO) IEEE 802.11ax (HE40) mode: 2T2R(MIMO)</p>
<p>Test Channel Frequencies</p>	<p>IEEE 802.11b mode: 1. Lowest Channel: 2412 MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2462 MHz IEEE 802.11g mode : 1. Lowest Channel: 2412 MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2462 MHz IEEE 802.11n HT20 mode : 1. Lowest Channel: 2412 MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2462 MHz IEEE 802.11 ax(HE20) mode : 1. Lowest Channel: 2412 MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2462 MHz IEEE 802.11n HT40 mode : 1. Lowest Channel: 2422 MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2452 MHz IEEE 802.11 ax(HE40) mode : 1. Lowest Channel: 2422 MHz 2. Middle Channel: 2437MHz 3. Highest Channel: 2452 MHz</p>

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

3.2 THE WORST MODE OF MEASUREMENT

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Adapter
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4
Worst Position	<input type="checkbox"/> Placed in fixed position. <input checked="" type="checkbox"/> Placed in fixed position at X-Plane (E2-Plane) <input type="checkbox"/> Placed in fixed position at Y-Plane (E1-Plane) <input type="checkbox"/> Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Adapter
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Power supply Mode	Mode 1: EUT power by Adapter
Worst Mode	<input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report.
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worst case.
4. The device supports SISO and MIMO at 802.11n20/n40/ax20/ax40 mode, per pre-test, MIMO 2TX mode was the worst and reported.
5. The device supports non_BF and BF modes. Since the non_BF mode has higher power and similar to BF radio frequency characteristics, some test items of BF mode will be exempted.

Report No.: TMWK2303000589KR

3.3 EUT DUTY CYCLE

Temperature: 22.0°C

Test date: March 30, 2023

Humidity: 65% RH

Tested by: David Li

Duty Cycle				
Configuration	Duty Cycle (%)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
802.11b	99.34	0.03	0.12	0.01
802.11g	96.08	0.17	0.72	1.00
802.11n_20	95.74	0.19	0.77	1.00
802.11n_40	91.91	0.37	1.54	2.00
802.11ax_20	84.72	0.72	3.16	4.00
802.11ax_40	84.55	0.73	3.21	4.00

Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR

4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a)(2)

Frequency Range (MHz)	Limits(dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup




4.1.4 Test Result

Pass.

Test Data

Test Mode:	Mode 1	Temp/Hum	23.4(°C)/ 58%RH
Phase:	Line	Test Date	April 6, 2023
Test Voltage:	120Vac, 60Hz	Test Engineer	Tony Chao




Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (d uV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1740	54.75	30.61	0.15	54.90	30.76	64.77	54.77	-9.87	-24.01	Pass
0.2220	49.46	26.76	0.15	49.61	26.91	62.74	52.74	-13.13	-25.83	Pass
0.4300	49.62	41.27	0.15	49.77	41.42	57.25	47.25	-7.48	-5.83	Pass
0.7460	40.21	28.74	0.16	40.37	28.90	56.00	46.00	-15.63	-17.10	Pass
1.6340	38.37	27.66	0.19	38.56	27.85	56.00	46.00	-17.44	-18.15	Pass
1.9140	40.15	28.08	0.21	40.36	28.29	56.00	46.00	-15.64	-17.71	Pass

Note: 1. Correction factor = LISN loss + Cable loss.

Report No.: TMWK2303000589KR

Test Mode:	Mode 1	Temp/Hum	23.4(°C)/ 58%RH
Phase:	Neutral	Test Date	April 6, 2023
Test Voltage:	120Vac, 60Hz	Test Engineer	Tony Chao



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1700	40.08	25.11	0.19	40.27	25.30	64.96	54.96	-24.69	-29.66	Pass
0.4260	34.07	19.01	0.19	34.26	19.20	57.33	47.33	-23.07	-28.13	Pass
0.7300	31.35	12.70	0.21	31.56	12.91	56.00	46.00	-24.44	-33.09	Pass
1.8060	32.21	23.60	0.24	32.45	23.84	56.00	46.00	-23.55	-22.16	Pass
2.2860	27.22	11.96	0.25	27.47	12.21	56.00	46.00	-28.53	-33.79	Pass
10.5220	26.65	13.01	0.38	27.03	13.39	60.00	50.00	-32.97	-36.61	Pass

Note: 1. Correction factor = LISN loss + Cable loss.

Report No.: TMWK2303000589KR

4.2 6dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

4.2.1 Test Limit

According to §15.247(a)(2)

6 dB Bandwidth :

Limit	Shall be at least 500kHz
-------	--------------------------


Occupied Bandwidth(99%) : For reporting purposes only.

4.2.2 Test Procedure

Test method Refer as ANSI C63.10: 2013,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 100kHz, VBW = 300kHz and Detector = Peak, to measurement 6 dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.

4.2.3 Test Setup



Report No.: TMWK2303000589KR

4.2.4 Test Result

Non-Beamforming

Temperature: 22.0°C

Test date: March 30, 2023

Humidity: 65% RH

Tested by: David Li

Test mode: IEEE 802.11b mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 6dB BW (kHz)	Chain 1 6dB BW (kHz)	6dB limit (kHz)
1	2412	12.673	12.823	8076.00	8059.00	≥500
6	2437	12.708	12.71	8084.00	8099.00	
11	2462	12.731	12.728	8091.00	8086.00	

Test mode: IEEE 802.11g mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 6dB BW (kHz)	Chain 1 6dB BW (kHz)	6dB limit (kHz)
1	2412	16.931	16.755	15680.00	15760.00	≥500
6	2437	17.28	17.517	15740.00	16070.00	
11	2462	16.956	16.875	15510.00	16060.00	

Test mode: IEEE 802.11n HT20 mode / 2412-2462 MHz						
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 6dB BW (kHz)	Chain 1 6dB BW (kHz)	6dB limit (kHz)
1	2412	17.906	17.795	16130.00	16380.00	≥500
6	2437	18.192	17.966	16530.00	17560.00	
11	2462	17.953	17.941	16120.00	17160.00	

Test mode: IEEE 802.11n HT40 mode / 2422-2452 MHz						
Channel	Frequency (MHz)	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 6dB BW (kHz)	Chain 1 6dB BW (kHz)	6dB limit (kHz)
3	2422	36.196	36.151	35290.00	35160.00	≥500
6	2437	36.454	36.217	35500.00	35170.00	
9	2452	36.43	36.174	35190.00	35170.00	

Test mode: IEEE 802.11ax HE20 mode / 2412-2462 MHz							
Channel	Frequency (MHz)	RU Config	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 6dB BW (kHz)	Chain 1 6dB BW (kHz)	6dB limit (kHz)
1	2412	full	18.855	18.878	18060.00	18280.00	≥500
6	2437	full	19.127	19.063	18690.00	17940.00	
11	2462	full	19.014	19.079	18570.00	18340.00	


Test mode: IEEE 802.11ax HE40 mode / 2422-2452 MHz							
Channel	Frequency (MHz)	RU Config	Chain 0 OBW (99%) (MHz)	Chain 1 OBW (99%) (MHz)	Chain 0 6dB BW (kHz)	Chain 1 6dB BW (kHz)	6dB limit (kHz)
3	2422	full	37.6	37.641	36480.00	37340.00	≥500
6	2437	full	37.615	37.701	36490.00	36030.00	
9	2452	full	37.725	37.696	36580.00	36100.00	

Report No.: TMWK2303000589KR


Test Data

6dB BANDWIDTH


Chain 0




Report No.: TMWK2303000589KR




Report No.: TMWK2303000589KR




Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR




Report No.: TMWK2303000589KR

Chain 1

IEEE 802.11b mode


Low CH




Mid CH




High CH




Report No.: TMWK2303000589KR




Report No.: TMWK2303000589KR




Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR




Report No.: TMWK2303000589KR


Test Data

BANDWIDTH 99%


Chain 0




Report No.: TMWK2303000589KR




Report No.: TMWK2303000589KR




Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR

Chain 1

IEEE 802.11b mode

Low CH




Mid CH




High CH




Report No.: TMWK2303000589KR




Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR



Report No.: TMWK2303000589KR

