

FCC Test Report

Report No.: RFBDOI-WTW-P20110878

FCC ID: KA2M32A1

Test Model: M32

Series Model: DIR-LX3260, M32-SP, M32-TR (refer to item 3.1 for more details)

Received Date: Mar. 27, 2021

Test Date: Apr. 10 ~ Jun. 22, 2021

Issued Date: Aug. 26, 2021

Applicant: D-Link Corporation

Address: 14420 Myford Road Suite 100 Irvine California United States 92606

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty.....	6
2.2 Modification Record.....	6
3 General Information	7
3.1 General Description of EUT.....	7
3.2 Description of Test Modes.....	9
3.2.1 Test Mode Applicability and Tested Channel Detail.....	10
3.3 Duty Cycle of Test Signal.....	12
3.4 Description of Support Units.....	13
3.4.1 Configuration of System under Test.....	13
3.5 General Description of Applied Standards and References.....	14
4 Test Types and Results	15
4.1 Radiated Emission and Bandedge Measurement.....	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement.....	15
4.1.2 Test Instruments.....	16
4.1.3 Test Procedures.....	17
4.1.4 Deviation from Test Standard.....	18
4.1.5 Test Setup.....	18
4.1.6 EUT Operating Conditions.....	19
4.1.7 Test Results.....	20
4.2 Conducted Emission Measurement.....	34
4.2.1 Limits of Conducted Emission Measurement.....	34
4.2.2 Test Instruments.....	34
4.2.3 Test Procedures.....	35
4.2.4 Deviation from Test Standard.....	35
4.2.5 Test Setup.....	35
4.2.6 EUT Operating Conditions.....	35
4.2.7 Test Results.....	36
4.3 6dB Bandwidth Measurement.....	38
4.3.1 Limits of 6dB Bandwidth Measurement.....	38
4.3.2 Test Setup.....	38
4.3.3 Test Instruments.....	38
4.3.4 Test Procedure.....	38
4.3.5 Deviation from Test Standard.....	38
4.3.6 EUT Operating Conditions.....	38
4.3.7 Test Result.....	39
4.4 Conducted Output Power Measurement.....	41
4.4.1 Limits of Conducted Output Power Measurement.....	41
4.4.2 Test Setup.....	41
4.4.3 Test Instruments.....	41
4.4.4 Test Procedures.....	41
4.4.5 Deviation from Test Standard.....	41
4.4.6 EUT Operating Conditions.....	41
4.4.7 Test Results.....	42
4.5 Power Spectral Density Measurement.....	44
4.5.1 Limits of Power Spectral Density Measurement.....	44
4.5.2 Test Setup.....	44
4.5.3 Test Instruments.....	44
4.5.4 Test Procedure.....	44
4.5.5 Deviation from Test Standard.....	45
4.5.6 EUT Operating Condition.....	45

4.5.7 Test Results	46
4.6 Conducted Out of Band Emission Measurement.....	50
4.6.1 Limits of Conducted Out of Band Emission Measurement	50
4.6.2 Test Setup.....	50
4.6.3 Test Instruments	50
4.6.4 Test Procedure	50
4.6.5 Deviation from Test Standard	50
4.6.6 EUT Operating Condition	50
4.6.7 Test Results	50
5 Pictures of Test Arrangements.....	64
Annex A - Band Edge Measurement.....	65
Appendix – Information of the Testing Laboratories	69



Release Control Record

Issue No.	Description	Date Issued
RFBDUI-WTW-P20110878	Original Release	Aug. 26, 2021

1 Certificate of Conformity

Product: AX3200 WI-FI 6 AI MESH SYSTEM, AX3200 WI-FI 6 AI MESH ROUTER, AX3200 MESH ROUTER, AX3200 MESH SYSTEM, AX3200 MESH WI-FI 6 ROUTER (refer to item 3.1 for more details)

Brand: D-Link

Test Model: M32

Series Model: DIR-LX3260, M32-SP, M32-TR (refer to item 3.1 for more details)

Sample Status: Engineering Sample

Applicant: D-Link Corporation

Test Date: Apr. 10 ~ Jun. 22, 2021

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Polly Chien , **Date:** Aug. 26, 2021
Polly Chien / Specialist

Approved by : Bruce Chen , **Date:** Aug. 26, 2021
Bruce Chen / Senior Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -25.57dB at 0.42353MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -0.7dB at 2390.00MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector are MHF compatible not a standard connector.

Note:

1. For 2.4G band compliance with rule 15.247(d) of the band-edge items, the test plots were recorded in Annex A. Test Procedures refer to report 4.1.3.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (\pm)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.79 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.04 dB
	30MHz ~ 200MHz	3.59 dB
	200MHz ~ 1000MHz	3.60 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	AX3200 WI-FI 6 AI MESH SYSTEM, AX3200 WI-FI 6 AI MESH ROUTER, AX3200 MESH ROUTER, AX3200 MESH SYSTEM, AX3200 MESH WI-FI 6 ROUTER (refer to note for more details)
Brand	D-Link
Test Model	M32
Series Model	DIR-LX3260, M32-SP, M32-TR
Model Difference	Refer to note
Sample Status	Engineering Sample
Power Supply Rating	12Vdc from Adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11n (HT20/40): up to 600Mbps 802.11n (VHT20/40): up to 800Mbps
Operating Frequency	2412 ~ 2462MHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20), 802.11n (VHT20): 11 802.11n (HT40), 802.11n (VHT40): 7
Output Power	CDD Mode: 930.243mW Beamforming Mode: 232.345mW
Antenna Type	Refer to note
Antenna Connector	Refer to note
Accessory Device	Refer to note
Cable Supplied	Refer to note

Note:

1. All models are listed as below. Model M32 is the representative for final test.

Brand	Product name	Model	Difference
D-Link	AX3200 WI-FI 6 AI MESH SYSTEM	M32	For marketing purpose
	AX3200 WI-FI 6 AI MESH ROUTER		
	AX3200 MESH ROUTER		
	AX3200 MESH SYSTEM		
	AX3200 MESH WI-FI 6 ROUTER	DIR-LX3260	
	AX3200 WI-FI 6 AI MESH SYSTEM	M32-SP	
	AX3200 WI-FI 6 AI MESH ROUTER		
	AX3200 MESH WI-FI 6 ROUTER		
	AX3200 WI-FI 6 AI MESH SYSTEM	M32-TR	
	AX3200 WI-FI 6 AI MESH ROUTER		
	AX3200 MESH WI-FI 6 ROUTER		

2. The top case of the EUT comes with two part number, which is MPCO3260BAXXU1XX and MPCOX320BAXAU1XX. After pretest, MPCO3260BAXXU1XX is found to be the worst case mode and therefore is recorded in the test report.
3. The EUT incorporates a MIMO function. Physically, the EUT provides 4 completed transmitters and 4 receivers.

Modulation Mode	Beamforming Mode	TX Function
802.11b	Not Support	1TX (Fixed Chain 0)
802.11g	Not Support	4TX
802.11n (HT20)	Support	4TX
802.11n (HT40)	Support	4TX
802.11n (VHT20)	Support	4TX
802.11n (VHT40)	Support	4TX

- * The bandwidth and modulation are similar for HT20/HT40/VHT20/VHT40 on 802.11n. Therefore the investigated worst case is the representative mode in test report. (Final test mode refer section 3.2.1)
- * For 802.11n, CDD mode and Beamforming mode are presented in power output test item. For other test items, CDD mode is the worst case for final tests after pretesting.

4. The EUT consumes power from the following accessory device.

Item	Brand	Model	Description
Adapter	Amigo	AMS200-1202000FU	Input Power: 100-240Vac, 50-60Hz, 0.8A Max Output Power: 12Vdc, 2A
CAT5E 24AWG CCA WHITE CABLE	Nienyi	NYS4710 REV.0	1.0m

5. The following antennas were provided to the EUT.

Antenna Type		Dipole x 4 for WiFi Printed PIFA Antenna x 1 for Bluetooth				
		MHF compatible				
Antenna No.		Gain (dBi)				
		2400MHz	2450MHz	2500MHz	5150MHz	5825MHz
1	WLAN Dual Band	4.5	4.0	3.5	3.3	3.1
2	WLAN Dual Band	3.0	3.1	3.6	4.0	3.8
3	WLAN Dual Band	4.6	4.5	5.4	5.4	6.7
4	WLAN Dual Band	5.4	5.7	5.9	3.8	6.7
5	BT 2.4G Band	4.4	4.8	4.9	-	-

- *The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

6. WLAN 2.4GHz, 5GHz and BT technology can transmit at same time.
7. Spurious emission of the simultaneous operation (WLAN 2.4GHz, 5GHz and BT) has been evaluated and no non-compliance was found.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20), 802.11n (VHT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40), 802.11n (VHT40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to				Description
	RE \geq 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where RE \geq 1G: Radiated Emission above 1GHz & Bandedge Measurement
 PLC: Power Line Conducted Emission
 RE<1G: Radiated Emission below 1GHz
 APCM: Antenna Port Conducted Measurement

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.
2. For radiated emission (below 1GHz) and power line conducted emission test items chosen the worst maximum power mode.

Radiated Emission Test (Above 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)	Remark
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0	-
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	
-	802.11n (VHT20)	1 to 11	1, 6, 11	OFDM	BPSK	7.2	
-	802.11n (VHT40)	3 to 9	3, 6, 9	OFDM	BPSK	15.0	

Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)	Remark
-	802.11g	1 to 11	6	OFDM	BPSK	6.0	-

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)	Remark
-	802.11g	1 to 11	6	OFDM	BPSK	6.0	-

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)	Remark
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0	-
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	
-	802.11n (VHT20)	1 to 11	1, 6, 11	OFDM	BPSK	7.2	
-	802.11n (VHT40)	3 to 9	3, 6, 9	OFDM	BPSK	15.0	

Test Condition:

Applicable to	Environmental Conditions	Input Power	Tested by
RE \geq 1G	22 deg. C, 68% RH	120Vac, 60Hz	Greg Lin
RE $<$ 1G	22 deg. C, 68% RH	120Vac, 60Hz	Greg Lin
PLC	25 deg. C, 75% RH	120Vac, 60Hz	Greg Lin
APCM	25 deg. C, 60% RH	120Vac, 60Hz	Ivan Tseng

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is $\geq 98\%$, duty factor is not required.


Duty cycle of test signal is $< 98\%$, duty factor is required.

802.11b: Duty cycle = $8.400/8.484 = 0.990$

802.11g: Duty cycle = $1.367/1.457 = 0.938$, Duty factor = $10 * \log(1/0.938) = 0.28$

802.11n (VHT20): Duty cycle = $1.299/1.384 = 0.939$, Duty factor = $10 * \log(1/0.939) = 0.28$

802.11n (VHT40): Duty cycle = $0.642/0.717 = 0.895$, Duty factor = $10 * \log(1/0.895) = 0.48$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	DELL	LATITUDE	F9MQBW1	FCC DoC Approved	Provided by lab
B.	Load	NA	NA	NA	NA	Provided by lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items A acted as communication partner to transfer data.

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	LAN	2	1.5	N	0	RJ45, Cat5e (provided by lab)
2.	LAN	1	1.5	N	0	RJ45, Cat5e (Accessory)
3.	LAN	1	7	N	0	RJ45, Cat5e (provided by lab)

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver KEYSIGHT	N9038A	MY55420137	Apr. 09, 2021	Apr. 08, 2022
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Sep. 16, 2020	Sep. 15, 2021
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Nov. 06, 2020	Nov. 05, 2021
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-1169	Nov. 22, 2020	Nov. 21, 2021
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Nov. 22, 2020	Nov. 21, 2021
Loop Antenna TESEQ	HLA 6121	45745	Jul. 06, 2020	Jul. 05, 2021
Preamplifier Agilent (Below 1GHz)	8447D	2944A10638	Jun. 08, 2020	Jun. 07, 2021
			Jun. 05, 2021	Jun. 04, 2022
Preamplifier Agilent (Above 1GHz)	8449B	3008A02367	Feb. 17, 2021	Feb. 16, 2022
RF signal cable HUBER+SUHNER&EMCI	SUCOFLEX 104 & EMC104-SM- SM8000	CABLE-CH9-02 (248780+171006)	Jan. 16, 2021	Jan. 15, 2022
RF signal cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-(250795 /4)	Jan. 16, 2021	Jan. 15, 2022
RF signal cable Woken	8D-FB	Cable-CH9-01	Jun. 08, 2020	Jun. 07, 2021
			Jun. 05, 2021	Jun. 04, 2022
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	NA	NA	NA
Antenna Tower & Turn BV ADT	AT100	AT93021705	NA	NA
Turn Table BV ADT	TT100	TT93021705	NA	NA
Turn Table Controller BV ADT	SC100	SC93021705	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
USB Wideband Power Sensor KEYSIGHT	U2021XA	MY55050005/MY5519 0004/MY55190007/MY 55210005	Jul. 13, 2020	Jul. 12, 2021

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 9.

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz. (802.11b: RBW = 1MHz, VBW = 10Hz; 802.11g: RBW = 1MHz, VBW = 1kHz; 802.11n (VHT20): RBW = 1MHz, VBW = 1kHz; 802.11n (VHT40): RBW = 1MHz, VBW = 3kHz)
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Prepared a notebook to act as a communication partner and placed it outside of testing area.
- c. The communication partner connected with EUT via an RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1GHz Data:

RF Mode	TX 802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	58.3 PK	74.0	-15.7	2.48 H	52	27.1	31.2
2	2390.00	47.5 AV	54.0	-6.5	2.48 H	52	16.3	31.2
3	*2412.00	111.3 PK			2.48 H	52	80.1	31.2
4	*2412.00	107.8 AV			2.48 H	52	76.6	31.2
5	4824.00	47.6 PK	74.0	-26.4	2.58 H	19	45.5	2.1
6	4824.00	42.7 AV	54.0	-11.3	2.58 H	19	40.6	2.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.8 PK	74.0	-12.2	3.30 V	351	30.6	31.2
2	2390.00	53.0 AV	54.0	-1.0	3.30 V	351	21.8	31.2
3	*2412.00	115.7 PK			3.30 V	351	84.5	31.2
4	*2412.00	112.2 AV			3.30 V	351	81.0	31.2
5	4824.00	47.3 PK	74.0	-26.7	2.39 V	211	45.2	2.1
6	4824.00	42.4 AV	54.0	-11.6	2.39 V	211	40.3	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	112.0 PK			2.44 H	57	80.9	31.1
2	*2437.00	108.5 AV			2.44 H	57	77.4	31.1
3	4874.00	48.4 PK	74.0	-25.6	2.53 H	15	46.3	2.1
4	4874.00	43.6 AV	54.0	-10.4	2.53 H	15	41.5	2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	116.5 PK			3.16 V	354	85.4	31.1
2	*2437.00	113.0 AV			3.16 V	354	81.9	31.1
3	4874.00	48.4 PK	74.0	-25.6	2.34 V	205	46.3	2.1
4	4874.00	43.4 AV	54.0	-10.6	2.34 V	205	41.3	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.7 PK			2.49 H	50	79.6	31.1
2	*2462.00	107.2 AV			2.49 H	50	76.1	31.1
3	2483.50	59.0 PK	74.0	-15.0	2.49 H	50	27.9	31.1
4	2483.50	48.3 AV	54.0	-5.7	2.49 H	50	17.2	31.1
5	4924.00	47.3 PK	74.0	-26.7	2.49 H	21	45.2	2.1
6	4924.00	42.2 AV	54.0	-11.8	2.49 H	21	40.1	2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	115.2 PK			3.40 V	353	84.1	31.1
2	*2462.00	111.7 AV			3.40 V	353	80.6	31.1
3	2483.50	62.0 PK	74.0	-12.0	3.40 V	353	30.9	31.1
4	2483.50	53.0 AV	54.0	-1.0	3.40 V	353	21.9	31.1
5	4924.00	47.0 PK	74.0	-27.0	2.42 V	208	44.9	2.1
6	4924.00	41.8 AV	54.0	-12.2	2.42 V	208	39.7	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	62.1 PK	74.0	-11.9	1.34 H	13	30.9	31.2
2	2390.00	48.8 AV	54.0	-5.2	1.34 H	13	17.6	31.2
3	*2412.00	113.6 PK			1.34 H	13	82.4	31.2
4	*2412.00	103.7 AV			1.34 H	13	72.5	31.2
5	4824.00	45.6 PK	74.0	-28.4	2.14 H	288	43.5	2.1
6	4824.00	32.8 AV	54.0	-21.2	2.14 H	288	30.7	2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	65.6 PK	74.0	-8.4	3.21 V	350	34.4	31.2
2	2390.00	52.8 AV	54.0	-1.2	3.21 V	350	21.6	31.2
3	*2412.00	118.7 PK			3.21 V	350	87.5	31.2
4	*2412.00	108.8 AV			3.21 V	350	77.6	31.2
5	4824.00	46.7 PK	74.0	-27.3	3.42 V	167	44.6	2.1
6	4824.00	33.8 AV	54.0	-20.2	3.42 V	167	31.7	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	116.9 PK			1.36 H	18	85.8	31.1
2	*2437.00	107.0 AV			1.36 H	18	75.9	31.1
3	4874.00	48.3 PK	74.0	-25.7	2.11 H	283	46.2	2.1
4	4874.00	35.5 AV	54.0	-18.5	2.11 H	283	33.4	2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	122.3 PK			3.41 V	6	91.2	31.1
2	*2437.00	112.2 AV			3.41 V	6	81.1	31.1
3	4874.00	49.6 PK	74.0	-24.4	3.34 V	165	47.5	2.1
4	4874.00	36.9 AV	54.0	-17.1	3.34 V	165	34.8	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11g	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	112.4 PK			1.33 H	19	81.3	31.1
2	*2462.00	102.5 AV			1.33 H	19	71.4	31.1
3	2483.50	61.4 PK	74.0	-12.6	1.33 H	19	30.3	31.1
4	2483.50	48.7 AV	54.0	-5.3	1.33 H	19	17.6	31.1
5	4924.00	45.3 PK	74.0	-28.7	2.14 H	286	43.2	2.1
6	4924.00	32.5 AV	54.0	-21.5	2.14 H	286	30.4	2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	117.5 PK			3.24 V	351	86.4	31.1
2	*2462.00	107.7 AV			3.24 V	351	76.6	31.1
3	2483.50	66.4 PK	74.0	-7.6	3.24 V	351	35.3	31.1
4	2483.50	52.8 AV	54.0	-1.2	3.24 V	351	21.7	31.1
5	4924.00	46.5 PK	74.0	-27.5	3.47 V	161	44.4	2.1
6	4924.00	33.6 AV	54.0	-20.4	3.47 V	161	31.5	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11n (VHT20)	Channel	CH 1 : 2412 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	61.5 PK	74.0	-12.5	1.35 H	21	30.3	31.2
2	2390.00	48.6 AV	54.0	-5.4	1.35 H	21	17.4	31.2
3	*2412.00	111.0 PK			1.35 H	21	79.8	31.2
4	*2412.00	101.0 AV			1.35 H	21	69.8	31.2
5	4824.00	45.4 PK	74.0	-28.6	2.08 H	291	43.3	2.1
6	4824.00	32.6 AV	54.0	-21.4	2.08 H	291	30.5	2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	64.9 PK	74.0	-9.1	3.25 V	348	33.7	31.2
2	2390.00	52.6 AV	54.0	-1.4	3.25 V	348	21.4	31.2
3	*2412.00	116.0 PK			3.25 V	348	84.8	31.2
4	*2412.00	106.0 AV			3.25 V	348	74.8	31.2
5	4824.00	46.8 PK	74.0	-27.2	3.37 V	169	44.7	2.1
6	4824.00	33.8 AV	54.0	-20.2	3.37 V	169	31.7	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11n (VHT20)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	114.4 PK			1.38 H	22	83.3	31.1
2	*2437.00	104.7 AV			1.38 H	22	73.6	31.1
3	4874.00	46.3 PK	74.0	-27.7	2.16 H	285	44.2	2.1
4	4874.00	32.9 AV	54.0	-21.1	2.16 H	285	30.8	2.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	119.5 PK			3.32 V	9	88.4	31.1
2	*2437.00	109.8 AV			3.32 V	9	78.7	31.1
3	4874.00	47.5 PK	74.0	-26.5	3.31 V	177	45.4	2.1
4	4874.00	35.0 AV	54.0	-19.0	3.31 V	177	32.9	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11n (VHT20)	Channel	CH 11 : 2462 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	112.7 PK			1.31 H	14	81.6	31.1
2	*2462.00	102.9 AV			1.31 H	14	71.8	31.1
3	2483.50	61.8 PK	74.0	-12.2	1.31 H	14	30.7	31.1
4	2483.50	48.9 AV	54.0	-5.1	1.31 H	14	17.8	31.1
5	4924.00	45.2 PK	74.0	-28.8	2.16 H	277	43.1	2.1
6	4924.00	32.5 AV	54.0	-21.5	2.16 H	277	30.4	2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	117.7 PK			3.03 V	351	86.6	31.1
2	*2462.00	108.1 AV			3.03 V	351	77.0	31.1
3	2483.50	66.4 PK	74.0	-7.6	3.03 V	351	35.3	31.1
4	2483.50	52.6 AV	54.0	-1.4	3.03 V	351	21.5	31.1
5	4924.00	46.4 PK	74.0	-27.6	3.38 V	173	44.3	2.1
6	4924.00	33.8 AV	54.0	-20.2	3.38 V	173	31.7	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11n (VHT40)	Channel	CH 3 : 2422 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	66.3 PK	74.0	-7.7	1.42 H	26	35.1	31.2
2	2390.00	50.3 AV	54.0	-3.7	1.42 H	26	19.1	31.2
3	*2422.00	106.6 PK			1.42 H	26	75.4	31.2
4	*2422.00	96.8 AV			1.42 H	26	65.6	31.2
5	4844.00	44.3 PK	74.0	-29.7	2.17 H	294	42.2	2.1
6	4844.00	31.4 AV	54.0	-22.6	2.17 H	294	29.3	2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	68.0 PK	74.0	-6.0	3.35 V	11	36.8	31.2
2	2390.00	53.3 AV	54.0	-0.7	3.35 V	11	22.1	31.2
3	*2422.00	111.7 PK			3.35 V	11	80.5	31.2
4	*2422.00	101.9 AV			3.35 V	11	70.7	31.2
5	4844.00	45.4 PK	74.0	-28.6	3.37 V	156	43.3	2.1
6	4844.00	32.5 AV	54.0	-21.5	3.37 V	156	30.4	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11n (VHT40)	Channel	CH 6 : 2437 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	65.0 PK	74.0	-9.0	1.32 H	14	33.8	31.2
2	2390.00	51.8 AV	54.0	-2.2	1.32 H	14	20.6	31.2
3	*2437.00	112.7 PK			1.32 H	14	81.6	31.1
4	*2437.00	103.0 AV			1.32 H	14	71.9	31.1
5	4874.00	44.9 PK	74.0	-29.1	2.07 H	280	42.8	2.1
6	4874.00	32.0 AV	54.0	-22.0	2.07 H	280	29.9	2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	66.4 PK	74.0	-7.6	3.18 V	349	35.2	31.2
2	2390.00	53.0 AV	54.0	-1.0	3.18 V	349	21.8	31.2
3	*2437.00	117.9 PK			3.18 V	349	86.8	31.1
4	*2437.00	108.2 AV			3.18 V	349	77.1	31.1
5	4874.00	46.3 PK	74.0	-27.7	3.39 V	170	44.2	2.1
6	4874.00	33.4 AV	54.0	-20.6	3.39 V	170	31.3	2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11n (VHT40)	Channel	CH 9 : 2452 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	107.8 PK			1.38 H	20	76.7	31.1
2	*2452.00	98.2 AV			1.38 H	20	67.1	31.1
3	2483.50	61.8 PK	74.0	-12.2	1.38 H	20	30.7	31.1
4	2483.50	49.3 AV	54.0	-4.7	1.38 H	20	18.2	31.1
5	4904.00	44.0 PK	74.0	-30.0	2.12 H	287	42.0	2.0
6	4904.00	31.4 AV	54.0	-22.6	2.12 H	287	29.4	2.0

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	113.2 PK			2.88 V	353	82.1	31.1
2	*2452.00	103.5 AV			2.88 V	353	72.4	31.1
3	2483.50	65.8 PK	74.0	-8.2	2.88 V	353	34.7	31.1
4	2483.50	52.8 AV	54.0	-1.2	2.88 V	353	21.7	31.1
5	4904.00	45.4 PK	74.0	-28.6	3.36 V	164	43.4	2.0
6	4904.00	32.5 AV	54.0	-21.5	3.36 V	164	30.5	2.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.


Below 1GHz worst-case data:

RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	30.00	30.0 QP	40.0	-10.0	1.25 H	309	40.2	-10.2
2	166.77	21.5 QP	43.5	-22.0	1.00 H	133	30.1	-8.6
3	260.86	26.1 QP	46.0	-19.9	1.50 H	192	34.4	-8.3
4	342.34	22.9 QP	46.0	-23.1	1.25 H	288	28.8	-5.9
5	717.73	28.7 QP	46.0	-17.3	1.00 H	16	27.2	1.5
6	946.65	31.2 QP	46.0	-14.8	1.00 H	1	24.7	6.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




RF Mode	TX 802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	39.70	28.6 QP	40.0	-11.4	1.25 V	24	38.3	-9.7
2	99.84	24.9 QP	43.5	-18.6	1.00 V	205	38.3	-13.4
3	289.96	22.1 QP	46.0	-23.9	1.25 V	46	29.1	-7.0
4	519.85	25.7 QP	46.0	-20.3	1.00 V	129	27.6	-1.9
5	721.61	28.9 QP	46.0	-17.1	1.00 V	27	27.3	1.6
6	906.88	31.4 QP	46.0	-14.6	1.50 V	340	25.6	5.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Tested date: Jun. 22, 2021

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESR3	102783	Dec. 21, 2020	Dec. 20, 2021
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond2-01	Sep. 04, 2020	Sep. 03, 2021
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Jan. 28, 2021	Jan. 27, 2022
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Aug. 18, 2020	Aug. 17, 2021
Software ADT	BV ADT_Cond_ V7.3.7.4	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2 (Conduction 2).

3. The VCCI Site Registration No. is C-12047.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.

4.2.7 Test Results

Worst-case data:


802.11g

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16105	0.14	38.50	24.34	38.64	24.48	65.41	55.41	-26.77	-30.93
2	0.18200	0.16	32.86	19.39	33.02	19.55	64.39	54.39	-31.37	-34.84
3	0.27134	0.19	21.26	7.86	21.45	8.05	61.08	51.08	-39.63	-43.03
4	0.42353	0.23	25.75	21.58	25.98	21.81	57.38	47.38	-31.40	-25.57
5	2.95224	0.38	9.63	4.22	10.01	4.60	56.00	46.00	-45.99	-41.40
6	11.51000	0.56	15.99	10.47	16.55	11.03	60.00	50.00	-43.45	-38.97

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.15400	0.14	38.95	24.27	39.09	24.41	65.78
2	0.25139	0.19	24.31	10.64	24.50	10.83	61.71	51.71	-37.21	-40.88
3	0.42802	0.25	22.14	14.22	22.39	14.47	57.29	47.29	-34.90	-32.82
4	1.92154	0.38	14.36	4.25	14.74	4.63	56.00	46.00	-41.26	-41.37
5	4.32600	0.49	8.86	3.15	9.35	3.64	56.00	46.00	-46.65	-42.36
6	7.27800	0.57	21.32	16.03	21.89	16.60	60.00	50.00	-38.11	-33.40

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz.
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	9.12	0.5	Pass
6	2437	9.11	0.5	Pass
11	2462	9.10	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	15.18	15.17	15.18	15.17	0.50	Pass
6	2437	15.18	15.18	15.18	15.18	0.50	Pass
11	2462	15.17	15.18	15.17	15.17	0.50	Pass

802.11n (VHT20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	15.17	15.18	15.18	15.18	0.50	Pass
6	2437	15.17	15.18	15.18	15.18	0.50	Pass
11	2462	15.17	15.17	15.18	15.18	0.50	Pass

802.11n (VHT40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
3	2422	35.24	35.25	35.25	35.25	0.50	Pass
6	2437	35.26	35.25	35.26	35.25	0.50	Pass
9	2452	35.24	35.25	35.24	35.25	0.50	Pass

Spectrum Plot of Worst Value


802.11b




802.11g



802.11n (VHT20)



802.11n (VHT40)



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as item 4.3.6.

4.4.7 Test Results

CDD Mode

802.11b

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	331.131	25.20	30.00	Pass
6	2437	341.193	25.33	30.00	Pass
11	2462	271.644	24.34	30.00	Pass

802.11g

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	19.29	18.97	18.65	19.15	319.311	25.04	30	Pass
6	2437	23.88	23.55	23.48	23.74	930.243	29.69	30	Pass
11	2462	19.24	18.94	18.62	19.08	315.977	25.00	30	Pass

802.11n (VHT20)

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	20.52	20.21	20.08	20.37	428.426	26.32	30	Pass
6	2437	23.86	23.61	23.41	23.75	929.253	29.68	30	Pass
11	2462	21.15	20.84	20.74	21.05	497.583	26.97	30	Pass

802.11n (VHT40)

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	17.56	17.32	17.09	17.48	218.111	23.39	30	Pass
6	2437	22.10	21.69	21.43	21.95	605.422	27.82	30	Pass
9	2452	17.39	17.14	17.03	17.28	210.511	23.23	30	Pass

Beamforming Mode

802.11n (VHT20)

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	14.50	14.19	14.06	14.35	107.121	20.30	25.09	Pass
6	2437	17.84	17.59	17.39	17.73	232.345	23.66	25.09	Pass
11	2462	15.13	14.82	14.72	15.03	124.413	20.95	25.09	Pass

Note: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 10.91\text{dBi} > 6\text{dBi}$, so the power limit shall be reduced to $30 - (10.91 - 6) = 25.09\text{dBm}$.

802.11n (VHT40)

Channel	Frequency (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	11.54	11.30	11.07	11.46	54.535	17.37	25.09	Pass
6	2437	16.08	15.67	15.41	15.93	151.376	21.80	25.09	Pass
9	2452	11.37	11.12	11.01	11.26	52.635	17.21	25.09	Pass


Note: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 10.91\text{dBi} > 6\text{dBi}$, so the power limit shall be reduced to $30 - (10.91 - 6) = 25.09\text{dBm}$.

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

For Average Power (Duty cycle $\geq 98\%$)

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.

For Average Power (Duty cycle $< 98\%$)

- Measure the duty cycle (x).
- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- Sweep time = auto couple.
- Do not use sweep triggering. Allow sweep to "free run".
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- Add $10 \log (1/x)$, where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as item 4.3.6

4.5.7 Test Results

802.11b

Channel	Frequency (MHz)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
1	2412	-7.78	8.00	Pass
6	2437	-7.32	8.00	Pass
11	2462	-7.97	8.00	Pass

802.11g

TX chain	Channel	Frequency (MHz)	PSD w/o Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
0	1	2412	-15.87	6.02	0.28	-9.57	3.09	Pass
	6	2437	-11.79	6.02	0.28	-5.49	3.09	Pass
	11	2462	-15.88	6.02	0.28	-9.58	3.09	Pass
1	1	2412	-16.09	6.02	0.28	-9.79	3.09	Pass
	6	2437	-11.79	6.02	0.28	-5.49	3.09	Pass
	11	2462	-15.28	6.02	0.28	-8.98	3.09	Pass
2	1	2412	-16.27	6.02	0.28	-9.97	3.09	Pass
	6	2437	-11.76	6.02	0.28	-5.46	3.09	Pass
	11	2462	-16.67	6.02	0.28	-10.37	3.09	Pass
3	1	2412	-15.60	6.02	0.28	-9.30	3.09	Pass
	6	2437	-11.79	6.02	0.28	-5.49	3.09	Pass
	11	2462	-15.88	6.02	0.28	-9.58	3.09	Pass

Note:

- Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure value and add 10 log (N_{ANT}) dB.
- Directional gain = Directional gain = $10 \log[(10^{G^1/20} + 10^{G^2/20} + \dots + 10^{G^N/20})^2/4] = 10.91\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8 - (10.91 - 6) = 3.09\text{dBm}$.
- Refer to section 3.3 for duty cycle spectrum plot.

802.11n (VHT20)

TX chain	Channel	Frequency (MHz)	PSD w/o Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
0	1	2412	-15.43	6.02	0.28	-9.13	3.09	Pass
	6	2437	-12.05	6.02	0.28	-5.75	3.09	Pass
	11	2462	-14.30	6.02	0.28	-8.00	3.09	Pass
1	1	2412	-15.47	6.02	0.28	-9.17	3.09	Pass
	6	2437	-11.73	6.02	0.28	-5.43	3.09	Pass
	11	2462	-13.92	6.02	0.28	-7.62	3.09	Pass
2	1	2412	-15.64	6.02	0.28	-9.34	3.09	Pass
	6	2437	-11.59	6.02	0.28	-5.29	3.09	Pass
	11	2462	-15.05	6.02	0.28	-8.75	3.09	Pass
3	1	2412	-15.38	6.02	0.28	-9.08	3.09	Pass
	6	2437	-12.05	6.02	0.28	-5.75	3.09	Pass
	11	2462	-14.30	6.02	0.28	-8.00	3.09	Pass

Note:

- Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure value and add 10 log (N_{ANT}) dB.
- Directional gain = Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 10.91\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8 - (10.91 - 6) = 3.09\text{dBm}$.
- Refer to section 3.3 for duty cycle spectrum plot.

802.11n (VHT40)


TX chain	Channel	Frequency (MHz)	PSD w/o Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
0	3	2422	-21.00	6.02	0.48	-14.50	3.09	Pass
	6	2437	-16.46	6.02	0.48	-9.96	3.09	Pass
	9	2452	-21.02	6.02	0.48	-14.52	3.09	Pass
1	3	2422	-21.16	6.02	0.48	-14.66	3.09	Pass
	6	2437	-16.49	6.02	0.48	-9.99	3.09	Pass
	9	2452	-21.31	6.02	0.48	-14.81	3.09	Pass
3	3	2422	-21.55	6.02	0.48	-15.05	3.09	Pass
	6	2437	-16.94	6.02	0.48	-10.44	3.09	Pass
	9	2452	-21.39	6.02	0.48	-14.89	3.09	Pass
4	3	2422	-21.27	6.02	0.48	-14.77	3.09	Pass
	6	2437	-16.46	6.02	0.48	-9.96	3.09	Pass
	9	2452	-21.02	6.02	0.48	-14.52	3.09	Pass

Note:


- Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density, Measure value and add 10 log (N_{ANT}) dB.
- Directional gain = Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 10.91\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8 - (10.91 - 6) = 3.09\text{dBm}$.
- Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11b




802.11g / Chain 2 / CH 6



802.11n (VHT20) / Chain 2 / CH 6



802.11n (VHT40) / Chain 0 / CH 6




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below -30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

- Set the RBW = 100 kHz.
- Set the VBW \geq 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW \geq 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition






Same as item 4.3.6

4.6.7 Test Results






The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.






802.11b




802.11g Chain 0











802.11g Chain 1








802.11g Chain 2








802.11g Chain 3











802.11n (VHT20)_Chain 0











802.11n (VHT20)_Chain 1








802.11n (VHT20)_Chain 2








802.11n (VHT20)_Chain 3








802.11n (VHT40)_Chain 0








802.11n (VHT40)_Chain 1



802.11n (VHT40)_Chain 2




802.11n (VHT40)_Chain 3




5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).


Annex A - Band Edge Measurement




802.11n (VHT20) Channel 1




802.11n (VHT20) Channel 11



802.11n (VHT40) Channel 3



802.11n (VHT40) Channel 11



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---