

MPE Evaluation Report for FCC

Applicant Name : D-Link Corporation
Applicant Address : 14420 Myford Road Suite 100 Irvine California United States 92606
Product Name : 5G NR AX3000 Wi-Fi 6 Router
Brand Name : D-Link
Model Number : G530
FCC ID : KA2RG520NA1

Report Number : USSC245283001
Compliant Standards : FCC 47 CFR §2.1091
Sample Received Date : May 23, 2024
Report Issued Date : Jul. 16, 2024

The above equipment has been tested by Eurofins E&E Wireless Taiwan Co., Ltd., and found compliance with the requirement of the above standards. The test record, data evaluation & Device Under Test (DUT) configurations represented herein are true and accurate accounts of the measurements of the sample's characteristics under the conditions specified in this report.

Note:

1. The test results are valid only for samples provided by customers and under the test conditions described in this report.
2. This report shall not be reproduced except in full, without the written approval of Eurofins E&E Wireless Taiwan Co., Ltd.
3. The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

Approved By :

Roy Wu / SAR Technical Director



Table of Contents

Revision History	3
1. Test Regulations.....	4
1.1. Reference Standard and Guidance.....	4
1.2. RF Exposure Limits.....	4
2. Information of Testing Laboratory	6
3. DUT (Device Under Test) Information	7
3.1. Device Overview	7
4. Maximum Permissible Exposure (MPE) Assessment.....	8
4.1. Introduction	8
4.2. Determination of Exemption for Low Power Devices	8
4.3. Standalone Maximum Permissible Exposure Evaluation	11
4.4. Total Exposure Ratio Evaluation for Simultaneous Transmission.....	13

Revision History

Rev.	Issued Date	Description	Revised by
00	Jul. 16, 2024	Initial Issue	Rowan Hsieh

1. Test Regulations

1.1. Reference Standard and Guidance

The Maximum Permissible Exposure (MPE) evaluation documented in this report were performed in accordance with following FCC published KDB guidance and standard :

47 CFR Part 1.1307

47 CFR Part 1.1310

47 CFR Part 2.1091

KDB Publication 447498 D01 – General RF Exposure Guidance v06

KDB Publication 447498 D04 – Interim General RF Exposure Guidance v01

1.2. RF Exposure Limits

According to 47 CFR §1.1310, for operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in below table, may be used instead of whole-body SAR limits to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b), except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093. At operating frequencies above 6 GHz, the MPE limits listed in below table shall be used in all cases to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b).

Limits for Maximum Permissible Exposure (MPE) to Radiofrequency Electromagnetic Fields

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(i) Limits for Occupational / Controlled Exposure				
0.3 – 3.0	614	1.63	*(100)	≤ 6
3.0 – 30	1842 / f	4.89 / f	*(900 / f ²)	< 6
30 – 300	61.4	0.163	1.0	< 6
300 – 1500	N/A	N/A	f / 300	< 6
1500 – 100000	N/A	N/A	5	< 6
(ii) Limits for General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*(100)	< 30
1.34 – 30	824 / f	2.19 / f	*(180 / f ²)	< 30
30 – 300	27.5	0.073	0.2	< 30
300 – 1500	N/A	N/A	f / 1500	< 30
1500 – 100000	N/A	N/A	1.0	< 30

Notes:

1. f = frequency in MHz. * = Plane-wave equivalent power density.

2. **Occupational / Controlled Exposure Limits** apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. The phrase fully aware in the context of applying these exposure limits means that an exposed person has received written and/or verbal information fully explaining the potential for RF exposure resulting from his or her employment. With the exception of transient persons, this phrase also means that an exposed person has received appropriate training regarding work practices relating to controlling or mitigating his or her exposure. In situations when an untrained person is transient through a location where occupational / controlled limits apply, he or she must be made aware of the potential for exposure and be supervised by trained personnel pursuant to §1.1307(b)(2) of this part where use of time averaging is required to ensure compliance with the general population exposure limit. The phrase exercise control means that an exposed person is allowed and also knows how to reduce or avoid exposure by administrative or engineering work practices, such as use of personal protective equipment or time averaging of exposure.
3. **General Population / Uncontrolled Exposure Limits** apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure. For example, RF sources intended for consumer use shall be subject to the limits for general population / uncontrolled exposure in this section.

2. Information of Testing Laboratory

Test Facilities

Company Name: Eurofins E&E Wireless Taiwan Co., Ltd.
 Address No.: 140-1, Changan Street, Bade District, Taoyuan City 334025, Taiwan
 Website: <https://www.atl.com.tw>
 Telephone: +886-3-271-0188
 Fax: +886-3-271-0190
 E-mail: infoEETW@eurofins.com

Test Site Location

- No. 140-1, Changan Street, Bade District, Taoyuan City 334025, Taiwan
- No. 2, Wuquan 5th Rd. Wugu Dist., New Taipei City, Taiwan

Laboratory Accreditation

Location	TAF	FCC	ISED
No. 140-1, Changan Street, Bade District, Taoyuan City 334025, Taiwan	Accreditation No.: 1330	Designation No.: TW0010	Company No.: 7381A CAB ID: TW1330
No. 2, Wuquan 5th Rd. Wugu Dist., New Taipei City, Taiwan	Accreditation No.: 1330	Designation No.: TW0034	Company No.: 28922 CAB ID: TW1330

3. DUT (Device Under Test) Information

3.1. Device Overview

Product Name	5G NR AX3000 Wi-Fi 6 Router	
Brand Name	D-Link	
Model Name	G530	
FCC ID	KA2RG520NA1	
Supported Wireless Technologies	Tx Frequency (MHz)	Operating Mode
	LTE Band 2 : 1850.7 ~ 1909.3 Band 4 : 1710.7 ~ 1754.3 Band 5 : 824.7 ~ 848.3 Band 7 : 2502.5 ~ 2567.5 Band 12 : 699.7 ~ 715.3 Band 13 : 779.5 ~ 784.5 Band 14 : 790.5 ~ 795.5 Band 17 : 706.5 ~ 713.5 Band 25 : 1850.7 ~ 1914.3 Band 26 : 814.7 ~ 848.3 Band 30 : 2307.5 ~ 2312.5 Band 38 : 2572.5 ~ 2617.5 Band 41 : 2498.5 ~ 2687.5 Band 42 : 3552.5 ~ 3597.5 Band 43 : 3652.5 ~ 3697.5 Band 66 : 1710.7 ~ 1779.3 Band 71 : 665.5 ~ 695.5	QPSK, 16QAM, 64QAM, 256QAM
	5G NR FR1 n2 : 1852.5 ~ 1907.5 n5 : 826.5 ~ 846.5 n7 : 2502.5 ~ 2567.5 n12 : 701.5 ~ 713.5 n13 : 777 ~ 787 n14 : 790.5 ~ 795.5 n25 : 1852.5 ~ 1912.5 n26 : 816.5 ~ 846.5 n30 : 2307.5 ~ 2312.5 n38 : 2575 ~ 2615 n41 : 2501.01 ~ 2685, 2506.02 ~ 2679.99 n48 : 3555 ~ 3694.98 n66 : 1712.5 ~ 1777.5 n70 : 1697.5 ~ 1707.5 n71 : 665.5 ~ 695.5 n77 : 3455.01 ~ 3645, 3705 ~ 3975 n78 : 3455.01 ~ 3544.98, 3705 ~ 3795	DFT-s-OFDM : π/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM CP-OFDM : QPSK, 16QAM, 64QAM, 256QAM
	WLAN 2.4G : 2412 ~ 2462 5G : 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5720, 5745 ~ 5805/5825	2.4G : 802.11b/g/n/ac/ax 5G : 802.11a/n/ac/ax

Note:

The above DUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

4. Maximum Permissible Exposure (MPE) Assessment

4.1. Introduction

According to 47 CFR §2.1091, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location while transmitting. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal desktop computer, are considered to be mobile devices if they meet the 20-centimeter separation requirement. The exposure limits to be used for MPE evaluation are specified in §1.1310. All unlicensed personal communications service (PCS) devices and unlicensed NII devices shall be subject to the limits for general population / uncontrolled exposure.

4.2. Determination of Exemption for Low Power Devices

For Single RF Sources, a single RF source is exempt if:

Option A :

The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph §1.1307(b)(3)(ii)(A). Medical implant devices may only use this exemption and that in paragraph §1.1307(b)(3)(ii)(A).

Option B :

The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th}(mW) = \begin{cases} ERP_{20\text{ cm}}(d/20\text{ cm})^x & d \leq 20\text{ cm} \\ ERP_{20\text{ cm}} & 20\text{ cm} < d \leq 40\text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20\text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$$

and

$$ERP_{20\text{ cm}}(mW) = \begin{cases} 2040f & 0.3\text{ GHz} \leq f < 1.5\text{ GHz} \\ 3060 & 1.5\text{ GHz} \leq f \leq 6\text{ GHz} \end{cases}$$

d = the separation distance (cm).

Option C :

Using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1: Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency (MHz)	Threshold ERP (Watts)
0.3 – 1.34	1.920 x R2
1.34 – 30	3.450 x R2 / f2
30 – 300	3.83 x R2
300 – 1500	0.0128 x R2 x f
1500 – 100000	19.2 x R2

For Multiple RF Sources, multiple RF sources are exempt if:

Option A :

The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those is §1.1307(b)(3)(i)(A). Medical implant devices may only use this exemption and that in §1.1307(b)(3)(i)(A).

Option B :

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

- a** = number of fixed, mobile, or portable RF sources claiming exemption per §1.1307(b)(3)(i)(B) for *P_{th}*, including existing exempt transmitters and those being added.
- b** = number of fixed, mobile, or portable RF sources claiming exemption per §1.1307(b)(3)(i)(C) for Threshold ERP, including existing exempt transmitters and those being added.
- c** = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.
- P_i** = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source *i* at a distance between 0.5 cm and 40 cm (inclusive).
- P_{th,i}** = the exemption threshold power (*P_{th}*) according to §1.1307(b)(3)(i)(B) for fixed, mobile, or portable RF source *i*.
- ERP_j** = the ERP of fixed, mobile, or portable RF source *j*.
- ERP_{th,j}** = exemption threshold ERP for fixed, mobile, or portable RF source *j*, at a distance of at least λ/2π according to the applicable formula of §1.1307(b)(3)(i)(C).
- Evaluated_k** = the maximum reported SAR or MPE of fixed, mobile, or portable RF source *k* either in the device or at the transmitter site from an existing evaluation at the location of exposure.
- Exposure Limit_k** = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source *k*, as applicable from §1.1310.

Tx Bands	Frequency (MHz)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Peak Antenna Gain (dBi)	ERP (mW)	LPE Level in Option A (mW)	LPE Level in Option B (mW)	LPE Level in Option C (mW)	Low-Power Exemption Verdict
LTE B2	1850.7	23.45	221	2.6	245.47	N/A	3060	768	Pass by Option B
LTE B4	1710.7	23.20	209	3.7	298.54	N/A	3060	768	Pass by Option B
LTE B5	824.7	22.81	191	2.3	197.70	N/A	1682	422	Pass by Option B
LTE B7	2502.5	23.50	224	0.1	139.64	N/A	3060	768	Pass by Option B
LTE B12	699.7	22.50	178	2.6	197.24	N/A	1427	358	Pass by Option B
LTE B13	779.5	22.38	173	2.7	196.34	N/A	1590	399	Pass by Option B
LTE B14	790.5	22.51	178	2.7	202.30	N/A	1613	405	Pass by Option B
LTE B17	706.5	22.61	182	2.6	202.30	N/A	1441	362	Pass by Option B
LTE B25	1850.7	23.45	221	2.6	245.47	N/A	3060	768	Pass by Option B
LTE B26	814.7	22.81	191	2.3	197.70	N/A	1662	417	Pass by Option B
LTE B30	2307.5	22.32	171	1.0	130.92	N/A	3060	768	Pass by Option B
LTE B38	2572.5	26.41	438	0.2	279.25	N/A	3060	768	Pass by Option B
LTE B41	2498.5	26.41	438	0.2	279.25	N/A	3060	768	Pass by Option B
LTE B42	3552.5	25.59	362	0.9	271.64	N/A	3060	768	Pass by Option B
LTE B43	3652.5	25.42	348	0.9	261.22	N/A	3060	768	Pass by Option B
LTE B66	1710.7	23.20	209	3.7	298.54	N/A	3060	768	Pass by Option B
LTE B71	665.5	22.45	176	2.2	177.83	N/A	1358	341	Pass by Option B
5G NR n2	1852.5	23.80	240	2.6	266.07	N/A	3060	768	Pass by Option B
5G NR n5	826.5	23.82	241	2.3	249.46	N/A	1686	423	Pass by Option B
5G NR n7	2502.5	24.69	294	0.1	183.65	N/A	3060	768	Pass by Option B
5G NR n12	701.5	23.54	226	2.6	250.61	N/A	1431	359	Pass by Option B
5G NR n13	777	22.71	187	2.7	211.84	N/A	1585	398	Pass by Option B
5G NR n14	790.5	23.56	227	2.7	257.63	N/A	1613	405	Pass by Option B
5G NR n25	1852.5	23.26	212	2.6	234.96	N/A	3060	768	Pass by Option B
5G NR n26	816.5	23.15	207	2.3	213.80	N/A	1666	418	Pass by Option B
5G NR n30	2307.5	22.62	183	1.1	143.55	N/A	3060	768	Pass by Option B
5G NR n38	2575	26.37	434	0.2	276.69	N/A	3060	768	Pass by Option B
5G NR n41	2501.01	29.70	933	0.2	595.66	N/A	3060	768	Pass by Option B
5G NR n48	3555	23.03	201	0.9	150.66	N/A	3060	768	Pass by Option B
5G NR n66	1712.5	24.23	265	3.7	378.44	N/A	3060	768	Pass by Option B
5G NR n70	1697.5	23.98	250	3.7	357.27	N/A	3060	768	Pass by Option B
5G NR n71	665.5	23.60	229	2.2	231.74	N/A	1358	341	Pass by Option B
5G NR n77	3455.01	28.89	774	0.9	580.76	N/A	3060	768	Pass by Option B
5G NR n78	3455.01	28.89	774	0.9	580.76	N/A	3060	768	Pass by Option B

Tx Bands	Frequency (MHz)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Peak Antenna / Directional Gain (dBi)	ERP (mW)	LPE Level in Option A (mW)	LPE Level in Option B (mW)	LPE Level in Option C (mW)	Low-Power Exemption Verdict
WLAN 2.4 GHz	2412	26.68	466	2.6	510.50	N/A	3060	768	Pass by Option B
WLAN 5.2 GHz	5180	26.42	439	3.2	558.47	N/A	3060	768	Pass by Option B
WLAN 5.3 GHz	5260	26.42	439	3.1	544.50	N/A	3060	768	Pass by Option B
WLAN 5.6 GHz	5500	20.69	117	3.1	145.21	N/A	3060	768	Pass by Option B
WLAN 5.8 GHz	5745	29.77	948	2.8	1099.01	N/A	3060	768	Pass by Option B

Summary:

Since the maximum ERP of this device is less than the LPE level and this device is qualified for Low Power Exemption under the field reference level exposure exemption limits of §1.1310, the emitted RF fields will be incapable of producing exposures that exceed the exposure limits. Hence, this device complies with the reference levels and a complete MPE evaluation is not required.

4.3. Standalone Maximum Permissible Exposure Evaluation

Maximum Permissible Exposure Assessment Method:

Calculations can be made to predict RF field strength and power density levels around typical RF sources. For example, in the case of a single radiating antenna, a prediction for power density in the far-field of the antenna can be made by use of the general Equations below. This equation is generally accurate in the far-field of an antenna but will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction.

$$S_{eq} = \frac{P_{avg} \cdot G}{4 \cdot \pi \cdot R^2}$$

Where:

Seq = Equivalent Plane Wave Power Density in mW/cm².

Pavg = Average Power at Antenna Terminals in Watts.

G = Gain of the Transmitting Antenna.

R = Distance from the Transmitting Antenna in meters.

Evaluation for Standalone MPE:

The manufacturer expects that the radiated component of this device will not close to the human body during normal usage and the warning statement was also stated in the user instruction. Since the transmitting antenna will be kept at least **20 cm** away from the human body, the MPE level is calculated based on this condition and the result is listed in below table.

Tx Bands	Frequency (MHz)	EIRP (mW)	Separation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	MPE Compliance
LTE B2	1850.7	245.5	20	0.05	1.00	Pass
LTE B4	1710.7	298.5	20	0.06	1.00	Pass
LTE B5	824.7	197.7	20	0.04	0.55	Pass
LTE B7	2502.5	139.6	20	0.03	1.00	Pass
LTE B12	699.7	197.2	20	0.04	0.47	Pass
LTE B13	779.5	196.3	20	0.04	0.52	Pass
LTE B14	790.5	202.3	20	0.04	0.53	Pass
LTE B17	706.5	202.3	20	0.04	0.47	Pass
LTE B25	1850.7	245.5	20	0.05	1.00	Pass
LTE B26	814.7	197.7	20	0.04	0.54	Pass
LTE B30	2307.5	130.9	20	0.03	1.00	Pass
LTE B38	2572.5	279.3	20	0.06	1.00	Pass
LTE B41	2498.5	279.3	20	0.06	1.00	Pass
LTE B42	3552.5	271.6	20	0.05	1.00	Pass
LTE B43	3652.5	261.2	20	0.05	1.00	Pass
LTE B66	1710.7	298.5	20	0.06	1.00	Pass
LTE B71	665.5	177.8	20	0.04	0.44	Pass
5G NR n2	1852.5	266.1	20	0.05	1.00	Pass
5G NR n5	826.5	249.5	20	0.05	0.55	Pass
5G NR n7	2502.5	183.7	20	0.04	1.00	Pass
5G NR n12	701.5	250.6	20	0.05	0.47	Pass
5G NR n13	777	211.8	20	0.04	0.52	Pass
5G NR n14	790.5	257.6	20	0.05	0.53	Pass
5G NR n25	1852.5	235.0	20	0.05	1.00	Pass
5G NR n26	816.5	213.8	20	0.04	0.54	Pass
5G NR n30	2307.5	143.5	20	0.03	1.00	Pass
5G NR n38	2575	276.7	20	0.06	1.00	Pass
5G NR n41	2501.01	595.7	20	0.12	1.00	Pass
5G NR n48	3555	150.7	20	0.03	1.00	Pass
5G NR n66	1712.5	378.4	20	0.08	1.00	Pass
5G NR n70	1697.5	357.3	20	0.07	1.00	Pass
5G NR n71	665.5	231.7	20	0.05	0.44	Pass
5G NR n77	3455.01	580.8	20	0.12	1.00	Pass
5G NR n78	3455.01	580.8	20	0.12	1.00	Pass

Tx Bands	Frequency (MHz)	EIRP (mW)	Separation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)	MPE Compliance
WLAN 2.4 GHz	2412	510.5	20	0.102	1.00	Pass
WLAN 5.2 GHz	5180	558.5	20	0.111	1.00	Pass
WLAN 5.3 GHz	5260	544.5	20	0.108	1.00	Pass
WLAN 5.6 GHz	5500	145.2	20	0.029	1.00	Pass
WLAN 5.8 GHz	5745	1099.0	20	0.219	1.00	Pass

4.4. Total Exposure Ratio Evaluation for Simultaneous Transmission

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency.

$$\sum_{i=1}^{\infty} \frac{S_{eq,i}}{S_{Limit,i}} \leq 1$$

Where:

$S_{eq,i}$ = Power Density for the source i .

$S_{Limit,i}$ = Power Density Limit for the source i .

Evaluation for Simultaneous Exposure:

Tx Bands	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	Exposure Ratio
LTE B2	0.05	1.0	0.049
LTE B4	0.06	1.0	0.059
LTE B5	0.04	0.5	0.072
LTE B7	0.03	1.0	0.028
LTE B12	0.04	0.5	0.084
LTE B13	0.04	0.5	0.075
LTE B14	0.04	0.5	0.076
LTE B17	0.04	0.5	0.085
LTE B25	0.05	1.0	0.049
LTE B26	0.04	0.5	0.072
LTE B30	0.03	1.0	0.026
LTE B38	0.06	1.0	0.056
LTE B41	0.06	1.0	0.056
LTE B42	0.05	1.0	0.054
LTE B43	0.05	1.0	0.052
LTE B66	0.06	1.0	0.059
LTE B71	0.04	0.4	0.080
5G NR n2	0.05	1.0	0.053
5G NR n5	0.05	0.6	0.090
5G NR n7	0.04	1.0	0.037
5G NR n12	0.05	0.5	0.107
5G NR n13	0.04	0.5	0.081
5G NR n14	0.05	0.5	0.097
5G NR n25	0.05	1.0	0.047
5G NR n26	0.04	0.5	0.078
5G NR n30	0.03	1.0	0.029
5G NR n38	0.06	1.0	0.055
5G NR n41	0.12	1.0	0.119
5G NR n48	0.03	1.0	0.030
5G NR n66	0.08	1.0	0.075
5G NR n70	0.07	1.0	0.071
5G NR n71	0.05	0.4	0.104
5G NR n77	0.12	1.0	0.116
5G NR n78	0.12	1.0	0.116

Tx Bands	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	Exposure Ratio
WLAN 2.4 GHz	0.102	1.0	0.102
WLAN 5.2 GHz	0.111	1.0	0.111
WLAN 5.3 GHz	0.108	1.0	0.108
WLAN 5.6 GHz	0.029	1.0	0.029
WLAN 5.8 GHz	0.219	1.0	0.219

Tx 1	Tx 2	Total Exposure Ratio (<= 1)
WWAN	WLAN 2.4G	0.220
0.119	0.102	

Tx 1	Tx 2	Total Exposure Ratio (<= 1)
WWAN	WLAN 5G	0.337
0.119	0.219	

Conclusion:

Since the Maximum Permissible Exposure evaluation for standalone and simultaneous exposure is below the criteria of 47 CFR §1.1310, this device complies with FCC RF exposure requirements.

Since the summation of the ratio on worst condition comply the above formula; the simultaneous transmission operations also complies with the FCC restriction as specified in 47 CFR §1.1310.

Note:

The basic calculation formula is a conservative formula used to estimate RF field strength or power density. No uncertainty estimates are required when using these formulas. Determination of MPE compliance is based on calculation results and does not take measurement uncertainty into account.

***** End of Report *****