

## RF Exposure Evaluation declaration

Product Name : Wireless ADSL2/2+ Ethernet Router

Model No. : DSL-2600B, DSL-2640B, DSL-2600U, DSL-2640U

FCC ID KA2SL2600UT

Applicant : D-Link Corporation

Address : No. 289, Sinhu 3rd Road, Nei-Hu District, Taipei City, 114,  
Taiwan. R.O.C.

Date of Receipt : Nov. 02, 2006

Date of Declaration : Dec. 11, 2006

Report No. : 06BL040-RF-US-P05V01

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : Wireless ADSL2/2+ Ethernet Router  
 Test Item : RF Exposure Evaluation  
 Test Site : No.3 OATS

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.8dBi in linear scale.

#### 802.11b

##### Output Power Into Antenna & RF Exposure Evaluation Distance (1.8dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412.00	22.4388	0.4324
6	2437.00	22.4388	0.4324
11	2462.00	23.1739	0.4466

#### 802.11g

##### Output Power Into Antenna & RF Exposure Evaluation Distance (1.8dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20cm (mW/cm <sup>2</sup> )
1	2412.00	26.8534	0.5175
6	2437.00	25.9418	0.4999
11	2462.00	25.1768	0.4852

The distance r (4<sup>th</sup> column) calculated from the Friis transmission formula is far shorter than 20 cm separation requirement.