

## RF Exposure Evaluation declaration

Product Name : WIRELESS G ADSL2+ MODEM ROUTER  
Model No. : DSL-2640R, DSL-2641R, DSL-2640U/RRU  
FCC ID. : KA2SL2640RB1

Applicant : D-Link Corporation

Address : No.289, Sinhu 3rd Rd., Neihu District, Taipei City 114,  
Taiwan, R.O.C.

Date of Receipt : 2008/06/03

Date of Declaration : 2008/06/26

Report No. : 086124R-RF-US-Exp

Version : V1.0

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

**1.3. Test Result of RF Exposure Evaluation**

Product	WIRELESS G ADSL2+ MODEM ROUTER
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

**Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2dBi or 1.58 in linear scale.

**Output Power into Antenna & RF Exposure Evaluation Distance:**

IEEE 802.11b			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412.00	69.3426	0.0219
6	2437.00	82.6038	0.0260
11	2462.00	73.2825	0.0231

IEEE 802.11g			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412.00	47.7529	0.0151
6	2437.00	61.2350	0.0193
11	2462.00	51.6416	0.0163

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.