

# **RF Exposure Report**

Report No.: SA180430C11A

FCC ID: KA2SPT115AA1

Test Model: DSP-T115A

Received Date: Jul. 12, 2018

Date of Evaluation: Jul. 13, 2018

**Issued Date:** Jul. 17, 2018

**Applicant:** D-Link Corporation

Address: 289 Xinhu 3rd RD Neihu district Taipei Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan,

R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City

33383, Taiwan (R.O.C)

FCC Registration /

788550 / TW0003

**Designation Number:** 





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. Afailure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA180430C11A Page No. 1 / 6 Report Format Version: 6.1.1



## **Table of Contents**

Rele	ease Control Record	
1	Certificate of Conformity	4
	RF Exposure	
	.1 Limits for Maximum Permissible Exposure (MPE)	
2.	.2 MPE Calculation Formula	5
2.	.3 Classification	5
	.4 Antenna Gain	
2.	.5 Calculation Result Of Maximum Conducted Power	6

Report No.: SA180430C11A Page No. 2 / 6 Report Format Version: 6.1.1



### **Release Control Record**

Issue No.	Description	Date Issued
SA180430C11A	Original Release	Jul. 17, 2018

Report No.: SA180430C11A Page No. 3 / 6 Report Format Version: 6.1.1



### 1 Certificate of Conformity

Product: Bluetooth Smart Plug

**Brand:** D-Link Corporation

Test Model: DSP-T115A

Sample Status: Identicial Prototype

Applicant: D-Link Corporation

Date of Evaluation: Jul. 13, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : , Date: Jul. 17, 2018

Rona Chen / Specialist

Approved by : , Date: Jul. 17, 2018

Dylan Chiou / Project Engineer



### 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)					
	Limits For General Population / Uncontrolled Exposure								
0.3-1.34	614	1.63	(100)*	30					
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30					
30-300	27.5	0.073	0.2	30					
300-1500			f/1500	30					
1500-100,000			1.0	30					

f = Frequency in MHz; \*Plane-wave equivalent power density

#### 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

#### 2.4 Antenna Gain

PCB antenna with -1.30 dBi gain

Report No.: SA180430C11A Page No. 5 / 6 Report Format Version: 6.1.1



### 2.5 Calculation Result Of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
Bluetooth LE	5.18	3.296	-1.30	20	0.0005	1

Note: Above used Max. Output Power is Max. Tune-up Power.

--- END ---

Report No.: SA180430C11A Page No. 6 / 6 Report Format Version: 6.1.1