

Test Laboratory: Compliance Certification Services Inc.

## **D2450V2 SN-728 Body**

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:728**

Communication System: CW2450; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### **DASY4 Configuration:**

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Pin=250mW,d=10mm/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 14.2 mW/g

**Pin=250mW,d=10mm/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 97.6 V/m; Power Drift = -0.033 dB



Peak SAR (extrapolated) = 28.3 W/kg

**SAR(1 g) = 13.5 mW/g; SAR(10 g) = 6.19 mW/g**

Maximum value of SAR (measured) = 19.2 mW/g

**Pin=250mW,d=10mm/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 19.7 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **D2450V2 SN-728 Body**

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:728**

Communication System: CW2450; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2450$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 51.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg



DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection) Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Pin=250mW,d=10mm/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 14.4 mW/g

**Pin=250mW,d=10mm/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm,  
dy=7.5mm, dz=5mm  
Reference Value = 98.1 V/m; Power Drift = -0.054 dB  
Peak SAR (extrapolated) = 28.7 W/kg  
**SAR(1 g) = 13.7 mW/g; SAR(10 g) = 6.29 mW/g**  
Maximum value of SAR (measured) = 19.5 mW/g

**Pin=250mW,d=10mm/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm  
Maximum value of SAR (measured) = 19.9 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **D2450V2 SN-728 Body**

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:728**

Communication System: CW2450; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.94$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg



DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Pin=250mW,d=10mm/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 10.1 mW/g

**Pin=250mW,d=10mm/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 88.2 V/m; Power Drift = -0.103 dB  
Peak SAR (extrapolated) = 33.2 W/kg  
**SAR(1 g) = 14.1 mW/g; SAR(10 g) = 6.2 mW/g**  
Maximum value of SAR (measured) = 15.8 mW/g

**Pin=250mW,d=10mm/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm  
Maximum value of SAR (measured) = 15.9 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11b Tip Touch mode

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=1M/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.559 mW/g

**Middle CH, Rate=1M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 20.6 V/m; Power Drift = -0.022 dB



Peak SAR (extrapolated) = 1.53 W/kg

**SAR(1 g) = 0.587 mW/g; SAR(10 g) = 0.237 mW/g**

Maximum value of SAR (measured) = 0.827 mW/g

**Middle CH, Rate=1M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm

Maximum value of SAR (measured) = 0.525 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 802.11g Tip Touch mode

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6M/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.528 mW/g

**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 20.4 V/m; Power Drift = -0.009 dB



Peak SAR (extrapolated) = 1.55 W/kg

**SAR(1 g) = 0.581 mW/g; SAR(10 g) = 0.233 mW/g**

Maximum value of SAR (measured) = 0.829 mW/g

**Middle CH, Rate=6M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm

Maximum value of SAR (measured) = 0.522 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Tip Touch mode HT20

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Low CH, Rate=6.5M/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.354 mW/g


**Low CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 16.1 V/m; Power Drift = -0.004 dB

Peak SAR (extrapolated) = 0.894 W/kg

**SAR(1 g) = 0.355 mW/g; SAR(10 g) = 0.144 mW/g**

Maximum value of SAR (measured) = 0.517 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Tip Touch mode HT20

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.748 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.0 V/m; Power Drift = -0.003 dB



Peak SAR (extrapolated) = 1.83 W/kg

**SAR(1 g) = 0.724 mW/g; SAR(10 g) = 0.294 mW/g**

Maximum value of SAR (measured) = 1.04 mW/g

**Middle CH, Rate=6.5M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm

Maximum value of SAR (measured) = 0.633 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Tip Touch mode HT20

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**High CH, Rate=6.5M/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.658 mW/g


**High CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.4 V/m; Power Drift = -0.003 dB

Peak SAR (extrapolated) = 1.75 W/kg

**SAR(1 g) = 0.695 mW/g; SAR(10 g) = 0.280 mW/g**

Maximum value of SAR (measured) = 1.02 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Tip Touch mode HT40

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg



DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x5x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.895 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 21.8 V/m; Power Drift = -0.002 dB  
Peak SAR (extrapolated) = 1.63 W/kg  
**SAR(1 g) = 0.640 mW/g; SAR(10 g) = 0.259 mW/g**  
Maximum value of SAR (measured) = 0.920 mW/g

**Middle CH, Rate=6.5M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm  
Maximum value of SAR (measured) = 0.569 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 802.11b Bottom Face Touch mode

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=1M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.732 mW/g


**Middle CH, Rate=1M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 11.9 V/m; Power Drift = -0.016 dB

Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 0.585 mW/g; SAR(10 g) = 0.264 mW/g**

Maximum value of SAR (measured) = 0.828 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11g Bottom Face Touch mode

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C


Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.630 mW/g

**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 11.3 V/m; Power Drift = -0.018 dB  
Peak SAR (extrapolated) = 1.13 W/kg  
**SAR(1 g) = 0.512 mW/g; SAR(10 g) = 0.236 mW/g**  
Maximum value of SAR (measured) = 0.716 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Bottom Face Touch mode HT20

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C


Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.892 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 11.0 V/m; Power Drift = -0.039 dB  
Peak SAR (extrapolated) = 1.46 W/kg  
**SAR(1 g) = 0.663 mW/g; SAR(10 g) = 0.306 mW/g**  
Maximum value of SAR (measured) = 0.933 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Bottom Face Touch mode HT40

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C


Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.633 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 11.3 V/m; Power Drift = -0.034 dB  
Peak SAR (extrapolated) = 1.15 W/kg  
**SAR(1 g) = 0.515 mW/g; SAR(10 g) = 0.237 mW/g**  
Maximum value of SAR (measured) = 0.731 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11b Side Touch mode

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C


Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=1M 2/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.173 mW/g

**Middle CH, Rate=1M 2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 6.14 V/m; Power Drift = -0.129 dB  
Peak SAR (extrapolated) = 0.318 W/kg  
**SAR(1 g) = 0.133 mW/g; SAR(10 g) = 0.060 mW/g**  
Maximum value of SAR (measured) = 0.198 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11g Side Touch mode

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg


DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.214 mW/g

**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 7.52 V/m; Power Drift = -0.010 dB  
Peak SAR (extrapolated) = 0.331 W/kg  
**SAR(1 g) = 0.149 mW/g; SAR(10 g) = 0.071 mW/g**  
Maximum value of SAR (measured) = 0.210 mW/g

**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 7.52 V/m; Power Drift = -0.010 dB  
Peak SAR (extrapolated) = 0.231 W/kg  
**SAR(1 g) = 0.108 mW/g; SAR(10 g) = 0.054 mW/g**  
Maximum value of SAR (measured) = 0.150 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Side Touch mode HT20

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:


- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.235 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 7.18 V/m; Power Drift = -0.064 dB  
Peak SAR (extrapolated) = 0.405 W/kg  
**SAR(1 g) = 0.174 mW/g; SAR(10 g) = 0.081 mW/g**  
Maximum value of SAR (measured) = 0.254 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 7.18 V/m; Power Drift = -0.064 dB  
Peak SAR (extrapolated) = 0.284 W/kg  
**SAR(1 g) = 0.131 mW/g; SAR(10 g) = 0.064 mW/g**  
Maximum value of SAR (measured) = 0.184 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 802.11n Side Touch mode HT40

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.5 deg C; Liquid Temperature: 23.5 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg


DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.165 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 6.26 V/m; Power Drift = -0.064 dB  
Peak SAR (extrapolated) = 0.316 W/kg  
**SAR(1 g) = 0.143 mW/g; SAR(10 g) = 0.068 mW/g**  
Maximum value of SAR (measured) = 0.205 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 6.26 V/m; Power Drift = -0.064 dB  
Peak SAR (extrapolated) = 0.219 W/kg  
**SAR(1 g) = 0.104 mW/g; SAR(10 g) = 0.052 mW/g**  
Maximum value of SAR (measured) = 0.145 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11b Tip Touch mode dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=1M/Area Scan (5x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.844 mW/g


**Middle CH, Rate=1M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 21.6 V/m; Power Drift = -0.001 dB

Peak SAR (extrapolated) = 1.51 W/kg

**SAR(1 g) = 0.577 mW/g; SAR(10 g) = 0.245 mW/g**

Maximum value of SAR (measured) = 0.852 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11g Tip Touch mode dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6M/Area Scan (5x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.799 mW/g


**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.5 V/m; Power Drift = -0.006 dB

Peak SAR (extrapolated) = 1.52 W/kg

**SAR(1 g) = 0.573 mW/g; SAR(10 g) = 0.239 mW/g**

Maximum value of SAR (measured) = 0.826 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Tip Touch mode HT20 dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Low CH, Rate=6.5M/Area Scan (5x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.695 mW/g


**Low CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 20.0 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 1.30 W/kg

**SAR(1 g) = 0.521 mW/g; SAR(10 g) = 0.215 mW/g**

Maximum value of SAR (measured) = 0.732 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Tip Touch mode HT20 dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.972 mW/g


**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.0 V/m; Power Drift = -0.008 dB

Peak SAR (extrapolated) = 1.73 W/kg

**SAR(1 g) = 0.689 mW/g; SAR(10 g) = 0.286 mW/g**

Maximum value of SAR (measured) = 1.01 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Tip Touch mode HT20 dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 51.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**High CH, Rate=6.5M/Area Scan (5x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.14 mW/g


**High CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 24.8 V/m; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 2.02 W/kg

**SAR(1 g) = 0.813 mW/g; SAR(10 g) = 0.339 mW/g**

Maximum value of SAR (measured) = 1.19 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 802.11n Tip Touch mode HT40 dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C


Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x5x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.836 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 21.0 V/m; Power Drift = -0.014 dB  
Peak SAR (extrapolated) = 1.45 W/kg  
**SAR(1 g) = 0.583 mW/g; SAR(10 g) = 0.242 mW/g**  
Maximum value of SAR (measured) = 0.848 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11b Bottom Face Touch mode dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Low CH, Rate=1M/Area Scan (5x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.26 mW/g


**Low CH, Rate=1M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.1 V/m; Power Drift = -0.009 dB

Peak SAR (extrapolated) = 2.20 W/kg

**SAR(1 g) = 0.980 mW/g; SAR(10 g) = 0.448 mW/g**

Maximum value of SAR (measured) = 1.37 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11b Bottom Face Touch mode dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=1M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.19 mW/g


**Middle CH, Rate=1M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.8 V/m; Power Drift = -0.052 dB

Peak SAR (extrapolated) = 2.08 W/kg

**SAR(1 g) = 0.947 mW/g; SAR(10 g) = 0.442 mW/g**

Maximum value of SAR (measured) = 1.32 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11b Bottom Face Touch mode dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 51.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**High CH, Rate=1M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.35 mW/g

**High CH, Rate=1M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 14.4 V/m; Power Drift = -0.017 dB



Peak SAR (extrapolated) = 2.41 W/kg

**SAR(1 g) = 1.060 mW/g; SAR(10 g) = 0.485 mW/g**

Maximum value of SAR (measured) = 1.50 mW/g

**High CH, Rate=1M/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 0.548 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11g Bottom Face Touch mode dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Low CH, Rate=6M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.48 mW/g


**Low CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 13.7 V/m; Power Drift = -0.005 dB

Peak SAR (extrapolated) = 2.38 W/kg

**SAR(1 g) = 1.100 mW/g; SAR(10 g) = 0.510 mW/g**

Maximum value of SAR (measured) = 1.50 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11g Bottom Face Touch mode dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.99 mW/g

**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.7 V/m; Power Drift = -0.011 dB



Peak SAR (extrapolated) = 3.25 W/kg

**SAR(1 g) = 1.490 mW/g; SAR(10 g) = 0.688 mW/g**

Maximum value of SAR (measured) = 2.00 mW/g

**Middle CH, Rate=6M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm

Maximum value of SAR (measured) = 0.334 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 802.11g Bottom Face Touch mode dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 51.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**High CH, Rate=6M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.77 mW/g


**High CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.2 V/m; Power Drift = -0.018 dB

Peak SAR (extrapolated) = 2.93 W/kg

**SAR(1 g) = 1.300 mW/g; SAR(10 g) = 0.603 mW/g**

Maximum value of SAR (measured) = 1.76 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Bottom Face Touch mode HT20 dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Low CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.05 mW/g


**Low CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.1 V/m; Power Drift = -0.064 dB

Peak SAR (extrapolated) = 1.58 W/kg

**SAR(1 g) = 0.739 mW/g; SAR(10 g) = 0.349 mW/g**

Maximum value of SAR (measured) = 1.01 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **802.11n Bottom Face Touch mode HT20 dell**

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### **DASY4 Configuration:**

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M 3/Area Scan (5x8x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.97 mW/g

**Middle CH, Rate=6.5M 3/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.6 V/m; Power Drift = -0.031 dB



Peak SAR (extrapolated) = 3.24 W/kg

**SAR(1 g) = 1.540 mW/g; SAR(10 g) = 0.722 mW/g**

Maximum value of SAR (measured) = 2.12 mW/g

**Middle CH, Rate=6.5M 3/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm

Maximum value of SAR (measured) = 0.409 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Bottom Face Touch mode HT20 dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 51.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**High CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.30 mW/g


**High CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.9 V/m; Power Drift = -0.091 dB

Peak SAR (extrapolated) = 3.23 W/kg

**SAR(1 g) = 1.520 mW/g; SAR(10 g) = 0.715 mW/g**

Maximum value of SAR (measured) = 2.06 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Bottom Face Touch mode HT40 dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Low CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.631 mW/g


**Low CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.69 V/m; Power Drift = -0.014 dB

Peak SAR (extrapolated) = 1.00 W/kg

**SAR(1 g) = 0.473 mW/g; SAR(10 g) = 0.221 mW/g**

Maximum value of SAR (measured) = 0.641 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **802.11n Bottom Face Touch mode HT40 dell**

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg



### **DASY4 Configuration:**

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 1.71 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 18.1 V/m; Power Drift = -0.010 dB  
Peak SAR (extrapolated) = 2.80 W/kg  
**SAR(1 g) = 1.310 mW/g; SAR(10 g) = 0.617 mW/g**  
Maximum value of SAR (measured) = 1.78 mW/g

**Middle CH, Rate=6.5M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm  
Maximum value of SAR (measured) = 0.436 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 802.11n Bottom Face Touch mode HT40 dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 51.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**High CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.872 mW/g


**High CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.0 V/m; Power Drift = -0.030 dB

Peak SAR (extrapolated) = 1.36 W/kg

**SAR(1 g) = 0.643 mW/g; SAR(10 g) = 0.305 mW/g**

Maximum value of SAR (measured) = 0.863 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11b Side Touch mode dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C


Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=1M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.087 mW/g

**Middle CH, Rate=1M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 4.70 V/m; Power Drift = -0.026 dB  
Peak SAR (extrapolated) = 0.164 W/kg  
**SAR(1 g) = 0.073 mW/g; SAR(10 g) = 0.035 mW/g**  
Maximum value of SAR (measured) = 0.105 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11g Side Touch mode dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C


Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.090 mW/g

**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 4.75 V/m; Power Drift = -0.091 dB  
Peak SAR (extrapolated) = 0.170 W/kg  
**SAR(1 g) = 0.076 mW/g; SAR(10 g) = 0.037 mW/g**  
Maximum value of SAR (measured) = 0.108 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Side Touch mode HT20 dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C


Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.088 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 4.77 V/m; Power Drift = -0.102 dB  
Peak SAR (extrapolated) = 0.167 W/kg  
**SAR(1 g) = 0.075 mW/g; SAR(10 g) = 0.037 mW/g**  
Maximum value of SAR (measured) = 0.104 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Side Touch mode HT40 dell

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.1 deg C; Liquid Temperature: 23.2 deg C


Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.070 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 4.06 V/m; Power Drift = -0.046 dB  
Peak SAR (extrapolated) = 0.133 W/kg  
**SAR(1 g) = 0.060 mW/g; SAR(10 g) = 0.029 mW/g**  
Maximum value of SAR (measured) = 0.085 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11b Tip Touch mode sony

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=1M/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.616 mW/g

**Middle CH, Rate=1M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 18.3 V/m; Power Drift = -0.014 dB



Peak SAR (extrapolated) = 1.28 W/kg

**SAR(1 g) = 0.477 mW/g; SAR(10 g) = 0.195 mW/g**

Maximum value of SAR (measured) = 0.696 mW/g

**Middle CH, Rate=1M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm

Maximum value of SAR (measured) = 0.397 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11g Tip Touch mode sony

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6M/Area Scan (5x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.525 mW/g

**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 16.2 V/m; Power Drift = -0.005 dB

Peak SAR (extrapolated) = 0.880 W/kg



**SAR(1 g) = 0.350 mW/g; SAR(10 g) = 0.150 mW/g**

Maximum value of SAR (measured) = 0.515 mW/g

**Middle CH, Rate=6M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm

Maximum value of SAR (measured) = 0.305 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 802.11n Tip Touch mode HT20 sony

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg



DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x6x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.537 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 16.3 V/m; Power Drift = -0.006 dB  
Peak SAR (extrapolated) = 0.915 W/kg  
**SAR(1 g) = 0.355 mW/g; SAR(10 g) = 0.153 mW/g**  
Maximum value of SAR (measured) = 0.512 mW/g

**Middle CH, Rate=6.5M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm  
Maximum value of SAR (measured) = 0.314 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Tip Touch mode HT40 sony

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C


Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x6x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.149 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 8.41 V/m; Power Drift = -0.061 dB  
Peak SAR (extrapolated) = 0.236 W/kg  
**SAR(1 g) = 0.102 mW/g; SAR(10 g) = 0.055 mW/g**  
Maximum value of SAR (measured) = 0.140 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11b Bottom Face Touch mode sony

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2472 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2472$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=1M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.490 mW/g


**Middle CH, Rate=1M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.40 V/m; Power Drift = -0.106 dB

Peak SAR (extrapolated) = 0.694 W/kg

**SAR(1 g) = 0.348 mW/g; SAR(10 g) = 0.178 mW/g**

Maximum value of SAR (measured) = 0.470 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11g Bottom Face Touch mode sony

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.420 mW/g


**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.83 V/m; Power Drift = -0.001 dB

Peak SAR (extrapolated) = 0.642 W/kg

**SAR(1 g) = 0.317 mW/g; SAR(10 g) = 0.162 mW/g**

Maximum value of SAR (measured) = 0.429 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **802.11n Bottom Face Touch mode HT20 sony**

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.507 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.01 V/m; Power Drift = -0.035 dB



Peak SAR (extrapolated) = 0.735 W/kg

**SAR(1 g) = 0.361 mW/g; SAR(10 g) = 0.180 mW/g**

Maximum value of SAR (measured) = 0.495 mW/g

**Middle CH, Rate=6.5M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm

Maximum value of SAR (measured) = 0.098 mW/g





Test Laboratory: Compliance Certification Services Inc.

## **802.11n Bottom Face Touch mode HT40 sony**

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg



DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.407 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 8.05 V/m; Power Drift = -0.040 dB  
Peak SAR (extrapolated) = 0.593 W/kg  
**SAR(1 g) = 0.291 mW/g; SAR(10 g) = 0.148 mW/g**  
Maximum value of SAR (measured) = 0.393 mW/g

**Middle CH, Rate=6.5M/Z Scan (1x1x26):** Measurement grid: dx=20mm, dy=20mm, dz=4mm  
Maximum value of SAR (measured) = 0.083 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11b Side Touch mode sony

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=1M/Area Scan (5x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.037 mW/g

**Middle CH, Rate=1M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 4.29 V/m; Power Drift = -0.006 dB

Peak SAR (extrapolated) = 0.055 W/kg

**SAR(1 g) = 0.028 mW/g; SAR(10 g) = 0.015 mW/g**

Maximum value of SAR (measured) = 0.033 mW/g


**Middle CH, Rate=1M/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 4.29 V/m; Power Drift = -0.006 dB

Peak SAR (extrapolated) = 0.055 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.010 mW/g**

Maximum value of SAR (measured) = 0.031 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11g Side Touch mode sony

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg


DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6M/Area Scan (5x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.035 mW/g

**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 4.09 V/m; Power Drift = -0.008 dB  
Peak SAR (extrapolated) = 0.050 W/kg  
**SAR(1 g) = 0.027 mW/g; SAR(10 g) = 0.015 mW/g**  
Maximum value of SAR (measured) = 0.036 mW/g

**Middle CH, Rate=6M/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 4.09 V/m; Power Drift = -0.008 dB  
Peak SAR (extrapolated) = 0.051 W/kg  
**SAR(1 g) = 0.019 mW/g; SAR(10 g) = 0.00895 mW/g**  
Maximum value of SAR (measured) = 0.028 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 802.11n Side Touch mode HT20 sony

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg


DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.037 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 3.88 V/m; Power Drift = -0.068 dB  
Peak SAR (extrapolated) = 0.056 W/kg  
**SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.015 mW/g**  
Maximum value of SAR (measured) = 0.038 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 3.88 V/m; Power Drift = -0.068 dB  
Peak SAR (extrapolated) = 0.049 W/kg  
**SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.010 mW/g**  
Maximum value of SAR (measured) = 0.031 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 802.11n Side Touch mode HT40 sony

**DUT: DWA-140; Type: Wireless USB Adapter; Serial: N/A**

Communication System: IEEE 802.11n WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.8 deg C; Liquid Temperature: 23.8 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV3 - SN3531; ConvF(7.88, 7.88, 7.88);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn500; Calibrated: 8/23/2006
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1150
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

**Middle CH, Rate=6.5M/Area Scan (5x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.035 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 3.55 V/m; Power Drift = -0.107 dB  
Peak SAR (extrapolated) = 0.052 W/kg  
**SAR(1 g) = 0.027 mW/g; SAR(10 g) = 0.014 mW/g**  
Maximum value of SAR (measured) = 0.036 mW/g

**Middle CH, Rate=6.5M/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm  
Reference Value = 3.55 V/m; Power Drift = -0.107 dB  
Peak SAR (extrapolated) = 0.058 W/kg  
**SAR(1 g) = 0.022 mW/g; SAR(10 g) = 0.00976 mW/g**  
Maximum value of SAR (measured) = 0.034 mW/g

