



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	D-Link Co.
Applicant Address	No.289, Shinhu 3rd Rd., Neihu District, Taipei City 114, Taiwan, R.O.C.
FCC ID	KA2WA160B1
Manufacturer's company	Alpha Networks Inc.
Manufacturer Address	1.No.8 Li-shing 7th Rd., Science-based Industrial Park, Hsinchu, Taiwan, R.O.C. 2.Jiekou Administration Zone, Canghan Town, Dongguan City, Guangdong Province, China

Product Name	Xtreme N Dual Band USB Adapter
Brand Name	D-Link
Model Name	DWA-160
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Nov. 26, 2007
Final Test Date	Feb. 02, 2008
Submission Type	Original Equipment
Operating Mode	Client (without radar detection function)



Statement

Test result included is only for the Draft n part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	7
3.6. Table for Testing Locations.....	8
3.7. Table for Supporting Units	8
3.8. Table for Parameters of Test Software Setting	8
3.9. Test Configurations	10
4. TEST RESULT	12
4.1. AC Power Line Conducted Emissions Measurement.....	12
4.2. Maximum Peak Output Power Measurement	16
4.3. Power Spectral Density Measurement	32
4.4. 6dB Spectrum Bandwidth Measurement	41
4.5. Radiated Emissions Measurement	50
4.6. Band Edge Emissions Measurement	78
4.7. Antenna Requirements	87
5. LIST OF MEASURING EQUIPMENTS	88
6. TEST LOCATION.....	89
7. TAF CERTIFICATE OF ACCREDITATION	90
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A11
APPENDIX B. TEST PHOTOS.....	B1 ~ B5



History of This Test Report

Original Issue Date: Feb. 25, 2008

Report No.: FR7D1705AC

No additional attachment.

Additional attachment were issued as following record:

Attachment No.	Issue Date	Description



1. CERTIFICATE OF COMPLIANCE

Product Name : Xtreme N Dual Band USB Adapter
Brand Name : D-Link
Model Name : DWA-160
Applicant : D-Link Co.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 26, 2007 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads "Wayne Hsu 2/25/08".

Wayne Hsu

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	6.24 dB
4.2	15.247(b)(3)	Maximum Peak Conducted Output Power	Complies	13.00 dB
4.3	15.247(e)	Power Spectral Density	Complies	18.34 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.31 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.15 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	see the below table for draft n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for Draft n
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11 for MCS8 20MHz bandwidth ; 7 for MCS8 40MHz bandwidth 3 for 11a MCS8 20MHz bandwidth ; 2 for 11a MCS8 40MHz bandwidth
Channel Band Width (99%)	MCS8 (20MHz) : 17.62 MHz ; MCS8 (40MHz) : 35.96 MHz 11a MCS8 (20MHz) : 17.59 MHz ; 11a MCS8 (40MHz) : 36.15 MHz
Conducted Output Power	MCS8 (20MHz) : 15.43 dBm ; MCS8 (40MHz) : 17.00 dBm 11a MCS8 (20MHz) : 15.79 MHz ; 11a MCS8 (40MHz) : 15.83 MHz
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)		Two (TX)	
	20 MHz	40 MHz	20 MHz	40 MHz
Draft n	X	X	V	V

Draft n spec

MCS Index	Nss	Modulation	R	NBPS	NCBPS		NDBPS		Data rate(Mbps)			
					800nsGI		20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
					20MHz	40MHz						
0	1	BPSK	$\frac{1}{2}$	1	52	108	26	54	6.5	13.5		
1	1	QPSK	$\frac{1}{2}$	2	104	216	52	108	13.0	27.0		
2	1	QPSK	$\frac{3}{4}$	2	104	216	78	162	19.5	40.5		
3	1	16-QAM	$\frac{1}{2}$	4	208	432	104	216	26.0	54.0		
4	1	16-QAM	$\frac{3}{4}$	4	208	432	156	324	39.0	81.0		
5	1	64-QAM	$\frac{2}{3}$	6	312	648	208	432	52.0	108.0		
6	1	64-QAM	$\frac{3}{4}$	6	312	648	234	486	58.5	121.5		
7	1	64-QAM	$\frac{5}{6}$	6	312	648	260	540	65.0	135.0		
8	2	BPSK	$\frac{1}{2}$	1	104	216	52	108	13.0	27.0		
9	2	QPSK	$\frac{1}{2}$	2	208	432	104	216	26.0	54.0		
10	2	QPSK	$\frac{3}{4}$	2	208	432	156	324	39.0	81.0		
11	2	16-QAM	$\frac{1}{2}$	4	416	864	208	432	52.0	108.0		
12	2	16-QAM	$\frac{3}{4}$	4	416	864	312	648	78.0	162.0		
13	2	64-QAM	$\frac{2}{3}$	6	624	1296	416	864	104.0	216.0		
14	2	64-QAM	$\frac{3}{4}$	6	624	1296	468	972	117.0	243.0		
15	2	64-QAM	$\frac{5}{6}$	6	624	1296	520	1080	130.0	270.0		

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPS	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories

Others
USB Cable: 1.4m, Shielded

3.3. Table for Filed Antenna

For 2.4GHz Band


Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
A	Wha Yu	N/A	Printed Antenna	N/A	2.27	TX / RX Ant.
B	Wha Yu	N/A	Printed Antenna	N/A	2.27	TX / RX Ant.

For 5GHz Band

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
A	Wha Yu	N/A	Printed Antenna	N/A	3.88	TX / RX Ant.
B	Wha Yu	N/A	Printed Antenna	N/A	3.88	TX / RX Ant.

Note : The EUT has two antennas.

Ant. A and Ant. B could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are two bandwidth systems for draft n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

There are two bandwidth systems for 11a draft n.

For both 20MHz bandwidth systems, use Channel 149, 157, 165.

For both 40MHz bandwidth systems, use Channel 151, 159.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz	149	5745 MHz	161	5805 MHz
	151	5755 MHz	165	5825 MHz
	153	5765 MHz		
	157	5785 MHz		
	159	5795 MHz		

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link / Mode 2	Auto	-	-
Maximum Peak Conducted Output Power	MCS8/20MHz	13 Mbps	1/6/11	A / B / A+B
	MCS8/40MHz	27 Mbps	3/6/9	A / B / A+B
	MCS8/20MHz	13 Mbps	149/157/165	A / B / A+B
	MCS8/40MHz	27 Mbps	151/159	A / B / A+B
Power Spectral Density 6dB Spectrum Bandwidth	MCS8/20MHz	13 Mbps	1/6/11	A+B
	MCS8/40MHz	27 Mbps	3/6/9	A+B
	MCS8/20MHz	13 Mbps	149/157/165	A+B
	MCS8/40MHz	27 Mbps	151/159	A+B
Radiated Emissions 9kHz~1GHz	Normal Link / Mode 2	Auto	-	-
Radiated Emissions 1GHz~10 th Harmonic	MCS8/20MHz	13 Mbps	1/6/11	A+B
	MCS8/40MHz	27 Mbps	3/6/9	A+B
	MCS8/20MHz	13 Mbps	149/157/165	A+B
	MCS8/40MHz	27 Mbps	151/159	A+B
Band Edge Emissions	MCS8/20MHz	13 Mbps	1/11	A+B
	MCS8/40MHz	27 Mbps	3/9	A+B
	MCS8/20MHz	13 Mbps	149/165	A+B
	MCS8/40MHz	27 Mbps	151/159	A+B

The following test modes were performed for all tests:

Mode 1: Dongle mode

Mode 2: Dongle +USB Cable mode

Cause "mode 2" generated the worst test result, it was reported as final data.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D400	E2K24GBRL
Mouse	QSKY	Lx-619B	DoC
Modem	ACEEX	DM1414	IFAXDM1414
Printer	EPSON	LQ-300	DoC
Wireless AP	Planex	GW-AP54SGX	DoC

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of Draft n MCS8 20MHz Ant. A+ Ant. B

Test Software Version	QA		
Frequency	2412 MHz	2437 MHz	2462 MHz
Draft n	08/07	07/07	06/06

Power Parameters of Draft n MCS8 40MHz Ant. A+ Ant. B

Test Software Version	QA		
Frequency	2422 MHz	2437 MHz	2452 MHz
Draft n	09/05	0A/0A	00/00

Power Parameters of 11a Draft n MCS8 20MHz Ant. A+ Ant. B

Test Software Version	QA		
Frequency	5745 MHz	5785 MHz	5825 MHz
Draft n	08/08	08/08	07/08

Power Parameters of 11a Draft n MCS8 40MHz Ant. A+ Ant. B

Test Software Version	QA	
Frequency	5755 MHz	5795 MHz
Draft n	08/08	08/09

An executive program, EMCTEST.EXE under WIN XP, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The NB sends " H " messages to the panel, and the panel displays " H " patterns on the screen.
- c. The NB sends " H " messages to the printer, then the printer prints them on the paper.
- d. The NB sends " H " messages to the modem.
- e. Repeat the steps from b to d.



At the same time, "QA" was executed to control the EUT continuously transmit RF signal.

Executed "ping.exe" to link with the remote workstation to receive and transmit signal by WLAN.


3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration


Test Configuration: 9KHz~1GHz



Test Configuration: above 1GHz



3.9.2. AC Power Line Conduction Emissions Test Configuration



AP

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	54%
Test Engineer	Cloud Peng	Phase	Line
Configuration	Mode 2		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.15080	43.16	-22.80	65.96	42.76	0.20	0.20	QP	LINE
2	0.15080	25.44	-30.52	55.96	25.04	0.20	0.20	AVERAGE	LINE
3	0.20289	52.89	-10.60	63.49	52.59	0.10	0.20	QP	LINE
4	0.20289	47.25	-6.24	53.49	46.95	0.10	0.20	AVERAGE	LINE
5	0.27009	43.02	-8.10	51.12	42.72	0.10	0.20	AVERAGE	LINE
6	0.27009	48.48	-12.64	61.12	48.18	0.10	0.20	QP	LINE
7	0.40400	34.15	-13.63	47.77	33.85	0.10	0.20	AVERAGE	LINE
8	0.40400	38.68	-19.10	57.77	38.38	0.10	0.20	QP	LINE
9	5.467	36.80	-13.20	50.00	36.48	0.02	0.30	AVERAGE	LINE
10	5.467	45.60	-14.40	60.00	45.28	0.02	0.30	QP	LINE
11	5.867	45.95	-14.05	60.00	45.62	0.03	0.30	QP	LINE
12	5.867	33.96	-16.04	50.00	33.63	0.03	0.30	AVERAGE	LINE

Temperature	23°C	Humidity	54%
Test Engineer	Cloud Peng	Phase	Neutral
Configuration	Mode 2		



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.20289	47.23	-6.26	53.49	46.83	0.20	0.20	AVERAGE	NEUTRAL
2	0.20289	52.68	-10.81	63.49	52.28	0.20	0.20	QP	NEUTRAL
3	0.27009	47.17	-13.95	61.12	46.80	0.17	0.20	QP	NEUTRAL
4	0.27009	42.33	-8.79	51.12	41.96	0.17	0.20	AVERAGE	NEUTRAL
5	0.40615	39.77	-17.96	57.73	39.47	0.10	0.20	QP	NEUTRAL
6	0.40615	35.07	-12.66	47.73	34.77	0.10	0.20	AVERAGE	NEUTRAL
7	5.551	37.82	-12.18	50.00	37.42	0.10	0.30	AVERAGE	NEUTRAL
8	5.551	46.96	-13.04	60.00	46.56	0.10	0.30	QP	NEUTRAL
9	5.683	50.08	-9.92	60.00	49.68	0.10	0.30	QP	NEUTRAL
10	5.683	39.31	-10.69	50.00	38.91	0.10	0.30	AVERAGE	NEUTRAL
11	5.813	50.87	-9.13	60.00	50.47	0.10	0.30	QP	NEUTRAL
12	5.813	39.43	-10.57	50.00	39.03	0.10	0.30	AVERAGE	NEUTRAL

Note:

$$\text{Level} = \text{Read Level} + \text{LISN Factor} + \text{Cable Loss}$$

4.2. Maximum Peak Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	Sample
Trace	Average
Sweep Time	Auto

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with FCC Conference Call, June 10, 2003.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Peak Output Power

Temperature	24°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	Draft n

Configuration Draft n MCS0 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	12.52	30.00	Complies
6	2437 MHz	12.25	30.00	Complies
11	2462 MHz	11.90	30.00	Complies

Configuration Draft n MCS0 20MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	12.06	30.00	Complies
6	2437 MHz	12.59	30.00	Complies
11	2462 MHz	11.89	30.00	Complies

Configuration Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	15.31	30.00	Complies
6	2437 MHz	15.43	30.00	Complies
11	2462 MHz	14.91	30.00	Complies

Configuration Draft n MCS0 40MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	12.64	30.00	Complies
6	2437 MHz	13.74	30.00	Complies
9	2452 MHz	9.01	30.00	Complies

Configuration Draft n MCS0 40MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	12.80	30.00	Complies
6	2437 MHz	14.23	30.00	Complies
9	2452 MHz	9.18	30.00	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	15.73	30.00	Complies
6	2437 MHz	17.00	30.00	Complies
9	2452 MHz	12.11	30.00	Complies

Temperature	23°C	Humidity	56%
Test Engineer	Barry Chen	Configurations	11a Draft n

Configuration 11a Draft n MCS8 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	12.98	30.00	Complies
157	5785 MHz	12.73	30.00	Complies
165	5825 MHz	10.98	30.00	Complies

Configuration 11a Draft n MCS8 20MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	12.56	30.00	Complies
157	5785 MHz	12.11	30.00	Complies
165	5825 MHz	11.13	30.00	Complies

Configuration 11a Draft n MCS8 20MHz Ant. A+ Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	15.79	30.00	Complies
157	5785 MHz	15.44	30.00	Complies
165	5825 MHz	14.07	30.00	Complies

Configuration 11a Draft n MCS8 40MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	12.54	30.00	Complies
159	5795 MHz	12.86	30.00	Complies


Configuration 11a Draft n MCS8 40MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	12.32	30.00	Complies
159	5795 MHz	12.78	30.00	Complies

Configuration 11a Draft n MCS8 40MHz Ant. A+ Ant. B


Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	15.44	30.00	Complies
159	5795 MHz	15.83	30.00	Complies

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. A / 2412 MHz




Date: 2.FEB.2008 09:54:30

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. A / 2437 MHz




Date: 2.FEB.2008 09:57:33

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. A / 2462 MHz




Date: 2.FEB.2008 09:59:36

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. B/ 2412 MHz




Date: 2.FEB.2008 09:53:59

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. B / 2437 MHz




Date: 2.FEB.2008 09:57:56

Channel Output Power Plot on Configuration Draft n MCS8 20MHz Ant. B / 2462 MHz




Date: 2.FEB.2008 09:59:09

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. A / 2422 MHz




Date: 2.FEB.2008 10:00:54

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. A / 2437 MHz




Date: 2.FEB.2008 10:03:40

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. A / 2452 MHz




Date: 2.FEB.2008 10:04:38

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. B/ 2422 MHz




Date: 2.FEB.2008 10:01:42

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. B / 2437 MHz




Date: 2.FEB.2008 10:03:02

Channel Output Power Plot on Configuration Draft n MCS8 40MHz Ant. B / 2452 MHz




Date: 2.FEB.2008 10:05:17

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. A / 5745 MHz




Date: 2.FEB.2008 09:31:45

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. A / 5785MHz




Date: 2.FEB.2008 09:32:43

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. A / 5825 MHz




Date: 2.FEB.2008 09:35:13

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. B / 5745 MHz




Date: 2.FEB.2008 09:30:56

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. B / 5785MHz



Date: 2.FEB.2008 09:33:19

Channel Output Power Plot on Configuration 11a Draft n MCS8 20MHz Ant. B / 5825 MHz




Date: 2.FEB.2008 09:36:05

Channel Output Power Plot on Configuration 11a Draft n MCS8 40MHz Ant. A / 5755 MHz



Date: 2.FEB.2008 09:12:21

Channel Output Power Plot on Configuration 11a Draft n MCS8 40MHz Ant. A / 5795 MHz



Date: 2.FEB.2008 09:13:32

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.
5. Measuring multiple antennas, the connector is required to link with spectrum analyzer through a combiner.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	24°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	Draft n

Configuration Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-11.37	8.00	Complies
6	2437 MHz	-10.34	8.00	Complies
11	2462 MHz	-10.46	8.00	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-11.67	8.00	Complies
6	2437 MHz	-10.54	8.00	Complies
9	2452 MHz	-15.39	8.00	Complies

Temperature	24°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	11a Draft n


Configuration 11a Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	-16.00	8.00	Complies
157	5785 MHz	-15.64	8.00	Complies
165	5827 MHz	-17.02	8.00	Complies

Configuration 11a Draft n MCS8 40MHz Ant. A + Ant. B


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	-18.99	8.00	Complies
159	5795 MHz	-17.62	8.00	Complies

Power Density Plot on Configuration Draft n MCS8 20MHz Ant. A + Ant. B / 2412 MHz




Date: 2.FEB.2008 12:13:34

Power Density Plot on Configuration Draft n MCS8 20MHz Ant. A + Ant. B / 2437 MHz




Date: 2.FEB.2008 12:15:09

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B / 2462 MHz




Date: 2.FEB.2008 12:16:20

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B / 2422 MHz




Date: 2.FEB.2008 10:15:35

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B / 2437 MHz




Date: 2.FEB.2008 10:13:41

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B / 2452 MHz




Date: 2.FEB.2008 10:12:22

Power Density Plot on Configuration 11a Draft n MCS8 20MHz Ant. A+ Ant. B / 5745 MHz




Date: 2.FEB.2008 11:36:32

Power Density Plot on Configuration 11a Draft n MCS8 20MHz Ant. A+ Ant. B / 5785 MHz




Date: 2.FEB.2008 11:41:21

Power Density Plot on Configuration 11a Draft n MCS8 20MHz Ant. A+ Ant. B / 5825 MHz




Date: 2.FEB.2008 11:46:08

Power Density Plot on Configuration 11a Draft n MCS8 40MHz Ant. A+ Ant. B / 5755MHz



Date: 2.FEB.2008 12:00:57

Power Density Plot on Configuration 11a Draft n MCS8 40MHz Ant. A+ Ant. B / 5795 MHz



Date: 2.FEB.2008 12:05:46

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.
4. Measuring multiple antennas, the connector is required to link with spectrum analyzer through a combiner.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	24°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	Draft n

Configuration Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.66	17.62	500	Complies
6	2437 MHz	17.62	17.62	500	Complies
11	2462 MHz	17.62	17.62	500	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.34	35.96	500	Complies
6	2437 MHz	36.08	35.89	500	Complies
9	2452 MHz	36.34	35.96	500	Complies

Temperature	24°C	Humidity	56%
Test Engineer	Jacky Ho	Configurations	11a Draft n


Configuration 11a Draft n MCS8 20MHz Ant. A+ Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.62	17.56	500	Complies
157	5785 MHz	17.66	17.59	500	Complies
165	5825 MHz	17.66	17.59	500	Complies

Configuration 11a Draft n MCS8 40MHz Ant. A+ Ant. B


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	36.41	36.15	500	Complies
159	5795 MHz	36.41	36.08	500	Complies

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. A + Ant. B / 2412 MHz




Date: 2.FEB.2008 12:13:08

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. A + Ant. B / 2437 MHz




Date: 2.FEB.2008 12:14:52

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. A + Ant. B / 2462 MHz




Date: 2.FEB.2008 12:16:04

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A + Ant. B / 2422 MHz




Date: 2.FEB.2008 10:15:10

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A + Ant. B / 2437 MHz




Date: 2.FEB.2008 10:13:15

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A + Ant. B / 2452 MHz




Date: 2.FEB.2008 10:11:56

6 dB Bandwidth Plot on Configuration 11a Draft n MCS8 20MHz Ant. A+ Ant. B / 5745 MHz




Date: 2.FEB.2008 11:32:42

6 dB Bandwidth Plot on Configuration 11a Draft n MCS8 20MHz Ant. A+ Ant. B / 5785MHz




Date: 2.FEB.2008 11:37:31


6 dB Bandwidth Plot on Configuration 11 a Draft n MCS8 20MHz Ant. A+ Ant. B / 5825 MHz



6 dB Bandwidth Plot on Configuration 11 a Draft n MCS8 40MHz Ant. A+ Ant. B / 5755MHz



6 dB Bandwidth Plot on Configuration 11a Draft n MCS8 40MHz Ant. 3+Ant. 5 / 5795 MHz



Date: 2.FEB.2008 12:01:56

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1000KHz / 1000KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	56%
Test Engineer	Jacky Ho		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	Normal Link / Mode 2

Horizontal



	Ereg	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	101.780	37.05	-6.45	43.50	55.74	11.52	1.50	31.71	Peak	400	-1	HORIZONTAL
2 @	366.590	37.35	-8.65	46.00	50.22	15.80	2.50	31.17	Peak	400	-1	HORIZONTAL
3 @	432.550	41.30	-4.70	46.00	52.44	16.99	2.83	30.96	Peak	400	-1	HORIZONTAL
4 @	699.300	40.10	-5.90	46.00	47.22	19.80	3.60	30.52	Peak	400	-1	HORIZONTAL
5 @	798.710	44.81	-1.20	46.00	50.50	20.68	3.80	30.18	QP	128	86	HORIZONTAL
6 @	835.100	36.74	-9.26	46.00	41.81	21.12	3.94	30.14	Peak	400	-1	HORIZONTAL

Vertical



	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
	MHz	dBUV/m	Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
			dB	dBUV/m	dBUV	dB/m	dB	dB		cm	deg
1	102.750	36.74	-6.76	43.50	55.27	11.68	1.50	31.72	Peak	400	-4 VERTICAL
2	451.950	37.91	-8.09	46.00	48.69	17.23	2.92	30.92	Peak	400	-4 VERTICAL
3	498.510	37.88	-8.12	46.00	47.66	17.87	3.28	30.94	Peak	400	-4 VERTICAL
4	699.300	42.76	-3.24	46.00	49.88	19.80	3.60	30.52	Peak	400	-4 VERTICAL
5	800.180	41.58	-4.42	46.00	47.26	20.70	3.80	30.18	Peak	400	-4 VERTICAL
6	898.150	41.00	-5.00	46.00	45.03	21.59	4.10	29.71	Peak	400	-4 VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)


Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	Draft n MCS8 20MHz Ch 1 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4822.720	33.92	-20.08	54.00	29.63	33.06	6.40	35.16	AVERAGE	100	126	HORIZONTAL
2	4824.940	47.28	-26.72	74.00	42.99	33.06	6.40	35.16	PEAK	100	126	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4825.400	38.38	-15.62	54.00	34.09	33.06	6.40	35.16	AVERAGE	129	301	VERTICAL
2	4829.200	49.22	-24.78	74.00	44.93	33.06	6.40	35.16	PEAK	129	301	VERTICAL


Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	Draft n MCS8 20MHz Ch 6 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4873.330	47.50	-26.50	74.00	43.08	33.16	6.42	35.15	PEAK	100	106	HORIZONTAL
2	4873.790	34.85	-19.15	54.00	30.43	33.16	6.42	35.15	AVERAGE	100	106	HORIZONTAL

Vertical




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4872.950	52.98	-21.02	74.00	48.55	33.16	6.42	35.15	PEAK	100	69	VERTICAL
2	4876.570	40.39	-13.61	54.00	35.96	33.16	6.42	35.15	AVERAGE	100	69	VERTICAL




Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	Draft n MCS8 20MHz Ch11 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4922.720	48.43	-25.57	74.00	43.88	33.26	6.44	35.14	PEAK	100	80	HORIZONTAL
2	4923.460	35.84	-18.16	54.00	31.29	33.26	6.44	35.14	AVERAGE	100	80	HORIZONTAL

Vertical




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4924.260	52.00	-22.00	74.00	47.45	33.26	6.44	35.14	PEAK	100	70	VERTICAL
2	4924.840	39.35	-14.65	54.00	34.79	33.26	6.44	35.14	AVERAGE	100	70	VERTICAL




Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	Draft n MCS8 40MHz Ch 3 Ant. A + Ant. B

Horizontal



	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	dB	dBuV/m	Level	Factor	Loss	Factor		Pos	Pos
					dBuV	dB/m	dB	dB		cm	deg
1	4841.810	42.94	-31.06	74.00	38.60	33.09	6.41	35.16	PEAK	125	0 HORIZONTAL
2	4846.460	33.43	-20.57	54.00	29.09	33.09	6.41	35.16	AVERAGE	125	0 HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4842.170	45.90	-28.10	74.00	41.56	33.09	6.41	35.16	PEAK	130	293	VERTICAL
2	4846.420	34.77	-19.23	54.00	30.44	33.09	6.41	35.16	AVERAGE	130	293	VERTICAL


Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	Draft n MCS8 40MHz Ch 6 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4872.240	50.41	-23.59	74.00	45.98	33.16	6.42	35.15	PEAK	109	145	HORIZONTAL
2	4876.500	38.24	-15.76	54.00	33.81	33.16	6.42	35.15	AVERAGE	109	145	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4872.530	50.19	-23.81	74.00	45.77	33.16	6.42	35.15	PEAK	110	295	VERTICAL
2	4876.500	39.28	-14.72	54.00	34.86	33.16	6.42	35.15	AVERAGE	110	295	VERTICAL


Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	Draft n MCS8 40MHz Ch 9 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4903.720	47.15	-26.85	74.00	42.64	33.23	6.43	35.15	PEAK	100	0	HORIZONTAL
2	4904.360	34.01	-19.99	54.00	29.50	33.23	6.43	35.15	AVERAGE	100	0	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4906.000	34.19	-19.81	54.00	29.68	33.23	6.43	35.15	AVERAGE	100	39	VERTICAL
2	4908.440	46.02	-27.98	74.00	41.51	33.23	6.43	35.15	PEAK	100	39	VERTICAL

Note:


The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	11a Draft n MCS8 20MHz CH 149 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB	cm	deg	
1	11483.760	62.06	-17.94	80.00	48.49	38.78	9.78	34.98	140	123	HORIZONTAL
2	11490.760	47.93	-12.07	60.00	34.36	38.78	9.78	34.98	140	123	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11483.480	71.04	-8.96	80.00	57.46	38.78	9.78	34.98	PEAK	115	282	VERTICAL
2	11491.120	57.26	-2.74	60.00	43.69	38.78	9.78	34.98	AVERAGE	115	282	VERTICAL


Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	1a Draft n MCS8 20MHz CH 157 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11563.440	58.35	-21.65	80.00	44.74	38.82	9.79	35.00	PEAK	100	141	HORIZONTAL
2	11569.000	50.19	-9.81	60.00	36.57	38.83	9.79	35.00	AVERAGE	100	141	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11569.240	59.69	-0.31	60.00	46.07	38.83	9.79	35.00	AVERAGE	113	283	VERTICAL
2	11572.400	70.01	-9.99	80.00	56.39	38.83	9.80	35.00	PEAK	113	283	VERTICAL


Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	11a Draft n MCS8 20MHz CH 165 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	11650.210	46.42	-13.58	60.00	32.76	38.86	9.82	35.01	AVERAGE	126	135	HORIZONTAL
2 @	11651.020	62.43	-17.57	80.00	48.76	38.86	9.82	35.01	PEAK	126	135	HORIZONTAL


Vertical



	Ereq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11647.850	68.53	-11.47	80.00	54.86	38.86	9.82	35.01	PEAK	115	117	VERTICAL
2	11650.110	50.66	-9.34	60.00	37.00	38.86	9.82	35.01	AVERAGE	115	117	VERTICAL


Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	11a Draft n MCS8 40MHz CH 151 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11511.020	61.48	-18.52	80.00	47.90	38.80	9.78	35.00	PEAK	134	316	HORIZONTAL
2	11512.500	49.11	-10.89	60.00	35.52	38.80	9.78	35.00	AVERAGE	134	316	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11510.810	49.21	-10.79	60.00	35.63	38.80	9.78	35.00	AVERAGE	111	205	VERTICAL
2	11511.090	63.39	-16.61	80.00	49.80	38.80	9.78	35.00	PEAK	111	205	VERTICAL


Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	11a Draft n MCS8 40MHz CH 159 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11586.520	53.85	-6.15	60.00	40.22	38.83	9.80	35.00	AVERAGE	122	22	HORIZONTAL
2	11594.080	67.76	-12.24	80.00	54.13	38.83	9.80	35.00	PEAK	122	22	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	11594.160	59.04	-0.96	60.00	45.41	38.83	9.80	35.00	AVERAGE	109	348	VERTICAL
2	11594.240	72.91	-7.09	80.00	59.27	38.83	9.80	35.00	PEAK	109	348	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	Draft n MCS8 20MHz Ch 1, 6, 11 Ant. A + Ant. B

Channel 1

	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
			Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2389.600	65.48	-8.52	74.00	33.18	28.17	4.13	0.00	PEAK	104	114 HORIZONTAL
2 @	2390.000	53.52	-0.48	54.00	21.19	28.17	4.15	0.00	AVERAGE	104	114 HORIZONTAL
3 ~	2419.200	98.90			66.52	28.21	4.18	0.00	PEAK	104	114 HORIZONTAL
4	2419.800	109.28			76.86	28.25	4.18	0.00	PEAK	104	114 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz

Channel 6

	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
			Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2439.200	110.42			77.95	28.29	4.18	0.00	PEAK	100	7 VERTICAL
2 @	2440.400	101.70			69.23	28.29	4.18	0.00	AVERAGE	100	7 VERTICAL

Item 1, 2 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
			Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	2468.400	109.17			76.62	28.32	4.23	0.00	PEAK	106	264 HORIZONTAL
2 @	2469.600	98.89			66.34	28.32	4.23	0.00	AVERAGE	106	264 HORIZONTAL
3 @	2483.500	53.79	-0.21	54.00	21.20	28.36	4.23	0.00	AVERAGE	106	264 HORIZONTAL
4 @	2484.100	66.80	-7.20	74.00	34.21	28.36	4.23	0.00	PEAK	106	264 HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	Draft n MCS8 40MHz Ch 3, 6, 9 Ant. A + Ant. B

Channel 3

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 ☺	2389.600	65.73	-8.27	74.00	33.43	28.17	4.13	0.00	PEAK	100	33	HORIZONTAL
2 ☺	2390.000	53.85	-0.15	54.00	21.52	28.17	4.15	0.00	AVERAGE	100	33	HORIZONTAL
3 ☺	2412.000	105.16			72.80	28.21	4.15	0.00	PEAK	100	33	HORIZONTAL
4 ☺	2419.200	94.74			62.35	28.21	4.18	0.00	AVERAGE	100	33	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 ☺	2390.000	51.33	-2.67	54.00	19.00	28.17	4.15	0.00	AVERAGE	130	293	HORIZONTAL
2 ☺	2390.000	65.23	-8.77	74.00	32.91	28.17	4.15	0.00	PEAK	130	293	HORIZONTAL
3 ☺	2441.800	95.87			63.38	28.29	4.20	0.00	AVERAGE	130	293	HORIZONTAL
4 ☺	2442.200	108.00			75.51	28.29	4.20	0.00	PEAK	130	293	HORIZONTAL
5 ☺	2483.500	65.62	-8.38	74.00	33.03	28.36	4.23	0.00	PEAK	130	293	HORIZONTAL
6 ☺	2483.500	51.70	-2.30	54.00	19.11	28.36	4.23	0.00	AVERAGE	130	293	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 ☺	2442.800	89.85			57.36	28.29	4.20	0.00	AVERAGE	100	172	HORIZONTAL
2 ☺	2448.000	100.39			67.90	28.29	4.20	0.00	PEAK	100	172	HORIZONTAL
3 ☺	2483.500	52.58	-1.42	54.00	19.99	28.36	4.23	0.00	AVERAGE	100	172	HORIZONTAL
4 ☺	2484.700	64.22	-9.78	74.00	31.63	28.36	4.23	0.00	PEAK	100	172	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	11a Draft n MCS8 20MHz CH 149, 157, 165 Ant. A + Ant. B

Channel 149

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 ☺	5740.600	111.62			70.43	34.35	6.84	0.00	PEAK	128	179	VERTICAL
2 ☺	5741.200	101.04			59.86	34.35	6.84	0.00	AVERAGE	128	179	VERTICAL

Item 1, 2 are the fundamental frequency at 5745 MHz.

Channel 157

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 ☺	5789.200	101.57			60.35	34.36	6.86	0.00	AVERAGE	135	187	VERTICAL
2 ☺	5790.800	111.30			70.08	34.36	6.86	0.00	PEAK	135	187	VERTICAL

Item 1, 2 are the fundamental frequency at 5785 MHz.

Channel 165

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	5828.400	106.14			64.90	34.37	6.88	0.00	PEAK	103	210	VERTICAL
2 ☺	5829.200	95.58			54.34	34.37	6.88	0.00	AVERAGE	103	210	VERTICAL

Item 1, 2 are the fundamental frequency at 5825 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24°C	Humidity	56%
Test Engineer	Jax Chen	Configurations	11a Draft n MCS8 40MHz CH 151, 159 Ant. A + Ant. B

Channel 151

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 over	5739.800	91.15			49.97	34.35	6.84	0.00	AVERAGE	134	182	VERTICAL
2 over	5751.800	97.21			56.03	34.35	6.84	0.00	PEAK	134	182	VERTICAL

Item 1, 2 are the fundamental frequency at 5755 MHz.

Channel 159

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	5784.200	94.25			53.03	34.36	6.86	0.00	AVERAGE	128	180	VERTICAL
2	5805.000	104.34			63.12	34.36	6.86	0.00	PEAK	128	180	VERTICAL

Item 1, 2 are the fundamental frequency at 5795 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration Draft n MCS0 20MHz Ant. A + Ant. B/ 2412 MHz



Date: 2.FEB.2008 12:13:43


High Band Edge Plot on Configuration Draft n MCS0 20MHz Ant. A + Ant. B/ 2462 MHz



Date: 2.FEB.2008 12:16:30


For Emission not in Restricted Band

Low Band Edge Plot on Configuration Drafft n MCS0 40MHz Ant. A + Ant. B/ 2422 MHz




Date: 2.FEB.2008 10:15:46

High Band Edge Plot on Configuration Drafft n MCS0 40MHz Ant. A + Ant. B/ 2452 MHz




Date: 2.FEB.2008 10:12:31

Low Band Edge Plot on Configuration 11a Draft n MCS8 40MHz Ant. A + Ant. B/ 5755 MHz



Date: 2.FEB.2008 12:01:06

High Band Edge Plot on Configuration 11a Draft n MCS8 40MHz Ant. A + Ant. B/ 5795 MHz



Date: 2.FEB.2008 12:05:55

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Mar. 03, 2007	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2007	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2007	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2007	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz – 30MHz	Mar. 27, 2007	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2007	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 14, 2008	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jun. 07, 2007	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100305	9 kHz - 40 GHz	Sep. 27, 2007	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 21, 2007	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 04, 2007	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan. 18, 2008	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 10, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 27, 2007	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 04, 2007*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 03, 2007	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Jan. 14, 2008	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Jan. 04, 2008	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Jan. 04, 2008	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 14, 2007	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 07, 2007	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Note: Calibration Interval of instruments listed above is two year.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-070110

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix Accreditation Program for Designated Testing Laboratory for Commodities Inspection
Specific Accreditation Program	: Accreditation Program for Telecommunication Equipment Testing Laboratory



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 10, 2007

PI, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.