


# FCC Test Report

**Equipment** : 802.11n Dual-band Unified Access Point  
**Brand Name** : D-Link  
**Model No.** : DWL-6700AP  
**FCC ID** : KA2WL6700APA1  
**Standard** : 47 CFR FCC Part 15.247  
**Operating Band** : 2400 MHz – 2483.5 MHz  
**FCC Classification** : DTS  
**Applicant** : D-Link Corporation  
No. 289, Xinhua 3rd Rd., Neihu District, Taipei City 11494,  
Taiwan, R. O. C.

The product sample received on Sep. 04, 2014 and completely tested on Mar. 05, 2015. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

  
James Fan / Assistant Manager





## Table of Contents

|          |                                                   |              |
|----------|---------------------------------------------------|--------------|
| <b>1</b> | <b>GENERAL DESCRIPTION .....</b>                  | <b>3</b>     |
| 1.1      | Information.....                                  | 3            |
| 1.2      | Accessories and Support Equipment .....           | 3            |
| 1.3      | Testing Applied Standards .....                   | 3            |
| 1.4      | Testing Location Information .....                | 3            |
| 1.5      | Measurement Uncertainty .....                     | 3            |
| <b>2</b> | <b>TEST CONFIGURATION OF EUT.....</b>             | <b>3</b>     |
| 2.1      | The Worst Case Modulation Configuration .....     | 3            |
| 2.2      | Test Channel Frequencies Configuration.....       | 3            |
| 2.3      | The Worst Case Power Setting Parameter .....      | 3            |
| 2.4      | The Worst Case Measurement Configuration.....     | 3            |
| 2.5      | Test Setup Diagram .....                          | 3            |
| <b>3</b> | <b>TRANSMITTER TEST RESULT .....</b>              | <b>3</b>     |
| 3.1      | AC Power-line Conducted Emissions .....           | 3            |
| 3.2      | 6dB Bandwidth .....                               | 3            |
| 3.3      | RF Output Power.....                              | 3            |
| 3.4      | Power Spectral Density .....                      | 3            |
| 3.5      | Emissions in non-restricted frequency bands ..... | 3            |
| 3.6      | Transmitter Radiated Unwanted Emissions .....     | 3            |
| <b>4</b> | <b>TEST EQUIPMENT AND CALIBRATION DATA .....</b>  | <b>3</b>     |
|          | <b>APPENDIX A. TEST PHOTOS .....</b>              | <b>A1-A5</b> |

## Summary of Test Result

| Conformance Test Specifications |                  |                                                       |                                                                                |                                                                |          |
|---------------------------------|------------------|-------------------------------------------------------|--------------------------------------------------------------------------------|----------------------------------------------------------------|----------|
| Report Clause                   | Ref. Std. Clause | Description                                           | Measured                                                                       | Limit                                                          | Result   |
| 1.1.2                           | 15.203           | Antenna Requirement                                   | Antenna connector mechanism complied                                           | FCC 15.203                                                     | Complied |
| 3.1                             | 15.207           | AC Power-line Conducted Emissions                     | [dBuV]: 19.709MHz<br>47.26 (Margin 12.74dB) – QP<br>43.21 (Margin 6.79dB) – AV | FCC 15.207                                                     | Complied |
| 3.2                             | 15.247(a)        | 6dB Bandwidth                                         | 6dB Bandwidth [MHz]<br>20M: 9.57 / 40M: 35.13                                  | ≥500kHz                                                        | Complied |
| 3.3                             | 15.247(b)        | RF Output Power (Maximum Peak Conducted Output Power) | Power [dBm]: 29.98                                                             | Power [dBm]: 30                                                | Complied |
| 3.4                             | 15.247(e)        | Power Spectral Density                                | PSD [dBm/3kHz]: 2.43                                                           | PSD [dBm/3kHz]: 8                                              | Complied |
| 3.5                             | 15.247(d)        | Emissions in non-restricted frequency bands           | Out-of -band emissions are 20dB below the highest power                        | Non-Restricted Bands: > 20 dBc<br>Restricted Bands: FCC 15.209 | Complied |
| 3.6                             | 15.247(d)        | Transmitter Radiated Unwanted Emissions               | Restricted Bands [dBuV/m at 3m]: 2483.50MHz<br>73.00 (Margin 1.00dB) – PK      | Non-Restricted Bands: > 20 dBc<br>Restricted Bands: FCC 15.209 | Complied |





# 1 General Description

## 1.1 Information

This device has two versions for different sources of SAW filter for 2.4G RF part. Two versions were both tested in this test report.

### 1.1.1 RF General Information

| RF General Information |                  |                 |                |                                    |                       |
|------------------------|------------------|-----------------|----------------|------------------------------------|-----------------------|
| Frequency Range (MHz)  | IEEE Std. 802.11 | Ch. Freq. (MHz) | Channel Number | Transmit Chains (N <sub>TX</sub> ) | RF Output Power (dBm) |
| 2400-2483.5            | b                | 2412-2462       | 1-11 [11]      | 1 <sup>NOTE 4</sup>                | 24.90                 |
| 2400-2483.5            | b                | 2412-2462       | 1-11 [11]      | 2                                  | 26.53                 |
| 2400-2483.5            | g                | 2412-2462       | 1-11 [11]      | 1 <sup>NOTE 4</sup>                | 29.30                 |
| 2400-2483.5            | g                | 2412-2462       | 1-11 [11]      | 2                                  | 29.98                 |
| 2400-2483.5            | HT20             | 2412-2462       | 1-11 [11]      | 2                                  | 29.93                 |
| 2400-2483.5            | HT40             | 2422-2452       | 3-9 [7]        | 2                                  | 29.68                 |

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.  
Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.  
Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.  
Note 4: 802.11b/g supports 1Tx and 2Tx function. Only chain 0 transmits under 1Tx mode.

1.1.2 Antenna Information

| Antenna Category                    |                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | Integral antenna (antenna permanently attached)                                                                                                                                                                                                                                                                   |
| <input checked="" type="checkbox"/> | Temporary RF connector provided                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/>            | No temporary RF connector provided<br>Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path. |
| <input type="checkbox"/>            | External antenna (dedicated antennas)                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/>            | Single power level with corresponding antenna(s).                                                                                                                                                                                                                                                                 |
| <input type="checkbox"/>            | Multiple power level and corresponding antenna(s).                                                                                                                                                                                                                                                                |
| <input type="checkbox"/>            | RF connector provided                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/>            | Unique antenna connector. (e.g., MMCX, U.FL, IPX, and RP-SMA, RP-N type...)                                                                                                                                                                                                                                       |
| <input type="checkbox"/>            | Standard antenna connector. (e.g., SMA, N, BNC, and TNC type...)                                                                                                                                                                                                                                                  |

| Antenna General Information |       |           |                                                  |           |
|-----------------------------|-------|-----------|--------------------------------------------------|-----------|
| No.                         | Type  | Connector | Operating Frequencies (MHz) / Antenna Gain (dBi) |           |
|                             |       |           | 2400~2483.5                                      | 5150~5850 |
| 1                           | Chip  | N/A       | 2                                                | -         |
| 2                           | Patch | N/A       | -                                                | 8.08      |

1.1.3 Type of EUT

| Identify EUT                        |                                                                                                                                   |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| EUT Serial Number                   | N/A                                                                                                                               |
| Presentation of Equipment           | <input type="checkbox"/> Production ; <input checked="" type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype     |
| Type of EUT                         |                                                                                                                                   |
| <input checked="" type="checkbox"/> | Stand-alone                                                                                                                       |
| <input type="checkbox"/>            | Combined (EUT where the radio part is fully integrated within another device)<br>Combined Equipment - Brand Name / Model No.: ... |
| <input type="checkbox"/>            | Plug-in radio (EUT intended for a variety of host systems)<br>Host System - Brand Name / Model No.: ...                           |



1.1.4 Test Signal Duty Cycle

| Operated Mode for Worst Duty Cycle                                          |                                       |
|-----------------------------------------------------------------------------|---------------------------------------|
| <input type="checkbox"/> Operated normally mode for worst duty cycle        |                                       |
| <input checked="" type="checkbox"/> Operated test mode for worst duty cycle |                                       |
| Test Signal Duty Cycle (x)                                                  | Power Duty Factor [dB] – (10 log 1/x) |
| <input checked="" type="checkbox"/> 100.00% - IEEE 802.11b – 1Tx            | 0.00                                  |
| <input checked="" type="checkbox"/> 100.00% - IEEE 802.11b – 2Tx            | 0.00                                  |
| <input checked="" type="checkbox"/> 98.33% - IEEE 802.11g – 1Tx             | 0.07                                  |
| <input checked="" type="checkbox"/> 98.33% - IEEE 802.11g – 2Tx             | 0.07                                  |
| <input checked="" type="checkbox"/> 98.20% - IEEE 802.11n (HT20) – 2Tx      | 0.08                                  |
| <input checked="" type="checkbox"/> 96.84% - IEEE 802.11n (HT40) – 2Tx      | 0.14                                  |

1.1.5 EUT Operational Condition

|                   |                |
|-------------------|----------------|
| Power Supply Type | 24Vdc from POE |
|-------------------|----------------|

## 1.2 Accessories and Support Equipment

| Accessories |            |                                                                                                                                             |
|-------------|------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| No.         | Equipment  | Description                                                                                                                                 |
| 1           | POE        | Brand: GME.<br>Model: GFP241DA-240100HB<br>I/P: 100-240Vac, 50-60Hz, 0.55A<br>O/P: 24Vdc, 1A<br>Power line: 0.75m non-shielded without core |
| 2           | RJ45 Cable | 2m shielded w/o core.                                                                                                                       |

| Support Equipment |           |            |            |        |
|-------------------|-----------|------------|------------|--------|
| No.               | Equipment | Brand Name | Model Name | FCC ID |
| 1                 | Notebook  | DELL       | E5420      | DoC    |

## 1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15.247
- ◆ ANSI C63.10-2009
- ◆ FCC KDB 558074 D01 DTS Meas Guidance v03r02
- ◆ FCC KDB 662911 D01 Multiple Transmitter Output v02r01

Note: FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014

## 1.4 Testing Location Information

| Testing Location                                                                               |               |                                                                                                                    |                      |                         |
|------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------------------------------------------------------------------------|----------------------|-------------------------|
| <input checked="" type="checkbox"/>                                                            | HWA YA        | ADD : No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. |                      |                         |
|                                                                                                |               | TEL : 886-3-327-3456                                                                                               | FAX : 886-3-327-0973 |                         |
| Test Condition                                                                                 | Test Site No. | Test Engineer                                                                                                      | Test Environment     | Test Date               |
| RF Conducted                                                                                   | TH01-HY       | Aaron Liang                                                                                                        | 22°C / 62%           | Feb. 06 ~ Mar. 03, 2015 |
| AC Conduction                                                                                  | CO04-HY       | Skys Huang                                                                                                         | 22°C / 61%           | Jan. 27 ~ Mar. 05, 2015 |
| Radiated Emission                                                                              | 03CH03-HY     | Mark Liao                                                                                                          | 21-24°C / 65-68%     | Feb. 02 ~ Feb. 27, 2015 |
| Test site registered number [643075] with FCC<br>Test site registered number [4086B-1] with IC |               |                                                                                                                    |                      |                         |

## 1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

| Measurement Uncertainty           |               |             |       |
|-----------------------------------|---------------|-------------|-------|
| Test Item                         |               | Uncertainty | Limit |
| AC power-line conducted emissions |               | ±2.26 dB    | N/A   |
| Emission bandwidth, 6dB bandwidth |               | ±1.42 %     | N/A   |
| RF output power, conducted        |               | ±0.63 dB    | N/A   |
| Power density, conducted          |               | ±0.81 dB    | N/A   |
| Unwanted emissions, conducted     | 30 – 1000 MHz | ±0.51 dB    | N/A   |
|                                   | 1 – 18 GHz    | ±0.67 dB    | N/A   |
|                                   | 18 – 40 GHz   | ±0.83 dB    | N/A   |
|                                   | 40 – 200 GHz  | N/A         | N/A   |
| All emissions, radiated           | 30 – 1000 MHz | ±2.56 dB    | N/A   |
|                                   | 1 – 18 GHz    | ±3.59 dB    | N/A   |
|                                   | 18 – 40 GHz   | ±3.82 dB    | N/A   |
|                                   | 40 – 200 GHz  | N/A         | N/A   |
| Temperature                       |               | ±0.8 °C     | N/A   |
| Humidity                          |               | ±3 %        | N/A   |
| DC and low frequency voltages     |               | ±3 %        | N/A   |
| Time                              |               | ±1.42 %     | N/A   |
| Duty Cycle                        |               | ±1.42 %     | N/A   |

## 2 Test Configuration of EUT

### 2.1 The Worst Case Modulation Configuration

| Worst Modulation Used for Conformance Testing |                                    |                 |                       |
|-----------------------------------------------|------------------------------------|-----------------|-----------------------|
| Modulation Mode                               | Transmit Chains (N <sub>TX</sub> ) | Data Rate / MCS | Worst Data Rate / MCS |
| 11b                                           | 1                                  | 1-11 Mbps       | 1 Mbps                |
| 11b                                           | 2                                  | 1-11 Mbps       | 1 Mbps                |
| 11g                                           | 1                                  | 6-54 Mbps       | 6 Mbps                |
| 11g                                           | 2                                  | 6-54 Mbps       | 6 Mbps                |
| HT20                                          | 2                                  | MCS 0-15        | MCS 0                 |
| HT40                                          | 2                                  | MCS 0-15        | MCS 0                 |

### 2.2 Test Channel Frequencies Configuration

| Test Channel Frequencies Configuration |                                 |
|----------------------------------------|---------------------------------|
| IEEE Std. 802.11                       | Test Channel Frequencies (MHz)  |
| b, g, n (HT-20)                        | 2412-(F1), 2437-(F2), 2462-(F3) |
| n (HT-40)                              | 2422-(F4), 2437-(F5), 2452-(F6) |

### 2.3 The Worst Case Power Setting Parameter

Sample 01

| The Worst Case Power Setting Parameter (2400-2483.5MHz band) |                                         |                      |      |      |            |      |      |
|--------------------------------------------------------------|-----------------------------------------|----------------------|------|------|------------|------|------|
| Test Software                                                | ART2-GUI, Version: ver_4_6_78_ap13x_Bin |                      |      |      |            |      |      |
| Modulation Mode                                              | N <sub>TX</sub>                         | Test Frequency (MHz) |      |      |            |      |      |
|                                                              |                                         | NCB: 20MHz           |      |      | NCB: 40MHz |      |      |
|                                                              |                                         | 2412                 | 2437 | 2462 | 2422       | 2437 | 2452 |
| 11b,1-11Mbps                                                 | 1                                       | 22.5                 | 22   | 23   | --         | --   | --   |
| 11b,1-11Mbps                                                 | 2                                       | 21.5                 | 21.5 | 21.5 | --         | --   | --   |
| 11g,6-54Mbps                                                 | 1                                       | 21.5                 | 27   | 20.5 | --         | --   | --   |
| 11g,6-54Mbps                                                 | 2                                       | 19                   | 19   | 19.5 | --         | --   | --   |
| HT20,M0-15                                                   | 2                                       | 19.5                 | 19   | 19.5 | --         | --   | --   |
| HT40,M0-15                                                   | 2                                       | --                   | --   | --   | 18         | 18.5 | 17.5 |

Sample 02

| The Worst Case Power Setting Parameter (2400-2483.5MHz band) |                                         |                      |      |      |            |      |      |
|--------------------------------------------------------------|-----------------------------------------|----------------------|------|------|------------|------|------|
| Test Software                                                | ART2-GUI, Version: ver_4_6_78_ap13x_Bin |                      |      |      |            |      |      |
| Modulation Mode                                              | N <sub>TX</sub>                         | Test Frequency (MHz) |      |      |            |      |      |
|                                                              |                                         | NCB: 20MHz           |      |      | NCB: 40MHz |      |      |
|                                                              |                                         | 2412                 | 2437 | 2462 | 2422       | 2437 | 2452 |
| 11b,1-11Mbps                                                 | 1                                       | 22.5                 | 22.5 | 24   | --         | --   | --   |
| 11b,1-11Mbps                                                 | 2                                       | 22                   | 22.5 | 23.5 | --         | --   | --   |
| 11g,6-54Mbps                                                 | 1                                       | 21                   | 27   | 20   | --         | --   | --   |
| 11g,6-54Mbps                                                 | 2                                       | 20.5                 | 20   | 20   | --         | --   | --   |
| HT20,M0-15                                                   | 2                                       | 20.5                 | 20   | 20   | --         | --   | --   |
| HT40,M0-15                                                   | 2                                       | --                   | --   | --   | 18         | 19.5 | 19   |


## 2.4 The Worst Case Measurement Configuration

| The Worst Case Mode for Following Conformance Tests |                                                                                         |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------|
| <b>Tests Item</b>                                   | AC power-line conducted emissions                                                       |
| <b>Condition</b>                                    | AC power-line conducted measurement for line and neutral<br>Test Voltage: 120Vac / 60Hz |
| <b>Operating Mode</b>                               | Operating Mode Description                                                              |
| 1                                                   | Sample 01: AC Power & Radio link (WLAN)                                                 |
| 2                                                   | Sample 02: AC Power & Radio link (WLAN)                                                 |

| The Worst Case Mode for Following Conformance Tests |                                                       |
|-----------------------------------------------------|-------------------------------------------------------|
| <b>Tests Item</b>                                   | RF Output Power,6dB bandwidth, Power Spectral Density |
| <b>Test Condition</b>                               | Conducted measurement at transmit chains              |
| <b>Modulation Mode</b>                              | 11b,11g                                               |
| <b>Operating Mode</b>                               | Operating Mode Description                            |
| 1                                                   | Sample 01: 1Tx / Chain 0                              |
| 2                                                   | Sample 01: 2Tx                                        |
| 3                                                   | Sample 02: 1Tx / Chain 0                              |
| 4                                                   | Sample 02: 2Tx                                        |
| <b>Modulation Mode</b>                              | HT20, HT40                                            |
| <b>Operating Mode</b>                               | Operating Mode Description                            |
| 1                                                   | Sample 01: 2Tx                                        |
| 2                                                   | Sample 02: 2Tx                                        |

| <b>The Worst Case Mode for Following Conformance Tests</b> |                                                                                                                                                                                                                                                     |                                                                                     |                                                                                       |
|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Tests Item</b>                                          | Transmitter Radiated Unwanted Emissions<br>Transmitter Radiated Bandedge Emissions                                                                                                                                                                  |                                                                                     |                                                                                       |
| <b>Test Condition</b>                                      | Radiated measurement<br>If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type. |                                                                                     |                                                                                       |
| <b>User Position</b>                                       | <input checked="" type="checkbox"/> EUT will be placed in fixed position.                                                                                                                                                                           |                                                                                     |                                                                                       |
|                                                            | <input type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed three orthogonal planes. The worst planes are Y-plane                                                                       |                                                                                     |                                                                                       |
|                                                            | <input type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes. The worst planes is X.                                               |                                                                                     |                                                                                       |
| <b>Modulation Mode</b>                                     | 11b,11g                                                                                                                                                                                                                                             |                                                                                     |                                                                                       |
| <b>Operating Mode</b>                                      | <input checked="" type="checkbox"/> 1. Sample 01: 1Tx / Chain 0                                                                                                                                                                                     |                                                                                     |                                                                                       |
|                                                            | <input checked="" type="checkbox"/> 2. Sample 01: 2Tx                                                                                                                                                                                               |                                                                                     |                                                                                       |
|                                                            | <input checked="" type="checkbox"/> 3. Sample 02: 1Tx / Chain 0                                                                                                                                                                                     |                                                                                     |                                                                                       |
|                                                            | <input checked="" type="checkbox"/> 4. Sample 02: 2Tx                                                                                                                                                                                               |                                                                                     |                                                                                       |
| <b>Modulation Mode</b>                                     | HT20, HT40                                                                                                                                                                                                                                          |                                                                                     |                                                                                       |
| <b>Operating Mode</b>                                      | <input checked="" type="checkbox"/> 2. Sample 01: 2Tx                                                                                                                                                                                               |                                                                                     |                                                                                       |
|                                                            | <input checked="" type="checkbox"/> 4. Sample 02: 2Tx                                                                                                                                                                                               |                                                                                     |                                                                                       |
| <b>Orthogonal Planes of EUT</b>                            | <b>X Plane</b>                                                                                                                                                                                                                                      | <b>Y Plane</b>                                                                      | <b>Z Plane</b>                                                                        |
|                                                            |                                                                                                                                                                  |  |  |

## 2.5 Test Setup Diagram



### 3 Transmitter Test Result

#### 3.1 AC Power-line Conducted Emissions

##### 3.1.1 AC Power-line Conducted Emissions Limit

| AC Power-line Conducted Emissions Limit |            |           |
|-----------------------------------------|------------|-----------|
| Frequency Emission (MHz)                | Quasi-Peak | Average   |
| 0.15-0.5                                | 66 – 56 *  | 56 – 46 * |
| 0.5-5                                   | 56         | 46        |
| 5-30                                    | 60         | 50        |

Note 1: \* Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


##### 3.1.3 Test Procedures

| Test Method                                                                                                      |
|------------------------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions. |

##### 3.1.4 Test Setup




### 3.1.5 Test Result of AC Power-line Conducted Emissions





AC Power-line Conducted Emissions Result

|                |   |             |      |
|----------------|---|-------------|------|
| Operating Mode | 1 | Power Phase | Line |
|----------------|---|-------------|------|




|    | Freq      | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark  |
|----|-----------|-------|------------|------------|------------|-------------|------------|---------|
|    | MHz       | dBuV  | dB         | dBuV       | dBuV       | dB          | dB         |         |
| 1  | 0.1500000 | 34.49 | -21.51     | 56.00      | 34.12      | 0.03        | 0.34       | Average |
| 2  | 0.1500000 | 54.20 | -11.80     | 66.00      | 53.83      | 0.03        | 0.34       | QP      |
| 3  | 0.1632710 | 52.26 | -13.04     | 65.30      | 51.85      | 0.03        | 0.38       | QP      |
| 4  | 0.1632710 | 35.64 | -19.66     | 55.30      | 35.23      | 0.03        | 0.38       | Average |
| 5  | 0.3621020 | 43.77 | -14.91     | 58.68      | 43.16      | 0.03        | 0.58       | QP      |
| 6  | 0.3621020 | 37.28 | -11.40     | 48.68      | 36.67      | 0.03        | 0.58       | Average |
| 7  | 4.410     | 31.67 | -24.33     | 56.00      | 30.85      | 0.11        | 0.71       | QP      |
| 8  | 4.410     | 24.37 | -21.63     | 46.00      | 23.55      | 0.11        | 0.71       | Average |
| 9  | 19.516    | 39.19 | -20.81     | 60.00      | 38.17      | 0.31        | 0.71       | QP      |
| 10 | 19.516    | 36.21 | -13.79     | 50.00      | 35.19      | 0.31        | 0.71       | Average |
| 11 | 22.315    | 41.86 | -18.14     | 60.00      | 40.87      | 0.34        | 0.65       | QP      |
| 12 | 22.315    | 39.17 | -10.83     | 50.00      | 38.18      | 0.34        | 0.65       | Average |

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)



AC Power-line Conducted Emissions Result

|                |   |             |         |
|----------------|---|-------------|---------|
| Operating Mode | 2 | Power Phase | Neutral |
|----------------|---|-------------|---------|




|    | Freq      | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark  |
|----|-----------|-------|------------|------------|------------|-------------|------------|---------|
|    | MHz       | dBuV  | dB         | dBuV       | dBuV       | dB          | dB         |         |
| 1  | 0.1500000 | 35.81 | -20.19     | 56.00      | 35.45      | 0.02        | 0.34       | Average |
| 2  | 0.1500000 | 53.23 | -12.77     | 66.00      | 52.87      | 0.02        | 0.34       | QP      |
| 3  | 0.3640320 | 37.74 | -10.90     | 48.64      | 37.12      | 0.03        | 0.59       | Average |
| 4  | 0.3640320 | 44.10 | -14.54     | 58.64      | 43.48      | 0.03        | 0.59       | QP      |
| 5  | 3.960     | 33.27 | -22.73     | 56.00      | 32.48      | 0.09        | 0.70       | QP      |
| 6  | 3.960     | 26.74 | -19.26     | 46.00      | 25.95      | 0.09        | 0.70       | Average |
| 7  | 12.466    | 40.47 | -19.53     | 60.00      | 39.44      | 0.23        | 0.80       | QP      |
| 8  | 12.466    | 39.12 | -10.88     | 50.00      | 38.09      | 0.23        | 0.80       | Average |
| 9  | 19.709    | 47.26 | -12.74     | 60.00      | 46.23      | 0.32        | 0.71       | QP      |
| 10 | 19.709    | 43.21 | -6.79      | 50.00      | 42.18      | 0.32        | 0.71       | Average |
| 11 | 28.685    | 32.98 | -17.02     | 50.00      | 32.02      | 0.43        | 0.53       | Average |
| 12 | 28.685    | 35.88 | -24.12     | 60.00      | 34.92      | 0.43        | 0.53       | QP      |

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)



AC Power-line Conducted Emissions Result

|                |   |             |      |
|----------------|---|-------------|------|
| Operating Mode | 2 | Power Phase | Line |
|----------------|---|-------------|------|



Date: 2015-03-05

|    | Freq      | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark  |
|----|-----------|-------|------------|------------|------------|-------------|------------|---------|
|    | MHz       | dBuV  | dB         | dBuV       | dBuV       | dB          | dB         |         |
| 1  | 0.1500000 | 34.45 | -21.55     | 56.00      | 34.08      | 0.03        | 0.34       | Average |
| 2  | 0.1500000 | 54.70 | -11.30     | 66.00      | 54.33      | 0.03        | 0.34       | QP      |
| 3  | 0.3615320 | 37.49 | -11.20     | 48.69      | 36.88      | 0.03        | 0.58       | Average |
| 4  | 0.3615320 | 43.96 | -14.73     | 58.69      | 43.35      | 0.03        | 0.58       | QP      |
| 5  | 4.220     | 31.17 | -24.83     | 56.00      | 30.36      | 0.10        | 0.71       | QP      |
| 6  | 4.220     | 23.88 | -22.12     | 46.00      | 23.07      | 0.10        | 0.71       | Average |
| 7  | 12.500    | 42.29 | -17.71     | 60.00      | 41.26      | 0.23        | 0.80       | QP      |
| 8  | 12.500    | 37.30 | -12.70     | 50.00      | 36.27      | 0.23        | 0.80       | Average |
| 9  | 19.708    | 46.80 | -13.20     | 60.00      | 45.78      | 0.31        | 0.71       | QP      |
| 10 | 19.708    | 42.66 | -7.34      | 50.00      | 41.64      | 0.31        | 0.71       | Average |
| 11 | 28.685    | 33.23 | -16.77     | 50.00      | 32.28      | 0.42        | 0.53       | Average |
| 12 | 28.685    | 36.23 | -23.77     | 60.00      | 35.28      | 0.42        | 0.53       | QP      |

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

### 3.2 6dB Bandwidth

#### 3.2.1 6dB Bandwidth Limit

| 6dB Bandwidth Limit                                                |
|--------------------------------------------------------------------|
| <b>Systems using digital modulation techniques:</b>                |
| <input checked="" type="checkbox"/> 6 dB bandwidth $\geq$ 500 kHz. |


#### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.2.3 Test Procedures

| Test Method                                                                                                      |                                                                                                                                                                                       |
|------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> For the emission bandwidth shall be measured using one of the options below: |                                                                                                                                                                                       |
| <input checked="" type="checkbox"/>                                                                              | Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 8.1 Option 1 for 6 dB bandwidth measurement.                                                                             |
| <input type="checkbox"/>                                                                                         | Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 8.2 Option 2 for 6 dB bandwidth measurement.                                                                             |
| <input type="checkbox"/>                                                                                         | Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.                                                                                                                    |
| <input checked="" type="checkbox"/> For conducted measurement.                                                   |                                                                                                                                                                                       |
| <input checked="" type="checkbox"/>                                                                              | The EUT supports single transmit chain and measurements performed on this transmit chain.                                                                                             |
| <input type="checkbox"/>                                                                                         | The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.                                                                                   |
| <input checked="" type="checkbox"/>                                                                              | The EUT supports multiple transmit chains using options given below:                                                                                                                  |
| <input type="checkbox"/>                                                                                         | Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1.   |
| <input checked="" type="checkbox"/>                                                                              | Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains. |

#### 3.2.4 Test Setup





3.2.5 Test Result of Emission Bandwidth

Sample 01


| Emission Bandwidth Result |                 |             |                          |              |              |              |                 |              |              |              |
|---------------------------|-----------------|-------------|--------------------------|--------------|--------------|--------------|-----------------|--------------|--------------|--------------|
| Condition                 |                 |             | Emission Bandwidth (MHz) |              |              |              |                 |              |              |              |
| Modulation Mode           | N <sub>TX</sub> | Freq. (MHz) | 99% Bandwidth            |              |              |              | 6dB Bandwidth   |              |              |              |
|                           |                 |             | Chain-Port 1             | Chain-Port 2 | Chain-Port 3 | Chain-Port 4 | Chain-Port 1    | Chain-Port 2 | Chain-Port 3 | Chain-Port 4 |
| 11b                       | 1               | 2412        | 13.53                    | --           | --           | --           | 9.57            | --           | --           | --           |
| 11b                       | 1               | 2437        | 13.76                    | --           | --           | --           | 10.03           | --           | --           | --           |
| 11b                       | 1               | 2462        | 13.85                    | --           | --           | --           | 9.57            | --           | --           | --           |
| 11b                       | 2               | 2412        | 13.57                    | 13.45        | --           | --           | 10.09           | 10.09        | --           | --           |
| 11b                       | 2               | 2437        | 13.77                    | 13.91        | --           | --           | 10.09           | 10.09        | --           | --           |
| 11b                       | 2               | 2462        | 13.86                    | 13.64        | --           | --           | 10.03           | 9.57         | --           | --           |
| 11g                       | 1               | 2412        | 16.87                    | --           | --           | --           | 16.00           | --           | --           | --           |
| 11g                       | 1               | 2437        | 19.54                    | --           | --           | --           | 15.77           | --           | --           | --           |
| 11g                       | 1               | 2462        | 17.25                    | --           | --           | --           | 15.71           | --           | --           | --           |
| 11g                       | 2               | 2412        | 16.83                    | 16.58        | --           | --           | 16.06           | 16.35        | --           | --           |
| 11g                       | 2               | 2437        | 17.04                    | 16.93        | --           | --           | 15.77           | 16.35        | --           | --           |
| 11g                       | 2               | 2462        | 17.21                    | 16.73        | --           | --           | 16.35           | 15.71        | --           | --           |
| HT-20                     | 2               | 2412        | 17.93                    | 17.79        | --           | --           | 16.70           | 17.22        | --           | --           |
| HT-20                     | 2               | 2437        | 18.11                    | 18.12        | --           | --           | 17.33           | 17.39        | --           | --           |
| HT-20                     | 2               | 2462        | 18.32                    | 17.97        | --           | --           | 16.35           | 15.71        | --           | --           |
| HT-40                     | 2               | 2422        | 38.50                    | 37.48        | --           | --           | 36.41           | 36.41        | --           | --           |
| HT-40                     | 2               | 2437        | 37.96                    | 38.26        | --           | --           | 36.06           | 36.06        | --           | --           |
| HT-40                     | 2               | 2452        | 37.34                    | 37.02        | --           | --           | 35.59           | 35.13        | --           | --           |
| <b>Limit</b>              |                 |             | <b>N/A</b>               |              |              |              | <b>≥500 kHz</b> |              |              |              |
| <b>Result</b>             |                 |             | <b>Complied</b>          |              |              |              |                 |              |              |              |

Note 1: N<sub>TX</sub> = Number of Transmit Chains




Worst Emission Bandwidth Plots

99% Bandwidth



6dB Bandwidth






Sample 02

| Emission Bandwidth Result                           |                 |             |                          |              |              |              |                 |              |              |              |
|-----------------------------------------------------|-----------------|-------------|--------------------------|--------------|--------------|--------------|-----------------|--------------|--------------|--------------|
| Condition                                           |                 |             | Emission Bandwidth (MHz) |              |              |              |                 |              |              |              |
| Modulation Mode                                     | N <sub>TX</sub> | Freq. (MHz) | 99% Bandwidth            |              |              |              | 6dB Bandwidth   |              |              |              |
|                                                     |                 |             | Chain-Port 1             | Chain-Port 2 | Chain-Port 3 | Chain-Port 4 | Chain-Port 1    | Chain-Port 2 | Chain-Port 3 | Chain-Port 4 |
| 11b                                                 | 1               | 2412        | 13.83                    | --           | --           | --           | 10.09           | --           | --           | --           |
| 11b                                                 | 1               | 2437        | 13.79                    | --           | --           | --           | 10.09           | --           | --           | --           |
| 11b                                                 | 1               | 2462        | 13.83                    | --           | --           | --           | 10.09           | --           | --           | --           |
| 11b                                                 | 2               | 2412        | 13.88                    | 13.81        | --           | --           | 10.09           | 10.09        | --           | --           |
| 11b                                                 | 2               | 2437        | 13.89                    | 13.79        | --           | --           | 10.09           | 10.09        | --           | --           |
| 11b                                                 | 2               | 2462        | 13.86                    | 13.78        | --           | --           | 10.09           | 10.09        | --           | --           |
| 11g                                                 | 1               | 2412        | 17.14                    | --           | --           | --           | 16.35           | --           | --           | --           |
| 11g                                                 | 1               | 2437        | 23.13                    | --           | --           | --           | 16.35           | --           | --           | --           |
| 11g                                                 | 1               | 2462        | 17.09                    | --           | --           | --           | 16.35           | --           | --           | --           |
| 11g                                                 | 2               | 2412        | 17.07                    | 16.80        | --           | --           | 16.35           | 16.35        | --           | --           |
| 11g                                                 | 2               | 2437        | 17.07                    | 16.84        | --           | --           | 16.35           | 16.35        | --           | --           |
| 11g                                                 | 2               | 2462        | 16.99                    | 16.82        | --           | --           | 16.35           | 16.35        | --           | --           |
| HT-20                                               | 2               | 2412        | 18.09                    | 17.97        | --           | --           | 17.62           | 17.62        | --           | --           |
| HT-20                                               | 2               | 2437        | 18.12                    | 18.06        | --           | --           | 17.57           | 17.57        | --           | --           |
| HT-20                                               | 2               | 2462        | 18.04                    | 18.03        | --           | --           | 17.51           | 17.57        | --           | --           |
| HT-40                                               | 2               | 2422        | 38.18                    | 38.10        | --           | --           | 36.41           | 36.41        | --           | --           |
| HT-40                                               | 2               | 2437        | 38.24                    | 37.90        | --           | --           | 36.41           | 36.41        | --           | --           |
| HT-40                                               | 2               | 2452        | 38.12                    | 37.94        | --           | --           | 36.41           | 36.41        | --           | --           |
| <b>Limit</b>                                        |                 |             | <b>N/A</b>               |              |              |              | <b>≥500 kHz</b> |              |              |              |
| <b>Result</b>                                       |                 |             | <b>Complied</b>          |              |              |              |                 |              |              |              |
| Note 1: N <sub>TX</sub> = Number of Transmit Chains |                 |             |                          |              |              |              |                 |              |              |              |




Worst Emission Bandwidth Plots

99% Bandwidth



6dB Bandwidth



### 3.3 RF Output Power

#### 3.3.1 RF Output Power Limit

| RF Output Power Limit                                                                                                                                                                                    |                                                                                                 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <b>Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit</b>                                                                                                                       |                                                                                                 |
| <input checked="" type="checkbox"/> 2400-2483.5 MHz Band:                                                                                                                                                |                                                                                                 |
| <input checked="" type="checkbox"/>                                                                                                                                                                      | If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)                                        |
| <input checked="" type="checkbox"/>                                                                                                                                                                      | Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm  |
| <input type="checkbox"/>                                                                                                                                                                                 | Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm     |
| <input type="checkbox"/>                                                                                                                                                                                 | Smart antenna system (SAS):                                                                     |
| <input type="checkbox"/>                                                                                                                                                                                 | Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm                      |
| <input type="checkbox"/>                                                                                                                                                                                 | Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm                     |
| <input type="checkbox"/>                                                                                                                                                                                 | Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dBm |
| <b>e.i.r.p. Power Limit:</b>                                                                                                                                                                             |                                                                                                 |
| <input checked="" type="checkbox"/> 2400-2483.5 MHz Band                                                                                                                                                 |                                                                                                 |
| <input checked="" type="checkbox"/>                                                                                                                                                                      | Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)                                 |
| <input type="checkbox"/>                                                                                                                                                                                 | Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm            |
| <input type="checkbox"/>                                                                                                                                                                                 | Smart antenna system (SAS)                                                                      |
| <input type="checkbox"/>                                                                                                                                                                                 | Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm                               |
| <input type="checkbox"/>                                                                                                                                                                                 | Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm                              |
| <input type="checkbox"/>                                                                                                                                                                                 | Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm        |
| $P_{Out}$ = maximum peak conducted output power or maximum conducted output power in dBm,<br>$G_{TX}$ = the maximum transmitting antenna directional gain in dBi.<br>$P_{eirp}$ = e.i.r.p. Power in dBm. |                                                                                                 |


#### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

| Test Method                         |                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | Maximum Peak Conducted Output Power                                                                                                                                                                                                                                                                              |
| <input type="checkbox"/>            | Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.1.1 (RBW ≥ DTS BW).                                                                                                                                                                                                                               |
| <input checked="" type="checkbox"/> | Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.1.2 (Peak power meter)                                                                                                                                                                                                                            |
| <input checked="" type="checkbox"/> | Maximum Conducted Output Power ( Reference only)                                                                                                                                                                                                                                                                 |
| <input type="checkbox"/>            | Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.2.2.2 Method AVGSA-1 (spectral trace averaging).                                                                                                                                                                                                  |
| <input type="checkbox"/>            | Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.2.2.3 Method AVGSA-1 Alt. (slow sweep speed)                                                                                                                                                                                                      |
| <input type="checkbox"/>            | Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.2.2.4 Method AVGSA-2 (spectral trace averaging).                                                                                                                                                                                                  |
| <input type="checkbox"/>            | Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.2.2.5 Method AVGSA-2 Alt. (slow sweep speed)                                                                                                                                                                                                      |
|                                     | RF power meter and average over on/off periods with duty factor or gated trigger                                                                                                                                                                                                                                 |
| <input checked="" type="checkbox"/> | Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.2.3.2 Method AVGPM-G (using a gated RF average power meter)                                                                                                                                                                                       |
| <input checked="" type="checkbox"/> | For conducted measurement.                                                                                                                                                                                                                                                                                       |
| <input checked="" type="checkbox"/> | The EUT supports single transmit chain and measurements performed on this transmit chain.                                                                                                                                                                                                                        |
| <input type="checkbox"/>            | The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.                                                                                                                                                                                                              |
| <input checked="" type="checkbox"/> | The EUT supports multiple transmit chains using options given below:<br>Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them. |
| <input type="checkbox"/>            | If multiple transmit chains, EIRP calculation could be following as methods:<br>$P_{total} = P_1 + P_2 + \dots + P_n$<br>(calculated in linear unit [mW] and transfer to log unit [dBm])<br>$EIRP_{total} = P_{total} + DG$                                                                                      |

3.3.4 Test Setup





3.3.5 Directional Gain for Power Measurement

| Directional Gain (DG) Result   |          |                 |                 |      |                 |
|--------------------------------|----------|-----------------|-----------------|------|-----------------|
| Transmit Chains No.            |          | 1               | 2               | -    | -               |
| Maximum G <sub>ANT</sub> (dBi) |          | 2               | 2               | -    | -               |
| Modulation Mode                | DG (dBi) | N <sub>TX</sub> | N <sub>SS</sub> | STBC | Array Gain (dB) |
| 11b,1-11Mbps                   | 2        | 1               | 1               | -    | -               |
| 11b,1-11Mbps                   | 2        | 2               | 1               |      |                 |
| 11g,6-54Mbps                   | 2        | 1               | 1               |      |                 |
| 11g,6-54Mbps                   | 2        | 2               | 1               | -    | -               |
| HT20,M0-15                     | 2        | 2               | 1               | -    | -               |
| HT40,M0-15                     | 2        | 2               | 1               | -    | -               |



3.3.6 Test Result of Maximum Conducted Output Power

Sample 01

| Maximum Peak Conducted Output Power |                 |             |                       |              |              |              |              |             |          |            |            |
|-------------------------------------|-----------------|-------------|-----------------------|--------------|--------------|--------------|--------------|-------------|----------|------------|------------|
| Condition                           |                 |             | RF Output Power (dBm) |              |              |              |              |             |          |            |            |
| Modulation Mode                     | N <sub>TX</sub> | Freq. (MHz) | Chain Port 1          | Chain Port 2 | Chain Port 3 | Chain Port 4 | Sum Chain    | Power Limit | DG (dBi) | EIRP Power | EIRP Limit |
| 11b                                 | 1               | 2412        | 23.58                 | --           | --           | --           | 23.58        | 30.00       | 2.00     | 25.58      | 36.00      |
| 11b                                 | 1               | 2437        | 23.63                 | --           | --           | --           | 23.63        | 30.00       | 2.00     | 25.63      | 36.00      |
| 11b                                 | 1               | 2462        | 24.76                 | --           | --           | --           | 24.76        | 30.00       | 2.00     | 26.76      | 36.00      |
| 11b                                 | 2               | 2412        | 22.19                 | 22.73        | --           | --           | 25.48        | 30.00       | 2.00     | 27.48      | 36.00      |
| 11b                                 | 2               | 2437        | 23.09                 | 23.21        | --           | --           | 26.16        | 30.00       | 2.00     | 28.16      | 36.00      |
| 11b                                 | 2               | 2462        | 23.48                 | 23.45        | --           | --           | 26.48        | 30.00       | 2.00     | 28.48      | 36.00      |
| 11g                                 | 1               | 2412        | 27.85                 | --           | --           | --           | 27.85        | 30.00       | 2.00     | 29.85      | 36.00      |
| 11g                                 | 1               | 2437        | 29.03                 | --           | --           | --           | 29.03        | 30.00       | 2.00     | 31.03      | 36.00      |
| 11g                                 | 1               | 2462        | 27.54                 | --           | --           | --           | 27.54        | 30.00       | 2.00     | 29.54      | 36.00      |
| 11g                                 | 2               | 2412        | 26.55                 | 26.43        | --           | --           | 29.50        | 30.00       | 2.00     | 31.50      | 36.00      |
| 11g                                 | 2               | 2437        | 26.62                 | 26.95        | --           | --           | 29.80        | 30.00       | 2.00     | 31.80      | 36.00      |
| 11g                                 | 2               | 2462        | 26.58                 | 26.92        | --           | --           | 29.76        | 30.00       | 2.00     | 31.76      | 36.00      |
| HT-20                               | 2               | 2412        | 26.84                 | 26.93        | --           | --           | <b>29.90</b> | 30.00       | 2.00     | 31.90      | 36.00      |
| HT-20                               | 2               | 2437        | 26.43                 | 26.98        | --           | --           | 29.72        | 30.00       | 2.00     | 31.72      | 36.00      |
| HT-20                               | 2               | 2462        | 26.78                 | 26.43        | --           | --           | 29.62        | 30.00       | 2.00     | 31.62      | 36.00      |
| HT-40                               | 2               | 2422        | 24.55                 | 25.21        | --           | --           | 27.90        | 30.00       | 2.00     | 29.90      | 36.00      |
| HT-40                               | 2               | 2437        | 26.35                 | 26.78        | --           | --           | 29.58        | 30.00       | 2.00     | 31.58      | 36.00      |
| HT-40                               | 2               | 2452        | 26.19                 | 26.28        | --           | --           | 29.25        | 30.00       | 2.00     | 31.25      | 36.00      |
| <b>Result</b>                       |                 |             | <b>Complied</b>       |              |              |              |              |             |          |            |            |



Sample 02

| Maximum Peak Conducted Output Power |                 |             |                       |              |              |              |              |             |          |            |            |
|-------------------------------------|-----------------|-------------|-----------------------|--------------|--------------|--------------|--------------|-------------|----------|------------|------------|
| Condition                           |                 |             | RF Output Power (dBm) |              |              |              |              |             |          |            |            |
| Modulation Mode                     | N <sub>TX</sub> | Freq. (MHz) | Chain Port 1          | Chain Port 2 | Chain Port 3 | Chain Port 4 | Sum Chain    | Power Limit | DG (dBi) | EIRP Power | EIRP Limit |
| 11b                                 | 1               | 2412        | 23.22                 | --           | --           | --           | 23.22        | 30.00       | 2.00     | 25.22      | 36.00      |
| 11b                                 | 1               | 2437        | 23.52                 | --           | --           | --           | 23.52        | 30.00       | 2.00     | 25.52      | 36.00      |
| 11b                                 | 1               | 2462        | 24.90                 | --           | --           | --           | 24.90        | 30.00       | 2.00     | 26.90      | 36.00      |
| 11b                                 | 2               | 2412        | 22.21                 | 22.38        | --           | --           | 25.31        | 30.00       | 2.00     | 27.31      | 36.00      |
| 11b                                 | 2               | 2437        | 23.26                 | 23.05        | --           | --           | 26.17        | 30.00       | 2.00     | 28.17      | 36.00      |
| 11b                                 | 2               | 2462        | 23.32                 | 23.72        | --           | --           | 26.53        | 30.00       | 2.00     | 28.53      | 36.00      |
| 11g                                 | 1               | 2412        | 27.82                 | --           | --           | --           | 27.82        | 30.00       | 2.00     | 29.82      | 36.00      |
| 11g                                 | 1               | 2437        | 29.30                 | --           | --           | --           | 29.30        | 30.00       | 2.00     | 31.30      | 36.00      |
| 11g                                 | 1               | 2462        | 27.03                 | --           | --           | --           | 27.03        | 30.00       | 2.00     | 29.03      | 36.00      |
| 11g                                 | 2               | 2412        | 26.67                 | 27.11        | --           | --           | 29.91        | 30.00       | 2.00     | 31.91      | 36.00      |
| 11g                                 | 2               | 2437        | 26.72                 | 27.20        | --           | --           | <b>29.98</b> | 30.00       | 2.00     | 31.98      | 36.00      |
| 11g                                 | 2               | 2462        | 26.74                 | 27.03        | --           | --           | 29.90        | 30.00       | 2.00     | 31.90      | 36.00      |
| HT-20                               | 2               | 2412        | 26.65                 | 27.06        | --           | --           | 29.87        | 30.00       | 2.00     | 31.87      | 36.00      |
| HT-20                               | 2               | 2437        | 26.64                 | 27.15        | --           | --           | 29.91        | 30.00       | 2.00     | 31.91      | 36.00      |
| HT-20                               | 2               | 2462        | 26.67                 | 27.15        | --           | --           | 29.93        | 30.00       | 2.00     | 31.93      | 36.00      |
| HT-40                               | 2               | 2422        | 24.56                 | 24.95        | --           | --           | 27.77        | 30.00       | 2.00     | 29.77      | 36.00      |
| HT-40                               | 2               | 2437        | 26.39                 | 26.93        | --           | --           | 29.68        | 30.00       | 2.00     | 31.68      | 36.00      |
| HT-40                               | 2               | 2452        | 25.92                 | 26.42        | --           | --           | 29.19        | 30.00       | 2.00     | 31.19      | 36.00      |
| <b>Result</b>                       |                 |             | <b>Complied</b>       |              |              |              |              |             |          |            |            |



Sample 01

| Maximum Conducted (Average) Output Power |                 |             |                       |              |              |              |              |             |          |            |            |
|------------------------------------------|-----------------|-------------|-----------------------|--------------|--------------|--------------|--------------|-------------|----------|------------|------------|
| Condition                                |                 |             | RF Output Power (dBm) |              |              |              |              |             |          |            |            |
| Modulation Mode                          | N <sub>TX</sub> | Freq. (MHz) | Chain Port 1          | Chain Port 2 | Chain Port 3 | Chain Port 4 | Sum Chain    | Power Limit | DG (dBi) | EIRP Power | EIRP Limit |
| 11b                                      | 1               | 2412        | 21.19                 | --           | --           | --           | 21.19        | 30.00       | 2.00     | 23.19      | 36.00      |
| 11b                                      | 1               | 2437        | 21.22                 | --           | --           | --           | 21.22        | 30.00       | 2.00     | 23.22      | 36.00      |
| 11b                                      | 1               | 2462        | 22.33                 | --           | --           | --           | 22.33        | 30.00       | 2.00     | 24.33      | 36.00      |
| 11b                                      | 2               | 2412        | 19.88                 | 20.27        | --           | --           | 23.09        | 30.00       | 2.00     | 25.09      | 36.00      |
| 11b                                      | 2               | 2437        | 20.73                 | 20.81        | --           | --           | 23.78        | 30.00       | 2.00     | 25.78      | 36.00      |
| 11b                                      | 2               | 2462        | 21.12                 | 21.05        | --           | --           | 24.10        | 30.00       | 2.00     | 26.10      | 36.00      |
| 11g                                      | 1               | 2412        | 20.32                 | --           | --           | --           | 20.32        | 30.00       | 2.00     | 22.32      | 36.00      |
| 11g                                      | 1               | 2437        | 25.14                 | --           | --           | --           | <b>25.14</b> | 30.00       | 2.00     | 27.14      | 36.00      |
| 11g                                      | 1               | 2462        | 20.06                 | --           | --           | --           | 20.06        | 30.00       | 2.00     | 22.06      | 36.00      |
| 11g                                      | 2               | 2412        | 18.06                 | 17.85        | --           | --           | 20.97        | 30.00       | 2.00     | 22.97      | 36.00      |
| 11g                                      | 2               | 2437        | 18.11                 | 18.45        | --           | --           | 21.29        | 30.00       | 2.00     | 23.29      | 36.00      |
| 11g                                      | 2               | 2462        | 18.35                 | 18.11        | --           | --           | 21.24        | 30.00       | 2.00     | 23.24      | 36.00      |
| HT-20                                    | 2               | 2412        | 18.32                 | 18.04        | --           | --           | 21.19        | 30.00       | 2.00     | 23.19      | 36.00      |
| HT-20                                    | 2               | 2437        | 18.11                 | 18.35        | --           | --           | 21.24        | 30.00       | 2.00     | 23.24      | 36.00      |
| HT-20                                    | 2               | 2462        | 18.32                 | 18.02        | --           | --           | 21.18        | 30.00       | 2.00     | 23.18      | 36.00      |
| HT-40                                    | 2               | 2422        | 15.66                 | 16.05        | --           | --           | 18.87        | 30.00       | 2.00     | 20.87      | 36.00      |
| HT-40                                    | 2               | 2437        | 17.82                 | 18.06        | --           | --           | 20.95        | 30.00       | 2.00     | 22.95      | 36.00      |
| HT-40                                    | 2               | 2452        | 16.85                 | 17.78        | --           | --           | 20.35        | 30.00       | 2.00     | 22.35      | 36.00      |
| <b>Result</b>                            |                 |             | <b>Complied</b>       |              |              |              |              |             |          |            |            |

Note: AV power is for reference only.



Sample 02

| Maximum Conducted (Average) Output Power |                 |             |                       |              |              |              |              |             |          |            |            |
|------------------------------------------|-----------------|-------------|-----------------------|--------------|--------------|--------------|--------------|-------------|----------|------------|------------|
| Condition                                |                 |             | RF Output Power (dBm) |              |              |              |              |             |          |            |            |
| Modulation Mode                          | N <sub>TX</sub> | Freq. (MHz) | Chain Port 1          | Chain Port 2 | Chain Port 3 | Chain Port 4 | Sum Chain    | Power Limit | DG (dBi) | EIRP Power | EIRP Limit |
| 11b                                      | 1               | 2412        | 20.91                 | --           | --           | --           | 20.91        | 30.00       | 2.00     | 22.91      | 36.00      |
| 11b                                      | 1               | 2437        | 21.22                 | --           | --           | --           | 21.22        | 30.00       | 2.00     | 23.22      | 36.00      |
| 11b                                      | 1               | 2462        | 22.51                 | --           | --           | --           | 22.51        | 30.00       | 2.00     | 24.51      | 36.00      |
| 11b                                      | 2               | 2412        | 19.89                 | 20.02        | --           | --           | 22.97        | 30.00       | 2.00     | 24.97      | 36.00      |
| 11b                                      | 2               | 2437        | 20.96                 | 20.75        | --           | --           | 23.87        | 30.00       | 2.00     | 25.87      | 36.00      |
| 11b                                      | 2               | 2462        | 20.93                 | 21.30        | --           | --           | 24.13        | 30.00       | 2.00     | 26.13      | 36.00      |
| 11g                                      | 1               | 2412        | 19.73                 | --           | --           | --           | 19.73        | 30.00       | 2.00     | 21.73      | 36.00      |
| 11g                                      | 1               | 2437        | 25.08                 | --           | --           | --           | <b>25.08</b> | 30.00       | 2.00     | 27.08      | 36.00      |
| 11g                                      | 1               | 2462        | 18.88                 | --           | --           | --           | 18.88        | 30.00       | 2.00     | 20.88      | 36.00      |
| 11g                                      | 2               | 2412        | 18.11                 | 18.28        | --           | --           | 21.21        | 30.00       | 2.00     | 23.21      | 36.00      |
| 11g                                      | 2               | 2437        | 18.25                 | 18.20        | --           | --           | 21.24        | 30.00       | 2.00     | 23.24      | 36.00      |
| 11g                                      | 2               | 2462        | 18.21                 | 18.02        | --           | --           | 21.13        | 30.00       | 2.00     | 23.13      | 36.00      |
| HT-20                                    | 2               | 2412        | 18.25                 | 18.38        | --           | --           | 21.33        | 30.00       | 2.00     | 23.33      | 36.00      |
| HT-20                                    | 2               | 2437        | 18.13                 | 18.15        | --           | --           | 21.15        | 30.00       | 2.00     | 23.15      | 36.00      |
| HT-20                                    | 2               | 2462        | 18.18                 | 18.05        | --           | --           | 21.13        | 30.00       | 2.00     | 23.13      | 36.00      |
| HT-40                                    | 2               | 2422        | 15.85                 | 16.03        | --           | --           | 18.95        | 30.00       | 2.00     | 20.95      | 36.00      |
| HT-40                                    | 2               | 2437        | 17.92                 | 18.08        | --           | --           | 21.01        | 30.00       | 2.00     | 23.01      | 36.00      |
| HT-40                                    | 2               | 2452        | 17.48                 | 17.50        | --           | --           | 20.50        | 30.00       | 2.00     | 22.50      | 36.00      |
| <b>Result</b>                            |                 |             | <b>Complied</b>       |              |              |              |              |             |          |            |            |

Note: AV power is for reference only.

### 3.4 Power Spectral Density

#### 3.4.1 Power Spectral Density Limit

| Power Spectral Density Limit                                                       |
|------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> Power Spectral Density (PSD) $\leq$ 8 dBm/3kHz |


#### 3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.4.3 Test Procedures

| Test Method                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).                                                                                                                                   |
| <input checked="" type="checkbox"/> Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 10.2 Method PKPSD (RBW=3kHz; detector=peak)..                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/> Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 10.3 Method AVGPSD-1 (spectral trace averaging).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <input type="checkbox"/> Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 10.4 Method AVGPSD-1 Alt. (slow sweep speed)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <input type="checkbox"/> Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 10.5 Method AVGPSD-2 (spectral trace averaging).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <input type="checkbox"/> Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 10.6 Method AVGPSD-2 Alt. (slow sweep speed)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <input checked="" type="checkbox"/> For conducted measurement.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input checked="" type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <input checked="" type="checkbox"/> The EUT supports multiple transmit chains using options given below:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input checked="" type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the N <sub>TX</sub> output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace. |
| <input type="checkbox"/> Option 2: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.                                                                                                                                                                                                                                                                                                                                         |

### 3.4.4 Test Setup




### 3.4.5 Test Result of Power Spectral Density

Sample 01

| Power Spectral Density Result |                 |             |                                   |             |
|-------------------------------|-----------------|-------------|-----------------------------------|-------------|
| Condition                     |                 |             | Power Spectral Density (dBm/3kHz) |             |
| Modulation Mode               | N <sub>TX</sub> | Freq. (MHz) | Sum Chain                         | Power Limit |
| 11b                           | 1               | 2412        | -2.92                             | 8.00        |
| 11b                           | 1               | 2437        | -3.03                             | 8.00        |
| 11b                           | 1               | 2462        | -1.85                             | 8.00        |
| 11b                           | 2               | 2412        | -1.06                             | 8.00        |
| 11b                           | 2               | 2437        | -0.73                             | 8.00        |
| 11b                           | 2               | 2462        | 0.33                              | 8.00        |
| 11g                           | 1               | 2412        | -4.79                             | 8.00        |
| 11g                           | 1               | 2437        | 2.43                              | 8.00        |
| 11g                           | 1               | 2462        | -4.59                             | 8.00        |
| 11g                           | 2               | 2412        | -5.47                             | 8.00        |
| 11g                           | 2               | 2437        | -3.41                             | 8.00        |
| 11g                           | 2               | 2462        | -3.48                             | 8.00        |
| HT-20                         | 2               | 2412        | -5.18                             | 8.00        |
| HT-20                         | 2               | 2437        | -4.29                             | 8.00        |
| HT-20                         | 2               | 2462        | -3.97                             | 8.00        |
| HT-40                         | 2               | 2422        | -8.46                             | 8.00        |
| HT-40                         | 2               | 2437        | -6.65                             | 8.00        |
| HT-40                         | 2               | 2452        | -7.68                             | 8.00        |
| <b>Result</b>                 |                 |             | <b>Complied</b>                   |             |

Note: Test results for 2TX mode are bin-by-bin summing measured value of each TX port.






Sample 02

| Power Spectral Density Result |                 |             |                                   |             |
|-------------------------------|-----------------|-------------|-----------------------------------|-------------|
| Condition                     |                 |             | Power Spectral Density (dBm/3kHz) |             |
| Modulation Mode               | N <sub>TX</sub> | Freq. (MHz) | Sum Chain                         | Power Limit |
| 11b                           | 1               | 2412        | -3.35                             | 8.00        |
| 11b                           | 1               | 2437        | -3.75                             | 8.00        |
| 11b                           | 1               | 2462        | -1.78                             | 8.00        |
| 11b                           | 2               | 2412        | -1.63                             | 8.00        |
| 11b                           | 2               | 2437        | -1.11                             | 8.00        |
| 11b                           | 2               | 2462        | -0.23                             | 8.00        |
| 11g                           | 1               | 2412        | -5.46                             | 8.00        |
| 11g                           | 1               | 2437        | 1.63                              | 8.00        |
| 11g                           | 1               | 2462        | -5.60                             | 8.00        |
| 11g                           | 2               | 2412        | -4.44                             | 8.00        |
| 11g                           | 2               | 2437        | -3.76                             | 8.00        |
| 11g                           | 2               | 2462        | -3.33                             | 8.00        |
| HT-20                         | 2               | 2412        | -5.60                             | 8.00        |
| HT-20                         | 2               | 2437        | -4.31                             | 8.00        |
| HT-20                         | 2               | 2462        | -4.51                             | 8.00        |
| HT-40                         | 2               | 2422        | -8.60                             | 8.00        |
| HT-40                         | 2               | 2437        | -7.13                             | 8.00        |
| HT-40                         | 2               | 2452        | -8.19                             | 8.00        |
| <b>Result</b>                 |                 |             | <b>Complied</b>                   |             |

Note: Test results for 2TX mode are bin-by-bin summing measured value of each TX port.



### 3.5 Emissions in non-restricted frequency bands

#### 3.5.1 Emissions in non-restricted frequency bands limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

#### 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.5.3 Test Procedures


##### Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

##### Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

#### 3.5.4 Test Setup





#### 3.5.5 Test Result of Emissions in non-restricted frequency bands

This test item is performed on each TX output individually without summing or adding  $10 \log(N_{ANT})$  since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.

### 3.5.6 Test Result of Emissions in non-restricted frequency bands

Sample 01 / 802.11b – 1Tx












802.11b - 2Tx












802.11g - 1Tx












802.11g - 2Tx












802.11n HT20 – 2Tx












802.11n HT40 – 2Tx









Sample 02  
802.11b - 1Tx

