


# RF Exposure Evaluation Report

APPLICANT : D-Link Co.  
EQUIPMENT : 4G LTE Router  
BRAND NAME : D-Link  
MODEL NAME : DWR-922  
FCC ID : KA2WR922C3  
STANDARD : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

- 1. ADMINISTRATION DATA ..... 4**
  - 1.1. Testing Laboratory ..... 4
- 2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) ..... 4**
- 3. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS ..... 4**
- 4. RF EXPOSURE LIMIT INTRODUCTION ..... 5**
- 5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION ..... 6**
  - 5.1. Standalone Power Density Calculation ..... 6
  - 5.2. Collocated Power Density Calculation..... 6



**Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA6O0550	Rev. 01	Initial issue of report	Dec. 07, 2016

## **1. Administration Data**

### **1.1. Testing Laboratory**

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	D-Link Co.
Address	No.289, Sinhu 3rd Rd, Neihu District Taipei City 114 Taiwan

Manufacturer	
Company Name	Advance Multimedia Internet Technology Inc.
Address	No.28, Lane 31, Sec. 1, Huandong Rd., Sinshih District, Tainan City 74146, Taiwan (R.O.C.)

## **2. Description of Equipment Under Test (EUT)**

Product Feature & Specification	
EUT Type	4G LTE Router
Brand Name	D-Link
Model Name	DWR-922
FCC ID	KA2WR922C3
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz
Mode	802.11b/g/n HT20/HT40
HW Version	C3
EUT Stage	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## **3. Maximum RF average output power among production units**

Band / Mode	IEEE 802.11 Average Power (dBm)			
	11b	11g	HT20	HT40
2.4GHz Band	14.5	17.5	16.0	16.0



### 4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



### 5. Radio Frequency Radiation Exposure Evaluation

#### 5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Power Density / Limit
2.4GHz WLAN	2412.0	3.80	17.50	21.300	0.135	134.896	0.027	1.000	0.027

Note: For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band

#### 5.2. Collocated Power Density Calculation

WWAN Power Density / Limit	WLAN Power Density / Limit	Σ (Power Density / Limit) of WWAN+WLAN
0.424	0.027	0.451

Note:

- The WWAN wireless module (FCC ID: N7NMC7355) is also integrated into this host, and collocated power density calculation in above table.
- Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WWAN + WLAN.
- Considering the WWAN module collocation with the WLAN transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 2 collocated transmitters is compliant

### Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.