

DECLARATION OF COMPLIANCE FCC PART 24(E) EMC MEASUREMENTS

Test Lab

CELLTECH LABS INC.
Testing and Engineering Services
1955 Moss Court
Kelowna, B.C.
Canada V1Y 9L3
Phone: 250-448-7047
Fax: 250-448-7046
e-mail: info@celltechlabs.com
web site: www.celltechlabs.com

Applicant Information

ITRONIX CORPORATION
801 South Stevens Street
Spokane, WA 99210-0179

Rule Part(s):	FCC 47 CFR §24(E), §2; IC RSS-133 Issue 2
Test Procedure(s):	FCC 47 CFR §24(E), §2; IC RSS-133 Issue 2; ANSI TIA/EIA-603-A-2001
FCC Device Classification:	PCS Licensed Transmitter (PCB)
IC Device Classification:	2GHz Personal Communication Services
Device Type:	Rugged Handheld PC with Sierra Wireless AirCard 750 PCS GPRS Modem
FCC ID:	KBCIX100AC750
Model(s):	IX100
Tx Frequency Range:	1850.2 - 1909.8 MHz
Max. RF Output Power:	0.824 Watts EIRP (29.16 dBm)
Conducted Power Tested:	28.0 dBm (1850.2 MHz) 28.1 dBm (1880.0 MHz) 27.9 dBm (1909.8 MHz)
Modulation:	GMSK
Emission Designator:	300KGXW
Frequency Tolerance:	0.1 PPM
Antenna Type:	¼ Wave Helix
Battery Type:	7.4V Lithium-ion, 2.8Ah
Keypad Type(s):	Alpha-numeric & Numeric

This wireless portable device has demonstrated compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in FCC 47 CFR §24(E), §2, IC RSS-133 Issue 2, and ANSI TIA/EIA-603-A-2001.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc. The results and statements contained in this report pertain only to the device(s) evaluated.



Russell Pipe
Senior Compliance Technologist
Celltech Labs Inc.



TABLE OF CONTENTS		
1.1	SCOPE	3
2.1	GENERAL INFORMATION - §2.1033(a)	3
MEASUREMENT PROCEDURES & DATA		4-6
3.1	RF Output Power - §2.1046	4
4.1	Spurious Emissions at Antenna Terminal - §2.1051	4
5.1	Radiated Measurement Test Setup	4
6.1	Effective Isotropic Radiated Power Output - §24.232(b)	5
7.1	Field Strength of Spurious Radiation - §2.1053	6-7
8.1	Occupied Bandwidth - §2.1049, §24.238	8
9.1	Frequency Stability / Temperature Variation - §2.1055, §24.235	9
10.1	LIST OF TEST EQUIPMENT	10
11.1	CONCLUSION	11
APPENDIX A - TEST PLOTS		12
APPENDIX B - RADIATED TEST SETUP PHOTOGRAPHS		13

FCC PART 24(E) EMC MEASUREMENT REPORT

1.1 SCOPE

Measurement and determination of electromagnetic emissions (EME) from radio frequency devices for compliance with the technical rules and regulations of the Federal Communications Commission and Industry Canada.

2.1 GENERAL INFORMATION - §2.1033(a)

APPLICANT

ITRONIX CORPORATION
 801 South Stevens Street
 Spokane, WA 99210-0179

FCC ID	KBCIX100AC750
Model(s)	IX100
Serial No.	Pre-production
EUT Type	Rugged Handheld PC with Sierra Wireless AirCard 750 PCS GPRS PCMCIA Modem Card
Rule Part(s)	FCC 47 CFR §24(E), §2; IC RSS-133 Issue 2
FCC Classification	PCS Licensed Transmitter (PCB)
IC Classification	2GHz Personal Communication Services
Test Procedure(s)	FCC 47 CFR §24(E), §2 IC RSS-133 Issue 2 ANSI TIA/EIA-603-A-2001
Tx Frequency Range	1850.20 - 1909.80 MHz
Modulation	GMSK
Max. RF Output Power	0.824 Watts EIRP (29.16 dBm)
RF Conducted Output Power Tested	28.0 dBm (1850.2 MHz) 28.1 dBm (1880.0 MHz) 27.9 dBm (1909.8 MHz)
Emission Designator	300KGXW
Frequency Tolerance	0.1 PPM
Battery Type(s)	7.4V Lithium-ion, 2.8Ah
Antenna Type	¼ Wave Helix (Length: 54 mm)

3.1 RF OUTPUT POWER MEASUREMENT - §2.1046

The conducted power was measured with a Gigatronics 8650A Universal Power Meter using burst average power mode. An offset was entered into the power meter to correct for the losses of the attenuator and cable installed before the sensor input. The transmitter terminal was coupled to the power meter and the EUT was placed into test mode via internal software. All subsequent tests were performed using the same tune-up procedures.

Frequency (MHz)	Peak Power (dBm)
1850.2	28.01
1880.0	28.10
1909.8	27.93

4.1 SPURIOUS EMISSIONS AT ANTENNA TERMINAL - §2.1051

The EUT was tested in GPRS mode via internal software at a full rated power. An offset was entered into the power meter to correct for all losses of the attenuator and cable installed before the sensor input. The level of the carrier and the various conducted spurious frequencies were measured by means of a calibrated spectrum analyzer. The resolution bandwidth and video bandwidth were set to 1MHz. The spectrum was scanned from 10MHz to 20GHz at the low, medium, and high channels. The radio transmitter was operating at maximum output power. The antenna output terminal of the EUT was connected to the input of a 50Ω spectrum analyzer through a matched 30dB attenuator and coaxial cable. The reported emissions were below the specified limit of -13dBm. The test plots are shown in Appendix A.

5.1 RADIATED MEASUREMENT TEST SETUP




Figure 1. Radiated Measurement Test Setup Diagram

6.1 EFFECTIVE ISOTROPIC RADIATED POWER OUTPUT - §24.232(b)

EIRP measurements were performed on a 3-meter open area test site using the Signal Substitution Method in accordance with ANSI TIA/EIA-603-A-2001. The EUT was placed on a turntable 3-meters from the receive antenna and tested in GPRS mode via internal software at a full rated power. The field of maximum intensity was found by rotating the EUT approximately 360 degrees and changing the height of the receive antenna from 1 to 4 meters. Once a peak was found the spectrum analyzer was set to peak hold and the value of the emission was extracted. The field strength was recorded for each channel being tested, and for both EUT antenna polarizations and modes. A standard gain horn antenna was substituted in place of the EUT. The antenna was fed through a directional coupler and the power at the coupler port was monitored. A signal generator and power amplifier controlled the antenna, and the input level of the antenna was adjusted to the same field strength level as the EUT. The feed point for the antenna was then connected to a calibrated power meter and the power adjusted to read the same as the coupler port previously recorded, this is to account for any mismatch in impedance, which may occur at the horn antenna. The conducted power at the antenna feed point was recorded. The forward conducted power for the horn antenna was then determined and the EIRP level was determined by adding the horn forward conducted power and the antenna gain in dB.

EUT Keypad Type	Freq. Tuned	EUT Conducted Power	Maximum Field Strength of EUT	Antenna Polariz.	Horn Gain	Horn Forward Conducted Power	EIRP of EUT Horn Gain + Horn Forward Conducted Power	
	MHz	dBm	dBm	H / V	dBi	dBm	dBm	Watts
Alpha-numeric	1850.20	28.01	-11.56	H	6.55	19.89	26.44	0.441
	1880.00	28.09	-10.86	H	6.58	21.06	27.64	0.581
	1909.80	27.92	-9.87	H	6.61	22.55	29.16	0.824
	1850.20	28.00	-15.41	V	6.55	16.69	23.24	0.211
	1880.00	28.10	-14.90	V	6.58	17.62	24.20	0.263
	1909.80	27.93	-14.99	V	6.61	17.69	24.30	0.269
Numeric	1850.20	28.01	-12.23	H	6.55	19.23	25.78	0.378
	1880.00	28.08	-11.86	H	6.58	20.04	26.62	0.459
	1909.80	27.91	-11.34	H	6.61	21.10	27.71	0.590
	1850.20	28.01	-16.21	V	6.55	15.88	22.43	0.175
	1880.00	28.09	-16.22	V	6.58	16.29	22.87	0.194
	1909.80	27.92	-16.04	V	6.61	16.65	23.26	0.212

7.1 FIELD STRENGTH OF SPURIOUS RADIATION - §2.1053

Radiated spurious emissions were measured on a 3-meter open area test site using the Signal Substitution Method in accordance with ANSI TIA/EIA-603-A-2001. The EUT was tested in GPRS mode via internal software at a full rated power. The EUT was placed on the turntable with the transmitter transmitting into a non-radiating load. A receiving antenna located 3 meters from the turntable received any signal radiated from the transmitter and its operating accessories. The receiving antenna was varied in height from 1 to 4 meters and the polarization was varied (horizontal and vertical) to determine the worst-case emission level. A standard gain horn antenna was substituted in place of the EUT. A modulated signal was fed through a directional coupler to the antenna and the power at the coupler port was monitored. A signal generator and power amplifier controlled the antenna, and the input level of the antenna was adjusted to the same field strength level as the EUT. The antenna feed point was then connected to a calibrated power meter and the power was adjusted to read the same power at the coupler port previously recorded, to account for any mismatch in impedance which may occur at the horn antenna. The conducted power at the antenna feed point was then recorded. The forward conducted power for the horn antenna was determined by measuring the power at the horn antenna feed point and reproducing the coupler power previously measured. The EIRP level was determined by adding the horn forward conducted power and the horn antenna gain. All spurious emissions from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier were investigated. The test data is shown on pages 6-7.

Alpha-numeric Keypad Unit

Operating Frequency (MHz): 1850.20
Channel: 512 (Low)
EUT Conducted Pwr. (dBm): 28.01
Measured EIRP (dBm): 26.44
Modulation: GMSK
Distance: 3 Meters
Limit: 43 + 10 log (W) = 39.44 dBc

Frequency	Field Strength of Spurious Radiation	Horn Forward Conducted Power	Standard Gain Horn Antenna Gain	POL	EIRP	ERP	dBc
MHz	dBm	dBm	dBi	H/V	dBm	dBm	
3700.40	-84.53	-51.64	6.6	H	-45.04	-47.18	73.62
5550.60	-85.05	-47.25	7.8	H	-39.45	-41.59	68.03
7400.80	-81.38	-44.80	7.8	H	-37.00	-39.14	65.58
9251.00	-82.79	-44.77	7.6	H	-37.17	-39.31	65.75
11101.20	-81.88	-45.52	8.5	H	-37.02	-39.16	65.60
12951.40	-82.78	-44.90	8.8	H	-36.10	-38.24	64.68
14801.60	-78.82	-40.94	9.6	H	-31.34	-33.48	59.92
16651.80	-79.25	-41.42	9.0	H	-32.42	-34.56	61.00
18502.00	-80.10	-43.89	9.3	H	-34.59	-36.73	63.17

FIELD STRENGTH OF SPURIOUS RADIATION - §2.1053 (Cont.)

Alpha-numeric Keypad Unit

Operating Frequency (MHz): 1880.00
 Channel: 661 (Mid)
 EUT Conducted Pwr. (dBm): 28.10
 Measured EIRP (dBm): 27.64
 Modulation: GMSK
 Distance: 3 Meters
 Limit: $43 + 10 \log (W) = 40.64 \text{ dBc}$

Frequency	Field Strength of Spurious Radiation	Horn Forward Conducted Power	Standard Gain Horn Antenna Gain	POL	EIRP	ERP	dBc
MHz	dBm	dBm	dBi	H/V	dBm	dBm	
3760.00	-84.37	-51.48	6.6	H	-44.88	-47.02	74.66
5640.00	-84.47	-46.67	7.8	H	-38.87	-41.01	68.65
7520.00	-81.48	-44.90	7.8	H	-37.10	-39.24	66.88
9400.00	-82.73	-44.71	7.6	H	-37.11	-39.25	66.89
11280.00	-82.54	-46.18	8.5	H	-37.68	-39.82	67.46
13160.00	-81.36	-43.48	8.8	H	-34.68	-36.82	64.46
15040.00	-78.60	-40.72	9.6	H	-31.12	-33.26	60.90
16920.00	-79.67	-41.84	9.0	H	-32.84	-34.98	62.62
18800.00	-80.34	-44.13	9.3	H	-34.83	-36.97	64.61

Alpha-numeric Keypad Unit

Operating Frequency (MHz): 1909.80
 Channel: 810 (High)
 EUT Conducted Pwr. (dBm): 27.93
 Measured EIRP (dBm): 29.16
 Modulation: GMSK
 Distance: 3 Meters
 Limit: $43 + 10 \log (W) = 42.16 \text{ dBc}$

Frequency	Field Strength of Spurious Radiation	Horn Forward Conducted Power	Standard Gain Horn Antenna Gain	POL	EIRP	ERP	dBc
MHz	dBm	dBm	dBi	H/V	dBm	dBm	
3819.60	-85.09	-52.20	6.6	H	-45.60	-47.74	76.90
5729.40	-83.50	-45.70	7.8	H	-37.90	-40.04	69.20
7639.20	-81.77	-45.19	7.8	H	-37.39	-39.53	68.69
9549.00	-82.22	-44.20	7.6	H	-36.60	-38.74	67.90
11458.80	-82.17	-45.81	8.5	H	-37.31	-39.45	68.61
13368.60	-77.97	-40.09	8.8	H	-31.29	-33.43	62.59
15278.40	-79.00	-41.12	9.6	H	-31.52	-33.66	62.82
17188.20	-79.61	-41.78	9.0	H	-32.78	-34.92	64.08
19098.00	-79.33	-43.12	9.3	H	-33.82	-35.96	65.12

8.1 OCCUPIED BANDWIDTH - §2.1049, §24.238

The EUT was placed into test mode via internal software at a full rated power. The EUT was connected to the input of a 50Ω spectrum analyzer through a matched 30dB attenuator. The resolution bandwidth and video bandwidth were set to 3kHz. The EUT was operating at maximum output power. Data was taken for low, mid and high frequencies. The table below lists the -26dBc occupied bandwidths. Spectrum analyzer plots for 99% power and -26 dBc occupied bandwidths are shown in Appendix A.

Frequency	-26 dBc Bandwidth
1850.2 MHz	301.8 kHz
1880.0 MHz	301.2 kHz
1909.8 MHz	301.8 kHz

Specified Limits:

§24.238

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurements of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.
- (e) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

9.1 FREQUENCY STABILITY / TEMPERATURE VARIATION - §2.1055, §24.235


The minimum frequency stability shall be $\pm 150\text{Hz}$ referenced to a received carrier frequency. This meets the requirement for operational accuracy of 0.00005% for digital mode. An HP 53181A Frequency Counter was used to measure the error in the fundamental frequency. The transmitter was set to maximum power at the center frequency of the band. The EUT was tested inside the temperature chamber.

The frequency stability of the transmitter was measured by:

1. **Temperature:** The temperature was varied from -30°C to $+60^{\circ}\text{C}$ at intervals no more than 10°C throughout the temperature range using an environmental chamber. A period of time sufficient to stabilize all of the components in the equipment was allowed prior to each frequency measurement.
2. **Primary Supply Voltage:** The primary supply voltage was set at the specified nominal rating and reduced to the battery operating endpoint specified by the manufacturer. The voltage was measured at the terminals of the power supply or at the input to the cable normally provided with the equipment.

Carrier Frequency (GHz): 1.88
Channel: 661
Mode: GPRS
Deviation Limit (PPM): 0.1

Temperature (°C)	Voltage (%)	Power (WDC)	Carrier Frequency Deviation		Specification	
			(Hz)	(PPM)	Lower Limit (PPM)	Upper Limit (PPM)
+20 (Ref)	100	7.4	-3.56	-0.002	0.1	-0.1
-30	100	7.4	-8.66	-0.005	0.1	-0.1
-20	100	7.4	6.59	0.004	0.1	-0.1
-10	100	7.4	-5.43	-0.003	0.1	-0.1
0	100	7.4	4.20	0.002	0.1	-0.1
+10	100	7.4	-7.14	-0.004	0.1	-0.1
+20	100	7.4	3.77	0.002	0.1	-0.1
+30	100	7.4	-9.85	-0.005	0.1	-0.1
+40	100	7.4	6.34	0.003	0.1	-0.1
+50	100	7.4	3.91	0.002	0.1	-0.1
+60	100	7.4	-2.60	-0.001	0.1	-0.1
+20	Endpoint	6.1	7.55	0.004	0.1	-0.1



Time Period and Procedure:

1. The carrier frequency of the transmitter was measured at room temperature (25°C to 27°C to provide a reference).
2. The equipment was subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C , the measurement of the carrier frequency of the transmitter was made within a three-minute interval after applying power to the transmitter.
4. Frequency measurements were made at 10°C intervals up to $+60^{\circ}\text{C}$, then back to room temperature. A minimum period of one hour was provided to allow stabilization of the equipment at each temperature level.

10.1 TEST EQUIPMENT LIST

Equipment Type	Model	Serial No.	Calibration Due Date
HP Signal Generator	8648D (9kHz-4.0GHz)	3847A00611	Feb 2004
Rohde & Schwarz Signal Generator	SMR40 (10MHz-40GHz)	835537/022	Nov 2003
Gigatronics Power Meter	8652A	1835272	Feb 2004
Gigatronics Power Sensor	80701A (0.05-18GHz)	1833535	Feb 2004
Gigatronics Power Sensor	80701A (0.05-18GHz)	1833542	Feb 2004
Amplifier Research Power Amp.	5S1G4 (5W, 800MHz-4.2GHz)	26235	N/A
Microwave System Amplifier	HP 83017A (0.5-26.5GHz)	3123A00587	N/A
Network Analyzer	HP 8753E (30kHz-3GHz)	US38433013	Feb 2004
Audio Analyzer	HP 8903B	3729A18691	Nov 2003
Modulation Analyzer	HP 8901A	3749A07154	July 2003
Frequency Counter	HP 53181A (3GHz)	3736A05175	May 2004
DC Power Supply	HP E3611A	KR83015294	N/A
Multi-Device Controller	EMCO 2090	9912-1484	N/A
Mini Mast	EMCO 2075	0001-2277	N/A
Turntable	EMCO 2080-1.2/1.5	0002-1002	N/A
Double Ridged Horn Antenna	ETS 3115 (1-18GHz)	6267	Oct. 2003
Double Ridged Horn Antenna	ETS 3115 (1-18GHz)	6276	Oct. 2003
Horn Antenna	Chase BBHA 9120-A (0.7-4.8GHz)	9120A-239	Sept 2003
Horn Antenna	Chase BBHA 9120-A (0.7-4.8GHz)	9120A-240	Sept 2003
Roberts Dipoles	Compliance Design (2 sets) 3121C		June 2004
Spectrum Analyzer	HP 8594E	3543A02721	Feb 2004
Spectrum Analyzer	HP E4408B	US39240170	Nov 2003
Shielded Screen Room	Lindgren R.F. 18W-2/2-0	16297	N/A
Environmental Chamber	ESPEC ECT-2 (Temperature/Humidity)	0510154-B	Feb 2004

Test Report S/N:	061003-386KBC
Test Date(s):	June 16-20, 2003
Test Type:	FCC Part 24(E) EMC Measurements

11.1 CONCLUSION

The data in this measurement report shows that the ITRONIX CORPORATION Model: IX100 FCC ID: KBCIX100AC750 Rugged Handheld PC with Sierra Wireless AirCard 750 PCS GPRS PCMCIA Modem Card complies with the requirements of FCC Rule Parts §24(E) and §2.

Test Report S/N:	061003-386KBC
Test Date(s):	June 16-20, 2003
Test Type:	FCC Part 24(E) EMC Measurements

APPENDIX A - TEST PLOTS

hp 14:55:10 Jun 20, 2003


FCC ID: KBCIX100AC750 COND SPURS CH 512

Mkr1 2.338 GHz

Ref 28 dBm

Atten 10 dB

-27.11 dBm



Start 10 MHz

#Res BW 1 MHz

#VBW 1 MHz

Stop 2.5 GHz

Sweep 6.225 ms

hp 14:56:24 Jun 20, 2003


FCC ID: KBCIX100AC750 COND SPURS CH 512

Mkr1 2.988 GHz

Ref 28 dBm

Atten 10 dB

-29.93 dBm



Start 2.5 GHz

*Res BW 1 MHz

*VBW 1 MHz

Stop 10 GHz

Sweep 18.75 ms

hp 14:57:24 Jun 20, 2003


FCC ID: KBCIX100AC750 COND SPURS CH 512

Ref 28 dBm

Atten 10 dB

Mkr1 13.23 GHz

-27.65 dBm



Start 10 GHz

*Res BW 1 MHz

*VBW 1 MHz

Stop 20 GHz

Sweep 100 ms



14:50:33 Jun 20, 2003


FCC ID: KBCIX100AC750 COND SPURS CH 661

Mkr1 2.425 GHz

Ref 28.1 dBm

Atten 10 dB

-27.73 dBm



Start 10 MHz

Stop 2.5 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 6.225 ms

hp 14:51:28 Jun 20, 2003


FCC ID: KBCIX100AC750 COND SPURS CH 661

Ref 28.1 dBm

Atten 10 dB

Mkr1 7.131 GHz

-29.84 dBm



Start 2.5 GHz

*Res BW 1 MHz

*VBW 1 MHz

Stop 10 GHz

Sweep 18.75 ms

hp 14:52:33 Jun 20, 2003


FCC ID: KBCIX100AC750 COND SPURS CH 661

Mkr1 13.83 GHz

Ref 28.1 dBm

Atten 10 dB

-28.32 dBm



Start 10 GHz

*Res BW 1 MHz

*VBW 1 MHz

Stop 20 GHz

Sweep 100 ms

hp 14:59:16 Jun 20, 2003


FCC ID: KBCIX100AC750 COND SPURS CH 810

Ref 27.9 dBm

Atten 10 dB

Mkr1 2.344 GHz

-27.62 dBm



Start 10 MHz

*Res BW 1 MHz

*VBW 1 MHz

Stop 2.5 GHz

Sweep 6.225 ms

hp 15:00:16 Jun 20, 2003


FCC ID: KBCIX100AC750 COND SPURS CH 810

Mkr1 2.988 GHz

Ref 27.9 dBm

Atten 10 dB

-29.31 dBm



Start 2.5 GHz
*Res BW 1 MHz

*VBW 1 MHz

Stop 10 GHz
Sweep 18.75 ms

hp 15:01:23 Jun 20, 2003


FCC ID: KBCIX100AC750 COND SPURS CH 810

Mkr1 13.20 GHz

Ref 27.9 dBm

Atten 10 dB

-28.47 dBm



Start 10 GHz
#Res BW 1 MHz

#VBW 1 MHz

Stop 20 GHz
Sweep 100 ms



16:31:35 Jun 20, 2003

FCC ID: KBCIX100AC750 RECEIVER SPURS

Mkr1 1.95812 GHz

Ref -50 dBm

Atten 5 dB

-56.99 dBm

Peak

Log

10

dB/

Offst


30

dB

M1 S2

S3 FC

AA



Start 1.931 GHz

Stop 1.989 GHz

*Res BW 30 kHz


*VBW 30 kHz

*Sweep 2 s

hp 16:21:45 15 Sep 2003

FCC ID: KBCIX100AC750 PCS GPRS CH 512
Ref 28 dBm Atten 10 dB

Mkr1 1.850200 GHz



Center 1.85 GHz

Span 1 MHz

*Res BW 3 kHz

*VBW 3 kHz

Sweep 277.8 ms

Emission Bandwidth Results (measuring..)

Emission Bandwidth
301.8 kHz

Emiss BW X dB -26.0 dB


hp 16:14:45 15 Sep 2003

FCC ID: KBCIX100AC750 PCS GPRS CH 661

Mkr1 1.880000 GHz

Ref 28.1 dBm

Atten 10 dB



Center 1.88 GHz

Span 1 MHz

*Res BW 3 kHz

*VBW 3 kHz

Sweep 277.8 ms

Emission Bandwidth Results (measuring...)

Emission Bandwidth
301.2 kHz

Emiss BW X dB -26.0 dB


hp 16:10:08 15 Sep 2003

FCC ID: KBCIX100AC750 PCS GPRS CH 810

Mkr1 1.909800 GHz

Ref 27.9 dBm

Atten 10 dB



Center 1.91 GHz

Span 1 MHz

*Res BW 3 kHz

*VBW 3 kHz

Sweep 277.8 ms

Emission Bandwidth Results (measuring..)

Emission Bandwidth
301.8 kHz

Emiss BW X dB -26.0 dB

hp 16:02:38 Jun 20, 2003


FCC ID: KBCIX100AC750 OCCUPIED BANDWIDTH

▲ Mkr1 250 kHz

Ref 28.1 dBm

Atten 10 dB

-5.084 dB



Center 1.88 GHz

*Res BW 3 kHz

*VBW 3 kHz

Span 1 MHz

*Sweep 2 s



16:19:26 Jun 20, 2003

FCC ID: KBCIX100AC750 BAND EDGE LOW CH

Ref 28 dBm

Atten 10 dB

Peak

Log

10

dB/

Offst

30

dB

DI


-13.0

dBm

W1 S2

S3 FS

AA



Center 1.85 GHz

*Res BW 3 kHz

*VBW 3 kHz

Span 1 MHz

*Sweep 2 s



16:13:50 Jun 20, 2003

FCC ID: KBCIX100AC750 BAND EDGE HIGH CH

Ref 27.9 dBm

Atten 10 dB

Peak

Log

10

dB/

Offst

30

dB

DI


-13.0

dBm

W1 S2

S3 FS

AA



Center 1.91 GHz

*Res BW 3 kHz

*VBW 3 kHz

Span 1 MHz

*Sweep 2 s



14:13:17 Jun 20, 2003

FCC ID: KBXIX100AC750 BLOCK 1 LOWER EDGE

Mkr1 1.849985 GHz

Ref 28 dBm

Atten 10 dB

-17.42 dBm

Peak

Log

10

dB/

Offst

30

dB

DI


-13.0

dBm

W1 S2

S3 FS

AA



Center 1.85 GHz

Span 1 MHz

*Res BW 3 kHz

VBW 3 kHz

*Sweep 2 s



14:23:25 Jun 20, 2003

FCC ID: KBXIX100AC750 BLOCK 1 UPPER EDGE

Mkr1 1.864990 GHz

Ref 28 dBm

Atten 10 dB

-21.02 dBm

Peak

Log

10

dB/

Offst

30

dB

DI


-13.0

dBm

W1 S2

S3 FS

AA



Center 1.865 GHz

#Res BW 3 kHz

VBW 3 kHz

Span 1 MHz

#Sweep 2 s



14:31:26 Jun 20, 2003


FCC ID: KBXIX100AC750 BLOCK 2 LOWER EDGE

Mkr1 1.864985 GHz

Ref 28 dBm

Atten 10 dB

-17.76 dBm



Center 1.865 GHz

*Res BW 3 kHz

VBW 3 kHz

Span 1 MHz

*Sweep 2 s



14:50:55 Jun 20, 2003

FCC ID: KBXIX100AC750 BLOCK 2 UPPER EDGE

Mkr1 1.869993 GHz

Ref 28 dBm

Atten 10 dB

-21.55 dBm

Peak

Log

10

dB/

Offst

30

dB

DI


-13.0

dBm

W1 S2

S3 FS

AA



Center 1.87 GHz

Span 1 MHz

*Res BW 3 kHz

VBW 3 kHz

*Sweep 2 s



15:30:08 Jun 20, 2003

FCC ID: KBXIX100AC750 BLOCK 3 LOWER EDGE

Mkr1 1.870013 GHz

Ref 28 dBm

Atten 10 dB

-17.02 dBm

Peak

Log

10

dB/

Offst

30

dB

DI


-13.0

dBm

W1 S2

S3 FS

AA



Center 1.87 GHz

*Res BW 3 kHz

VBW 3 kHz

Span 1 MHz

*Sweep 2 s



11:16:14 Jun 20, 2003

FCC ID: KBXIX100AC750 BLOCK 3 UPPER EDGE

Mkr1 1.884990 GHz

Ref 28.1 dBm

Atten 10 dB

-21.09 dBm

Peak

Log

10

dB/

Offst

30

dB

DI


-13.0

dBm

W1 S2

S3 FS

AA



Center 1.885 GHz

*Res BW 3 kHz

VBW 3 kHz

Span 1 MHz

*Sweep 2 s



11:24:13 Jun 20, 2003


FCC ID: KBXIX100AC750 BLOCK 4 LOWER EDGE

Mkr1 1.884985 GHz

Ref 28.1 dBm

Atten 10 dB

-17.6 dBm



Center 1.885 GHz

*Res BW 3 kHz

VBW 3 kHz

Span 1 MHz

*Sweep 2 s

hp 11:34:46 Jun 20, 2003


FCC ID: KBXIX100AC750 BLOCK 4 UPPER

Mkr1 1.889990 GHz

Ref 28 dBm

Atten 10 dB

-20.6 dBm



Center 1.89 GHz

*Res BW 3 kHz

VBW 3 kHz

Span 1 MHz

*Sweep 2 s



11:50:42 Jun 20, 2003


FCC ID: KBXIX100AC750 BLOCK 5 LOWER EDGE

Mkr1 1.889985 GHz

Ref 28 dBm

Atten 10 dB

-17.31 dBm



Center 1.89 GHz

*Res BW 3 kHz

VBW 3 kHz

Span 1 MHz

*Sweep 2 s

hp 12:01:06 Jun 20, 2003

FCC ID: KBXIX100AC750 BLOCK 5 UPPER EDGE

Mkr1 1.894990 GHz

Ref 28 dBm

Atten 10 dB

-20.69 dBm

Peak

Log

10

dB/

Offst

30

dB

DI


-13.0

dBm

W1 S2

S3 FS

AA



Center 1.895 GHz

*Res BW 3 kHz

VBW 3 kHz

Span 1 MHz

*Sweep 2 s



12:08:15 Jun 20, 2003

FCC ID: KBXIX100AC750 BLOCK 6 LOWER EDGE

Mkr1 1.894985 GHz

Ref 28 dBm

Atten 10 dB

-17.72 dBm

Peak

Log

10

dB/

Offst

30

dB

DI


-13.0

dBm

W1 S2

S3 FS

AA



Center 1.895 GHz

*Res BW 3 kHz

VBW 3 kHz

Span 1 MHz

*Sweep 2 s



12:22:22 Jun 20, 2003

FCC ID: KBXIX100AC750 BLOCK 6 UPPER EDGE

Mkr1 1.909993 GHz

Ref 27.9 dBm

Atten 10 dB

-21.06 dBm

Peak

Log

10

dB/

Offst

30

dB

DI


-13.0

dBm

W1 S2

S3 FS

AA



Center 1.91 GHz

*Res BW 3 kHz

VBW 3 kHz

Span 1 MHz

*Sweep 2 s