

Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

APPENDIX A - SAR MEASUREMENT DATA

Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter							
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 18 of 47							



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - PCS Band - GPRS Mode - Back Side of DUT with Carry Case

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Body-Worn Accessories: Nylon Carry-Case (P/N: 54-0644-001), Ear-Microphone (Model: JABRA)

Ambient Temp: 24.7 °C; Fluid Temp: 22.5 °C; Barometric Pressure: 100.8 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: PCS GPRS RF Output Power: 28.9 dBm (Peak Conducted) Frequency: 1880.0 MHz; Channel 661; Duty Cycle: 1:2 Medium: M1880 (σ = 1.53 mho/m; ϵ_r = 51.0; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(4.57, 4.57, 4.57); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn370; Calibrated: 14/05/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - PCS GPRS - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 1880.0 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - PCS GPRS - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 1880.0 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 17.8 V/m; Power Drift = 0.0004 dB Peak SAR (extrapolated) = 0.577 W/kg SAR(1 g) = 0.396 mW/g; SAR(10 g) = 0.257 mW/g



Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter							
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 19 of 47							



Test Report S/N:102604KBC-T577-S24GTest Date(s):December 01-02, 2004Test Type:FCC/IC SAR Evaluation

Date Tested: 12/01/04

Body-Worn SAR - PCS Band - GPRS Mode - Front Side of DUT with Carry Case

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Body-Worn Accessories: Nylon Carry-Case (P/N: 54-0644-001), Ear-Microphone (Model: JABRA)

Ambient Temp: 24.7 °C; Fluid Temp: 22.5 °C; Barometric Pressure: 100.8 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: PCS GPRS RF Output Power: 28.9 dBm (Peak Conducted) Frequency: 1880.0 MHz; Channel 661; Duty Cycle: 1:2 Medium: M1880 (σ = 1.53 mho/m; ϵ_r = 51.0; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(4.57, 4.57, 4.57); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 06/07/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - PCS GPRS - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 1880.0 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - PCS GPRS - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 1880.0 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 16.8 V/m; Power Drift = -0.369 dB Peak SAR (extrapolated) = 0.601 W/kg SAR(1 g) = 0.380 mW/g; SAR(10 g) = 0.235 mW/g



Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter							
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 20 of 47							



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - PCS Band - GPRS Mode - Back Side of DUT with Carry Case Simultaneous Transmit with Co-located Bluetooth

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Body-Worn Accessories: Nylon Carry-Case (P/N: 54-0644-001), Ear-Microphone (Model: JABRA)

Ambient Temp: 24.7 °C; Fluid Temp: 22.5 °C; Barometric Pressure: 100.8 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: PCS GPRS RF Output Power: 28.9 dBm (Peak Conducted) Frequency: 1880.0 MHz; Channel 661; Duty Cycle: 1:2 RF Output Power: 4.3 dBm (Peak Conducted) Bluetooth Frequency: 2441 MHz; Duty Cycle: 1:1 Medium: M1880 (σ = 1.53 mho/m; ϵ_r = 51.0; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(4.57, 4.57, 4.57); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn353; Calibrated: 06/07/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - PCS GPRS with Bluetooth - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 1880.0 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - PCS GPRS with Bluetooth - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 1880.0 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 17.5 V/m; Power Drift = -0.0105 dB Peak SAR (extrapolated) = 0.597 W/kg SAR(1 g) = 0.401 mW/g; SAR(10 g) = 0.253 mW/g



 Applicant:
 Itronix Corporation
 FCC ID:
 KBCIX100XA775WLBT
 IC ID:
 1943A-IX100Xe
 Model:
 IX100XA775WLBT

 Rugged Harden Keiter Vertein Vertein



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Z-Axis Scan



Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter							
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 22 of 47							



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - PCS Band - GPRS Mode - Front Side of DUT with Carry Case Simultaneous Transmit with Co-located Bluetooth

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Body-Worn Accessories: Nylon Carry-Case (P/N: 54-0644-001), Ear-Microphone (Model: JABRA)

Ambient Temp: 24.7 °C; Fluid Temp: 22.5 °C; Barometric Pressure: 100.8 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: PCS GPRS RF Output Power: 28.9 dBm (Peak Conducted) Frequency: 1880.0 MHz; Channel 661; Duty Cycle: 1:2 RF Output Power: 4.3 dBm (Peak Conducted) Bluetooth Frequency: 2441 MHz; Duty Cycle: 1:1 Medium: M1880 (σ = 1.53 mho/m; ϵ_r = 51.0; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(4.57, 4.57, 4.57); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn353; Calibrated: 06/07/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - PCS GPRS with Bluetooth - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 1880.0 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - PCS GPRS with Bluetooth - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 1880.0 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 16.5 V/m; Power Drift = -0.002 dB Peak SAR (extrapolated) = 0.594 W/kg OAD(4 = 0.202 mW/kg

SAR(1 g) = 0.373 mW/g; SAR(10 g) = 0.229 mW/g



 Applicant:
 Itronix Corporation
 FCC ID:
 KBCIX100XA775WLBT
 IC ID:
 1943A-IX100Xe
 Model:
 IX100XA775WLBT

 Rugged Harden Keiter Vertein Vertein



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - Cellular Band - GPRS Mode - Front Side of DUT with Carry Case

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Body-Worn Accessories: Nylon Carry-Case (P/N: 54-0644-001), Ear-Microphone (Model: JABRA)

Ambient Temp: 25.1 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 103.0 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: Cellular GPRS RF Output Power: 32.0 dBm (Peak Conducted) Frequency: 836.6 MHz; Channel 190; Duty Cycle: 1:2 Medium: M835 (σ = 1.00 mho/m; ϵ_r = 53.6; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.24, 6.24, 6.24); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 06/07/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - Cellular GPRS - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 836.6 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - Cellular GPRS - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 836.6 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 33.4 V/m; Power Drift = -0.0230 dB Peak SAR (extrapolated) = 1.28 W/kg SAR(1 g) = 0.982 mW/g; SAR(10 g) = 0.734 mW/g



Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter							
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 24 of 47							



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - Cellular Band - GPRS Mode - Front Side of DUT with Carry Case

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Body-Worn Accessories: Nylon Carry-Case (P/N: 54-0644-001), Ear-Microphone (Model: JABRA)

Ambient Temp: 25.1 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 103.0 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: Cellular GPRS RF Output Power: 32.1 dBm (Peak Conducted) Frequency: 824.2 MHz; Channel 128; Duty Cycle: 1:2 Medium: M835 (σ = 1.00 mho/m; ϵ_r = 53.6; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.24, 6.24, 6.24); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 14/05/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - Cellular GPRS - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Low Channel - 824.2 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - Cellular GPRS - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Low Channel - 824.2 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 33.5 V/m; Power Drift = -0.0119 dB Peak SAR (extrapolated) = 1.28 W/kg SAR(1 g) = 0.982 mW/g; SAR(10 g) = 0.736 mW/g



Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter							
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 25 of 47							



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - Cellular Band - GPRS Mode - Front Side of DUT with Carry Case

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Body-Worn Accessories: Nylon Carry-Case (P/N: 54-0644-001), Ear-Microphone (Model: JABRA)

Ambient Temp: 25.1 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 103.0 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: Cellular GPRS RF Output Power: 32.0 dBm (Peak Conducted) Frequency: 848.8 MHz; Channel 251; Duty Cycle: 1:2 Medium: M835 (σ = 1.00 mho/m; ϵ_r = 53.6; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.24, 6.24, 6.24); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 14/05/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - Cellular GPRS - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - High Channel - 848.8 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - Cellular GPRS - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - High Channel - 848.8 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 32.1 V/m; Power Drift = 0.00149 dB Peak SAR (extrapolated) = 1.2 W/kg SAR(1 g) = 0.921 mW/g; SAR(10 g) = 0.691 mW/g



Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter							
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 26 of 47							



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - Cellular Band - GPRS Mode - Back Side of DUT with Carry Case

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Body-Worn Accessories: Nylon Carry-Case (P/N: 54-0644-001), Ear-Microphone (Model: JABRA)

Ambient Temp: 25.1 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 103.0 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: Cellular GPRS RF Output Power: 32.0 dBm (Peak Conducted) Frequency: 836.6 MHz; Channel 190; Duty Cycle: 1:2 Medium: M835 (σ = 1.00 mho/m; ϵ_r = 53.6; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.24, 6.24, 6.24); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 14/05/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - Cellular GPRS - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 836.6 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - Cellular GPRS - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 836.6 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 38.9 V/m; Power Drift = -0.0132 dB Peak SAR (extrapolated) = 1.68 W/kg SAR(1 g) = 1.33 mW/g; SAR(10 g) = 0.980 mW/g



Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter							
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 27 of 47							



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - Cellular Band - GPRS Mode - Back Side of DUT with Carry Case

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Body-Worn Accessories: Nylon Carry-Case (P/N: 54-0644-001), Ear-Microphone (Model: JABRA)

Ambient Temp: 25.1 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 103.0 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: Cellular GPRS RF Output Power: 32.1 dBm (Peak Conducted) Frequency: 824.2 MHz; Channel 128; Duty Cycle: 1:2 Medium: M835 (σ = 1.00 mho/m; ϵ_r = 53.6; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.24, 6.24, 6.24); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 14/05/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - Cellular GPRS - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Low Channel - 824.4 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - Cellular GPRS - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Low Channel - 824.4 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 39.6 V/m; Power Drift = -0.00747 dB Peak SAR (extrapolated) = 1.74 W/kg SAR(1 g) = 1.37 mW/g; SAR(10 g) = 1.01 mW/g



Applicant:	Itronix Corpor	ation I	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter								
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 28 of 47								



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - Cellular Band - GPRS Mode - Back Side of DUT with Carry Case

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Body-Worn Accessories: Nylon Carry-Case (P/N: 54-0644-001), Ear-Microphone (Model: JABRA)

Ambient Temp: 25.1 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 103.0 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: Cellular GPRS RF Output Power: 32.0 dBm (Peak Conducted) Frequency: 848.8 MHz; Channel 251; Duty Cycle: 1:2 Medium: M835 (σ = 1.00 mho/m; ϵ_r = 53.6; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.24, 6.24, 6.24); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 14/05/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - Cellular GPRS - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - High Channel - 848.8 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - Cellular GPRS - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - High Channel - 848.8 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 39.9 V/m; Power Drift = -0.0171 dB Peak SAR (extrapolated) = 1.79 W/kg SAR(1 g) = 1.39 mW/g; SAR(10 g) = 1.03 mW/g



Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter							
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 29 of 47							



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Z-Axis Scan



Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter							
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc. 30 of 47							



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - Cellular Band - GPRS Mode - Back Side of DUT with Carry Case Simultaneous Transmit with Co-located Bluetooth

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Ambient Temp: 25.1 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 103.0 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: Cellular GPRS RF Output Power: 32.0 dBm (Peak Conducted) Frequency: 848.8 MHz; Channel 251; Duty Cycle: 1:2 RF Output Power: 4.3 dBm (Peak Conducted) Bluetooth Frequency: 2441 MHz; Duty Cycle: 1:1 Medium: M835 (σ = 1.00 mho/m; ϵ_r = 53.6; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.24, 6.24, 6.24); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn370; Calibrated: 14/05/2004

- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - Cellular GPRS with Bluetooth - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - High Channel - 848.8 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - Cellular GPRS with Bluetooth - Back Side of DUT (Battery Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - High Channel - 848.8 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 39.6 V/m; Power Drift = 0.00384 dB Peak SAR (extrapolated) = 1.74 W/kg SAR(1 g) = 1.37 mW/g; SAR(10 g) = 1.01 mW/g



Applicant:
Itronix Corporation
FCC ID:
KBCIX100XA775WLBT
IC ID:
1943A-IX100Xe
Model:
IX100XA775WLBT

Rugged Hardheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Blue to th Combo Trammitter
Image: Comparison of the period combo of the period combo



Test Report S/N:	102604KBC-T577-S24G
Test Date(s):	December 01-02, 2004
Test Type:	FCC/IC SAR Evaluation

Body-Worn SAR - Cellular Band - GPRS Mode - Front Side of DUT with Carry Case Simultaneous Transmit with Co-located Bluetooth

DUT: Itronix Model: IX100XA775WLBT; Handheld PC with Dual-Band GSM GPRS/EDGE & 802.11b/Bluetooth; Serial: MH002

Ambient Temp: 25.1 °C; Fluid Temp: 22.2 °C; Barometric Pressure: 103.0 kPa; Humidity: 30%

7.4V, 3.0Ah Li-ion Battery Pack Communication System: Cellular GPRS RF Output Power: 32.0 dBm (Peak Conducted) Frequency: 836.6 MHz; Channel 190; Duty Cycle: 1:2 RF Output Power: 4.3 dBm (Peak Conducted) Bluetooth Frequency: 2441 MHz; Duty Cycle: 1:1 Medium: M835(σ = 1.00 mho/m; ϵ_r = 53.6; ρ = 1000 kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.24, 6.24, 6.24); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 06/07/2004
- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - Cellular GPRS with Bluetooth - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 836.6 MHz Area Scan (10x22x1): Measurement grid: dx=15mm, dy=15mm

Body-Worn - Cellular GPRS with Bluetooth - Front Side of DUT (LCD/Keypad Side) facing front of Carry Case & Planar Phantom 0.0 cm Separation Distance from front of carry case to planar phantom - Mid Channel - 836.6 MHz Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 33.2 V/m; Power Drift = -0.00547 dB Peak SAR (extrapolated) = 1.26 W/kg SAR(1 g) = 0.978 mW/g; SAR(10 g) = 0.732 mW/g



Applicant:	Itronix Corporation	FCC ID:	KBCIX100XA775WLBT	IC ID:	1943A-IX100Xe	Model:	IX100XA775WLBT	
Rugged Handheld PC with Dual-Band GSM GPRS/EDGE Modem & 802.11b/Bluetooth Combo Transmitter								
2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.								