

DECLARATION OF COMPLIANCE MPE EVALUATION REPORT

Test Lab

CELLTECH LABS INC.
Testing and Engineering Services
1955 Moss Court
Kelowna, B.C.
Canada V1Y 9L3
Phone: 250-448-7047
Fax: 250-448-7046
e-mail: info@celltechlabs.com
web site: www.celltechlabs.com

Applicant Information

ITRONIX CORPORATION
801 South Stevens Street
Spokane, WA 99204

<p>FCC Rule Part(s): IC Rule Part(s): FCC Classification: IC Classification: Device Type:</p> <p>FCC ID: Model(s): Tx Frequency Range: Max. RF Output Power: Antenna Type(s): Power Supply:</p>	<p>47 CFR §24(E), §2.1091; §1.1310 RSS-133 Issue 2, RSS-102 Issue 1 (Provisional) PCS Licensed Transmitter (PCB) 2GHz Personal Communication Services (RSS-133 Issue 2) Rugged Laptop PC with Sierra Wireless AirCard 750 PCS GSM/GPRS PCMCIA Modem (co-located with Cisco MPI-350 Mini-PCI DSSS WLAN & Mitsumi WML-C11 Bluetooth Transmitter), Vehicle Cradle, & Mobile Vehicle-Mount Antenna KBCIX260A750MPIBT IX260 1850.2 - 1909.8 MHz 28.12 dBm (Peak Conducted) Mobile Vehicle Antenna (MaxRad P/N: WMLPVDB800/1900 - 3 dBi Gain) 12V Vehicle Battery</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

This transmitter has been shown to be compliant for localized Maximum Permissible Exposure (MPE) for uncontrolled environment / general population exposure limits specified in FCC 47 CFR §1.1310 & Health Canada's Safety Code 6, and has been tested in accordance with the measurement procedures specified in FCC OET Bulletin 65, Edition 97-01. This device complies with the rules and regulations for Maximum Permissible Exposure (MPE) specified by the Federal Communications Commission and Industry Canada.

I attest to the accuracy of data. All measurements and/or calculations were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This evaluation report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc. The results and statements contained in this report pertain only to the device(s) evaluated.



Russell Pipe
Senior Compliance Technologist
Celltech Labs Inc.



Introduction

The Maximum Permissible Exposure (MPE) limit specified in 47 CFR §1.1310 of the FCC Rules and Health Canada's Safety Code 6 is as follows:

The limit for the frequency range of the PCS band (1900MHz) is $1\text{mW}/\text{cm}^2$ for General Population/Uncontrolled Access.

The EUT is designed for telecommunications transmissions in the PCS band and may use an external antenna of 3dBi gain. In this configuration the device is classified as mobile.

Summary

According to 47CFR 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
30-300	61.4	0.163	1.0	6
300-1500	F/300	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

Formula used to determine MPE

$$S = \frac{PG}{4\pi R^2}$$

$$R = \sqrt{\frac{PG}{4\pi S}}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna

MPE Calculation Data

The following calculation data shows that this device complies with the Maximum Permissible Exposure (MPE) requirements set forth in FCC §2.1091, §1.1310, OET Bulletin 65, Edition 97-01, and Health Canada's Safety Code 6 for General Population / Uncontrolled Exposure environment based on the specified frequencies listed.

	Tx Frequency:	1880.00	(MHz)
Maximum Peak Power at Antenna Input Terminal:		28.12	(dBm)
Antenna gain (typical)+9dB for 8-element array:		3.00	(dBi)

S =	1.00	(mW/cm ²)
P =	648.6344	(mW)
G =	2.00	(numeric)

R = 10.15 (cm)
