	Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
	Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
	Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
	Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

Appendix D - Maximum Permissible Exposure Calculation

D.1 REFERENCES

Normative Reference Standard	FCC CFR 47§1.1310 IEEE Std C95.1-1999
Procedure Reference	FCC CFR 47§2.1091

D.2 LIMITS

FCC CFR 47§1.1310 Table 1(b)	Frequency	Power Density
	300 - 1500 MHz	f/1500 mW/cm ²
	1500 - 100,000 MHz	1.0 mW/cm ²

D.3 ENVIRONMENTAL CONDITIONS

Temperature	na
Humidity	na
Barometric Pressure	na

D.4 MEASUREMENT EQUIPMENT SETUP

MEASUREMENT EQUIPMENT CONNECTIONS	The results described herein were determined by calculations, so no measurement equipment was used. The power measurements for each radio used in these calculations were made as described in Appendix A of this report.
MEASUREMENT EQUIPMENT SETTINGS	n/a

D.5 DUT OPERATING DESCRIPTION

Dual-Band GPRS	The maximum GPRS RF conducted output power in each band used for these calculations was measured on Channel 251 for Cellular and Channel 661 for PCS.
Dual-Band EDGE	The maximum EDGE RF conducted output power in each band used for these calculations was measured on Channel 190 for Cellular and Channel 661 for PCS.
Dual-Band UMTS	The maximum UMTS RF conducted output power in each band used for these calculations was measured on Channel 4233 for Cellular and Channel 9400 for PCS.

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6 TEST RESULTS

D.6.1 Calculations:

Swivel Dipole Antenna (Max. Measured Conducted Power - Cellular GPRS Mode)

Prediction of MPE Limit
OET Bulletin 65, Edition 97-01

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna
SL= power density limit

$$R = \sqrt{\frac{PG}{4\pi S}}$$

Ratio of Time On versus Total Transmit Time 0.25

Choose
↓
Occupational/Controlled
General Population/Uncontrolled
Tx Frequency: 848.80 (MHz)
Maximum Peak Power at Antenna Input Terminal: 32.28 (dBm)
Source-Based Time-Average Factor: -6.02 (dB)
Antenna gain: 2.60 (dBi)

SL= 0.57 (mW/cm²)
P= 422.6102 (mW)
G= 1.82 (numeric)

R = 10.40 (cm)

S (mw/cm²)
at 20cm

0.15282675

Formulae:

$$S = \frac{PG}{4\pi R^2}$$

where: S = Power Density Limit
P = Power Output of the Device
G = Numeric Antenna Gain
R = Distance from Antenna

$$R = \sqrt{\frac{P}{4\pi S}}$$

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))

Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Company:	Itronix Corporation	FCC ID:	KBCIX260PLUSAC860	Model(s):	IX260PLUSAC860	
DUT Type:	Laptop PC with Sierra Wireless AC860 Dual-Band GSM/GPRS/EDGE/UMTS PCMCIA Modem					
2006 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 38 of 51

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.2 Calculations:

Swivel Dipole Antenna (Max. Measured Conducted Power - PCS GPRS Mode)

**Prediction of MPE Limit
OET Bulletin 65, Edition 97-01**

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

$$R = \sqrt{\frac{PG}{4\pi S}}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna
SL= power density limit

Ratio of Time On versus Total Transmit Time 0.25

Choose

Occupational/Controlled
 General Population/Uncontrolled

ENTER

Tx Frequency: 1880.00 (MHz)
 Maximum Peak Power at Antenna Input Terminal: 28.63 (dBm)
 Source-Based Time-Average Factor: -6.02 (dB)
 Antenna gain: 2.60 (dBi)

SL= 1.00 (mW/cm²)
P= 182.3644 (mW)
G= 1.82 (numeric)

R = 5.14 (cm)

**S (mw/cm²)
at 20cm**

0.065947658

Formulae:

$S = \frac{PG}{4\pi R^2}$ where: S = Power Density Limit
 $R = \sqrt{\frac{PG}{4\pi S}}$ P = Power Output of the Device
 G = Numeric Antenna Gain
 R = Distance from Antenna

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))
 Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.3 Calculations:

Swivel Dipole Antenna (Max. Measured Conducted Power - Cellular EDGE Mode)

**Prediction of MPE Limit
OET Bulletin 65, Edition 97-01**

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

$$R = \sqrt{\frac{PG}{4\pi S}}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna
SL= power density limit

Ratio of Time On versus Total Transmit Time 0.25

Choose

- Occupational/Controlled
 General Population/Uncontrolled

ENTER

Tx Frequency: 836.60 (MHz)
 Maximum Peak Power at Antenna Input Terminal: 26.89 (dBm)
 Source-Based Time-Average Factor: -6.02 (dB)
 Antenna gain: 2.60 (dBi)

SL= 0.56 (mW/cm²)
P= 122.1631 (mW)
G= 1.82 (numeric)

R = 5.63 (cm)

**S (mw/cm²)
 at 20cm**
 0.044177321

Formulae:

$S = \frac{PG}{4\pi R^2}$ where: S = Power Density Limit
 $R = \sqrt{\frac{PG}{4\pi S}}$ P = Power Output of the Device
 G = Numeric Antenna Gain
 R = Distance from Antenna

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))
 Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.4 Calculations:

Swivel Dipole Antenna (Max. Measured Conducted Power - PCS EDGE Mode)

**Prediction of MPE Limit
OET Bulletin 65, Edition 97-01**

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator

$$R = \sqrt{\frac{PG}{4\pi S}}$$

R= distance to the center of radiation of the antenna
SL= power density limit

Ratio of Time On versus Total Transmit Time 0.25

Choose

Occupational/Controlled
General Population/Uncontrolled

ENTER

Tx Frequency: 1880.00 (MHz)
Maximum Peak Power at Antenna Input Terminal: 25.73 (dBm)
Source-Based Time-Average Factor: -6.02 (dB)
Antenna gain: 2.60 (dBi)

SL= 1.00 (mW/cm²)
P= 93.5276 (mW)
G= 1.82 (numeric)

R = 3.68 (cm)

**S (mw/cm²)
at 20cm**

0.033822007

Formulae:

$S = \frac{PG}{4\pi R^2}$ where: S = Power Density Limit
P = Power Output of the Device
G = Numeric Antenna Gain
R = Distance from Antenna

$R = \sqrt{\frac{PG}{4\pi S}}$

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))
Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.5 Calculations:

Swivel Dipole Antenna (Max. Measured Conducted Power - Cellular UMTS Mode)

**Prediction of MPE Limit
OET Bulletin 65, Edition 97-01**

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna
SL= power density limit

$$R = \sqrt{\frac{PG}{4\pi S}}$$

Ratio of Time On versus Total Transmit Time 1.00

Choose

Occupational/Controlled
General Population/Uncontrolled

ENTER

Tx Frequency: 846.60 (MHz)
Maximum Peak Power at Antenna Input Terminal: 24.00 (dBm)
Source-Based Time-Average Factor: 0.00 (dB)
Antenna gain: 2.60 (dBi)

SL= 0.56 (mW/cm²)
P= 251.1886 (mW)
G= 1.82 (numeric)

R = 8.03 (cm)

S (mw/cm²)
at 20cm
0.090836286

Formulae:

$S = \frac{PG}{4\pi R^2}$ where: S = Power Density Limit
P = Power Output of the Device
G = Numeric Antenna Gain
R = Distance from Antenna

$R = \sqrt{\frac{PG}{4\pi S}}$

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))
Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.6 Calculations:

Swivel Dipole Antenna (Max. Measured Conducted Power - PCS UMTS Mode)

**Prediction of MPE Limit
OET Bulletin 65, Edition 97-01**

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

$$R = \sqrt{\frac{PG}{4\pi S}}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna
SL= power density limit

Ratio of Time On versus Total Transmit Time 1.00

Choose

Occupational/Controlled
 General Population/Uncontrolled

Tx Frequency: 1880.00 (MHz)
 Maximum Peak Power at Antenna Input Terminal: 23.00 (dBm)
 Source-Based Time-Average Factor: 0.00 (dB)
 Antenna gain: 2.60 (dBi)

SL= 1.00 (mW/cm²)
P= 199.5262 (mW)
G= 1.82 (numeric)

R = 5.38 (cm)

**S (mw/cm²)
 at 20cm**
 0.072153826

Formulae:

$S = \frac{PG}{4\pi R^2}$ where: S = Power Density Limit
 P = Power Output of the Device
 G = Numeric Antenna Gain
 R = Distance from Antenna
 $R = \sqrt{\frac{PG}{4\pi S}}$

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))
 Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.7 Calculations:

Vehicle-Mount Antenna (Max. Measured Conducted Power - Cellular GPRS Mode)

Prediction of MPE Limit
OET Bulletin 65, Edition 97-01

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

$$R = \sqrt{\frac{PG}{4\pi S}}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna
SL= power density limit

Ratio of Time On versus Total Transmit Time 0.25

Choose

↓

Occupational/Controlled

General Population/Uncontrolled

ENTER

↓

Tx Frequency: 848.80 (MHz)

Maximum Peak Power at Antenna Input Terminal: 32.28 (dBm)

Source-Based Time-Average Factor: -6.02 (dB)

Antenna gain and Cable Loss: 1.11 (dBi)

SL= 0.57 (mW/cm²)
P= 422.6102 (mW)
G= 1.29 (numeric)

R = 8.76 (cm)

S (mw/cm²)
at 20cm
0.108442464

Formulae:

$S = \frac{PG}{4\pi R^2}$ where: S = Power Density Limit
 P = Power Output of the Device
 G = Numeric Antenna Gain
 R = Distance from Antenna

$R = \sqrt{\frac{PG}{4\pi S}}$

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))
 Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.8 Calculations:

Vehicle-Mount Antenna (Max. Measured Conducted Power - PCS GPRS Mode)

Prediction of MPE Limit
OET Bulletin 65, Edition 97-01

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

- S**= power density
- P**= power input to the antenna
- G**= power gain of the antenna in the direction of interest relative to an isotropic radiator
- R**= distance to the center of radiation of the antenna
- SL**= power density limit

$$R = \sqrt{\frac{PG}{4\pi S}}$$

Ratio of Time On versus Total Transmit Time 0.25

Choose

- Occupational/Controlled
- General Population/Uncontrolled

ENTER

Tx Frequency: 1880.00 (MHz)
 Maximum Peak Power at Antenna Input Terminal: 28.63 (dBm)
 Source-Based Time-Average Factor: -6.02 (dB)
 Antenna gain and Cable Loss: 0.20 (dBi)

SL= 1.00 (mW/cm²)
P= 182.3644 (mW)
G= 1.05 (numeric)

R = 3.90 (cm)

S (mw/cm²)
at 20cm

0.037948916

Formulae:

$$S = \frac{PG}{4\pi R^2}$$

where: S = Power Density Limit
 P = Power Output of the Device
 G = Numeric Antenna Gain
 R = Distance from Antenna

$$R = \sqrt{\frac{PG}{4\pi S}}$$

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))
 Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.9 Calculations:

Vehicle-Mount Antenna (Max. Measured Conducted Power - Cellular EDGE Mode)

Prediction of MPE Limit
OET Bulletin 65, Edition 97-01

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna
SL= power density limit

$$R = \sqrt{\frac{PG}{4\pi S}}$$

Ratio of Time On versus Total Transmit Time 0.25

Choose

↓

Occupational/Controlled

General Population/Uncontrolled

ENTER

↓

Tx Frequency: 836.60 (MHz)

Maximum Peak Power at Antenna Input Terminal: 26.89 (dBm)

Source-Based Time-Average Factor: -6.02 (dB)

Antenna gain and Cable Loss: 1.11 (dBi)

SL= 0.56 (mW/cm²)

P= 122.1631 (mW)

G= 1.29 (numeric)

R = 4.74 (cm)

S (mw/cm²)
at 20cm

0.031347245

Formulae:

$$S = \frac{PG}{4\pi R^2}$$

where: S = Power Density Limit
P = Power Output of the Device
G = Numeric Antenna Gain
R = Distance from Antenna

$$R = \sqrt{\frac{PG}{4\pi S}}$$

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))
Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.10 Calculations:

Vehicle-Mount Antenna (Max. Measured Conducted Power - PCS EDGE Mode)

Prediction of MPE Limit
OET Bulletin 65, Edition 97-01

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna
SL= power density limit

$$R = \sqrt{\frac{PG}{4\pi S}}$$

Ratio of Time On versus Total Transmit Time 0.25

Choose

Occupational/Controlled

General Population/Uncontrolled

Tx Frequency: 1880.00 (MHz)

Maximum Peak Power at Antenna Input Terminal: 25.73 (dBm)

Source-Based Time-Average Factor: -6.02 (dB)

Antenna gain and Cable Loss: 0.20 (dBi)

SL= 1.00 (mW/cm²)
P= 93.5276 (mW)
G= 1.05 (numeric)

R = 2.79 (cm)

S (mw/cm²)
at 20cm

0.019462534

Formulae:

$$S = \frac{PG}{4\pi R^2}$$

where: S = Power Density Limit
P = Power Output of the Device
G = Numeric Antenna Gain
R = Distance from Antenna

$$R = \sqrt{\frac{PG}{4\pi S}}$$

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))
Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.11 Calculations:

Vehicle-Mount Antenna (Max. Measured Conducted Power - Cellular UMTS Mode)

**Prediction of MPE Limit
OET Bulletin 65, Edition 97-01**

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

$$R = \sqrt{\frac{PG}{4\pi S}}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna
SL= power density limit

Ratio of Time On versus Total Transmit Time 1.00

Choose

- Occupational/Controlled
 General Population/Uncontrolled

ENTER

Tx Frequency: 846.60 (MHz)
 Maximum Peak Power at Antenna Input Terminal: 24.00 (dBm)
 Source-Based Time-Average Factor: 0.00 (dB)
 Antenna gain and Cable Loss: 1.11 (dBi)

SL= 0.56 (mW/cm²)
P= 251.1886 (mW)
G= 1.29 (numeric)

R = 6.76 (cm)

**S (mw/cm²)
at 20cm**

0.064455409

Formulae:

$S = \frac{PG}{4\pi R^2}$ where: S = Power Density Limit
 P = Power Output of the Device
 G = Numeric Antenna Gain
 R = Distance from Antenna
 $R = \sqrt{\frac{PG}{4\pi S}}$

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))
 Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.6.12 Calculations:

Vehicle-Mount Antenna (Max. Measured Conducted Power - PCS UMTS Mode)

**Prediction of MPE Limit
OET Bulletin 65, Edition 97-01**

Equation from page 18

$$S = \frac{PG}{4\pi R^2}$$

$$R = \sqrt{\frac{PG}{4\pi S}}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna
SL= power density limit

Ratio of Time On versus Total Transmit Time 1.00

Choose

- Occupational/Controlled
- General Population/Uncontrolled

ENTER

Tx Frequency: 1880.00 (MHz)

Maximum Peak Power at Antenna Input Terminal: 23.00 (dBm)

Source-Based Time-Average Factor: 0.00 (dB)

Antenna gain and Cable Loss: 0.20 (dBi)

SL= 1.00 (mW/cm²)

P= 199.5262 (mW)

G= 1.05 (numeric)

R = 4.08 (cm)

S (mw/cm²)
at 20cm

0.041520193

Formulae:


$$S = \frac{PG}{4\pi R^2}$$

where: S = Power Density Limit
 P = Power Output of the Device
 G = Numeric Antenna Gain
 R = Distance from Antenna

$$R = \sqrt{\frac{PG}{4\pi S}}$$

Source-Based Time-Average Factor = 10 * log (Time On / (Time On + Time Off))

Power Output of the Device (W) = 10 * log (RF Output Power (dBm) + Source-Based Time Average Factor (dB))

	Test Report Serial No.:	061506KBC-T756-E24G	Report Issue Date:	August 22, 2006
	Date(s) of Evaluation:	June 21 - July 27, 2006	Report Revision No.:	Revision 1.0
	Test Standard(s):	FCC 47 CFR §2, §22H, §24E	Industry Canada RSS-132, RSS-133	
	Test Lab Registration(s):	FCC Lab Registration #714830	Industry Canada Lab File #3874	

D.7 PASS/FAIL

In reference to the results outlined in D6 the DUT passes the requirements as stated in the reference standards as follows:
 1) The DUT must comply with the minimum spacing requirement of 20 cm to ensure an exposure of not more than f/1500 mW/cm² for frequencies between 300 and 1500 MHz and 1 mW/cm² for frequencies between 1500 and 100,000 MHz.


D.8 SIGN-OFF

I attest to the accuracy of the data. All measurements reported herein were performed by me and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements.

Spencer Watson

Spencer Watson
 EMC Manager
 Celltech Labs Inc.

June 27, 2006
 Date

Company:	Itronix Corporation	FCC ID:	KBCIX260PLUSAC860	Model(s):	IX260PLUSAC860	
DUT Type:	Laptop PC with Sierra Wireless AC860 Dual-Band GSM/GPRS/EDGE/UMTS PCMCIA Modem					
2006 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 50 of 51