

EXHIBIT 11 - MPE CALCULATION DATA

Model: IX300 with the three co-located transmitters listed below.

1.) AirCard 555, (WAN)

S (mw/cm²) at 20cm = 0.055623635

Tx Freq: 825.25 MHz

Max Peak Power @ antenna terminal input:

Antenna Gain: -3.2 dBi

27.67 dBm

S (mw/cm²) at 20cm = 0.071987877

Tx Freq: 1850.20 MHz

Max Peak Power @ antenna terminal input:

Antenna Gain: -0.9 dBi

26.49 dBm

| Channel # | Frequency (MHz) | Peak Power (Watts) | Peak Power (dBm) |
|-----------|-----------------|--------------------|------------------|
| (Ch.8) | 825.25 | 0.204 | 26.85 |
| (Ch.383) | 836.50 | 0.160 | 27.67 |
| (Ch.758) | 847.75 | 0.174 | 27.07 |
| (Ch.512) | 1850.2 | 0.414 | 25.30 |
| (Ch.661) | 1880.0 | 0.340 | 26.49 |
| (Ch.810) | 1909.8 | 0.302 | 25.12 |

2.) WM168b-Molex, (WLAN),

S (mw/cm²) at 20cm = 0.0039

Tx Freq: 2412 MHz

Max Peak Power @ antenna terminal input:

Antenna Gain: -3.04 dBi

16.03 dBm

| Frequency GHz | Power dBm | Cable loss | Corrected Level dBm | Ant. Gain dBi | EIRP |
|---------------|-----------|------------|---------------------|---------------|-------|
| 2.412 | 15.45 | .58 | 16.03 | -3.04 | 12.99 |
| 2.437 | 15.30 | .58 | 15.88 | -3.04 | 12.84 |
| 2.462 | 14.97 | .58 | 15.55 | -3.04 | 12.51 |

3.) MUBTC2-TH, (Bluetooth)

S (mw/cm²) at 20cm = 0.0002

Tx Freq: 2441MHz

Max Peak Power @ antenna terminal input:

Antenna Gain: 0.11 dBi

0.557dBm

| Channel | Frequency (GHz) | Measured Peak Output Power (dBm) | Internal EUT Cable loss dB | Corrected Peak Output Power (dBm) | Corrected Peak Output Power (mW) |
|---------|-----------------|----------------------------------|----------------------------|-----------------------------------|----------------------------------|
| Low | 2.402 | -0.932 | 1.3 | .368 | 1.088 |
| Middle | 2.441 | -0.743 | 1.3 | .557 | 1.137 |
| High | 2.480 | -1.273 | 1.3 | .027 | 1.006 |

The MPE calculations are submitted for multiple frequency exposure criteria. The ratio of the field strength or power density to the applicable exposure limit at the exposure location was determined for each transmitter below. The sum of these ratios does not exceed the 1 mW/cm² limit for uncontrolled exposure / general population exposure limits detailed in CFR 47, Part 1.1310.

Multiple Frequency Exposure Requirements

| Ratio 1 | Ratio 2 | Ratio 3 | Limit |
|------------------------------------|------------|------------|-------|
| AIRCARD555 Cell | MPI350 | Bluetooth | |
| 0.0556 / 0.55 | 0.0039 / 1 | 0.0002 / 1 | <1.0 |
| = 0.1011 | = .0039 | = .0002 | <1.0 |
| Sum = 0.1052 (mW/cm ²) | | | <1.0 |

Multiple Frequency Exposure Requirements

| Ratio 1 | Ratio 2 | Ratio 3 | Limit |
|------------------------------------|------------|------------|-------|
| AIRCARD555 PCS | MPI350 | Bluetooth | |
| 0.0720 / 1 | 0.0039 / 1 | 0.0002 / 1 | <1.0 |
| = 0.0720 | = .0039 | = .0002 | <1.0 |
| Sum = 0.0761 (mW/cm ²) | | | <1.0 |

Prediction of MPE Limit OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \qquad R = \sqrt{PG/4\pi S}$$

- S= power density
- P= power input to the antenna
- G= power gain of the antenna in the direction of interest relative to an isotropic radiator
- R= distance to the center of radiation of the antenna

General Population/Uncontrolled

Cellular Tx Frequency: 825.250 MHz
 Max. Peak Power Antenna Input Terminal: 27.67 dBm
 Antenna gain: -3.20 dBi

S= 0.55 (mW/cm²)
 P= 584.7901 (mW)
 G= 0.48 (numeric)
 R = 6.36 (cm)

S (mw/cm²) at 20cm = 0.055623635

PCS Tx Frequency: 1880.00 MHz
 Max. Peak Power Antenna Input Terminal: 26.49 dBm
 Antenna gain: -0.9 dBi

S= 1.00 (mW/cm²)
 P= 445.6562 (mW)
 G= 0.81 (numeric)
 R = 5.37 (cm)

S (mw/cm²) at 20cm = 0.071987877

Bluetooth Tx Frequency: 2412.00 MHz
Max. Peak Power Antenna Input Terminal: 16.03 dBm
Antenna gain: -3.04 dBi

S= 1.00 mW/cm²
P= 40.0867 (mW)
G= 0.50 (numeric)
R = 1.26 (cm)

S (mw/cm²) at 20cm = 0.003956028

WLAN Tx Frequency: 2441.00 MHz
Max. Peak Power Antenna Input Terminal: 0.56 dBm
Antenna gain: 0.11 dBi

S= 1.00 (mW/cm²)
P= 1.1368 (mW)
G= 1.03 (numeric)
R = 0.30 (cm)

S (mw/cm²) at 20cm = 0.000231718