

General Population/Uncontrolled

1.) AirCard775, (WAN) GSM850

Tx Frequency: 836.60 MHz
Max. Peak Power Antenna Input Terminal: 31.44 dBm
Antenna gain: -2.80 dBi

S= 0.56 (mW/cm²)
P= 1393.1568 (mW)
G= 0.52 (numeric)
R = 10.21 (cm)

S (mw/cm²) at 20cm = 0.14529791

2.) AirCard775, (WAN) PCS1900

Tx Frequency: 188000 MHz
Max. Peak Power Antenna Input Terminal: 28.41 dBm
Antenna gain: 2.00 dBi

S= 1.00 (mW/cm²)
P= 693.4258 (mW)
G= 1.58 (numeric)
R = 9.35 (cm)

S (mw/cm²) at 20cm = 0.218403386

3.) WM168b-Molex, (WLAN)

Tx Frequency: 2412.00 MHz
Max. Peak Power Antenna Input Terminal: 16.03 dBm
Antenna gain: -3.04 dBi

S= 1.00 mW/cm²
P= 40.0867 (mW)
G= 0.50 (numeric)
R = 1.26 (cm)

S (mw/cm²) at 20cm = 0.003956028

4.) MUBTC2-TH, (Bluetooth)

Tx Frequency: 2441.00 MHz
Max. Peak Power Antenna Input Terminal: 0.56 dBm
Antenna gain: 0.11 dBi

S= 1.00 (mW/cm²)
P= 1.1368 (mW)
G= 1.03 (numeric)
R = 0.30 (cm)

S (mw/cm²) at 20cm = 0.000231718