



Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093 IC RSS-102 Issue 2

RF EXPOSURE EVALUATION

SPECIFIC ABSORPTION RATE

SAR TEST REPORT

FOR

ITRONIX CORPORATION

MODEL: IX325-AC580BT

IX325 SERIES RUGGED TABLET PC

WITH

DUAL-BAND PCS/CELLULAR CDMA PCMCIA MODEM

AND

COLOCATED BLUETOOTH

FCC ID: KBCIX325-AC580BT

IC: 1943A-IX325f

Test Report Serial Number

100305KBC-T674-S24C

Test Report Issue No.

S674C-021706-R0

Test Lab

**Celltech Compliance Testing & Engineering Lab
(Celltech Labs Inc.)**

**1955 Moss Court
Kelowna, BC
Canada
V1Y 9L3**

<p>Test Report Prepared By:</p> <p><i>Cheri Frangiadakis</i></p> <hr/> <p>Cheri Frangiadakis Test Report Writer Celltech Labs Inc.</p>	<p>Test Report Approved By:</p> <p><i>[Signature]</i></p> <hr/> <p>Jonathan Hughes General Manager Celltech Labs Inc.</p>
--	---

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 1 of 49



Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
Type of Evaluation:	RF Exposure SAR	FCC 47 CFR §2.1093	IC RSS-102 Issue 2



DECLARATION OF COMPLIANCE SAR RF EXPOSURE EVALUATION

<p>Test Lab</p> <p>CELLTECH LABS INC. Testing and Engineering Services 1955 Moss Court Kelowna, B.C. Canada V1Y 9L3 Phone: 250-448-7047 Fax: 250-448-7046 e-mail: info@celltechlabs.com web site: www.celltechlabs.com</p>	<p>Applicant Information</p> <p>ITRONIX CORPORATION 12825 E. Mirabeau Parkway Spokane Valley, WA 99216 United States</p>
<p>FCC IDENTIFIER: KBCIX325-AC580BT IC IDENTIFIER: 1943A-IX325f Model(s): IX325-AC580BT</p>	
<p>Rule Part(s): FCC 47 CFR §2.1093; Health Canada Safety Code 6 Test Procedure(s): FCC OET Bulletin 65, Supplement C (Edition 01-01) Industry Canada RSS-102 Issue 2 FCC Device Classification: PCS Licensed Transmitter (PCB) IC Device Classification: 2 GHz Personal Communication Services (RSS-133 Issue 3) 800 MHz Cellular Telephones Employing New Technologies (RSS-132 Issue 2)</p>	
<p>Device Description: Rugged Tablet PC with CDMA & Bluetooth User Orientation(s): 0 Degrees Landscape, -90 Degrees Portrait Internal Transmitter: Sierra Wireless AirCard 580 Dual-Band PCS/Cellular CDMA PCMCIA Modem Co-located Transmitter(s): MSI MS-6837 Bluetooth (simultaneous transmission) Transmitter Frequency Range(s): 1851.25 - 1908.75 MHz (PCS Band) 824.70 - 848.31 MHz (Cellular Band) 2402 - 2480 MHz (Bluetooth) Max. RF Output Power Tested: 24.2 dBm (0.263 Watts) Conducted (PCS CDMA) 23.2 dBm (0.209 Watts) Conducted (Cellular CDMA) 4.46 dBm (0.00279 Watts) - Peak Conducted (Bluetooth) Power Source(s) Tested: Internal Lithium-ion Battery - 11.1 V, 3600 mAh (Model: T8M-E) Antenna Type(s) Tested: External Hinged Dipole (CDMA) Internal PIFA (Bluetooth)</p>	
<p>Max. SAR Level(s) Evaluated: Body: 0.130 W/kg (1g average) - PCS Band Body: 0.0673 W/kg (1g average) - Cellular Band</p>	

Celltech Labs Inc. declares under its sole responsibility that this wireless device was compliant with the Specific Absorption Rate (SAR) RF exposure requirements specified in FCC 47 CFR §2.1093 and Health Canada's Safety Code 6. The device was tested in accordance with the measurement standards and procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01) and Industry Canada RSS-102 Issue 2 for the General Population / Uncontrolled Exposure environment. All measurements were performed in accordance with the SAR system manufacturer recommendations.

I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc. The results and statements contained in this report pertain only to the device(s) evaluated.

<p>Tested By:</p>  <p>Sean Johnston Compliance Technologist Celltech Labs Inc.</p>	<p>Reviewed By:</p>  <p>Spencer Watson Senior Compliance Technologist Celltech Labs Inc.</p>
---	---



Applicant: Itronix Corporation	FCC ID: KBCIX325-AC580BT	IC ID: 1943A-IX325f	
Model: IX325-AC580BT	DUT: Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth		
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.		Page 2 of 49


	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure SAR	FCC 47 CFR §2.1093	IC RSS-102 Issue 2

TABLE OF CONTENTS	
1.0 INTRODUCTION	4
2.0 DESCRIPTION of DEVICE UNDER TEST (DUT)	4
3.0 SAR MEASUREMENT SYSTEM	5
4.0 MEASUREMENT SUMMARY	6
5.0 DETAILS OF SAR EVALUATION	8
6.0 EVALUATION PROCEDURES	9
7.0 SYSTEM PERFORMANCE CHECK	10
8.0 SIMULATED EQUIVALENT TISSUES	11
9.0 SAR SAFETY LIMITS	11
10.0 ROBOT SYSTEM SPECIFICATIONS	12
11.0 PROBE SPECIFICATION (ET3DV6)	13
12.0 PLANAR PHANTOM	13
13.0 DEVICE HOLDER	13
14.0 TEST EQUIPMENT LIST	14
15.0 MEASUREMENT UNCERTAINTIES	15
16.0 REFERENCES	17
APPENDIX A - SAR MEASUREMENT DATA	18
APPENDIX B - SYSTEM PERFORMANCE CHECK DATA	31
APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS	38
APPENDIX D - SAR TEST SETUP PHOTOGRAPHS	42
APPENDIX E - SYSTEM VALIDATION	47
APPENDIX F - PROBE CALIBRATION	48
APPENDIX G - PLANAR PHANTOM CERTIFICATE OF CONFORMITY	49


	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093


1.0 INTRODUCTION

This measurement report demonstrates that the ITRONIX CORPORATION Model: IX325-AC580BT Rugged Tablet PC FCC ID: KBCIX325-AC580BT, incorporating the Sierra Wireless AirCard 580 Dual-Band PCS/Cellular CDMA PCMCIA Modem co-located with MSI MS-6837 Bluetooth, complies with the SAR (Specific Absorption Rate) RF exposure requirements specified in FCC 47 CFR §2.1093 (see reference [1]), and Health Canada's Safety Code 6 (see reference [2]) for the General Population / Uncontrolled Exposure environment. The test procedures described in FCC OET Bulletin 65, Supplement C, Edition 01-01 (see reference [3]), and IC RSS-102 Issue 2 (see reference [4]) were employed. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

2.0 DESCRIPTION of DEVICE UNDER TEST (DUT)

FCC Rule Part(s)	47 CFR §2.1093		IC Rule Part(s)	Health Canada Safety Code 6
Test Procedure(s)	FCC OET Bulletin 65, Supplement C (01-01)		IC RSS-102 Issue 2	
FCC Device Classification	PCS Licensed Transmitter (PCB)			24E, 22H
IC Device Classification	2 GHz Personal Communication Services			RSS 133 Issue 3
	800MHz Cellular Telephones Employing New Technologies			RSS-132 Issue 2
Device Description	Rugged Tablet PC	LCD Display User Orientation(s)	0 Degrees Landscape, -90 Degrees Portrait	
Internal Transmitter	Sierra Wireless AirCard 580 Dual-Band PCS/Cellular CDMA PCMCIA Modem			
Co-located Transmitter(s)	MSI MS-6837 Bluetooth			
FCC IDENTIFIER	KBCIX325-AC580BT		IC IDENTIFIER	1943A-IX325f
Model(s)	IX325-AC580BT			
Test Sample Serial No.(s)	ZZGEG5073ZZ9782		IX325 Tablet PC	Identical Prototype
	60209FBS		AirCard 580	Production Unit
	BH5070000122		MSI Bluetooth	Production Unit
Mode(s) of Operation	Dual-Band CDMA		Code Division Multiple Access	
	Bluetooth FHSS		Frequency Hopping Spread Spectrum	
Transmitter Frequency Range(s)	1851.25 - 1908.75 MHz	PCS Band	824.70 - 848.31 MHz	Cellular Band
	2402 - 2480 MHz		Bluetooth	
Max. Conducted RF Output Power Level(s) Measured	23.2 dBm	0.209 Watts	1851.25 MHz	PCS CDMA
	24.2 dBm	0.263 Watts	1880.00 MHz	PCS CDMA
	24.2 dBm	0.263 Watts	1909.75 MHz	PCS CDMA
	23.2 dBm	0.209 Watts	824.70 MHz	Cellular CDMA
	23.2 dBm	0.209 Watts	836.52 MHz	Cellular CDMA
	23.2 dBm	0.209 Watts	848.31 MHz	Cellular CDMA
	4.46 dBm	0.00279 Watts	2441 MHz	Bluetooth
Antenna Type(s) Tested	External Hinged Dipole	Dual-Band CDMA	Internal PIFA	Bluetooth
DUT Position(s) Tested	Bottom Side of Tablet PC			
Antenna Positions Tested	AirCard 580 Dual-Band CDMA External Antenna (Hinged Dipole)	Position 1	Parallel Straight	Antenna 180° to card
		Position 2	Parallel Bent	Antenna 180° to card
		Position 3	Perpendicular	Antenna 90° to card
Power Source(s) Tested	Internal Lithium-ion Battery		11.1 V, 3600 mAh	Model: T8M-E
Additional Power Source(s) Testing Not Required	External Second Lithium-ion Battery		11.1 V, 3600 mAh	Model: T8S-E
	Note: The external second lithium-ion battery was not evaluated for SAR due to the fact that it has exactly the same power specifications as the internal battery and provides additional separation distance to user.			

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 4 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093

3.0 SAR MEASUREMENT SYSTEM


Celltech Labs Inc. SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 measurement system is comprised of the measurement server, robot controller, computer, near-field probe, probe alignment sensor, specific anthropomorphic mannequin (SAM) phantom, and various planar phantoms for brain and/or body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY4 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the DASY4 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.



DASY4 SAR Measurement System with planar phantom



DASY4 SAR Measurement System with planar phantom and validation dipole

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 5 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure SAR	FCC 47 CFR §2.1093	IC RSS-102 Issue 2


4.0 MEASUREMENT SUMMARY

BODY SAR EVALUATION RESULTS - CELLULAR CDMA

Test Date	Test Mode	Freq. (MHz)	Chan.	Antenna Position	Power Source	DUT Position to Planar Phantom	Separation Distance to Planar Phantom (cm)	Cond. Power Before Test (dBm)	SAR Drift During Test (dB)	Measured SAR 1g (W/kg)
Oct. 04	Cellular CDMA	836.52	384	Perpendicular	Li-Ion Battery	Bottom Side	0.0	23.2	-0.503 ⁴	0.0305
Oct. 04	Cellular CDMA	836.52	384	Parallel Straight	Li-Ion Battery	Bottom Side	0.0	23.2	-0.140 ³	0.0673
Oct. 04	Cellular CDMA	836.52	384	Parallel Bent	Li-Ion Battery	Bottom Side	0.0	23.2	-0.498 ⁴	0.0394
Oct. 24	Cellular CDMA	836.52	384	Parallel Straight	Li-Ion Battery	Bottom Side	0.0	23.2	0.143 ³	0.0249
	Bluetooth Modulated Fixed Frequency	2441	Mid	Internal				4.46		
ANSI / IEEE C95.1 1999 - SAFETY LIMIT				BODY: 1.6 W/kg (averaged over 1 gram)			Spatial Peak Uncontrolled Exposure / General Population			
Test Date(s)	October 04, 2005			October 24, 2005			Test Date(s)	Oct. 04	Oct. 24	Unit
Dielectric Constant ϵ_r	835 MHz Body					Relative Humidity		32	32	%
	IEEE Target		Date	Measured	Deviation	Atmospheric Pressure		101.6	102.3	kPa
	55.2	± 5%	Oct 4	53.3	-3.4%	Ambient Temperature		22.8	23.7	°C
Conductivity σ (mho/m)	835 MHz Body					Fluid Temperature		22.4	22.4	°C
	IEEE Target		Date	Measured	Deviation	Fluid Depth		≥ 15	≥ 15	cm
	0.97	± 5%	Oct 4	0.99	+2.1%	ρ (Kg/m³)		1000		
			Oct 24	0.98	+1.0%					

Note(s):

- The measurement results were obtained with the DUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the DUT are reported in Appendix A.
- If the scaled SAR levels evaluated at the mid channel were ≥ 3 dB below the SAR limit, SAR evaluation for the low and high channels was optional (per FCC OET Bulletin 65, Supplement C, Edition 01-01 - see reference [3]).
- The power drift of the DUT measured by the SAR system during the evaluation was $< 5\%$ from the start power.
- The power drifts reported were measured at the reference point of the phantom with low SAR. The drift values shown are inaccurate due to the SAR value at the reference point is close to the measurement noise floor; therefore power drift scaling was not applied in this case.
- The DUT battery was fully charged prior to the SAR evaluations.
- The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the SAR evaluations. The temperatures reported in the table above were consistent for all measurement periods.
- The dielectric parameters of the simulated tissue mixture were measured prior to the SAR evaluations using an ALS-PR-DIEL Dielectric Probe Kit and an HP 8753ET Network Analyzer (see Appendix C).
- The SAR evaluations were performed within 24 hours of the system performance check.

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 6 of 49



Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
Type of Evaluation:	RF Exposure SAR	FCC 47 CFR §2.1093	IC RSS-102 Issue 2

MEASUREMENT SUMMARY (Cont.)


BODY SAR EVALUATION RESULTS - PCS CDMA

Test Mode	Freq. (MHz)	Chan.	Antenna Position	Power Source	DUT Position to Planar Phantom	Separation Distance to Planar Phantom (cm)	Cond. Power Before Test (dBm)	SAR Drift During Test (dB)	Measured SAR 1g (W/kg)
PCS CDMA	1880.00	600	Parallel Straight	Li-ion Battery	Bottom Side	0.0	24.2	-0.0483	0.130
PCS CDMA	1880.00	600	Parallel Bent	Li-ion Battery	Bottom Side	0.0	24.2	0.000159	0.0939
PCS CDMA	1880.00	600	Perpendicular	Li-ion Battery	Bottom Side	0.0	24.2	-0.134	0.0882
PCS CDMA	1880.00	600	Parallel Straight	Li-ion Battery	Bottom Side	0.0	24.2	0.0118	0.116
Bluetooth Modulated Fixed Frequency	2441	Mid	Internal				4.46		
ANSI / IEEE C95.1 1999 - SAFETY LIMIT			BODY: 1.6 W/kg (averaged over 1 gram)			Spatial Peak Uncontrolled Exposure / General Population			
Test Date(s)	October 21, 2005				Relative Humidity		31	%	
Measured Fluid Type	1880 MHz Body				Atmospheric Pressure		103.0	kPa	
Dielectric Constant ϵ_r	IEEE Target		Measured	Deviation	Ambient Temperature		23.4	°C	
	53.3	± 5%	50.8	-4.7%	Fluid Temperature		22.0	°C	
Conductivity σ (mho/m)	IEEE Target		Measured	Deviation	Fluid Depth		≥ 15	cm	
	1.52	± 5%	1.46	-3.9%	ρ (Kg/m³)		1000		

Note(s):

- The measurement results were obtained with the DUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the DUT are reported in Appendix A.
- If the scaled SAR levels evaluated at the mid channel were ≥ 3 dB below the SAR limit, SAR evaluation for the low and high channels was optional (per FCC OET Bulletin 65, Supplement C, Edition 01-01 - see reference [3]).
- The power drift of the DUT measured by the SAR system during the evaluations was $< 5\%$ from the start power.
- The DUT battery was fully charged prior to the SAR evaluations.
- The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the SAR evaluations. The temperatures reported in the table above were consistent for all measurement periods.
- The dielectric parameters of the simulated tissue mixture were measured prior to the SAR evaluations using an ALS-PR-DIEL Dielectric Probe Kit and an HP 8753ET Network Analyzer (see Appendix C).
- The SAR evaluations were performed within 24 hours of the system performance check.

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 7 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093

5.0 DETAILS OF SAR EVALUATION

The ITRONIX CORPORATION Model: IX325-AC580BT Rugged Tablet PC FCC ID: KBCIX325-AC580BT, with internal Sierra Wireless AirCard 580 Dual-Band PCS/Cellular CDMA PCMCIA Modem co-located with MSI MS-6837 Bluetooth, was compliant for localized Specific Absorption Rate (Uncontrolled Exposure) based on the test provisions and conditions described below. The detailed test setup photographs are shown in Appendix D.

Body SAR Test Configuration

1. The DUT was tested for body SAR with the bottom side of the Tablet PC placed parallel to, and touching, the outer surface of the planar phantom. The DUT was evaluated with the AirCard 580 antenna placed in the “Parallel Straight” position, “Parallel Bent” position, and “Perpendicular” position (see photos below).
2. A 2nd SAR scan was performed over the entire surface of the tablet PC bottom side in the worst-case SAR test configurations for both PCS and Cellular bands in order to show there was no SAR distribution over bottom surface area of the DUT.
3. The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the SAR evaluations. The temperatures reported were consistent for all measurement periods.
4. The dielectric parameters of the simulated tissue mixtures were measured prior to the SAR evaluations using an ALS-PR-DIEL Dielectric Probe Kit and an HP 8753ET Network Analyzer (see Appendix C).
5. The SAR evaluations were performed within 24 hours of the system performance check.

Test Modes & Power Settings

6. The DUT was controlled in test mode via internal software with the DUT transmitting in the “always up” power control mode with a modulated CDMA signal. For co-located simultaneous transmit evaluations the Bluetooth transmitter was placed in continuous transmit operation at maximum power on a fixed frequency with the frequency hopping disabled and a modulated signal.
7. The conducted power levels of the DUT were measured at the AirCard 580 hatch antenna port prior to the SAR evaluations using a Gigatronics 8652A Universal Power Meter according to the procedures described in FCC 47 CFR §2.1046.
8. The power drift was measured by the DASY4 system for the duration of the SAR evaluations.
9. The DUT battery was fully charged prior to each SAR evaluation.




**Antenna “Parallel Straight”
 (“0 Degrees Landscape”
 Device User Orientation)**




**Antenna “Parallel Bent”
 (“-90 Degrees Portrait”
 Device User Orientation)**



**Antenna “Perpendicular”
 (“0 Degrees Landscape”
 Device User Orientation)**

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 8 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093

6.0 EVALUATION PROCEDURES


- a. (i) The evaluation was performed in the applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated using the SAM phantom.
- (ii) For body-worn and face-held devices a planar phantom was used.
- b. The SAR was determined by a pre-defined procedure within the DASY4 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 15mm x 15mm.


An area scan was determined as follows:

- c. Based on the defined area scan grid, a more detailed grid is created to increase the points by a factor of 10. The interpolation function then evaluates all field values between corresponding measurement points.
- d. A linear search is applied to find all the candidate maxima. Subsequently, all maxima are removed that are >2 dB from the global maximum. The remaining maxima are then used to position the cube scans.

A 1g and 10g spatial peak SAR was determined as follows:

- e. Extrapolation is used to find the points between the dipole center of the probe and the surface of the phantom. This data cannot be measured, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.4 mm (see probe calibration document in Appendix F). The extrapolation was based on trivariate quadratics computed from the previously calculated 3D interpolated points nearest the phantom surface.
- f. Interpolated data is used to calculate the average SAR over 1g and 10g cubes by spatially discretizing the entire measured cube. The volume used to determine the averaged SAR is a 1mm grid (42875 interpolated points).
- g. A zoom scan volume of 32 mm x 32 mm x 30 mm (5 x 5 x 7 points) centered at the peak SAR location determined from the area scan is used for all zoom scans for devices with a transmit frequency < 800 MHz. Zoom scans for frequencies ≥ 800 MHz are determined with a scan volume of 30 mm x 30 mm x 30 mm (7 x 7 x 7) to ensure complete capture of the peak spatial-average SAR.

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 9 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure SAR	FCC 47 CFR §2.1093	IC RSS-102 Issue 2

7.0 SYSTEM PERFORMANCE CHECK

Prior to the SAR evaluations a system check was performed using a planar phantom with an 835MHz dipole and a 1900MHz dipole (see Appendix E for system validation procedures). The dielectric parameters of the simulated tissue mixtures were measured prior to the system performance check using an ALS-PR-DIEL Dielectric Probe Kit and an HP 8753ET Network Analyzer (see Appendix C). A forward power of 250 mW was applied to the dipole and the system was verified to a tolerance of $\pm 10\%$ (see Appendix B for system performance check test plots). See Table 1 below for the SAR system manufacturer's reference body SAR values from the DASY4 Operation Manual, March 2005 (see reference [6]).

SYSTEM PERFORMANCE CHECK EVALUATIONS

Test Date	Equiv. Tissue Body (MHz)	SAR 1g (W/kg)			Dielectric Constant ϵ_r			Conductivity σ (mho/m)			ρ (Kg/m ³)	Amb. Temp. (°C)	Fluid Temp. (°C)	Fluid Depth (cm)	Humid. (%)	Barom. Press. (kPa)
		IEEE Target	Meas.	Dev.	IEEE Target	Meas.	Dev.	IEEE Target	Meas.	Dev.						
10/04/05	835	2.43 $\pm 10\%$	2.61	+7.4%	55.2 $\pm 5\%$	53.3	-3.4%	0.97 $\pm 5\%$	0.99	+2.1%	1000	24.1	22.4	≥ 15	31	101.5
10/21/05	1900	9.95 $\pm 10\%$	10.2	+2.5%	53.3 $\pm 5\%$	50.7	-4.9%	1.52 $\pm 5\%$	1.48	-2.6%	1000	23.0	22.0	≥ 15	31	103.0
10/24/05	835	2.43 $\pm 10\%$	2.63	+8.2%	55.2 $\pm 5\%$	52.6	-4.7%	0.97 $\pm 5\%$	0.98	+1.0%	1000	23.4	22.4	≥ 15	32	102.3

Note(s):

1. The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the system performance check. The temperatures listed in the table above were consistent for all measurement periods.




Figure 1. System Performance Check Setup Diagram

Dipole Type	Distance [mm]	Frequency [MHz]	SAR (1g) [W/kg]	SAR (10g) [W/kg]	SAR (peak) [W/kg]
D300V2	15	300	3.02	2.06	4.36
D450V2	15	450	5.01	3.36	7.22
D835V2	15	835	9.71	6.38	14.1
D900V2	15	900	11.1	7.17	16.3
D1450V2	10	1450	29.6	16.6	49.8
D1500V2	10	1500	30.8	17.1	52.1
D1640V2	10	1640	34.4	18.7	59.4
D1800V2	10	1800	38.5	20.3	67.5
D1900V2	10	1900	39.8	20.8	69.6
D2000V2	10	2000	40.9	21.2	71.5
D2450V2	10	2450	51.2	23.7	97.6
D3000V2	10	3000	61.9	24.8	136.7

Table 32.1: Numerical reference SAR values for SPEAG dipoles and flat phantom filled with body-tissue simulating liquid. Note: All SAR values normalized to 1 W forward power.


Table 1. SAR system manufacturer's reference body SAR values



1900MHz Dipole Setup



835MHz Dipole Setup

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 10 of 49

8.0 SIMULATED EQUIVALENT TISSUES

The 1880/1900MHz simulated equivalent tissue mixture consisted of Glycol-monobutyl, water, and salt. The 835MHz simulated equivalent tissue mixture consisted of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution. Preservation with a bactericide was added and visual inspection was made to ensure air bubbles were not trapped during the mixing process. The fluids were prepared according to standardized procedures and measured for dielectric parameters (permittivity and conductivity).

1880/1900MHz TISSUE MIXTURES		
INGREDIENT	1900 MHz Body	1880 MHz Body
	System Performance Check	DUT Evaluation
Water	69.85 %	69.85 %
Glycol Monobutyl	29.89 %	29.89 %
Salt	0.26 %	0.26 %

835MHz TISSUE MIXTURES		
INGREDIENT	835 MHz Body	835 MHz Body
	System Performance Check	DUT Evaluation
Water	53.79 %	53.79 %
Sugar	45.13 %	45.13 %
Salt	0.98 %	0.98 %
HEC	--	--
Bactericide	0.10 %	0.10 %

9.0 SAR SAFETY LIMITS

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Notes:

1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093 IC RSS-102 Issue 2

10.0 ROBOT SYSTEM SPECIFICATIONS

Specifications

POSITIONER: Stäubli Unimation Corp. Robot Model: RX60L
Repeatability: 0.02 mm
No. of axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: AMD Athlon XP 2400+
Clock Speed: 2.0 GHz
Operating System: Windows XP Professional

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, and control logic
Software: DASY4 software
Connecting Lines: Optical downlink for data and status info.
 Optical uplink for commands and clock

DASY4 Measurement Server


Function: Real-time data evaluation for field measurements and surface detection
Hardware: PC/104 166MHz Pentium CPU; 32 MB chipdisk; 64 MB RAM
Connections: COM1, COM2, DAE, Robot, Ethernet, Service Interface


E-Field Probe

Model: ET3DV6
Serial No.(s): 1387
Construction: Triangular core fiber optic detection system
Frequency: 10 MHz to 6 GHz
Linearity: ±0.2 dB (30 MHz to 3 GHz)

Phantom(s)

Type: Planar Phantom
Shell Material: Fiberglass
Thickness: 2.0 ±0.1 mm
Volume: Approx. 72 liters

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 12 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure SAR	FCC 47 CFR §2.1093	IC RSS-102 Issue 2

11.0 PROBE SPECIFICATION (ET3DV6)

Construction: Symmetrical design with triangular core
 Built-in shielding against static charges
 PEEK enclosure material (resistant to organic solvents, e.g. glycol)

Calibration: In air from 10 MHz to 2.5 GHz
 In brain simulating tissue at frequencies of 900 MHz and 1.8 GHz (accuracy $\pm 8\%$)

Frequency: 10 MHz to >6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz)

Directivity: ± 0.2 dB in brain tissue (rotation around probe axis)
 ± 0.4 dB in brain tissue (rotation normal to probe axis)

Dynamic Range: 5 μ W/g to >100 mW/g; Linearity: ± 0.2 dB

Surface Detection: ± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces

Dimensions: Overall length: 330 mm
 Tip length: 16 mm
 Body diameter: 12 mm
 Tip diameter: 6.8 mm
 Distance from probe tip to dipole centers: 2.7 mm

Application: General dosimetry up to 3 GHz
 Compliance tests of portable devices



ET3DV6 E-Field Probe

12.0 PLANAR PHANTOM

The planar phantom is a fiberglass shell phantom with a 2.0 mm (+/-0.2mm) thick device measurement area at the center of the phantom for SAR evaluations of devices with a larger surface area than the planar section of the SAM phantom. The planar phantom is integrated in a wooden table (see Appendix G for dimensions and specifications of the planar phantom).




Planar Phantom

13.0 DEVICE HOLDER

The DASY4 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. For evaluations of larger devices such as Laptop and Tablet PCs, a Plexiglas platform is attached to the device holder.




Device Holder


Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 13 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093

14.0 TEST EQUIPMENT LIST

TEST EQUIPMENT		ASSET NO.	SERIAL NO.	DATE CALIBRATED		CALIBRATION DUE DATE
USED	DESCRIPTION					
x	Schmid & Partner DASY4 System	-	-	-	-	-
x	-DASY4 Measurement Server	00158	1078	N/A	N/A	N/A
x	-Robot	00046	599396-01	N/A	N/A	N/A
x	-DAE4	00019	353	15Jun05	15Jun06	15Jun06
	-DAE3	00018	370	25Jan05	25Jan06	25Jan06
x	-ET3DV6 E-Field Probe	00016	1387	18Mar05	18Mar06	18Mar06
	-ET3DV6 E-Field Probe	00017	1590	20May05	20May06	20May06
	-EX3DV4 E-Field Probe	00125	3547	21Jan05	21Jan06	21Jan06
	-300MHz Validation Dipole	00023	135	26Oct04	26Oct05	26Oct05
	-450MHz Validation Dipole	00024	136	04Nov04	04Nov05	04Nov05
x	-835MHz Validation Dipole	00022	411	Brain	30Mar05	30Mar06
				Body	12Apr05	12Apr06
	-900MHz Validation Dipole	00020	054	Brain	10Jun05	10Jun06
				Body	10Jun05	10Jun06
	-1800MHz Validation Dipole	00021	247	Brain	14Jun05	14Jun06
				Body	14Jun05	14Jun06
x	-1900MHz Validation Dipole	00032	151	Brain	17Jun05	17Jun06
				Body	22Apr05	22Apr06
	-2450MHz Validation Dipole	00025	150	Brain	20Sep05	20Sep06
				Body	22Apr05	22Apr06
	-5000MHz Validation Dipole	00126	1031	Brain	11Jan05	11Jan06
				Body	11Jan05	11Jan06
	-SAM Phantom V4.0C	00154	1033	N/A	N/A	N/A
x	-Barski Planar Phantom	00155	03-01	N/A	N/A	N/A
	-Plexiglas Side Planar Phantom	00156	161	N/A	N/A	N/A
	-Plexiglas Validation Planar Phantom	00157	137	N/A	N/A	N/A
	HP 85070C Dielectric Probe Kit	00033	N/A	N/A	N/A	N/A
x	ALS-PR-DIEL Dielectric Probe Kit	00160	260-00953	N/A	N/A	N/A
x	Gigatronics 8652A Power Meter	00110	1835801	16Apr05	16Apr06	16Apr06
	Gigatronics 8652A Power Meter	00008	1835267	29Apr05	29Apr06	29Apr06
x	Gigatronics 80701A Power Sensor	00012	1834350	12Sep05	12Sep06	12Sep06
x	Gigatronics 80701A Power Sensor	00014	1833699	07Sep05	07Sep06	07Sep06
x	Gigatronics 80701A Power Sensor	00109	1834366	16Apr05	16Apr06	16Apr06
x	HP 8753ET Network Analyzer	00134	US39170292	04May05	04May06	04May06
x	HP 8648D Signal Generator	00005	3847A00611	29Apr05	29Apr06	29Apr06
	Rohde & Schwarz SMR40 Signal Generator	00006	100104	12Apr05	12Apr06	12Apr06
x	Amplifier Research 5S1G4 Power Amplifier	00106	26235	N/A	N/A	N/A


Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 14 of 49


	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093

15.0 MEASUREMENT UNCERTAINTIES

UNCERTAINTY BUDGET FOR DEVICE EVALUATION						
Error Description	Uncertainty Value ±%	Probability Distribution	Divisor	ci 1g	Uncertainty Value ±% (1g)	V _i or V _{eff}
Measurement System						
Probe calibration	5.5	Normal	1	1	5.5	∞
Axial isotropy of the probe	4.7	Rectangular	1.732050808	0.7	1.9	∞
Spherical isotropy of the probe	9.6	Rectangular	1.732050808	0.7	3.9	∞
Spatial resolution	0	Rectangular	1.732050808	1	0.0	∞
Boundary effects	1	Rectangular	1.732050808	1	0.6	∞
Probe linearity	4.7	Rectangular	1.732050808	1	2.7	∞
Detection limit	1	Rectangular	1.732050808	1	0.6	∞
Readout electronics	0.3	Normal	1	1	0.3	∞
Response time	0.8	Rectangular	1.732050808	1	0.5	∞
Integration time	2.6	Rectangular	1.732050808	1	1.5	∞
RF ambient conditions	3	Rectangular	1.732050808	1	1.7	∞
Mech. constraints of robot	0.4	Rectangular	1.732050808	1	0.2	∞
Probe positioning	2.9	Rectangular	1.732050808	1	1.7	∞
Extrapolation & integration	1	Rectangular	1.732050808	1	0.6	∞
Test Sample Related						
Device positioning	2.9	Normal	1	1	2.9	12
Device holder uncertainty	3.6	Normal	1	1	3.6	8
Power drift	5	Rectangular	1.732050808	1	2.9	∞
Phantom and Setup						
Phantom uncertainty	4	Rectangular	1.732050808	1	2.3	∞
Liquid conductivity (target)	5	Rectangular	1.732050808	0.64	1.8	∞
Liquid conductivity (measured)	2.5	Normal	1	0.64	1.6	∞
Liquid permittivity (target)	5	Rectangular	1.732050808	0.6	1.7	∞
Liquid permittivity (measured)	2.5	Normal	1	0.6	1.5	∞
Combined Standard Uncertainty					10.58	
Expanded Uncertainty (k=2)					21.16	

Measurement Uncertainty Table in accordance with IEEE Standard 1528-2003 (see reference [5])


Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 15 of 49


	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093

MEASUREMENT UNCERTAINTIES (Cont.)

UNCERTAINTY BUDGET FOR SYSTEM VALIDATION						
Error Description	Uncertainty Value ±%	Probability Distribution	Divisor	ci 1g	Uncertainty Value ±% (1g)	V _i or V _{eff}
Measurement System						
Probe calibration	5.5	Normal	1	1	5.5	∞
Axial isotropy of the probe	4.7	Rectangular	1.732050808	1	2.7	∞
Spherical isotropy of the probe	0	Rectangular	1.732050808	1	0.0	∞
Spatial resolution	0	Rectangular	1.732050808	1	0.0	∞
Boundary effects	1	Rectangular	1.732050808	1	0.6	∞
Probe linearity	4.7	Rectangular	1.732050808	1	2.7	∞
Detection limit	1	Rectangular	1.732050808	1	0.6	∞
Readout electronics	0.3	Normal	1	1	0.3	∞
Response time	0	Rectangular	1.732050808	1	0.0	∞
Integration time	0	Rectangular	1.732050808	1	0.0	∞
RF ambient conditions	3	Rectangular	1.732050808	1	1.7	∞
Mech. constraints of robot	0.4	Rectangular	1.732050808	1	0.2	∞
Probe positioning	2.9	Rectangular	1.732050808	1	1.7	∞
Extrapolation & integration	1	Rectangular	1.732050808	1	0.6	∞
Test Sample Related						
Dipole Positioning	2	Normal	1.732050808	1	1.2	∞
Power & Power Drift	4.7	Normal	1.732050808	1	2.7	∞
Phantom and Setup						
Phantom uncertainty	4	Rectangular	1.732050808	1	2.3	∞
Liquid conductivity (target)	5	Rectangular	1.732050808	0.64	1.8	∞
Liquid conductivity (measured)	2.5	Normal	1	0.64	1.6	∞
Liquid permittivity (target)	5	Rectangular	1.732050808	0.6	1.7	∞
Liquid permittivity (measured)	2.5	Normal	1	0.6	1.5	∞
Combined Standard Uncertainty					8.79	
Expanded Uncertainty (k=2)					17.57	


Measurement Uncertainty Table in accordance with IEEE Standard 1528-2003 (see reference [5])


Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 16 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093


16.0 REFERENCES

- [1] Federal Communications Commission, "Radiofrequency radiation exposure evaluation: portable devices", Rule Part 47 CFR §2.1093: 1999.
- [2] Health Canada, "Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz", Safety Code 6: 1999.
- [3] Federal Communications Commission, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields", OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- [4] Industry Canada, "Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)", Radio Standards Specification RSS-102 Issue 2: November 2005.
- [5] IEEE Standard 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques": December 2003.
- [6] Schmid & Partner Engineering AG, "DASY4 Manual", V4.5 March 2005.

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 17 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093 IC RSS-102 Issue 2

APPENDIX A - SAR MEASUREMENT DATA

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 18 of 49

Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093
			IC RSS-102 Issue 2

Date Tested: 10/04/2005

Body SAR - Cellular CDMA - Bottom Side of DUT - Antenna “Perpendicular” - Channel 384

DUT: Itronix Model: IX325-AC580BT; Type: Tablet PC with PCS/Cellular CDMA PCMCIA Modem; Serial: ZZGEG5073ZZ9782

Ambient Temp: 22.8 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 101.6 kPa; Humidity: 32%

11.1V, 3600mAh Internal Lithium-ion Battery Pack (Model: T8M-E)

Communication System: Cellular CDMA

RF Output Power: 23.2 dBm (Conducted)


Frequency: 836.52 MHz; Channel 384; Duty Cycle: 1:1

Medium: M835 ($\sigma = 0.99$ mho/m; $\epsilon_r = 53.3$; $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.1, 6.1, 6.1); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body SAR - Cellular CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 384
Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm

Body SAR - Cellular CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 384
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 5.81 V/m; Power Drift = -0.503 dB
 Peak SAR (extrapolated) = 0.049 W/kg
SAR(1 g) = 0.0305 mW/g; SAR(10 g) = 0.0209 mW/g



Date Tested: 10/04/2005

Body SAR - Cellular CDMA - Bottom Side of DUT - Antenna “Parallel Straight” - Channel 384

DUT: Itronix Model: IX325-AC580BT; Type: Tablet PC with PCS/Cellular CDMA PCMCIA Modem; Serial: ZZGEG5073ZZ9782


Ambient Temp: 22.8 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 101.6 kPa; Humidity: 32%

11.1V, 3600mAh Internal Lithium-ion Battery Pack (Model: T8M-E)
 Communication System: Cellular CDMA
 RF Output Power: 23.2 dBm (Conducted)
 Frequency: 836.52 MHz; Channel 384; Duty Cycle: 1:1
 Medium: M835 ($\sigma = 0.99$ mho/m; $\epsilon_r = 53.3$; $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.1, 6.1, 6.1); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

**Body SAR - Cellular CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 384
 Area Scan (16x9x1): Measurement grid: dx=15mm, dy=15mm**

**Body SAR - Cellular CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 384
 Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm**
 Reference Value = 8.83 V/m; Power Drift = -0.140 dB
 Peak SAR (extrapolated) = 0.094 W/kg
SAR(1 g) = 0.0673 mW/g; SAR(10 g) = 0.0449 mW/g



Fluid Depth (≥ 15 cm)



Date Tested: 10/24/2005

2nd Scan

Body SAR - Cellular CDMA - Bottom Side of DUT - Antenna “Parallel Straight” - Channel 384


DUT: Itronix Model: IX325-AC580BT; Type: Tablet PC with PCS/Cellular CDMA PCMCIA Modem; Serial: ZZGEG5073ZZ9782

Ambient Temp: 23.7 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 102.3 kPa; Humidity: 32%

11.1V, 3600mAh Internal Lithium-ion Battery Pack (Model: T8M-E)
 Communication System: Cellular CDMA
 RF Output Power: 23.2 dBm (Conducted)
 Frequency: 836.52 MHz; Channel 384; Duty Cycle: 1:1
 Medium: M835 ($\sigma = 0.98 \text{ mho/m}$; $\epsilon_r = 52.6$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(6.1, 6.1, 6.1); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASy4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body SAR - Cellular CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 384
Area Scan (18x23x1): Measurement grid: dx=15mm, dy=15mm



2nd Scan to show SAR Distribution over the entire bottom surface of the Tablet PC

Date Tested: 10/04/2005

Body SAR - Cellular CDMA - Bottom Side of DUT - Antenna “Parallel Bent” - Channel 384

DUT: Itronix Model: IX325-AC580BT; Type: Tablet PC with PCS/Cellular CDMA PCMCIA Modem; Serial: ZZGEG5073ZZ9782

Ambient Temp: 22.8 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 101.6 kPa; Humidity: 32%

11.1V, 3600mAh Internal Lithium-ion Battery Pack (Model: T8M-E)

Communication System: Cellular CDMA

RF Output Power: 23.2 dBm (Conducted)

Frequency: 836.52 MHz; Channel 384; Duty Cycle: 1:1


Medium: M835 ($\sigma = 0.99$ mho/m; $\epsilon_r = 53.3$; $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(6.1, 6.1, 6.1); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body SAR - Cellular CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 384 Area Scan (8x16x1): Measurement grid: dx=15mm, dy=15mm

Body SAR - Cellular CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 384 Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.28 V/m; Power Drift = -0.498 dB
 Peak SAR (extrapolated) = 0.058 W/kg
SAR(1 g) = 0.0394 mW/g; SAR(10 g) = 0.0274 mW/g



Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093
			IC RSS-102 Issue 2

Date Tested: 10/24/2005

Body SAR - Cellular CDMA - Bottom Side of DUT - Antenna “Parallel Straight” - Channel 384 Simultaneous Transmit with Co-located Bluetooth


DUT: Itronix Model: IX325-AC580BT; Type: Tablet PC with PCS/Cellular CDMA & Bluetooth; Serial: ZZGEG5073ZZ9782

Ambient Temp: 23.7 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 102.3 kPa; Humidity: 32%

- 11.1V, 3600mAh Internal Lithium-ion Battery Pack (Model: T8M-E)
- Communication System: Cellular CDMA
- RF Output Power: 23.2 dBm (Conducted)
- Frequency: 836.52 MHz; Channel 384; Duty Cycle: 1:1
- RF Output Power: 4.46 dBm (Peak Conducted) Bluetooth
- Communication System: Modulated Fixed Frequency (Bluetooth)
- Frequency: 2441 MHz; Duty Cycle: 1:1 (Bluetooth)
- Medium: M835 ($\sigma = 0.98$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³)
- Probe: ET3DV6 - SN1387; ConvF(6.1, 6.1, 6.1); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body SAR - Cellular CDMA & Bluetooth - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 384 Area Scan (16x9x1): Measurement grid: dx=15mm, dy=15mm

Body SAR - Cellular CDMA & Bluetooth - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 384 Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 5.24 V/m; Power Drift = 0.143 dB
 Peak SAR (extrapolated) = 0.034 W/kg
SAR(1 g) = 0.0249 mW/g; SAR(10 g) = 0.018 mW/g



Date Tested: 10/21/2005

Body SAR - PCS CDMA - Bottom Side of DUT - Antenna “Parallel Straight” - Channel 600

DUT: Itronix Model: IX325-AC580BT; Type: Tablet PC with PCS/Cellular CDMA PCMCIA Modem; Serial: ZZGEG5073ZZ9782


Ambient Temp: 23.4 °C; Fluid Temp: 22.0 °C; Barometric Pressure: 103.0 kPa; Humidity: 31%

11.1V, 3600mAh Internal Lithium-ion Battery Pack (Model: T8M-E)
 Communication System: PCS CDMA
 RF Output Power: 24.2 dBm (Conducted)
 Frequency: 1880.00 MHz; Channel 600; Duty Cycle: 1:1
 Medium: M1880 ($\sigma = 1.46 \text{ mho/m}$; $\epsilon_r = 50.8$; $\rho = 1000 \text{ kg/m}^3$)


- Probe: ET3DV6 - SN1387; ConvF(4.75, 4.75, 4.75); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body SAR - PCS CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 600 Area Scan (16x9x1): Measurement grid: dx=15mm, dy=15mm

Body SAR - PCS CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 600 Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 10.2 V/m; Power Drift = -0.0483 dB
 Peak SAR (extrapolated) = 0.202 W/kg
SAR(1 g) = 0.130 mW/g; SAR(10 g) = 0.079 mW/g



Z-Axis Scan



Date Tested: 10/21/2005

2nd Scan

Body SAR - PCS CDMA - Bottom Side of DUT - Antenna "Parallel Straight" - Channel 600

DUT: Itronix Model: IX325-AC580BT; Type: Tablet PC with PCS/Cellular CDMA PCMCIA Modem; Serial: ZZGEG5073ZZ9782

Ambient Temp: 23.4 °C; Fluid Temp: 22.0 °C; Barometric Pressure: 103.0 kPa; Humidity: 31%

11.1V, 3600mAh Internal Lithium-ion Battery Pack (Model: T8M-E)

Communication System: PCS CDMA

RF Output Power: 24.2 dBm (Conducted)


Frequency: 1880.00 MHz; Channel 600; Duty Cycle: 1:1

Medium: M1880 ($\sigma = 1.46 \text{ mho/m}$; $\epsilon_r = 50.8$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(4.75, 4.75, 4.75); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body SAR - PCS CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 600

Area Scan (18x23x1): Measurement grid: dx=15mm, dy=15mm



Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093
			IC RSS-102 Issue 2

Date Tested: 10/21/2005

Body SAR - PCS CDMA - Bottom Side of DUT - Antenna “Parallel Bent” - Channel 600

DUT: Itronix Model: IX325-AC580BT; Type: Tablet PC with PCS/Cellular CDMA PCMCIA Modem; Serial: ZZGEG5073ZZ9782

Ambient Temp: 23.4 °C; Fluid Temp: 22.0 °C; Barometric Pressure: 103.0 kPa; Humidity: 31%

11.1V, 3600mAh Internal Lithium-ion Battery Pack (Model: T8M-E)

Communication System: PCS CDMA

RF Output Power: 24.2 dBm (Conducted)


Frequency: 1880.00 MHz; Channel 600; Duty Cycle: 1:1

Medium: M1880 ($\sigma = 1.46 \text{ mho/m}$; $\epsilon_r = 50.8$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(4.75, 4.75, 4.75); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglas Planar; Serial: 03-01
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

**Body SAR - PCS CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 600
Area Scan (8x16x1):** Measurement grid: dx=15mm, dy=15mm

**Body SAR - PCS CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 600
Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 8.79 V/m; Power Drift = 0.000159 dB
Peak SAR (extrapolated) = 0.141 W/kg
SAR(1 g) = 0.0939 mW/g; SAR(10 g) = 0.059 mW/g



Date Tested: 10/21/2005

Body SAR - PCS CDMA - Bottom Side of DUT - Antenna “Perpendicular” - Channel 600

DUT: Itronix Model: IX325-AC580BT; Type: Tablet PC with PCS/Cellular CDMA PCMCIA Modem; Serial: ZZGEG5073ZZ9782

Ambient Temp: 23.4 °C; Fluid Temp: 22.0 °C; Barometric Pressure: 103.0 kPa; Humidity: 31%

11.1V, 3600mAh Internal Lithium-ion Battery Pack (Model: T8M-E)

Communication System: PCS CDMA

RF Output Power: 24.2 dBm (Conducted)


Frequency: 1880.00 MHz; Channel 600; Duty Cycle: 1:1

Medium: M1880 ($\sigma = 1.46 \text{ mho/m}$; $\epsilon_r = 50.8$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(4.75, 4.75, 4.75); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body SAR - PCS CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 600
Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm

Body SAR - PCS CDMA - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 600
Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 8.44 V/m; Power Drift = -0.134 dB
 Peak SAR (extrapolated) = 0.133 W/kg
SAR(1 g) = 0.0882 mW/g; SAR(10 g) = 0.055 mW/g



Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093
			IC RSS-102 Issue 2

Date Tested: 10/21/2005

Body SAR - PCS CDMA - Bottom Side of DUT - Antenna "Parallel Straight" - Channel 600 Simultaneous Transmit with Co-located Bluetooth

DUT: Itronix Model: IX325-AC580BT; Type: Tablet PC with PCS/Cellular CDMA & Bluetooth; Serial: ZZGEG5073ZZ9782
 Ambient Temp: 23.4 °C; Fluid Temp: 22.0 °C; Barometric Pressure: 103.0 kPa; Humidity: 31%

11.1V, 3600mAh Internal Lithium-ion Battery Pack (Model: T8M-E)

Communication System: PCS CDMA

RF Output Power: 24.2 dBm (Conducted)

Frequency: 1880.00 MHz; Channel 600; Duty Cycle: 1:1

RF Output Power: 4.46 dBm (Peak Conducted) Bluetooth

Communication System: Modulated Fixed Frequency (Bluetooth)

Frequency: 2441 MHz; Duty Cycle: 1:1 (Bluetooth)

Medium: M1880 ($\sigma = 1.46 \text{ mho/m}$; $\epsilon_r = 50.8$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(4.75, 4.75, 4.75); Calibrated: 18/03/2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn353; Calibrated: 15/06/2005

- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01

- Measurement SW: DAS4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159


Body SAR - PCS CDMA & Bluetooth - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 600 Area Scan (16x9x1): Measurement grid: dx=15mm, dy=15mm

Body SAR - PCS CDMA & Bluetooth - 0.0 cm Separation Distance from Bottom of DUT to Planar Phantom - Channel 600 Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 9.89 V/m; Power Drift = 0.0118 dB

Peak SAR (extrapolated) = 0.179 W/kg


SAR(1 g) = 0.116 mW/g; SAR(10 g) = 0.071 mW/g




Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 30 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093 IC RSS-102 Issue 2

APPENDIX B - SYSTEM PERFORMANCE CHECK DATA

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 31 of 49

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093

Date Tested: 10/04/2005

System Performance Check (Body) - 835 MHz Dipole

DUT: Dipole 835 MHz; Model: D835V2; Type; System Performance Check; Serial: 411; Calibrated: 04/12/2005

Ambient Temp: 24.1 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 101.5 kPa; Humidity: 31%

Communication System: CW
 Forward Conducted Power: 250 mW
 Frequency: 835 MHz; Duty Cycle: 1:1
 Medium: M835 ($\sigma = 0.99$ mho/m; $\epsilon_r = 53.3$; $\rho = 1000$ kg/m³)


- Probe: ET3DV6 - SN1387; ConvF(6.1, 6.1, 6.1); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159


835 MHz Dipole - System Performance Check/Area Scan (6x10x1):

Measurement grid: dx=10mm, dy=10mm


835 MHz Dipole - System Performance Check/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 55.2 V/m; Power Drift = -0.049 dB
 Peak SAR (extrapolated) = 3.80 W/kg
SAR(1 g) = 2.61 mW/g; SAR(10 g) = 1.71 mW/g



Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 32 of 49

Z-Axis Scan



Date Tested: 10/21/2005

System Performance Check (Body) - 1900 MHz Dipole

DUT: Dipole 1900 MHz; Model: D1900V2; Type: System Performance Check; Serial: 151; Calibrated: 06/17/2005

Ambient Temp: 23.0 °C; Fluid Temp: 22.0 °C; Barometric Pressure: 103.0 kPa; Humidity: 31%

Communication System: CW
 Forward Conducted Power: 250 mW
 Frequency: 1900 MHz; Duty Cycle: 1:1
 Medium: M1900 ($\sigma = 1.48$ mho/m; $\epsilon_r = 50.7$; $\rho = 1000$ kg/m³)


- Probe: ET3DV6 - SN1387; ConvF(4.75, 4.75, 4.75); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASYS4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

1900 MHz Dipole - System Performance Check/Area Scan (5x8x1):


Measurement grid: dx=15mm, dy=15mm

1900 MHz Dipole - System Performance Check/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 91.5 V/m; Power Drift = 0.027 dB
 Peak SAR (extrapolated) = 17.6 W/kg
SAR(1 g) = 10.2 mW/g; SAR(10 g) = 5.35 mW/g



Z-Axis Scan



Date Tested: 10/24/2005

System Performance Check (Body) - 835 MHz Dipole

DUT: Dipole 835 MHz; Model: D835V2; Type: System Performance Check; Serial: 411; Calibrated: 04/12/2005

Ambient Temp: 23.4 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 102.3 kPa; Humidity: 32%

Communication System: CW

Forward Conducted Power: 250 mW

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: M835 ($\sigma = 0.98 \text{ mho/m}$; $\epsilon_r = 52.6$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(6.1, 6.1, 6.1); Calibrated: 18/03/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

835 MHz Dipole - System Performance Check/Area Scan (6x10x1):

Measurement grid: dx=10mm, dy=10mm


835 MHz Dipole - System Performance Check/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 55.5 V/m; Power Drift = -0.060 dB


Peak SAR (extrapolated) = 3.82 W/kg

SAR(1 g) = 2.63 mW/g; SAR(10 g) = 1.72 mW/g





Z-Axis Scan



	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093 IC RSS-102 Issue 2

APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 38 of 49


	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093

835 MHz System Performance Check & DUT Evaluation (Body)

Celltech Labs Inc.
 Test Result for UIM Dielectric Parameter
 Tue 04/Oct/2005
 Frequency(GHz)

FCC_eHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Epsilon
 FCC_sHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma
 FCC_eB FCC Limits for Body Epsilon
 FCC_sB FCC Limits for Body Sigma
 Test_e Epsilon of UIM
 Test_s Sigma of UIM

Freq	FCC_eB	FCC_sB	Test_e	Test_s
0.7350	55.59	0.96	54.12	0.8750
0.7450	55.55	0.96	53.82	0.8928
0.7550	55.51	0.96	53.94	0.8994
0.7650	55.47	0.96	53.89	0.9165
0.7750	55.43	0.97	53.75	0.9179
0.7850	55.39	0.97	53.80	0.9318
0.7950	55.36	0.97	53.88	0.9398
0.8050	55.32	0.97	53.64	0.9533
0.8150	55.28	0.97	53.44	0.9641
0.8250	55.24	0.97	53.34	0.9793
0.8350	55.20	0.97	53.30	0.9880
0.8450	55.17	0.98	53.11	1.005
0.8550	55.14	0.99	53.12	1.008
0.8650	55.11	1.01	52.93	1.021
0.8750	55.08	1.02	52.72	1.033
0.8850	55.05	1.03	52.62	1.043
0.8950	55.02	1.04	52.69	1.054
0.9050	55.00	1.05	52.60	1.067
0.9150	55.00	1.06	52.43	1.075
0.9250	54.98	1.06	52.34	1.092

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 39 of 49



Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093
			IC RSS-102 Issue 2

1900 MHz System Performance Check & 1880 MHz DUT Evaluation (Body)

Celltech Labs Inc.
 Test Result for UIM Dielectric Parameter
 Fri 21/Oct/2005
 Frequency(GHz)

FCC_eHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Epsilon
 FCC_sHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma
 FCC_eB FCC Limits for Body Epsilon
 FCC_sB FCC Limits for Body Sigma
 Test_e Epsilon of UIM
 Test_s Sigma of UIM

Freq	FCC_eB	FCC_sB	Test_e	Test_s
1.8000	53.30	1.52	51.08	1.376
1.8100	53.30	1.52	51.08	1.390
1.8200	53.30	1.52	50.95	1.412
1.8300	53.30	1.52	50.93	1.415
1.8400	53.30	1.52	50.92	1.434
1.8500	53.30	1.52	50.94	1.441
1.8600	53.30	1.52	50.72	1.448
1.8700	53.30	1.52	50.74	1.461
1.8800	53.30	1.52	50.79	1.463
1.8900	53.30	1.52	50.67	1.483
1.9000	53.30	1.52	50.70	1.480
1.9100	53.30	1.52	50.65	1.509
1.9200	53.30	1.52	50.69	1.512
1.9300	53.30	1.52	50.61	1.522
1.9400	53.30	1.52	50.61	1.531
1.9500	53.30	1.52	50.63	1.545
1.9600	53.30	1.52	50.63	1.550
1.9700	53.30	1.52	50.51	1.555
1.9800	53.30	1.52	50.43	1.572
1.9900	53.30	1.52	50.36	1.583



Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093
			IC RSS-102 Issue 2

835 MHz System Performance Check & DUT Evaluation (Body)

Celltech Labs Inc.
 Test Result for UIM Dielectric Parameter
 Mon 24/Oct/2005
 Frequency(GHz)


FCC_eHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Epsilon
 FCC_sHFCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma
 FCC_eB FCC Limits for Body Epsilon
 FCC_sB FCC Limits for Body Sigma
 Test_e Epsilon of UIM
 Test_s Sigma of UIM

Freq	FCC_eB	FCC_sB	Test_e	Test_s
0.7350	55.59	0.96	53.75	0.8750
0.7450	55.55	0.96	53.60	0.8815
0.7550	55.51	0.96	53.32	0.8933
0.7650	55.47	0.96	53.20	0.8996
0.7750	55.43	0.97	53.20	0.9097
0.7850	55.39	0.97	53.15	0.9171
0.7950	55.36	0.97	52.91	0.9291
0.8050	55.32	0.97	52.78	0.9395
0.8150	55.28	0.97	52.89	0.9502
0.8250	55.24	0.97	52.65	0.9634
0.8350	55.20	0.97	52.58	0.9763
0.8450	55.17	0.98	52.51	0.9864
0.8550	55.14	0.99	52.43	0.9898
0.8650	55.11	1.01	52.41	1.009
0.8750	55.08	1.02	52.26	1.009
0.8850	55.05	1.03	52.01	1.024
0.8950	55.02	1.04	52.04	1.026
0.9050	55.00	1.05	51.69	1.037
0.9150	55.00	1.06	51.72	1.049
0.9250	54.98	1.06	51.63	1.056
0.9350	54.96	1.07	51.58	1.066

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.				Page 41 of 49


	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093 IC RSS-102 Issue 2

APPENDIX D - SAR TEST SETUP PHOTOGRAPHS




Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 42 of 49


BODY SAR TEST SETUP PHOTOGRAPHS
0.0 cm Separation Distance from Bottom of DUT to Planar Phantom
Antenna "Parallel Straight" Position




	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure SAR	FCC 47 CFR §2.1093	IC RSS-102 Issue 2

BODY SAR TEST SETUP PHOTOGRAPHS
0.0 cm Separation Distance from Bottom of DUT to Planar Phantom
Antenna "Parallel Straight" Position
2nd Area Scan





Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 44 of 49

BODY SAR TEST SETUP PHOTOGRAPHS
0.0 cm Separation Distance from Bottom of DUT to Planar Phantom
Antenna "Parallel Bent" Position




BODY SAR TEST SETUP PHOTOGRAPHS
0.0 cm Separation Distance from Bottom of DUT to Planar Phantom
Antenna "Perpendicular" Position



	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093 IC RSS-102 Issue 2

APPENDIX E - SYSTEM VALIDATION

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 47 of 49

835 MHz SYSTEM VALIDATION DIPOLE

Type:

835 MHz Validation Dipole

Serial Number:

411

Place of Calibration:

Celltech Labs Inc.

Date of Calibration:

April 12, 2005

Celltech Labs Inc. hereby certifies that this device has been calibrated on the date indicated above.

Calibrated by:




Approved by:





1. Validation Dipole Construction & Electrical Characteristics

The validation dipole was constructed in accordance with the IEEE Standard “Annex G (informative) Reference dipoles for use in system validation”. The electrical properties were measured using an HP 8753ET Network Analyzer. The network analyzer was calibrated to the validation dipole N-type connector feed point using an HP85032E Type N calibration kit. The dipole was placed parallel to a planar phantom at a separation distance of 15.0mm from the simulating fluid using a loss-less dielectric spacer. The measured input impedance is:

Feed point impedance at 835MHz	$Re\{Z\} = 47.627\Omega$ $Im\{Z\} = -0.67188\Omega$
Return Loss at 835MHz	-31.954dB



2. Validation Dipole VSWR Data



3. Validation Dipole Dimensions

Frequency (MHz)	L (mm)	h (mm)	d (mm)
300	420.0	250.0	6.2
450	288.0	167.0	6.2
835	161.0	89.8	3.6
900	149.0	83.3	3.6
1450	89.1	51.7	3.6
1800	72.0	41.7	3.6
1900	68.0	39.5	3.6
2000	64.5	37.5	3.6
2450	51.8	30.6	3.6
3000	41.5	25.0	3.6

4. Validation Phantom

The validation phantom is the SAM (Specific Anthropomorphic Mannequin) phantom manufactured by Schmid & Partner Engineering AG. The SAM phantom is a Fiberglass shell integrated in a wooden table. The shape of the shell corresponds to the phantom defined by SCC34-SC2. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness: 2.0 ± 0.1 mm
Filling Volume: Approx. 25 liters
Dimensions: 50 cm (W) x 100 cm (L)

5. 835 MHz System Validation Setup



6. 835 MHz Validation Dipole Setup



7. Measurement Conditions

The SAM phantom was filled with 835 MHz simulated body tissue mixture having the following parameters:

Relative Permittivity: 53.0
 Conductivity: 0.98 mho/m
 Fluid Temperature: 21.2 °C
 Fluid Depth: ≥ 15.0 cm

Environmental Conditions:
 Ambient Temperature: 22.6 °C
 Barometric Pressure: 103.4 kPa
 Humidity: 36 %


Measurements were made at the planar section of the SAM phantom using a dosimetric E-field probe ET3DV5 (S/N: 1590, conversion factor 6.71).

The 835 MHz simulated body tissue mixture consisted of the following ingredients:

Ingredient	Percentage by weight
Water	53.79%
Sugar	45.13%
Salt	0.98%
Dowicil 75	0.10%
Target Dielectric Parameters at 22 °C	$\epsilon_r = 55.2$ $\sigma = 0.97 \text{ S/m}$

8. SAR Measurement

The SAR measurement was performed with the E-field probe in mechanical detection mode only. The setup and determination of the forward power into the dipole was performed using the following procedures.



First the power meter PM1 (including attenuator Att1) is connected to the cable to measure the forward power at the location of the dipole connector (X). The signal generator is adjusted for the desired forward power at the dipole connector (taking into account the attenuation of Att1) as read by power meter PM2. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2. If the signal generator does not allow adjustment in 0.01dB steps, the remaining difference at PM2 must be taken into consideration. PM3 records the reflected power from the dipole to ensure that the value is not changed from the previous value. The reflected power should be 20dB below the forward power.

9. Validation Dipole SAR Test Results

Ten SAR measurements were performed in order to achieve repeatability and to establish an average target value.

Validation Measurement	SAR @ 0.25W Input averaged over 1g	SAR @ 1W Input averaged over 1g	SAR @ 0.25W Input averaged over 10g	SAR @ 1W Input averaged over 10g	Peak SAR @ 0.25W Input
Test 1	2.61	10.44	1.72	6.88	3.79
Test 2	2.61	10.44	1.72	6.88	3.83
Test 3	2.60	10.40	1.71	6.84	3.79
Test 4	2.60	10.40	1.71	6.84	3.80
Test 5	2.59	10.36	1.71	6.84	3.77
Test 6	2.60	10.40	1.71	6.84	3.77
Test 7	2.60	10.40	1.71	6.84	3.78
Test 8	2.60	10.40	1.71	6.84	3.81
Test 9	2.59	10.36	1.71	6.84	3.76
Test10	2.61	10.44	1.72	6.88	3.80
Average SAR	2.60	10.40	1.71	6.85	3.79

Target SAR @ 1 Watt Input averaged over 1 gram (W/kg)		Measured SAR @ 1 Watt Input averaged over 1 gram (W/kg)	Deviation from Target (%)	Target SAR @ 1 Watt Input averaged over 10 grams (W/kg)		Measured SAR @ 1 Watt Input averaged over 10 grams (W/kg)	Deviation from Target (%)
9.71	+/- 10%	10.4	+ 7.2	6.38	+/- 10%	6.85	+ 7.4

Dipole Type	Distance [mm]	Frequency [MHz]	SAR (1g) [W/kg]	SAR (10g) [W/kg]	SAR (peak) [W/kg]
D300V2	15	300	3.02	2.06	4.36
D450V2	15	450	5.01	3.36	7.22
D835V2	15	835	9.71	6.38	14.1
D900V2	15	900	11.1	7.17	16.3
D1450V2	10	1450	29.6	16.6	49.8
D1500V2	10	1500	30.8	17.1	52.1
D1640V2	10	1640	34.4	18.7	59.4
D1800V2	10	1800	38.5	20.3	67.5
D1900V2	10	1900	39.8	20.8	69.6
D2000V2	10	2000	40.9	21.2	71.5
D2450V2	10	2450	51.2	23.7	97.6
D3000V2	10	3000	61.9	24.8	136.7

Table 32.1: Numerical reference SAR values for SPEAG dipoles and flat phantom filled with body-tissue simulating liquid. Note: All SAR values normalized to 1 W forward power.

835 MHz System Validation (Body) - April 12, 2005

DUT: Dipole 835 MHz; Type: D835V2; Serial: 411
Ambient Temp: 22.6°C; Fluid Temp: 21.2°C; Barometric Pressure: 103.4 kPa; Humidity: 36%
Communication System: CW
Forward Conducted Power: 250 mW
Frequency: 835 MHz; Duty Cycle: 1:1
Medium: MSL835 Medium parameters used: $f = 835$ MHz; $\sigma = 0.98$ mho/m; $\epsilon_r = 53$; $\rho = 1000$ kg/m³
- Probe: ET3DV6 - SN1590; ConvF(6.54, 6.54, 6.54); Calibrated: 24/05/2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 06/07/2004
- Phantom: SAM 4.0; Type: Fiberglass; Serial: 1033
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

835 MHz System Performance Check/Area Scan (6x10x1): Measurement grid: dx=10mm, dy=10mm

835 MHz System Performance Check/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.2 V/m; Power Drift = 0.020 dB
Peak SAR (extrapolated) = 3.79 W/kg
SAR(1 g) = 2.61 mW/g; SAR(10 g) = 1.72 mW/g

835 MHz System Performance Check/Zoom Scan 2 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.7 V/m; Power Drift = -0.054 dB
Peak SAR (extrapolated) = 3.83 W/kg
SAR(1 g) = 2.61 mW/g; SAR(10 g) = 1.72 mW/g

835 MHz System Performance Check/Zoom Scan 3 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.4 V/m; Power Drift = -0.025 dB
Peak SAR (extrapolated) = 3.79 W/kg
SAR(1 g) = 2.60 mW/g; SAR(10 g) = 1.71 mW/g

835 MHz System Performance Check/Zoom Scan 4 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.3 V/m; Power Drift = -0.010 dB
Peak SAR (extrapolated) = 3.80 W/kg
SAR(1 g) = 2.60 mW/g; SAR(10 g) = 1.71 mW/g

835 MHz System Performance Check/Zoom Scan 5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.2 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 3.77 W/kg
SAR(1 g) = 2.59 mW/g; SAR(10 g) = 1.71 mW/g


835 MHz System Performance Check/Zoom Scan 6 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.2 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 3.77 W/kg
SAR(1 g) = 2.60 mW/g; SAR(10 g) = 1.71 mW/g

835 MHz System Performance Check/Zoom Scan 7 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.4 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 3.78 W/kg
SAR(1 g) = 2.60 mW/g; SAR(10 g) = 1.71 mW/g


835 MHz System Performance Check/Zoom Scan 8 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.1 V/m; Power Drift = 0.013 dB
Peak SAR (extrapolated) = 3.81 W/kg
SAR(1 g) = 2.60 mW/g; SAR(10 g) = 1.71 mW/g

835 MHz System Performance Check/Zoom Scan 9 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.5 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 3.76 W/kg
SAR(1 g) = 2.59 mW/g; SAR(10 g) = 1.71 mW/g

835 MHz System Performance Check/Zoom Scan 10 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 55.2 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 3.80 W/kg
SAR(1 g) = 2.61 mW/g; SAR(10 g) = 1.72 mW/g



1 g average of 10 measurements: 2.60 mW/g
 10 g average of 10 measurements: 1.71 mW/g



10. Measured Fluid Dielectric Parameters

835 MHz System Validation (Body)

Measured Fluid Dielectric Parameters (Muscle)

April 12, 2005

Frequency	e'	e''
735.000000 MHz	54.0378	21.6286
745.000000 MHz	53.8896	21.5691
755.000000 MHz	53.8006	21.4920
765.000000 MHz	53.6592	21.4574
775.000000 MHz	53.5651	21.4082
785.000000 MHz	53.4598	21.3813
795.000000 MHz	53.3996	21.3224
805.000000 MHz	53.2805	21.2791
815.000000 MHz	53.2061	21.2382
825.000000 MHz	53.1022	21.1974
835.000000 MHz	52.9838	21.1959
845.000000 MHz	52.8546	21.1661
855.000000 MHz	52.7335	21.1454
865.000000 MHz	52.5991	21.1198
875.000000 MHz	52.4868	21.0980
885.000000 MHz	52.4035	21.0714
895.000000 MHz	52.3499	21.0447
905.000000 MHz	52.2262	21.0295
915.000000 MHz	52.1465	20.9572
925.000000 MHz	52.0498	20.9643
935.000000 MHz	51.9344	20.8879

1900 MHz SYSTEM VALIDATION DIPOLE

Type:

1900 MHz Validation Dipole

Serial Number:

151

Place of Calibration:

Celltech Labs Inc.

Date of Calibration:

April 22, 2005

Celltech Labs Inc. hereby certifies that this device has been calibrated on the date indicated above.

Calibrated by:



Approved by:




1. Dipole Construction & Electrical Characteristics

The validation dipole was constructed in accordance with the IEEE Standard “Annex G (informative) Reference dipoles for use in system validation”. The electrical properties were measured using an HP 8753E Network Analyzer. The network analyzer was calibrated to the validation dipole N-type connector feed point using an HP85032E Type N calibration kit. The dipole was placed parallel to a planar phantom at a separation distance of 10.0mm from the simulating fluid using a loss-less dielectric spacer. The measured input impedance is:



Feed point impedance at 1900MHz $\text{Re}\{Z\} = 48.715\Omega$

$\text{Im}\{Z\} = 9.412\Omega$

Return Loss at 1900MHz -20.371dB



2. Validation Dipole VSWR Data



3. Validation Dipole Dimensions

Frequency (MHz)	L (mm)	h (mm)	d (mm)
300	420.0	250.0	6.2
450	288.0	167.0	6.2
835	161.0	89.8	3.6
900	149.0	83.3	3.6
1450	89.1	51.7	3.6
1800	72.0	41.7	3.6
1900	68.0	39.5	3.6
2000	64.5	37.5	3.6
2450	51.8	30.6	3.6
3000	41.5	25.0	3.6

4. Validation Phantom

The validation phantom is a Fiberglass shell planar phantom manufactured by Barski Industries Ltd. The phantom is in conformance with the requirements defined by IEEE SCC34-SC2 for the dosimetric evaluations of body-worn and lap-held operating configurations. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids.

Shell Thickness: 2.0 ± 0.1 mm
Filling Volume: Approx. 55 liters
Dimensions: 44 cm (W) x 94 cm (L)

5. 1900 MHz System Validation Setup



6. 1900 MHz System Validation Setup



7. Measurement Conditions

The phantom was filled with 1900 MHz Body simulating tissue.

Relative Permittivity:	50.7
Conductivity:	1.59 mho/m
Fluid Temperature:	23.8 °C
Fluid Depth:	≥ 15.0 cm

Environmental Conditions:


Ambient Temperature:	25.6 °C
Barometric Pressure:	102.1 kPa
Humidity:	30%

The 1900 MHz simulated Body tissue mixture consists of the following ingredients:

Ingredient	Percentage by weight
Water	69.85%
Glycol	29.89%
Salt	0.26%
Target Dielectric Parameters at 22 °C	$\epsilon_r = 53.3$ $\sigma = 1.52 \text{ S/m}$

8. SAR Measurement

The SAR measurement was performed with the E-field probe in mechanical detection mode only. The setup and determination of the forward power into the dipole was performed using the following procedures.



First the power meter PM1 (including attenuator Att1) is connected to the cable to measure the forward power at the location of the dipole connector (X). The signal generator is adjusted for the desired forward power at the dipole connector (taking into account the attenuation of Att1) as read by power meter PM2. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2. If the signal generator does not allow adjustment in 0.01dB steps, the remaining difference at PM2 must be taken into consideration. PM3 records the reflected power from the dipole to ensure that the value is not changed from the previous value. The reflected power should be 50dB below the forward power.

9. Validation Dipole SAR Test Results

Ten SAR measurements were performed in order to achieve repeatability and to establish an average target value.

Validation Measurement	SAR @ 0.25W Input averaged over 1g	SAR @ 1W Input averaged over 1g	SAR @ 0.25W Input averaged over 10g	SAR @ 1W Input averaged over 10g	Peak SAR @ 0.25W Input
Test 1	10.7	42.80	5.71	22.84	17.7
Test 2	10.7	42.80	5.72	22.88	17.6
Test 3	10.7	42.80	5.73	22.92	17.6
Test 4	10.7	42.80	5.73	22.92	17.6
Test 5	10.7	42.80	5.72	22.88	17.6
Test 6	10.7	42.80	5.70	22.80	17.5
Test 7	10.7	42.80	5.70	22.80	17.5
Test 8	10.6	42.40	5.69	22.76	17.4
Test 9	10.6	42.40	5.69	22.76	17.4
Test 10	10.6	42.40	5.69	22.76	17.5
Average	10.67	42.68	5.71	22.83	17.54

The results have been normalized to 1W (forward power) into the dipole.

Target SAR @ 1 Watt Input averaged over 1 gram (W/kg)		Measured SAR @ 1 Watt Input averaged over 1 gram (W/kg)	Deviation from Target (%)	Target SAR @ 1 Watt Input averaged over 10 grams (W/kg)		Measured SAR @ 1 Watt Input averaged over 10 grams (W/kg)	Deviation from Target (%)
39.8	+/- 10%	42.68	+7.24	20.8	+/- 10%	22.83	+9.76

Dipole Type	Distance [mm]	Frequency [MHz]	SAR (1g) [W/kg]	SAR (10g) [W/kg]	SAR (peak) [W/kg]
D300V2	15	300	3.02	2.06	4.36
D450V2	15	450	5.01	3.36	7.22
D835V2	15	835	9.71	6.38	14.1
D900V2	15	900	11.1	7.17	16.3
D1450V2	10	1450	29.6	16.6	49.8
D1500V2	10	1500	30.8	17.1	52.1
D1640V2	10	1640	34.4	18.7	59.4
D1800V2	10	1800	38.5	20.3	67.5
D1900V2	10	1900	39.8	20.8	69.6
D2000V2	10	2000	40.9	21.2	71.5
D2450V2	10	2450	51.2	23.7	97.6
D3000V2	10	3000	61.9	24.8	136.7

Table 32.1: Numerical reference SAR values for SPEAG dipoles and flat phantom filled with body-tissue simulating liquid. Note: All SAR values normalized to 1 W forward power.

1900 MHz System Validation (Body) - April 22, 2005

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 151; Calibrated: 04/22/2005
Ambient Temp: 25.6 °C; Fluid Temp: 23.8 °C; Barometric Pressure: 102.1 kPa; Humidity: 30%
Communication System: CW
Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: M1900 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.59$ mho/m; $\epsilon_r = 50.7$; $\rho = 1000$ kg/m³
- Probe: ET3DV6 - SN1590; ConvF(4.58, 4.58, 4.58); Calibrated: 24/05/2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 06/07/2004
- Phantom: Barski Industries; Type: Fiberglass Planar; Serial: 03-01
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

1900 MHz System Validation/Area Scan (5x8x1): Measurement grid: dx=15mm, dy=15mm

1900 MHz System Validation/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 93.9 V/m; Power Drift = -0.079 dB
Peak SAR (extrapolated) = 17.7 W/kg
SAR(1 g) = 10.7 mW/g; SAR(10 g) = 5.71 mW/g

1900 MHz System Validation/Zoom Scan 2 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 93.7 V/m; Power Drift = -0.026 dB
Peak SAR (extrapolated) = 17.6 W/kg
SAR(1 g) = 10.7 mW/g; SAR(10 g) = 5.72 mW/g

1900 MHz System Validation/Zoom Scan 3 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 94.3 V/m; Power Drift = -0.026 dB
Peak SAR (extrapolated) = 17.6 W/kg
SAR(1 g) = 10.7 mW/g; SAR(10 g) = 5.73 mW/g

1900 MHz System Validation/Zoom Scan 4 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 94.2 V/m; Power Drift = -0.025 dB
Peak SAR (extrapolated) = 17.6 W/kg
SAR(1 g) = 10.7 mW/g; SAR(10 g) = 5.73 mW/g

1900 MHz System Validation/Zoom Scan 5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 94.2 V/m; Power Drift = -0.027 dB
Peak SAR (extrapolated) = 17.6 W/kg
SAR(1 g) = 10.7 mW/g; SAR(10 g) = 5.72 mW/g


1900 MHz System Validation/Zoom Scan 6 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 93.8 V/m; Power Drift = -0.056 dB
Peak SAR (extrapolated) = 17.5 W/kg
SAR(1 g) = 10.7 mW/g; SAR(10 g) = 5.70 mW/g

1900 MHz System Validation/Zoom Scan 7 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 93.8 V/m; Power Drift = -0.043 dB
Peak SAR (extrapolated) = 17.5 W/kg
SAR(1 g) = 10.7 mW/g; SAR(10 g) = 5.70 mW/g


1900 MHz System Validation/Zoom Scan 8 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 93.6 V/m; Power Drift = -0.050 dB
Peak SAR (extrapolated) = 17.4 W/kg
SAR(1 g) = 10.6 mW/g; SAR(10 g) = 5.69 mW/g

1900 MHz System Validation/Zoom Scan 9 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 93.7 V/m; Power Drift = -0.033 dB
Peak SAR (extrapolated) = 17.4 W/kg
SAR(1 g) = 10.6 mW/g; SAR(10 g) = 5.69 mW/g

1900 MHz System Validation/Zoom Scan 10 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 93.5 V/m; Power Drift = -0.045 dB
Peak SAR (extrapolated) = 17.5 W/kg
SAR(1 g) = 10.6 mW/g; SAR(10 g) = 5.69 mW/g



1 g average of 10 measurements: 10.67 mW/g
10 g average of 10 measurements: 5.71 mW/g




10. Measured Fluid Dielectric Parameters

System Validation - 1900 MHz Dipole


Measured Fluid Dielectric Parameters (Muscle)

April 22, 2005

Frequency	ϵ'	ϵ''
1.800000000 GHz	51.0964	14.7202
1.810000000 GHz	51.0396	14.7503
1.820000000 GHz	51.0220	14.7911
1.830000000 GHz	50.9811	14.8228
1.840000000 GHz	50.9466	14.8388
1.850000000 GHz	50.9152	14.8773
1.860000000 GHz	50.8658	14.8924
1.870000000 GHz	50.8337	14.9214
1.880000000 GHz	50.7654	14.9640
1.890000000 GHz	50.7233	15.0059
1.900000000 GHz	50.6734	15.0407
1.910000000 GHz	50.6457	15.0744
1.920000000 GHz	50.6058	15.1083
1.930000000 GHz	50.5785	15.1423
1.940000000 GHz	50.5378	15.1671
1.950000000 GHz	50.4983	15.1913
1.960000000 GHz	50.4575	15.2240
1.970000000 GHz	50.4075	15.2443
1.980000000 GHz	50.3458	15.2616
1.990000000 GHz	50.3079	15.3071
2.000000000 GHz	50.2546	15.3145

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093 IC RSS-102 Issue 2

APPENDIX F - PROBE CALIBRATION

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 48 of 49



Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Celltech Labs**

Certificate No: **ET3-1387_Mar05**

CALIBRATION CERTIFICATE

Object **ET3DV6 - SN:1387**

Calibration procedure(s) **QA CAL-01.v5
Calibration procedure for dosimetric E-field probes**

Calibration date: **March 18, 2005**



Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	5-May-04 (METAS, No. 251-00388)	May-05
Power sensor E4412A	MY41495277	5-May-04 (METAS, No. 251-00388)	May-05
Reference 3 dB Attenuator	SN: S5054 (3c)	10-Aug-04 (METAS, No. 251-00403)	Aug-05
Reference 20 dB Attenuator	SN: S5086 (20b)	3-May-04 (METAS, No. 251-00389)	May-05
Reference 30 dB Attenuator	SN: S5129 (30b)	10-Aug-04 (METAS, No. 251-00404)	Aug-05
Reference Probe ES3DV2	SN: 3013	7-Jan-05 (SPEAG, No. ES3-3013_Jan05)	Jan-06
DAE4	SN: 617	19-Jan-05 (SPEAG, No. DAE4-617_Jan05)	Jan-06
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092180	18-Sep-02 (SPEAG, in house check Oct-03)	In house check: Oct 05
RF generator HP 8648C	US3642U01700	4-Aug-99 (SPEAG, in house check Dec-03)	In house check: Dec-05
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Nov-04)	In house check: Nov 05

Calibrated by:	Name Nico Vetterli	Function Laboratory Technician	Signature 
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature 

Issued: March 18, 2005

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- CENELEC EN 50361, "Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz - 3 GHz), July 2001

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E²-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * *frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * *ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ET3DV6

SN:1387

Manufactured:	September 21, 1999
Last calibrated:	March 18, 2004
Recalibrated:	March 18, 2005

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

DASY - Parameters of Probe: ET3DV6 SN:1387

Sensitivity in Free Space^A

NormX	1.61 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$
NormY	1.70 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	1.70 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$

Diode Compression^B

DCP X	92 mV
DCP Y	92 mV
DCP Z	92 mV

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect

TSL 900 MHz Typical SAR gradient: 5 % per mm

Sensor Center to Phantom Surface Distance		3.7 mm	4.7 mm
SAR _{be} [%]	Without Correction Algorithm	9.4	4.9
SAR _{be} [%]	With Correction Algorithm	0.1	0.3

TSL 1810 MHz Typical SAR gradient: 10 % per mm

Sensor Center to Phantom Surface Distance		3.7 mm	4.7 mm
SAR _{be} [%]	Without Correction Algorithm	14.3	9.6
SAR _{be} [%]	With Correction Algorithm	0.6	0.1

Sensor Offset

Probe Tip to Sensor Center **2.7 mm**


The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Page 8).

^B Numerical linearization parameter: uncertainty not required.




Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (Waveguide R22, $f = 1800 \text{ MHz}$)



Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment




f [MHz]	Validity [MHz] ^c	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.65	1.81	6.47 ± 11.0% (k=2)
1810	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.62	2.39	5.18 ± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.76	2.09	4.56 ± 11.8% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.60	2.01	6.10 ± 11.0% (k=2)
1810	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.60	2.67	4.75 ± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.82	1.82	4.30 ± 11.8% (k=2)

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

Deviation from Isotropy in HSL

Error (ϕ , ϑ), $f = 900$ MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ ($k=2$)


Additional Conversion Factors

for Dosimetric E-Field Probe

Type:	ET3DV6
Serial Number:	1387
Place of Assessment:	Zurich
Date of Assessment:	March 21, 2005
Probe Calibration Date:	March 18, 2005

Schmid & Partner Engineering AG hereby certifies that conversion factor(s) of this probe have been evaluated on the date indicated above. The assessment was performed using the FDTD numerical code SEMCAD of Schmid & Partner Engineering AG. Since the evaluation is coupled with measured conversion factors, it has to be recalculated yearly, i.e., following the re-calibration schedule of the probe. The uncertainty of the numerical assessment is based on the extrapolation from measured value at 900 MHz or at 1800 MHz.

Assessed by:




Dosimetric E-Field Probe ET3DV6 SN:1387Conversion factor (\pm standard deviation)

f = 150 MHz	ConvF	8.8 \pm 10%	$\epsilon_r = 52.3 \pm 5\%$ $\sigma = 0.76 \pm 5\%$ mho/m (head tissue)
f = 300 MHz	ConvF	7.9 \pm 9%	$\epsilon_r = 45.3 \pm 5\%$ $\sigma = 0.87 \pm 5\%$ mho/m (head tissue)
f = 450 MHz	ConvF	7.5 \pm 8%	$\epsilon_r = 43.5 \pm 5\%$ $\sigma = 0.87 \pm 5\%$ mho/m (head tissue)
f = 150 MHz	ConvF	8.4 \pm 10%	$\epsilon_r = 61.9 \pm 5\%$ $\sigma = 0.80 \pm 5\%$ mho/m (body tissue)
f = 450 MHz	ConvF	7.5 \pm 8%	$\epsilon_r = 56.7 \pm 5\%$ $\sigma = 0.94 \pm 5\%$ mho/m (body tissue)


Important Note:

For numerically assessed probe conversion factors, parameters Alpha and Delta in the DASY software must have the following entries: Alpha = 0 and Delta = 1.


Please see also Section 4.7 of the DASY4 Manual.

	Test Report Serial No.:	100305KBC-T674-S24C	Report Issue No.:	S674C-021706-R0
	Dates of Evaluation:	October 04, 21 & 24, 2005	Report Issue Date:	February 17, 2006
	Type of Evaluation:	RF Exposure	SAR	FCC 47 CFR §2.1093 IC RSS-102 Issue 2

APPENDIX G - PLANAR PHANTOM CERTIFICATE OF CONFORMITY

Applicant:	Itronix Corporation	FCC ID:	KBCIX325-AC580BT	IC ID:	1943A-IX325f	
Model:	IX325-AC580BT	DUT:	Rugged Tablet PC with PCS/Cellular CDMA Modem & Bluetooth			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.					Page 49 of 49

2378 Westlake Road
Kelowna, B.C. Canada
V1Z-2V2



Ph. # 250-769-6848
Fax # 250-769-6334
E-mail: barskiind@shaw.ca
Web: www.bcfiberglass.com

FIBERGLASS FABRICATORS

Certificate of Conformity

Item : Flat Planar Phantom Unit # 03-01
Date: June 16, 2003
Manufacturer: Barski Industries (1985 Ltd)

Test	Requirement	Details
Shape	Compliance to geometry according to drawing	Supplied CAD drawing
Material Thickness	Compliant with the requirements	2mm +/- 0.2mm in measurement area
Material Parameters	Dielectric parameters for required frequencies Based on Dow Chemical technical data	100 MHz-5 GHz Relative permittivity < 5 Loss Tangent < 0.05

Conformity

Based on the above information, we certify this product to be compliant to the requirements specified.

Signature: _____

A handwritten signature in black ink, appearing to read 'Daniel Chailier', is written over a horizontal line.

Daniel Chailier



Fiberglass Planar Phantom - Top View



Fiberglass Planar Phantom - Front View




Fiberglass Planar Phantom - Back View



Fiberglass Planar Phantom - Bottom View

Dimensions of Fiberglass Planar Phantom

(Manufactured by Barski Industries Ltd. - Unit# 03-01)



Note: Measurements that aren't repeated for the opposite sides are the same as the side measured. This drawing is not to scale.