



JAPAN QUALITY ASSURANCE ORGANIZATION
21-25, KINUTA 1-CHOME, SETAGAYA-KU, TOKYO 157-8573 JAPAN
PHONE (03) 3416-0111, TELEX 242-2531 JQA J FAX (03) 3416-9691

JQA APPLICATION NO.: 80-90448
Issue Date : October 13, 1999
Page 1 of 23

EMI TEST REPORT

JQA APPLICATION NO. : 80-90448
Model No. : KBRASTU10
Type of Equipment : Keyless Entry System
(Transmitter)
Regulations Applied : CFR 47 FCC Rules and Regulations Part 15
FCC ID : KBRASTU10
Applicant : KANSEI Corporation
Address : 2-1910 Nisshin-cho, Omiya,
Saitama 331-0044, Japan
Manufacture : KANSEI Corporation
Address : 2-1910 Nisshin-cho, Omiya,
Saitama 331-0044, Japan
Final Judgment : **Passed**

TEST RESULTS IN THIS REPORT are obtained in use of equipment that is traceable to
Electrotechnical Lab. of MITI Japan and Communications Research Lab. of MPT Japan.

The **test results** only respond to the tested sample. It is not allowed to copy this
report even partly without the allowance of the JQA EMC Engineering Dept. Testing Div.



TABLE OF CONTENTS

	Page
1 Documentation	
1.1 Test Regulation	<u>3</u>
1.2 General Information	<u>3</u>
1.3 Test Condition	<u>4 - 7</u>
1.4 EUT Modifications	<u>8</u>
1.5 Test results	<u>9</u>
1.6 Summary	<u>10</u>
1.7 Test Configuration / Operation of EUT	<u>11</u>
1.8 Preliminary Test and Test-setup (Drawings)	<u>12 - 16</u>
1.9 EUT Arrangement (Photographs)	<u>17</u>
2 Test Data	
2.1 AC Power Line Conducted Emission 0.45 MHz - 30 MHz	<u>N/A</u>
2.2 Radiated Emission (Electric Field)	<u>18 - 21</u>
2.3 Frequency Stability	<u>N/A</u>
2.4 Occupied Bandwidth	<u>22 - 23</u>



1 DOCUMENTATION

1.1 TEST REGULATION

FCC Rules and Regulations Part 15 Subpart A and C (June 23, 1989) Intentional Radiators

Test procedure :

AC power line conducted emission, radiated emission, frequency stability and occupied bandwidth tests were performed according to the procedures in ANSI C63.4-1992.

1.2 GENERAL INFORMATION

1.2.1 Test facility :

- 1) Test Facility located at EMC Engineering Dept. Testing Div. : No.2 and 3 Anechoic Chambers(3 meters Site)
FCC filing No. : 31040/SIT 1300F2
- 2) EMC Engineering Dept. Testing Div. is recognized under the National Voluntary Laboratory accreditation Program for satisfactory compliance established in title 15, Part 285 Code of Federal Regulations.
NVLAP Lab Code : 200189-0 (Effective through : June 30, 2000)

1.2.2 Description of the Equipment Under Test (EUT) :

1) Type of Equipment	: Keyless Entry System(Transmitter)
2) Product Type	: Pre-Production
3) Category	: Security/Remote Control Transmitter
4) EUT Authorization	: Certification
5) FCC ID	: KBRASTU10
6) Trade Name	: NISSAN
7) Model No.	: KBRASTU10
8) Operating Frequency Range	: 315 MHz
9) Highest Frequency Used in the EUT	: 315 MHz
10) Serial No.	: None
11) Date of Manufacture	: -
12) Power Rating	: DC 3.0(Battery)
13) EUT Grounding	: None

1.2.3 Definitions for symbols used in this test report :

x - indicates that the listed condition, standard or equipment is applicable for this report.
— - indicates that the listed condition, standard or equipment is not applicable for this report.

1.3 TEST CONDITION**1.3.1 The measurement of the AC Power Line Conducted Emission**

 - was performed in the following test site.
 - was not applicable.

Test location :

Safety Testing Center EMC Engineering Dept. Testing Div.
21-25, Kinuta 1-chome, Setagaya-ku, Tokyo 157-8573, Japan

 - Shielded Enclosure
 - Anechoic Chamber No. 2 (portable Type)

Used test instruments :

Type	Model No.	Manufacturer	Serial No.	Last Cal.	Interval
<u> </u> - Field Strength Meter	ESH-2	Rohde & Schwarz	880370/016	May 1999	1 Year
<u> </u> - Field Strength Meter	ESH-3	Rohde & Schwarz	881460/016	May 1999	1 Year
<u> </u> - Field Strength Meter	ESH-3	Rohde & Schwarz	881460/030	Nov 1999	1 Year
<u> </u> - LISN	KNW-407	Kyoritsu Electrical	8-833-6	Apr. 1999	1 Year
<u> </u> - LISN	KNW-407	Kyoritsu Electrical	8-855-2	Apr. 1999	1 Year
<u> </u> - LISN	KNW-407	Kyoritsu Electrical	8-757-1	Apr. 1999	1 Year
<u> </u> - RF Cable	3D-2W	Fujikura	155-21-005	Apr. 1999	1 Year
<u> </u> - RF Cable	3D-2W	Fujikura	155-21-006	Apr. 1999	1 Year

1.3.2 The measurement of the Radiated Emission(30 MHz - 1000 MHz)

x - was performed in the following test site.
 - was not applicable.

Test location :

Safety Testing Center EMC Engineering Dept. Testing Div.
21-25, Kinuta 1-chome, Setagaya-ku, Tokyo 157-8573, Japan

x - Anechoic Chamber No. 2 (3 meters)
 - Anechoic Chamber No. 3 (3 meters)

Validation of Site Attenuation :

1) Last Confirmed Date :March, 1999
2) Interval :1 year

Used test instruments :

Type	Model No.	Manufacturer	Serial No.	Last Cal.	Interval
<u> </u> - Field Strength Meter	ESV	Rohde & Schwarz	872148/039	May 1999	1 Year
<u> </u> - Field Strength Meter	ESVP	Rohde & Schwarz	879783/030	May 1999	1 Year
<u>x</u> - Field Strength Meter	ESVP	Rohde & Schwarz	881478/004	May 1999	1 Year
<u> </u> - Field Strength Meter	ESVP	Rohde & Schwarz	881478/005	May 1999	1 Year
<u> </u> - Antenna	KBA-511A	Kyoritsu Electrical	0-201-13	Nov. 1998	1 Year
<u>x</u> - Antenna	KBA-511A	Kyoritsu Electrical	0-170-1	Nov. 1998	1 Year
<u> </u> - Antenna	KBA-611	Kyoritsu Electrical	0-210-5	Nov. 1998	1 Year
<u>x</u> - Antenna	KBA-611	Kyoritsu Electrical	0-147-14	Nov. 1998	1 Year
<u>x</u> - RF Cable	5D-2W	Fujikura	155-21-001	Feb. 1999	1 Year
<u> </u> - RF Cable	5D-2W	Fujikura	155-21-002	Feb. 1999	1 Year



JQA Application No. :80-90448
Model No. :KBRASTU10
Standard :CFR 47 FCC Rules Part 15

FCC ID :KBRASTU10
Issue Date :October 13, 1999
Page 6 of 23

1.3.3 The measurement of the Radiated Emission(Above 1000 MHz)

x - was performed in the following test site.
 - was not applicable.

Test location :

Safety Testing Center EMC Engineering Dept. Testing Div.
21-25, Kinuta 1-chome, Setagaya-ku, Tokyo 157-8573, Japan

x - No. 2 site (3 meters)
 - No. 3 site (3 meters)

Validation of Site Attenuation :

- 1) Last Confirmed Date :March, 1999
- 2) Interval :1 year

Used test instruments :

Type	Model No.	Manufacturer	Serial No.	Last Cal.	Interval
<u> </u> - Spectrum Analyzer	8566B	Hewlett Packard	2140A01091	Apr. 1999	1 Year
<u>x</u> - Spectrum Analyzer	8566B	Hewlett Packard	2747A05855	May 1999	1 Year
<u>x</u> - Log-Periodic Antenna	HL 025	Rohde & Schwarz	340182/015	Nov. 1998	1 Year
<u>x</u> - RF Cable	S 04272B	Suhner	155-21-011	May 1999	1 Year

1.3.4 The measurement of the Frequency Stability

 - was performed.
x - was not applicable.

Used test instruments :

Type	Model No.	Manufacturer	Serial No.	Last Cal.	Interval
— - Frequency Counter	53131A	Hewlett Packard	3546A11807	June 1998	1 Year
— - Oven	-	Ohnishi Co. Ltd.	-	July 1998	1 Year
— - DC Power Supply	6628A	Hewlett Packard	3224A00284	July 1998	1 Year

1.3.5 The measurement of the Occupied Bandwidth

x - was performed.
 - was not applicable.

Used test instruments :

Type	Model No.	Manufacturer	Serial No.	Last Cal.	Interval
<u>x</u> - Spectrum Analyzer	8566B	Hewlett Packard	2140A01091	Apr. 1999	1 Year
— - Spectrum Analyzer	8566B	Hewlett Packard	2747A05855	May 1999	1 Year
— - Function Generator	3325A	Hewlett Packard	2512A21776	June 1999	1 Year
— - FM Linear Detector	MS61A	Anritsu Corp.	M77486	Sep. 1999	1 Year
— - Level Meter	ML422C	Anritsu Corp.	M87571	June 1999	1 Year



JQA Application No. :80-90448

Model No.

:KBRASTU10

Standard

:CFR 47 FCC Rules Part 15

FCC ID :KBRASTU10

Issue Date :October 13, 1999

Page 8 of 23

1.4 EUT MODIFICATION

-No modifications were conducted by JQA to achieve compliance to Class B levels.
 -To achieve compliance to Class B levels, the following changes were made by JQA during the compliance test.

The modifications will be implemented in all production models of this equipment.

Applicant :

Date :

Typed Name :

Position :



JQA Application No. :80-90448
Model No. :KBRASTU10
Standard :CFR 47 FCC Rules Part 15

FCC ID :KBRASTU10
Issue Date :October 13, 1999
Page 9 of 23

1.5 TEST RESULTS

AC Power Line Conducted Emission - Applicable - NOT Applicable

The requirements are - PASSED - NOT PASSED

Remarks :

Radiated Emission [§15.231(b)] - Applicable - NOT Applicable

The requirements are - PASSED - NOT PASSED

Remarks:

Frequency Stability - Applicable - NOT Applicable

The requirements are - PASSED - NOT PASSED

Remarks:

Occupied Bandwidth [§15.231(c)] - Applicable - NOT Applicable

The requirements are - PASSED - NOT PASSED

Remarks:

1.6 SUMMARY

General Remarks :

The EUT was tested according to the requirements of FCC Rules and Regulations Part 15 Subpart A and C (June 23, 1989) under the test configuration, as shown in clause 1.7 to 1.9.

The conclusion for the test items of which are required by the applied regulation is indicated under the final judgment.

Final Judgment :

The "as received" sample;

- x - fulfill the test requirements of the regulation mentioned on clause 1.1.
- fulfill the test requirements of the regulation mentioned on clause 1.1, but with certain qualifications.
- doesn't fulfill the test regulation mentioned on clause 1.1.

Begin of testing : October 7, 1999

End of testing : October 7, 1999

- JAPAN QUALITY ASSURANCE ORGANIZATION -

Signatories:



Masaaki Takahashi
Manager
JQA EMC Engineering Dept.



Shigeru Osawa
Assistant Manager
JQA EMC Engineering Dept.



JQA Application No. :80-90448
Model No. :KBRASTU10
Standard :CFR 47 FCC Rules Part 15

FCC ID :KBRASTU10
Issue Date :October 13, 1999
Page 11 of 23

1.7 TEST CONFIGURATION / OPERATION OF EUT

1.7.1 Test Configuration

The equipment under test (EUT) consists of :

Item	Manufacturer	Model No.	FCC ID	Serial No.
Keyless Entry System (Transmitter)	KANSEI Corporation	KBRASTU10	KBRASTU10	-

1.7.2 Operating condition

Power supply Voltage : 3.0 VDC(Battery)

The tests have been carried out under the transmitting condition.

1.8 PRELIMINARY TEST AND TEST-SETUP (DRAWINGS)

1.8.1 AC Power Line Conducted Emission (450 kHz - 30 MHz) :

According to description of ANSI C63.4-1992 sec.13.1.3.1, the AC power line preliminary conducted emissions measurements were carried out.


The preliminary conducted measurements were performed using the spectrum analyzer to observe the emission characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions. These configurations were used for final AC power line conducted emissions measurements.

Shielded Enclosure

- Side View -

Vertical
Ground
Plane




1.8.2 Radiated Emission (30 MHz - 1000 MHz) :

According to description of ANSI C63.4-1992 sec.13.1.4.1, the preliminary radiated emissions measurement were carried out. The preliminary radiated measurements were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions. These configurations were used for the final radiated emissions measurements.

Anechoic Chamber

- Side View -




1.8.3 Radiated Emission (Above 1 GHz) :

According to description of ANSI C63.4-1992 sec.13.1.4.1, the preliminary radiated emissions measurements were carried out. The preliminary radiated measurements were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions. These configurations were used for the final radiated emissions measurements.

Anechoic Chamber


- Side View -



1.8.4 Frequency Stability :

According to description of ANSI C63.4-1992 sec.13.1.5 and sec.13.1.6, the frequency stability measurements were carried out. By using frequency counter with suitable RF amplifier, the carrier frequency of the transmitter under test was measured with a temperature variation of -20°C to $+50^{\circ}\text{C}$ at the normal supply voltage, and if required, with a variation in the primary voltage from 85 % to 115 % the rated supply voltage at the temperature of $+20^{\circ}\text{C}$.


These measurements were carried out after allow sufficient time (approximately 1 hour) for the temperature of the chamber to stabilize.



1.8.5 Occupied Bandwidth :

According to description of ANSI C63.4-1992 sec.13.1.7, the occupied bandwidth measurements were carried out. By using a spectrum analyzer with a vertical antenna for picking up the signal, the measurements of the emission were made under the transmitting modes of the EUT.

The resolution bandwidth of spectrum analyzer was set to the value specified in sec.13.1.7.



1.9 TEST ARRANGEMENT (PHOTOGRAPHS)

PHOTOGRAPHS OF EUT CONFIGURATION FOR RADIATED EMISSIONS MEASUREMENT

Photograph present configuration with maximum emission
for Horizontal Plane

for Vertical Plane





JQA Application No. :80-90448
Model No. :KBRASTU10
Standard :CFR 47 FCC Rules Part 15

FCC ID :KBRASTU10
Issue Date :October 13, 1999
Page 18 of 23

TEST DATA

2.2 Radiated Emissions Measurement

Date : October 7, 1999
Temp.: 23 °C Humi.: 63 %

Operating Frequency : 315 MHz
Distance of Measurement : 3.0 meters

Frequency (MHz)	Factor (dB/m)	Correction		Meter Reading		Field Strength at 3 m	
		Horiz. (dB μ V)	Vert. (dB μ V)	Factor*	Limits (dB μ V/m)	Horiz. (dB μ V/m)	Vert. (dB μ V/m)
Fundamental							
315.000	20.8	57.1	53.9	-6.1	75.6	71.8	68.6
Harmonics & other Frequency components							
630.000	27.8	4.7	5.0	-6.1	55.6	26.4	26.7
945.000	32.9	< 0.0	< 0.0	-6.1	55.6	< 26.8	< 26.8
1260.000	26.7	6.6	9.7	-6.1	55.6	27.2	30.3
1575.000	29.5	< 5.0	< 5.0	-6.1	55.6	< 28.4	< 28.4
1890.000	31.1	< 5.0	< 5.0	-6.1	55.6	< 30.0	< 30.0
2205.000	-13.2	< 47.0	< 47.0	-6.1	55.6	< 27.7	< 27.7
2520.000	-12.3	< 47.0	< 47.0	-6.1	55.6	< 28.6	< 28.6
2835.000	-10.8	< 47.0	< 47.0	-6.1	55.6	< 30.1	< 30.1
3150.000	-9.5	< 47.0	< 47.0	-6.1	55.6	< 31.4	< 31.4



JQA Application No. :80-90448
Model No. :KBRASTU10
Standard :CFR 47 FCC Rules Part 15

FCC ID :KBRASTU10
Issue Date :October 13, 1999
Page 19 of 23

Note: 1. The spectrum was checked from 30 MHz to tenth harmonics.
All emissions not listed were found to be more than 20 dB below
the limits.

2. The symbol of "<" means "or less".

3. The cable loss and amplifier gain were included in the correction factor.

4. Sample calculation :
at 315.000 MHz
 $Cf + Mr + F = 20.8 + 57.1 - 6.1 = 71.8 \text{ dB}\mu\text{V/m}$
Where,
Cf = Correction Factor
Mr = Meter Reading
F = Peak to Average Factor


5. "*": The factor due to the pulsed waveform as shown in tha attached sheet.

6. Measuring Instrument Setting:

Less than 1000 MHz
Detector function : Peak
IF Bandwidth : 120 kHz

Above 1000 MHz
Resolution Bandwidth : 1 MHz


Tested by : Shigeru Osawa
Shigeru Osawa
Testing Engineer

*Radiated Fundamental & Spurious Emissions**FCC ID : KBRASTU10**Operating Frequency : 315 MHz**FUNDAMENTAL LIMITS [Sec. 15.231 (b)] : 6042uV/m*

The encoded waveform in the time domain

FCC ID : KBRASTU10
Model : KBRASTU10

Mode of EUT : Transmit



The above waveform indicates the case when field strength averaged over 100 milliseconds was maximum value. In order to obtain the peak to average factor, calculation of the period of total on-time was computed by personal computer. Results was obtained by following.

$$\begin{aligned}\text{Duty cycle} &= (\text{Maximum total on-time} / 100 \text{ msec}) \times 100 \\ &= (49.4 \text{ msec} / 100 \text{ msec}) \times 100 = 49.4 \%\end{aligned}$$

Therefore

$$\text{Factor is } 20 \log (0.4940) = -6.1 \text{ dB}$$



JQA Application No. :80-90448
Model No. :KBRASTU10
Standard :CFR 47 FCC Rules Part 15

FCC ID :KBRASTU10
Issue Date :October 13, 1999
Page 22 of 23

2.4 Occupied Bandwidth Measurement

Date : October 13, 1999
Temp.: 24 °C Humi.: 60 %

Measurements Results :

Specified Limits : 0.25 % of the fundamental frequency
315 MHz x 0.0025 = 787.5 kHz

Refer to the attached graphs.

Tested by : Shigeru Osawa

Shigeru Osawa
Testing Engineer

Emission Limitation

FCC ID : KBRASTU10
Model : KBRASTU10

Mode of EUT : Transmit

