

Company: Sensus Metering Systems

FCC ID: KCHMXU530T

IC Certification No.: 2220A-530T

Request for transmitter modular approval

Transmitter Module Characteristics

Item	Requirements	EUT
1	Have its own RF shielding	RF circuits covered by metal shields
2	Have buffered modulation/data inputs (if such inputs are provided),	All inputs to the modules are buffered through logic or microprocessor inputs.
3	Have it own power supply regulation	Power management control circuits between battery input and radio, refer to block diagram
4	Meet the antenna requirements of Section 15.203	Device is equipped with integrated circuit board antenna.
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	Device was tested on a test fixture board. Refer to test set-up photographs.
6	Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	Two proposed FCC ID label format are included in the filing. One of label is to be placed on the module and the other label is to be placed on the outside of system. Refer to FCC ID label format and location file.
7	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.	Refer to “User’s Guide” Exhibit
8	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	Calculation shows MPE and distance of approximately 7.1 cm