

FCC ID PER PART 18
MEASUREMENT AND TEST REPORT


For

Link USA International Inc.

40-22 Collegepoint Blvd.
Flushing, New York 11354
USA

FCC ID: KE7LK3S30

February 19, 2002

This Report Concerns: <input checked="" type="checkbox"/> Original Report	Equipment Type: LIGHT BULB
Test Engineer: Hien Pham	
Test Date: December 19, 2001	
Reviewed By: 	
	John Y. Chan – Engineering Manager
Prepared By:	Bay Area Compliance Laboratory Corporation 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732-9164

Note: The test report is specially limited to the use of the above client company and the product model. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

TABLE OF CONTENTS

1 - GENERAL INFORMATION..... 3

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3

1.2 OBJECTIVE3

1.3 RELATED SUBMITTAL(S)/GRANT(S).....3

1.4 TEST METHODOLOGY3

1.5 TEST FACILITY3

1.6 TEST EQUIPMENT LIST AND DETAILS.....4

1.7 EQUIPMENT UNDER TEST (EUT).....4

1.8 LOCAL SUPPORT EQUIPMENT4

2 - SYSTEM TEST CONFIGURATION..... 5

2.1 JUSTIFICATION5

2.2 SCHEMATICS / BLOCK DIAGRAM5

2.3 EQUIPMENT MODIFICATIONS.....5

2.4 CONFIGURATION OF TEST SYSTEM6

2.5 TEST SETUP BLOCK DIAGRAM6

3 - CONDUCTED EMISSIONS TEST DATA..... 7

3.1 MEASUREMENT UNCERTAINTY7

3.2 EUT SETUP7

3.3 SPECTRUM ANALYZER SETUP7

3.4 TEST PROCEDURE7

3.5 SUMMARY OF TEST RESULTS.....8

3.6 CONDUCTED EMISSIONS TEST DATA.....8

3.7 PLOT(S) OF CONDUCTED EMISSIONS TEST DATA.....8

4 - RADIATED EMISSION DATA..... 10

4.1 MEASUREMENT UNCERTAINTY10

4.2 EUT SETUP10

4.3 SPECTRUM ANALYZER SETUP10

4.4 TEST PROCEDURE10

4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION11

4.6 SUMMARY OF TEST RESULTS.....11

4.7 RADIATED EMISSIONS TEST DATA11

5 – FCC PRODUCT LABELING AND WARNING STATEMENT..... 12

5.1 PROPOSED FCC LABEL FORMAT12

5.2 PROPOSED LABEL LOCATION ON EUT.....12

5.3 FCC WARNING STATEMENT12

6 - CONDUCTED AND RADIATED SETUP PHOTOGRAPHS 13

6.1 CONDUCTED EMISSION PHOTOGRAPH – FRONT VIEW13

6.2 CONDUCTED EMISSION PHOTOGRAPH – SIDE VIEW13

6.3 RADIATED EMISSION PHOTOGRAPH – FRONT VIEW14

6.4 RADIATED EMISSION PHOTOGRAPH – REAR VIEW14

7 - PHOTOGRAPHS 15

7.1 EUT - FRONT VIEW15

7.2 EUT - REAR VIEW15

APPENDIX A - BLOCK DIAGRAM/SCHEMATICS/PARTS LIST..... 16

APPENDIX B - USER MANUAL..... 17

1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

The *Link USA's LK30X Sprial* or the "EUT" as referred to in this report is a wall light which measures 5.50" L x 2.50" W x 5.50"H.

Note: The test data was only good for the test sample. It may have deviation for other test sample.

1.2 Objective

The following test report is prepared on behalf of *Link USA* in accordance with Part 2, Subpart J, and Part 18, Subparts A, B, and C of the Federal Communication Commissions rules and regulations.

The objective of the manufacturer is to demonstrate compliance with FCC Part 18 limit requirements for Industrial, Scientific, and Medical Equipment.

1.3 Related Submittal(s)/Grant(s)

No Related Submittals.

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4 –1992, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 Meters.

1.5 Test Facility

The Open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated and conducted emission measurement data is located in the back parking lot of the building at the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-1992.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corporation is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices,

IEC/CISPR 22: 1998, and AS/NZS 3548: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods under NVLAP Lab Code 200167-0.

1.6 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Last Cal. Date	Cal. Due Date
HP	Spectrum Analyzer	8568B	Panel 2408A00105 Display 2403A06544	5/1/2001	5/1/2002
HP	Spectrum Analyzer	8593A	29190A00242	5/1/2001	5/1/2002
HP	Amplifier	8447E	1937A01054	5/1/2001	5/1/2002
HP	Quasi-Peak Adapter	85650A	2521A00718	5/1/2001	5/1/2002
HP	Signal generator	8640B	1727A06741	5/1/2001	5/1/2002
HP	Signal generator	8685A	2214A03081	5/1/2001	5/1/2002
Com-Power	Biconical Antenna	AB-100	14012	5/1/2001	5/1/2002
SOLAR	LISN	9252-50-R-24-BNC	984412	5/1/2001	5/1/2002
SOLAR	LISN	9252-50-R-20-BNC	984413	5/1/2001	5/1/2002
Com-Power	Log Periodic Antenna	AL-100	16091	5/1/2001	5/1/2002
Com-Power	Log Periodic Antenna	AB-900	15049	5/1/2001	5/1/2002

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp certifies that all calibration has been performed using suitable standards traceable to the NATIONAL INSTITUTE of STANDARDS and TECHNOLOGY (NIST).

1.7 Equipment Under Test (EUT)

Manufacturer	Description	Model	Serial Number	FCC ID
LINK USA	LIGHT BULB	LK3S30	None	KE7LK3S30

1.8 Local Support Equipment

Manufacturer	Description	Model	Serial Number	FCC ID
Commercial Electric	Power Cord extension	E192912	42927	None
LEVITON	Outlet Adapter	660W-125V	78477107164	None

2 - SYSTEM TEST CONFIGURATION

2.1 Justification

The EUT was tested under normal mode as used by a common (typical) user.


2.2 Schematics / Block Diagram

Appendix A contains a copy of the EUT's schematics diagram as reference.


2.3 Equipment Modifications

No modifications were made by BACL Corporation to ensure the EUT to comply with the application limits and requirements.

2.4 Configuration of Test System



2.5 Test Setup Block Diagram



3 - CONDUCTED EMISSIONS TEST DATA

3.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BAEL is ± 2.4 dB.

3.2 EUT Setup

The measurement was performed at the **Open Area Test Site**, using the same setup per ANSI C63.4 - 1992 measurement procedure. The specification used was the FCC Part 18 limits.

The EUT with the outlet adapter was connected to the power cord extension and placed on the center of the back edge on the test table.

The power cord extension was connected with 110 Vac/60 Hz power source.

3.3 Spectrum Analyzer Setup

The spectrum analyzer was set with the following configuration during the conduction test:

Start Frequency	450 kHz
Stop Frequency	30 MHz
Sweep Speed	Auto
IF Bandwidth	10 kHz
Video Bandwidth	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal

3.4 Test Procedure

During the conducted emission test, the power cord of the power cord extension was connected to the auxiliary outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions to ensure that the EUT is compliant with all installation combination.

All data was recorded in the peak detection mode. Quasi-peak readings were only performed when an emission was found to be marginal (within -4 dB μ V of specification limits). Quasi-peak readings are distinguished with a "Qp".

The EUT was tested under the normal modes during the final qualification test to represent the worst case results.

3.5 Summary of Test Results

According to the data in section 3.6, the EUT complied with the FCC 18 Conducted margin for industry, scientific and medical device, and with the worst margin reading of:

-8.0 dB μ V at 0.51 MHz at the Neutral mode with the Commercial Electric power cord extension, M/N: E192912, 0.45-30MHz


3.6 Conducted Emissions Test Data

3.6.1 Test Data, 0.45-30MHz

LINE CONDUCTED EMISSIONS				FCC PART 18	
Frequency MHz	Amplitude dB μ V	Detector Qp/Ave/Peak	Phase Line/Neutral	Limit dB μ V	Margin dB
0.51	40.0	QP	Neutral	48	-8.0
0.51	38.0	QP	Line	48	-10.0
7.54	33.2	QP	Line	48	-14.8
0.98	32.6	QP	Line	48	-15.4
1.01	31.0	QP	Neutral	48	-17.0
8.04	26.6	QP	Neutral	48	-21.4

3.7 Plot(s) of Conducted Emissions Test Data

The plot of conducted emission tested was presented hereinafter as reference.



4 - RADIATED EMISSION DATA

4.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BAEL is ± 4.0 dB.

4.2 EUT Setup

The radiated emission tests were performed in the open area 3-meter test site, using the setup accordance with the ANSI C63.4 - 1992. The specification used in this report was the FCC Part 18 limits.

The EUT with the outlet adapter was connected to the power cord extension and placed on the center of the back edge on the test table.

The power cord extension was connected to 110VAC/60Hz power source.

4.3 Spectrum Analyzer Setup

According to FCC Rules, the system was tested to 1000 MHz.

Start Frequency	30 MHz
Stop Frequency	1000 MHz
Sweep Speed	Auto
IF Bandwidth	1 MHz
Video Bandwidth	1 MHz
Quasi-Peak Adapter Bandwidth	120 kHz
Quasi-Peak Adapter Mode	Normal
Resolution Bandwidth	1 MHz

4.4 Test Procedure

For the radiated emissions test, the power cord of the power cord extension was connected to the AC floor outlet.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT is compliant with all installation combinations.

All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB μ V of specification limits), and are distinguished with a "Qp" in the data table.

The EUT was under normal mode during the final qualification test and the configuration was used to represent the worst case results.

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB μ V means the emission is 7dB μ V below the maximum limit for FCC Part 18. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 18 Limit}$$

4.6 Summary of Test Results

According to the data in section 4.7, the EUT complied with the FCC Part 18 standards for a industry, scientific and medical device, and had the worst margin of:

-5.9 dBmV at 39.73 MHz in the Vertical polarization, 30 to 1000MHz, 3 meters

4.7 Radiated Emissions Test Data

4.7.1 Final Test Data, 30-1000MHz, 3 Meters

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC PART 18	
Frequency MHz	Ampl. dBmV/m	Angle Degree	Height Meter	Polar H/ V	Antenna dBmV/m	Cable dB	Amp. dB	Corr. Ampl. dBmV/m	Limit dBmV/m	Margin dB
39.73	43.0	180	1.2	V	14.6	1.5	25.0	34.1	40	-5.9
39.73	42.2	180	2.2	H	14.4	1.5	25.0	33.1	40	-6.9
53.43	39.3	270	1.2	V	9.2	1.7	25.0	25.2	40	-14.8
53.43	40.0	210	2.2	H	11.3	1.7	25.0	28.0	40	-12.0
74.64	42.1	340	1.2	V	9.1	1.9	25.0	28.1	40	-11.9
74.64	41.8	270	2.2	H	9.4	1.9	25.0	28.1	40	-11.9
86.29	42.7	90	1.2	V	8.4	2.2	25.0	28.3	40	-11.7
86.29	42.2	120	2.2	H	9.0	2.2	25.0	28.4	40	-11.6

5 – FCC PRODUCT LABELING AND WARNING STATEMENT

5.1 Proposed FCC Label Format




Specifications: Text is black or white in color and is left justified. Labels are silk-screened and shall be “permanently affixed” at a conspicuous location on the EUT.

5.2 Proposed Label Location on EUT

Rear View of EUT

Proposed FCC Label Location



5.3 FCC Warning Statement

This device complies with Part 18 of FCC rules.

Information on the following matters shall be provided to the user in the instruction manual or on the packaging if an instruction manual is not provided for any type of any ISM equipment:

- The interference potential of the device or system
- Maintenance of the system
- Simple measures that can be taken by the user to correct interference.

6 - Conducted and Radiated Setup Photographs

6.1 Conducted Emission Photograph – Front View



6.2 Conducted Emission Photograph – Side View



6.3 Radiated Emission Photograph – Front View



6.4 Radiated Emission Photograph – Rear View



7 - PHOTOGRAPHS

7.1 EUT - Front View



7.2 EUT - Rear View



APPENDIX A - BLOCK DIAGRAM/SCHEMATICS/PARTS LIST

APPENDIX B - USER MANUAL

Not Available at Time of Testing