



# Retlif Testing Laboratories

101 New Boston Road, Goffstown, NH 03045  
603-497-4600 - Fax: 603-497-5281

CORPORATE OFFICE  
795 Marconi Avenue  
Ronkonkoma, NY 11779  
631-737-1500 Fax 631-737-1497  
(A NY Corporation)

WASHINGTON  
REGULATORY OFFICE  
703-533-1614 Fax 703-533-1612

## RETLIF TESTING LABORATORIES TEST REPORT R-3945N May 1, 2002

### FCC PART 15 COMPLIANCE TEST REPORT ON

ORTOVOX X1 AVALANCHE TRANSCEIVER  
FCC ID: KF5ORTOVOXX1

|   |                      |
|---|----------------------|
| APPLICANT<br>Ortovox Sportartikel GmbH<br>Rotwandweg 5<br>D-82024 Taufkirchen Germany | MANUFACTURER<br>SAME |
|---|----------------------|

TEST SPECIFICATION: FCC Rules and Regulations Part 15, Subpart C, Para. 15.209

TEST PROCEDURE: ANSI C63.4:1992

#### TEST SAMPLE DESCRIPTION

BRANDNAME: Ortovox MODEL: X1

TYPE: Avalanche Transceiver

POWER REQUIREMENTS: 3VDC Internal Battery (tested with new battery installed)

FREQUENCY OF OPERATION: 457kHz

MODULATION: Pulsed

FCC ID: KF5ORTOVOXX1

APPLICABLE RULE SECTION: Part 15, Subpart C, Section 15.209

#### TESTS PERFORMED

Field Strength of Fundamental Emission 457kHz

Field Strength of Spurious Emissions 450kHz-1GHz

#### TEST SAMPLE OPERATION

The Ortovox Model X1 Avalanche Transceiver is used to locate avalanche victims. It is manually activated by the user and is manually switched between transmit and receive modes. When in transmit mode it will transmit continuously at 457kHz.



**Retlif Testing Laboratories**

Test Report R-3945N

## TEST SAMPLE / TEST PROGRAM

### 15.203 ANTENNA REQUIREMENTS

The device uses a permanently attached internal ferrite antenna. The antenna is totally enclosed inside the case.

### 15.205 RESTRICTED BANDS OF OPERATION

No emissions from the EUT were observed in any of the restricted bands.

### 15.207 CONDUCTED EMISSIONS

Not applicable (battery operated device).

### 15.209 RADIATED EMISSIONS

Fundamental Frequency

.457MHz

Out of Band, Spurious, Harmonics

450kHz - 1000MHz

No spurious emissions were observed within 20dB of the specified limit at a test distance of 3 meters throughout the required frequency range. The measurements taken at 457kHz were performed at 3 meters and extrapolated to the 300 meter limit using the 40dB/decade extrapolation factor specified for frequencies less than 30MHz.

Determination of Field Strength Limit:

#### **Fundamental Frequency: 457kHz**

Where F = the frequency in kHz, the formula for calculating the maximum permitted fundamental field strength at 300 meters is:

$$2400/(F)$$

$$2400/(457) = 5.25\mu\text{V/M}$$

Unwanted emissions cannot exceed the level of the fundamental emissions.

Duty Cycle:

No Duty Cycle Factor was used. The test sample was operating at close to 100% duty cycle and the maximized peak signal of the 457kHz fundamental frequency met the average limit specified in 15.209.



**Retlif Testing Laboratories**

Test Report R-3945N

## TEST RESULTS

The maximized peak field strength at 457kHz was below the average limit specified in 15.209 and therefore also met the peak emission requirement specified in 15.35. No harmonic or spurious emissions were observed.

### Radiated Emissions Equipment List

| <b>EN</b> | <b>Type</b>          | <b>Manufacturer</b> | <b>Description</b> | <b>Model No.</b> | <b>Cal Date</b> | <b>Due Date</b> |
|-----------|----------------------|---------------------|--------------------|------------------|-----------------|-----------------|
| 4029      | Test Site            | Retlif              | 3/10 Meter         | RNH              | 8/3/01          | 8/3/02          |
| 3207      | Loop Antenna, Active | EMCO                | 10 kHz - 30 MHz    | 6502             | 5/6/01          | 5/6/02          |
| 4202      | Biconilog            | EMCO                | 26 MHz - 2 GHz     | 3142             | 7/16/01         | 7/16/02         |
| 4986      | EMI Test Receiver    | Rhode & Schwarz     | 20 Hz - 26.5GHz    | ES126            | 6/9/01          | 6/9/02          |



**Retlif Testing Laboratories**

Test Report R-3945N

## **RETLIF TESTING LABORATORIES**

## EMISSIONS DATA SHEET

|                     |  |             |         |
|---------------------|--|-------------|---------|
| Test Method:        | Radiated Emissions 450 kHz to 1 GHz              |             |         |
| Customer:           | Ortovox  | Job No.:    | R-3945N |
| Test Sample:        | Avalanche Transceiver                            |             |         |
| Model No.:          | x1   | Serial No.: | 3       |
| Test Specification: | FCC Part 15, Subpart C<br>Paragraph: 15.209      |             |         |
| Operating Mode:     | Transmitting                                     |             |         |
| Technician:         | T. Firkowski                                     | Date:       | 4/15/02 |
| Notes:              | Test Distance: 3 Meters      Detector used: Peak |             |         |

#### Radiated Emission Limit (Per 15.209)

The frequency range from 450 kHz to 1 GHz was scanned. No other EUT emissions were observed within 20 dB of the limit at 3 meters.