



Instructions / Notes		
1	Dimensions	2.75" (W) x 2.00" (H); sharp radius
2	Material	GE: 8B35; Lexan; 7 mil thick; matted surface
3	Adhesive	3M: 468 MP; 5 mil adhesive; apply to back side
4	White	Background flood
5	Black	All text and graphics

**DucTrak**<sup>TM</sup>

**DDS 12- Short-Range    2.4-3V  $\equiv$  130mA Max**

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

 **ARBN**  
090 007 962

**FCC ID: KKGA040412**  
**IC: 2213A-A040412**  
**12kHz Frequency**  
450-4202-00-01-B

 DIGITAL CONTROL INCORPORATED

Phone 800-288-3610 or 425-251-0559  
**www.digitrak.com**

DL	7-10-07	Removed Made In USA					B	
KH	7-8-03	Create new label per ECO 1066					A	
By	Date	Description					Rev.	
Approval		<div>TOLERANCES (Standard units unless otherwise specified)</div> <div>Decimal .X    ±0.030    Fractions ±1/32               .XX    ±0.010               .XXX ±0.005    Angles ±1°</div>		<div> DIGITAL CONTROL INCORPORATED</div> <div>19625 62nd Ave. S., Kent, WA 98032 425-251-0701 Fax 425-251-0702 www.digitrak.com</div>		Title Long-Range		Sheet
Approval						DucTrak™ Transmitter		1/1
Drafter	KH					Drawing No.		Rev.
Engineer						450-4101-00-01		B