



TYPE APPROVAL CERTIFICATE

For a 406 Megahertz Distress Beacon for use with the Cospas-Sarsat Satellite System

Certificate Number: 204


Manufacturer: McMurdo Ltd., United Kingdom
Beacon Type(s): FF EPIRB and Non FF EPIRB
Beacon Model(s): G5 Smartfind Plus (a) & (m) / E5 Smartfind (a) & (m)
Additional Names: SGE406-II (a) & (m), EG50:AUTO & EG50:MAN
SE406-II (a) & (m), EP50:AUTO & EP50:MAN
Test Laboratory: TUV Product Service, UK
Dates of Test: February 2006 – June 2006

Details of the beacon features and battery type are provided overleaf.

The Cospas-Sarsat Council hereby certifies that the 406 MHz Distress Beacon Model identified above is compatible with the Cospas-Sarsat System as defined in documents:

C/S T.001 Specification for Cospas-Sarsat 406 MHz Distress Beacon
Issue 3 – Rev. 7, November 2005
C/S T.007 Cospas-Sarsat 406 MHz Distress Beacon Type Approval Standard
Issue 4, November 2005

Original TAC 163 issued: **23 August 2006**
TAC 163 re-issued to Signature Industries Ltd.: **30 March 2007**
TAC 163 re-issued to McMurdo Ltd.: **18 November 2009**
1-st extension TAC 204 issued: **10 May 2010**


D. Levesque
Head of Cospas-Sarsat Secretariat

NOTE, HOWEVER:

1. This certificate does not authorize the operation or sale of any 406 MHz distress beacon. Such authorization may require type acceptance by national administrations in countries where the beacon will be distributed, and may also be subject to national licensing requirements.
2. This certificate is intended only as a formal notification to the above identified manufacturer that the Cospas-Sarsat Council has determined, on the basis of test data of a beacon submitted by the manufacturer, that 406 MHz distress beacons of the type identified herein meet the standards for use with the Cospas-Sarsat System.
3. Although the manufacturer has formally stated that all beacons identified with the above model name(s) will meet the Cospas-Sarsat specification referenced above, this certificate is not a warranty and Cospas-Sarsat hereby expressly disclaims any and all liability arising out of or in connection with the issuance, use or misuse of the certificate.
4. This certificate is subject to revocation by the Cospas-Sarsat Council should the beacon type for which it is issued cease to meet the Cospas-Sarsat specification. A new certificate may be issued after satisfactory corrective action has been taken and correct performance demonstrated in accordance with the Cospas-Sarsat Type Approval Standard.
5. Cospas-Sarsat type approval testing requirements only address the electrical performance of the beacon at 406 MHz. Conformance of the beacon to operational and environmental requirements is the responsibility of national administrations.

Beacon Model(s): G5 Smartfind Plus (a) & (m) / E5 Smartfind (a) & (m)

Operating temperature range: -20°C to +55°C

Battery Details: VARTA, Lithium-Manganese Dioxide (Li-MnO₂), 3 x 3 'CR 2/3 AH' cells, or
Panasonic, Lithium-Manganese Dioxide (Li-MnO₂), 3 x 3 'CR 123A' cells

Operating Lifetime: 48 hours

Transmit Frequency: 406.028 MHz

Beacon Model Features:

- Internal Navigation device (GPS), EAZIX model EZGPM01 or uBlox model TIM-4P (*);
- 121.5 MHz auxiliary radio locating device (50 mW, continuous duty cycle);
- Built-in strobe light (Intensity 0.75 cd, flash rate: 21 per minute);
- Manual activation;
- Automatic activation combined with hydrostatic beacon release mechanism; and
- Self-test mode, one burst of 520 ms - long format (*) and 440 ms - short format (**).

Approved Beacon Message Protocols: Beacon is approved for use with the message protocols indicated with "Yes" and black text below:

USER PROTOCOLS (**)	USER-LOCATION PROTOCOLS (*)	LOCATION PROTOCOLS (*)
Yes Maritime with MMSI	Yes Maritime with MMSI	Yes Standard Location: EPIRB with MMSI
Yes Maritime with Radio Call Sign	Yes Maritime with Radio Call Sign	Yes Standard Location: EPIRB with Serial Number
Yes EPIRB Float Free with Serial Number	Yes EPIRB Float Free with Serial Number	No Standard Location: ELT with 24-bit Address
Yes EPIRB Non Float Free with Serial Number	Yes EPIRB Non Float Free with Serial Number	No Standard Location: ELT with Aircraft Operator Designator
Yes Radio Call Sign	Yes Radio Call Sign	No Standard Location: ELT with Serial Number
No Aviation	No Aviation	No Standard Location: PLB with Serial Number
No ELT with Serial Number	No ELT with Serial Number	Yes National Location: EPIRB
No ELT with Aircraft Operator and Serial Number	No ELT with Aircraft Operator and Serial Number	No National Location: ELT
No ELT with Aircraft 24-bit Address	No ELT with Aircraft 24-bit Address	No National Location: PLB
No PLB with Serial Number	No PLB with Serial Number	
No National (Short Format Message)		
No National (Long Format Message)		

NOTES: * - applicable only to G5 Smartfind Plus (a) & (m), SGE406-II (a) & (m), EG50:AUTO & EG50:MAN
 ** - applicable only to E5 Smartfind (a) & (m), SE406-II (a) & (m), EP50:AUTO & EP50:MAN