



Spectrum Research & Testing Lab., Inc.

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
Report No.:FCCA02081407-A
Page:1 of 32
Issued Date:Nov. 27, 2002

Product Name: Remote controller (TX)
Model Number: Tx174FP
Applicant: IOWA Export-Import Trading Co.
512 Tuttle Street, Des Moines, Iowa 50309-4168, U.S.A.
Date of Receipt: Aug. 14, 2002
Finished date of Test: Nov. 25, 2002
Applicable Standards: 47 CFR Part 15, Subpart C

We, **Spectrum Research & Testing Laboratory Inc.**, hereby certify that one sample of the above was tested in our laboratory with positive results according to the above-mentioned standards. The records in the report are an accurate account of the results. Details of the results are given in the subsequent pages of this report.

Checked By : Spring Wang , Date: Nov. 27, 2002
(Spring Wang)

Approved By : Harris W. Lai , Date: Nov. 27, 2002
(Harris W. Lai, Director)

NVLAQ[®]

Lab Code: 200099-0

FCC ID:KNFMULTIRCU7TX



Table of Contents

1. DOCUMENT POLICY AND TEST STATEMENT	3
1.1 DOCUMENT POLICY	3
1.2 TEST STATEMENT	3
2. DESCRIPTION OF EUT AND TEST MODE	4
2.1 GENERAL DESCRIPTION OF EUT	4
2.2 DESCRIPTION OF EUT INTERNAL DEVICE	4
2.3 DESCRIPTION OF TEST MODE	4
2.4 DESCRIPTION OF SUPPORT UNIT	5
3. DESCRIPTION OF APPLIED STANDARDS	5
4. CONDUCTED EMISSION TEST	5
5. RADIATED EMISSION TEST	6
5.1 RADIATED EMISSION LIMIT	6
5.2 TEST EQUIPMENT	7
5.3 TEST SET-UP	8
5.4 TEST PROCEDURE	8
5.5 EUT OPERATING CONDITION	8
5.6 RADIATED EMISSION TEST RESULT	9
6. BAND EDGE TEST	15
6.1 BAND EDGE LIMIT	15
6.2 TEST EQUIPMENT	15
6.3 TEST SET-UP	16
6.4 TEST PROCEDURE	16
6.5 EUT OPERATING CONDITION	16
6.6 BAND EDGE TEST RESULT	16
7. FREQUENCY BANDWIDTH	21
7.1 FREQUENCY BANDWIDTH LIMIT	21
7.2 TEST EQUIPMENT	21
7.3 TEST SET-UP	21
7.4 TEST PROCEDURE	22
7.5 EUT OPERATING CONDITION	22
7.6 FREQUENCY BANDWIDTH TEST RESULT	22
8. RELEASE OR OPERATING TIME	29
8.1 RELEASE TIME OR OPERATING LIMIT	29
8.2 TEST EQUIPMENT	29
8.3 TEST SET-UP	29
8.4 TEST PROCEDURE	30
8.5 EUT OPERATING CONDITION	30
8.6 RELEASE OR OPERATING TIME TEST RESULT	30
9. PHOTOS OF TESTING	31
10. TERMS OF ABRIVATION	32



1. DOCUMENT POLICY AND TEST STATEMENT

1.1 DOCUMENT POLICY

- The report shall not be reproduced except in full, without the written approval of SRT Lab, Inc.
- The report must not be used by the applicant to claim that the product is endorsed by NVLAP.
- The NVLAP logo applies only to the applicable standards specified in this report.

1.2 TEST STATEMENT

- The test results in the report apply only to the unit tested by SRT Lab.
- There was no deviation from the requirements of test standards during the test.
- The new battery power source 12 Vdc, was used during the test.



2. DESCRIPTION OF EUT AND TEST MODE

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Remote controller (TX)
MODEL NO.	Tx174FP
POWER SUPPLY	12Vdc(Battery)
CABLE	N/A
I/O PORT/INTERFACE	N/A
FREQUENCY BAND	289-321.9MHz, 335.5-392MHz
CARRIER FREQUENCY	1.289.5MHz,2.303.8 MHz,3.320.5MHz 4.337.4MHz,5.346.5MHz,6.355.1MHz,7.384.5MHz
NUMBER OF CHANNEL	7
CHANNEL SPACING	N/A
RF OUTPUT POWER	-25 dBm (eirp)
I.F. & L.O.	L.O 303.875MHz
MODULATION TYPE	ASK
BIT RATE OF TRANSMISSION	4 kbps
ANTENNA TYPE	Loop Antenna integrated on PCB

NOTE: The EUT is the transmitter part of a remote controller which includes a receiver part. For more detailed information, please refer to the specifications or User's manual provided by manufacturer.

2.2 DESCRIPTION OF EUT INTERNAL DEVICE

DEVICE	BRAND / MAKER	MODEL #	FCC ID/DOC	REMARK
N/A				

2.3 DESCRIPTION OF TEST MODE

The EUT was operated in continually transmitting mode.

2.4 DESCRIPTION OF SUPPORT UNIT

The EUT was configured by the requirement of ANSI C63.4 and CISPR 22. All interface ports were connected to the appropriate support units via specific cables. The support units and cables are listed below.

NO	DEVICE	BRAND	MODEL #	FCC ID/DOC	CABLE
	N/A				

NOTE: For the actual test configuration, please refer to the photos of testing.

3. DESCRIPTION OF APPLIED STANDARDS

The EUT is a kind of wireless product and according to the specifications provided by the applicant, must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C

All tests have been performed and recorded as per the above standards.

4. CONDUCTED EMISSION TEST

The test item was not performed, because the EUT uses 12Vdc battery as power source.



5. RADIATED EMISSION TEST

5.1 RADIATED EMISSION LIMIT

FCC part15C 15.209 limits of radiated emission measurement for frequency below 1000 MHz

FREQUENCY (MHz)	DISTANCE (m)	FIELS STRENGTH (dB μ V/m)
30 - 88	3	40.0
88 - 216	3	43.5
216 - 960	3	46.0
ABOVE 960	3	54.0

FCC part15C 15.231(b) limit of fundamental and spurious emissions measurement.

FREQUENCY (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.66-40.70	2250	225
70-130	1250	125
130-174	1250 to 3750 (NOTE 5)	125 to 375 (NOTE 7)
174-260	3750	375 (NOTE 7)
260-470	3750 to 12500 (NOTE 6)	375 to 1250
Above 470	12500	1250

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
3. In the emission tables above, the tighter limit applies at the band edges.
4. Distance refers to the distance between measuring nstrument, antenna, and the closest point of any part of the device or system.
5. Limit = $20\log(56.81818(F) - 6136.3636)$; F : Fundamental Frequency (MHz)
6. Limit = $20\log(41.667 \times F - 7083.3333)$; F : Fundamental Frequency (MHz)
7. Limit = The Limit of Fundamental Frequency – 20dB
8. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.



5.2 TEST EQUIPMENT


The following test equipment was used during the radiated emission test :

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9 kHz TO 2750 MHz	ROHDE & SCHWARZ	ESCS30/ 836858/008	DEC. 2002 R&S
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3142/ 9701-1124	APR. 2003 ETC
PRE-AMPLIFIER	1GHz-26.5GHz Gain:30dB(typ.)	HP	8449B/ 3008A01019	NOV. 2002 ETC
SPECTRUM	9KHz TO 26.5GHz	HP	8953E/ 3710A03220	MAY 2003 ETC
HORN ANTENNA	1GHz TO 18GHz	EMCO	3115/ 9012-3619	JAN. 2003 ETC
OATS	3 – 10 M MEASUREMENT	SRT	SRT-1	MAY 2003 SRT

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.
2. The Open Area Test Site (SRT-1) is registered by FCC with No. 90957 and VCCI with No. R-1081.
3. The Open Area Test Site (SRT-2) is registered by FCC with No. 98458 and VCCI with No. R-1168.



5.3 TEST SET-UP



NOTE :

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.

5.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4 and CISPR 22. The measurements were made at an open area test site with 3 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz, all readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak or average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

5.5 EUT OPERATING CONDITION

Same as section 2.3 of this report.



TEST REPORT

5.6 RADIATED EMISSION TEST RESULT

Temperature:	30°C	Humidity:	52%RH
Frequency:	289.554MHz	Channel:	1
Frequency Range:	30MHz - 18GHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested by:	James Lee

Antenna Polarization : Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
289.5540	2.00	14.24	53.6	69.8	73.9	-4.1	50.0	1.0
579.0927	3.06	20.07	17.7	40.8	53.9	-13.1	297.0	1.3
868.6139	3.09	23.06	10.1	36.2	53.9	-17.7	276.0	1.0
1158.2160	*	*	*	*	*	*	*	*
1447.7700	*	*	*	*	*	*	*	*

Antenna Polarization : Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
289.5320	2.00	14.24	25.9	42.1	73.9	-31.8	165.0	1.7
579.0564	3.06	20.07	6.9	30.0	53.9	-23.9	234.0	1.7
868.5757	3.09	23.06	3.0	29.1	53.9	-24.8	298.0	1.0
1158.1280	*	*	*	*	*	*	*	*
1447.6600	*	*	*	*	*	*	*	*

NOTE :

1. Measurement uncertainty is 4dB.
2. "*": Measurement value was too low to be detected.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.
5. The emission level is lower than equipment 's noise.



TEST REPORT

Temperature:	30°C	Humidity:	52%RH
Frequency:	303.870MHz	Channel:	2
Ferquency Range:	30MHz - 18GHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested by:	James Lee

Antenna Polarization : Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
303.870	1.64	14.92	54.8	71.3	74.9	-3.6	250.0	1.0
607.616	2.37	20.77	24.7	47.8	54.9	-6.2	25.0	1.2
911.393	2.91	23.71	19.4	46.0	54.9	-8.0	190.0	1.2
1215.480	*	*	*	*	*	*	*	*
1519.350	*	*	*	*	*	*	*	*

Antenna Polarization : Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
303.860	1.64	14.92	31.5	48.1	74.9	-26.8	21.0	1.2
607.616	2.37	20.77	14.9	38.1	54.9	-15.9	300.0	1.3
911.393	2.91	23.71	12.8	39.4	54.9	-14.6	280.0	1.0
1215.480	*	*	*	*	*	*	*	*
1519.350	*	*	*	*	*	*	*	*

NOTE :

1. Measurement uncertainty is 4dB.
2. "*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.
- 5.The emission level is lower than equipment 's noise.



Temperature:	30°C	Humidity:	52%RH
Frequency:	320.5278	Channel:	3
Ferquency Range:	30MHz - 18GHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested by:	James Lee

Antenna Polarization : Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
320.5278	1.94	15.00	53.8	70.7	76.0	-5.3	77.6	1.0
641.0487	2.68	20.71	22.9	46.3	56.0	-9.7	280.0	1.2
961.5772	3.12	23.61	10.6	37.3	56.0	-18.7	272.0	1.0
1282.1112	*	*	*	*	*	*	*	*
1602.6390	*	*	*	*	*	*	*	*

Antenna Polarization : Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
321.3258	1.97	15.01	32.6	49.6	76.0	-26.4	233.0	1.0
641.0760	2.68	20.71	13.4	36.8	56.0	-19.2	0	1.0
961.5884	3.12	23.61	4.1	30.8	56.0	-25.2	283.0	1.6
1285.3032	*	*	*	*	*	*	*	*
1606.629	*	*	*	*	*	*	*	*

NOTE :

1. Measurement uncertainty is 4dB.
2. "*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.
- 5.The emission level is lower than equipment 's noise.



Temperature:	30°C	Humidity:	52%RH
Frequency:	337.433MHz	Channel:	4
Ferquency Range:	30MHz - 18GHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested by:	James Lee

Antenna Polarization : Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
337.4330	2.21	15.09	53.4	70.7	76.8	-6.1	103.0	1.0
674.7990	2.63	21.25	21.6	45.5	56.8	-11.3	273.0	1.2
1012.1803	2.33	24.20	7.1	33.6	56.8	-23.2	278.0	1.4
1349.7320	*	*	*	*	*	*	*	*
1687.165	*	*	*	*	*	*	*	*

Antenna Polarization : Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
337.3888	2.21	15.09	30.3	47.6	76.8	-29.2	0	2.9
674.7605	2.63	21.25	9.9	33.8	56.8	-23.0	348.0	2.0
1012.1632	2.33	24.20	4.0	30.5	56.8	-26.3	278.0	1.3
1349.5552	*	*	*	*	*	*	*	*
1686.944	*	*	*	*	*	*	*	*

NOTE :

1. Measurement uncertainty is 4dB.
2. "*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.
- 5.The emission level is lower than equipment 's noise.



Temperature:	30°C	Humidity:	52%RH
Frequency:	355.1635MHz	Channel:	6
Ferquency Range:	30MHz - 18GHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested by:	James Lee

Antenna Polarization : Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
355.1635	2.26	15.48	54.3	72.0	77.7	-5.7	110.0	1.0
710.3110	2.49	21.70	24.2	48.4	57.7	-9.3	274.0	1.1
1065.5570	2.38	24.50	15.4	42.3	57.7	-15.4	278.0	1.0
1420.7590	2.66	25.40	4.7	32.8	57.7	-24.9	59.0	1.0
1775.8175	*	*	*	*	*	*	*	*

Antenna Polarization : Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
355.1365	2.26	15.48	35.4	53.1	77.7	-24.6	237.0	1.1
710.2556	2.49	21.70	9.7	33.9	57.7	-23.8	25.0	1.0
1065.5988	2.38	24.31	4.6	31.3	57.7	-26.4	274.0	1.3
1420.5460	*	*	*	*	*	*	*	*
1775.6825	*	*	*	*	*	*	*	*

NOTE :

1. Measurement uncertainty is 4dB.
2. "*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.
5. The emission level is lower than equipment 's noise.



Temperature:	30°C	Humidity:	52%RH
Frequency:	384.585MHz	Channel:	7
Ferquency Range:	30MHz - 18GHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested by:	James Lee

Antenna Polarization : Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
384.5850	2.17	16.06	52.9	71.1	79.0	-7.9	122.0	1.0
769.1450	2.68	22.04	21.5	46.2	59.0	-12.8	270.0	1.3
1153.7315	2.54	24.65	17.5	44.7	59.0	-14.3	265.0	1.0
1538.3422	2.96	25.55	3.6	32.1	59.0	-26.9	277.0	1.0
1922.9250	*	*	*	*	*	*	*	*

Antenna Polarization : Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
384.5707	2.17	16.06	31.4	49.6	79.0	-29.4	28.0	1.6
769.1352	2.68	22.04	12.1	36.8	59.0	-22.2	260.0	1.9
1153.7768	2.54	24.65	6.8	34.0	59.0	-25.0	263.0	1.0
1538.8280	*	*	*	*	*	*	*	*
1923.5350	*	*	*	*	*	*	*	*

NOTE :

1. Measurement uncertainty is 4dB.
2. "*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



6. BAND EDGE TEST

6.1 BAND EDGE LIMIT

FCC part15C 15.231(b) limit of fundamental and spurious emissions measurement.

FREQUENCY (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.66-40.70	2250	225
70-130	1250	125
130-174	1250 to 3750 (NOTE 4)	125 to 375 (NOTE 6)
174-260	3750	375
260-470	3750 to 12500 (NOTE 5)	375 to 1250 (NOTE 6)
Above 470	12500	1250

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level ($\mu\text{V}/\text{m}$) = 20 log Emission level ($\mu\text{V}/\text{m}$).
3. In the emission tables above, the tighter limit applies at the band edges.
4. Limit = $20\log(56.81818(F) - 6136.3636)$; F : Fundamental Frequency (MHz)
5. Limit = $20\log(41.667 \times F - 7083.3333)$; F : Fundamental Frequency (MHz)
6. Limit = The Limit of Fundamental Frequency – 20dB
7. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

6.2 TEST EQUIPMENT


The following test equipment was used during the radiated emission test :

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9 kHz TO 7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2003 ETC

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

6.3 TEST SET-UP

The EUT was connected to Receiver(or spectrum) by 50Ω coaxial cable.



6.4 TEST PROCEDURE

Please refer to FCC Part15C 15.231.

6.5 EUT OPERATING CONDITION

Same as section 2.3 of this report.

6.6 BAND EDGE TEST RESULT

Temperature:	<u>25 °C</u>	Humidity:	<u>60%RH</u>
Receiver Detector:	<u>PK.</u>	Tested by:	<u>James Lee</u>

Frequency (MHz)	RF LEVEL 120kHz Bw (dBμV)	Limit (dBμV)	Margin (dB)
288.988	43.74	55.46	-11.72
321.900	47.10	56.38	-9.28
335.500	40.26	57.78	-17.52
393.788	25.97	57.49	-31.52




Spectrum Research & Testing Lab., Inc.

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:17 of 32
Issued Date:Nov. 27, 2002

*Frequency: 288.988 MHz



Date: 22.NOV.2002 16:26:16




Spectrum Research & Testing Lab., Inc.

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:18 of 32
Issued Date:Nov. 27, 2002

*Frequency: 321.900 MHz



Date: 22.NOV.2002 16:34:05




Spectrum Research & Testing Lab., Inc.

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:19 of 32
Issued Date:Nov. 27, 2002

*Frequency: 335.500 MHz



Date: 22.NOV.2002 16:36:26




Spectrum Research & Testing Lab., Inc.

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:20 of 32
Issued Date:Nov. 27, 2002

*Frequency: 393.788 MHz



Date: 22.NOV.2002 16:38:55



7. FREQUENCY BANDWIDTH

7.1 FREQUENCY BANDWIDTH LIMIT

FREQUENCY (MHz)	BANDWIDTH LIMIT(kHz)
Above 70-900	0.25%×Center Frequency(MHz)
Above 900	0.5%×Center Frequency(MHz)

NOTE:

1. Bandwidth is determined at the points 20dB down from the modulated carrier.

7.2 TEST EQUIPMENT


The following test equipment was used during the radiated emission test :

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9 kHz TO 7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2003 ETC

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

7.3 TEST SET-UP

The EUT was connected to receiver(or spectrum) by 50Ω coaxial cable.





Spectrum Research & Testing Lab., Inc.

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:22 of 32
Issued Date:Nov. 27, 2002

7.4 TEST PROCEDURE

Please refer to FCC Part15C 15.231.

7.5 EUT OPERATING CONDITION

Same as section 2.3 of this report.

7.6 FREQUENCY BANDWIDTH TEST RESULT

Temperature: 25 °C Humidity: 60%RH

Receiver Detector: PK. Tested by: James Lee

Test Result: Pass

CHANNEL	FREQUENCY (MHz)	<u>20</u> dB DOWN BANDWIDTH (kHz)	MINIMUM LIMIT (kHz)	MAXMUM LIMIT (kHz)
1	289.982	444	N/A	724.95
2	303.988	476	N/A	759.67
3	320.970	456	N/A	802.42
4	337.815	452	N/A	844.53
6	354.958	468	N/A	887.39
7	385.986	484	N/A	964.96




Spectrum Research & Testing Lab., Inc.

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:23 of 32
Issued Date:Nov. 27, 2002

*Channel: 1
*Frequency: 298.982 MHz



Date: 22.NOV.2002 13:24:50




Spectrum Research & Testing Lab., Inc.

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:25 of 32
Issued Date:Nov. 27, 2002

*Channel: 3
*Frequency: 320.970 MHz



Date: 22.NOV.2002 13:14:12




Spectrum Research & Testing Lab., Inc.
 No. 101-10, Ling 8,
 Shan-Tong Li, Chung-Li
 City, Taoyuan, Taiwan,
 R.O.C.

TEST REPORT

Reference No.:A02081407
 ReportNo.:FCCA02081407-A
 Page:26 of 32
 Issued Date:Nov. 27, 2002

*Channel: 4
 *Frequency: 337.815 MHz



Date: 22.NOV.2002 13:03:25




Spectrum Research & Testing Lab., Inc.

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:27 of 32
Issued Date:Nov. 27, 2002

*Channel: 6
*Frequency: 354.958 MHz



Date: 22.NOV.2002 13:09:09




Spectrum Research & Testing Lab., Inc.

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:28 of 32
Issued Date:Nov. 27, 2002

*Channel: 7
*Frequency: 385.986 MHz



Date: 22.NOV.2002 12:32:08



8. RELEASE OR OPERATING TIME

8.1 RELEASE TIME OR OPERATING LIMIT

1. A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
2. A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- 3). Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions to determine system integrity of transmitters used in security or safety applications are allowed if the periodic rate of transmission does not exceed one transmission of not more than one second duration per hour for each transmitter.
4. Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.


8.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test :

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
OSCILLOSCOPE	500MHz	HP	54616B/ US39150351	JUN 2003 ETC

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

8.3 TEST SET-UP





8.4 TEST PROCEDURE

A specific loop antenna was connected to oscilloscope to detect the EUT's release time. The oscilloscope displayed the EUT's release time and take a picture of measurement.

8.5 EUT OPERATING CONDITION

The EUT is normal use function.


8.6 RELEASE OR OPERATING TIME TEST RESULT

Temperature:	<u>25 °C</u>	Humidity:	<u>60%RH</u>
Tested by:	<u>James Lee</u>	Test Result:	<u>Pass</u>

Start release time(ms)	Stop time(ms)	Total release time(ms)	Limit of release time<(s)
-18.4	12.4	30.8	5

NOTE:

1. The EUT was manually operated.





**Spectrum Research
& Testing Lab., Inc.**


No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:31 of 32
Issued Date:Nov. 27, 2002

9. PHOTOS OF TESTING

- Radiated test





**Spectrum Research
& Testing Lab., Inc.**

No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan,
R.O.C.

TEST REPORT

Reference No.:A02081407
ReportNo.:FCCA02081407-A
Page:32 of 32
Issued Date:Nov. 27, 2002

10. TERMS OF ABRIVATION

AV.	Average detection
AZ(°)	Turn table azimuth
Correct.	Correction
EL(m)	Antenna height (meter)
EUT	Equipment Under Test
Horiz.	Horizontal direction
LISN	Line Impedance Stabilization Network
NSA	Normalized Site Attenuation
PK.	Peak detection
Q.P.	Quasi-peak detection
SRT Lab	Spectrum Research & Testing Laboratory, Inc.
Vert.	Vertical direction