	RF Exposure Report					
Report No.:	SA151116C23A					
FCC ID:	KNYPRW0010WP					
Test Model:	WPV10					
Received Date:	Nov. 16, 2015					
Test Date:	Nov. 30 ~ Dec. 21, 2015					
Issued Date:	Mar. 28, 2016					
Applicant:	FreeWave Technologies, Inc.					
Address:	5395 Pearl Pkwy Ste 100, Boulder, CO 80301, U.S.A.					
Issued By:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch					
Lab Address:	No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.					
Test Location:	No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)					



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specification, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Relea	ase Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
2.2	Limits for Maximum Permissible Exposure (MPE) 2 MPE Calculation Formula 3 Classification	5
3	Calculation Result Of Maximum Conducted Power	5



Release Control Record

Issue No.	Description	Date Issued
SA151116C23A	Original release.	Mar. 28, 2016

1 Certificate of Conformity

Product:	2 Megapixel Wireless Bullet Camera	
Test Model:	WPV10	
Sample Status:	Engineering sample	
Applicant:	FreeWave Technologies, Inc.	
Test Date:	Nov. 30 ~ Dec. 21, 2015	
Standards:	FCC Part 2 (Section 2.1091)	
	KDB 447498 D01 (October 23, 2015)	
	IEEE C95.1	

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :	Pettie Chen / Senior Specialist	,	Date:	Mar. 28, 2016
Approved by :	Ken Liu / Senior Manager	,	Date:	Mar. 28, 2016



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)			Average Time (minutes)	
Limits For General Population / Uncontrolled Exposure					
300-1500			F/1500	30	
1500-100,000			1.0	30	

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout^*G) / (4^*pi^*r^2)$

where

 $Pd = power density in mW/cm^{2}$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result Of Maximum Conducted Power

Frequency Band	Max Power	Antenna Gain	Distance	Power Density	Limit
(MHz)	(dBm)	(dBi)	(cm)	(mW/cm ²)	(mW/cm ²)
2412-2462	20.36	1.68	20	0.032	

---END----