



The University of Michigan  
Radiation Laboratory  
3228 EECS Building  
Ann Arbor, MI 48109-2122  
Tel: (734) 764-0500  
Fax: (734) 647-2106

Measured Radio Frequency Emissions  
From

**Lear Corporation Receiver**  
**FCC ID: KOBFR10A**  
**IC: 3521A-FR10A**

Test Report No. 417124-538  
December 17, 2009

Copyright © 2009

For:  
Lear Corporation  
21557 Telegraph Rd  
Southfield, MI 48033  
Contact: Jason Summerford  
jsummerford@lear.com  
Phone: 248.447.1357  
Fax: 248.447.1689

Measurements made by: Valdis V. Liepa

Test report written by: Joseph D. Brunett

Testing supervised by:  
Report Approved by:

A handwritten signature in black ink, reading "Valdis V. Liepa".

Valdis V. Liepa  
Research Scientist

---

## Summary

Tests for compliance with FCC Regulations, CFR 47, Part 15 and with Industry Canada RSS-210/Gen, were performed on a Lear, FCC ID: KOBFR10A, IC: 3521A-FR10A. This device under test (DUT) is subject to the rules and regulations as a Receiver.

In testing completed on November 10, 2009, the DUT tested met the allowed specifications for radiated emissions by 8.0 dB. Antenna conducted emissions were minimal. AC power line conducted emissions are not subject to regulation as the DUT is powered by a 12 VDC automotive source.

## **Table of Contents**

1.	Introduction.....	3
2.	Equipment Used.....	3
3.	Device Under Test .....	4
3.1	Description & Block Diagram .....	4
3.2	Variants & Samples .....	4
3.3	Modes of Operation .....	4
3.4	Exemptions .....	4
3.5	EMC Relevant Modifications .....	4
4.	Emissions Limits.....	5
4.1	Radiated Emissions Limits.....	5
4.2	Power Line Conducted Emissions Limits .....	5
4.3	Antenna Power Conduction Limits.....	5
5.	Measurement Procedures .....	5
5.1	Semi-Anechoic Chamber Radiated Emissions.....	5
5.2	Outdoor Radiated Emissions.....	6
5.3	Radiated Field Computations.....	6
5.4	Indoor Power Line Conducted Emissions.....	6
5.5	Supply Voltage Variation.....	6
6.	Test Results : Radiated Emissions .....	7
6.1.1	Emission Spectrum .....	7
6.1.2	Supply Voltage and Supply Voltage Variation.....	7
6.1.3	Antenna Conducted Emissions .....	7

## 1. Introduction

This Lear Receiver was tested for compliance with FCC Regulations, Part 15, adopted under Docket 87-389, April 18, 1989 as subsequently amended, and with Industry Canada RSS-210/Gen, Issue 7, June 2007. Tests were performed at the University of Michigan Radiation Laboratory Willow Run Test Range following the procedures described in ANSI C63.4-2003 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The Site description and attenuation characteristics of the Open Site facility are on file with FCC Laboratory, Columbia, Maryland (FCC Reg. No: 91050) and with Industry Canada, Ottawa, ON (File Ref. No: IC 2057A-1).

## 2. Equipment Used

The test equipment commonly used in our facility is listed in Table 2.1. Except where indicated as a pre-test, monitoring, or support device; all equipment listed below is a part of the University of Michigan Radiation Laboratory (UMRL) quality system. This quality system has been established to ensure all equipment has a clearly identifiable classification, calibration expiry date, and that all calibrations are traceable to national standards.

**Table 2.1 Test Equipment.**

<b>Test Instrument</b>	<b>Used</b>	<b>Manufacturer/Model</b>	<b>Q Number</b>
Spectrum Analyzer (9kHz-26GHz)	<input checked="" type="checkbox"/>	Hewlett-Packard 8593E, SN: 3412A01131	HP8593E1
Spectrum Analyzer (9kHz-6.5GHz)	<input checked="" type="checkbox"/>	Hewlett-Packard 8595E, SN: 3543A01546	JDB8595E
Power Meter	<input type="checkbox"/>	Hewlett-Packard, 432A	HP432A1
Harmonic Mixer (26-40 GHz)	<input type="checkbox"/>	Hewlett-Packard 11970A, SN: 3003A08327	HP11970A1
Harmonic Mixer (40-60 GHz)	<input type="checkbox"/>	Hewlett-Packard 11970U, SN: 2332A00500	HP11970U1
Harmonic Mixer (75-110 GHz)	<input type="checkbox"/>	Hewlett-Packard 11970W, SN: 2521A00179	HP11970W1
Harmonic Mixer (140-220 GHz)	<input type="checkbox"/>	Pacific Millimeter Prod., GMA, SN: 26	PMPGMA1
S-Band Std. Gain Horn	<input type="checkbox"/>	S/A, Model SGH-2.6	SBAND1
C-Band Std. Gain Horn	<input type="checkbox"/>	University of Michigan, NRL design	CBAND1
XN-Band Std. Gain Horn	<input type="checkbox"/>	University of Michigan, NRL design	XNBAND1
X-Band Std. Gain Horn	<input type="checkbox"/>	S/A, Model 12-8.2	XBAND1
X-band horn (8.2- 12.4 GHz)	<input type="checkbox"/>	Narda 640	XBAND2
X-band horn (8.2- 12.4 GHz)	<input type="checkbox"/>	Scientific Atlanta , 12-8.2, SN: 730	XBAND3
K-band horn (18-26.5 GHz)	<input type="checkbox"/>	FXR, Inc., K638KF	KBAND1
Ka-band horn (26.5-40 GHz)	<input type="checkbox"/>	FXR, Inc., U638A	KABAND1
U-band horn (40-60 GHz)	<input type="checkbox"/>	Custom Microwave, HO19	UBAND1
W-band horn(75-110 GHz)	<input type="checkbox"/>	Custom Microwave, HO10	WBAND1
G-band horn (140-220 GHz)	<input type="checkbox"/>	Custom Microwave, HO5R	GBAND1
Bicone Antenna (30-250 MHz)	<input checked="" type="checkbox"/>	University of Michigan, RLBC-1	LBBIC1
Bicone Antenna (200-1000 MHz)	<input checked="" type="checkbox"/>	University of Michigan, RLBC-2	HBBIC1
Dipole Antenna Set (30-1000 MHz)	<input checked="" type="checkbox"/>	University of Michigan, RLDP-1,-2,-3	UMDIP1
Dipole Antenna Set (30-1000 MHz)	<input type="checkbox"/>	EMCO 3121C, SN: 992 (Ref. Antennas)	EMDIP1
Active Rod Antenna (30 Hz-50 MHz)	<input type="checkbox"/>	EMCO 3301B, SN: 3223	EMROD1
Active Loop Antenna (30 Hz-50 MHz)	<input type="checkbox"/>	EMCO 6502, SN:2855	EMLOOP1
Ridge-horn Antenna (300-5000 MHz)	<input checked="" type="checkbox"/>	University of Michigan	UMRH1
Amplifier (5-1000 MHz)	<input checked="" type="checkbox"/>	Avantek, A11-1, A25-1S	AVAMP1
Amplifier (5-4500 MHz)	<input checked="" type="checkbox"/>	Avantek	AVAMP2
Amplifier (4.5-13 GHz)	<input type="checkbox"/>	Avantek, AFT-12665	AVAMP3
Amplifier (6-16 GHz)	<input type="checkbox"/>	Trek	TRAMP1
Amplifier (16-26 GHz)	<input type="checkbox"/>	Avantek	AVAMP4
LISN Box	<input type="checkbox"/>	University of Michigan	UMLISN1
Signal Generator	<input type="checkbox"/>	Hewlett-Packard 8657B	HPSG1

### 3. Device Under Test

#### 3.1 Description & Block Diagram

The DUT is a 315 MHz receiver designed for automotive/vehicular applications, and as such it is powered by a 12 VDC source. The device is housed in a plastic case approximately 6 x 7 x 2 cm in dimension. For testing, a generic harness was provided by the manufacturer. The DUT is designed and manufactured by Lear Corporation, 5100 W. Waters Ave., Apodaca, Mexico.

Device	[Make], Model	[S/N],P/N	EMC Consideration
DUT	[Lear], 5E0AM0	-	Fully populated – fully tested
DUT	[Lear], 5E0SD0	-	Digital depopulation
variant	[Lear], 5E0SR0	-	Digital depopulation

Cable	[Make], Model	Length	EMC Consideration
Harness	[Lear],	50 cm	-

#### 3.2 Variants & Samples

There are three variants of the device as tested. Model 5E0AM0 is the fully populated device employing passive entry passive start digital circuitry. This model may employ either an external antenna (attached to the antenna port) or the internal antenna built onto the PCB. The internal antenna is always present, but can be disabled in software when not used. Models 5E0SR0 and 5E0SD0 are identical, and have the digital circuitry for the PEPS functionality depopulated.

Two samples were provided for testing, one fully populated (5E0AM0) and one (5E0SD0) with the PEPS circuitry depopulated.

#### 3.3 Modes of Operation

The receiver in question is capable of employing either its internal antenna or an external antenna via the antenna port provided.

#### 3.4 Exemptions

The DUT is permanently installed in a transportation vehicle. As such, digital emissions are exempt (per FCC 15.103(a) and IC correspondence on ICES-003) from regulation.

#### 3.5 EMC Relevant Modifications

No EMI Relevant Modifications were performed by this test laboratory.

## 4. Emissions Limits

### 4.1 Radiated Emissions Limits

The DUT tested falls under the category of an Unintentional Radiator. The applicable testing frequencies and corresponding emission limits set by both the FCC and IC are given in Table 4.2 below.

**Table 4.2. Spurious Emission Limits (FCC: 15.33, .35, .109/209; IC: RSS-210 2.7, T2)**

Freq. (MHz)	E <sub>lim</sub> (3m) $\mu$ V/m	E <sub>lim</sub> dB( $\mu$ V/m)
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
960-2000	500	54.0

Note: Average readings apply above 1000 MHz (1 MHz BW), Quasi-Peak readings apply to 1000 MHz (120 kHz RBW), PRF of intentional emissions > 20 Hz for QPK to apply.

### 4.2 Power Line Conducted Emissions Limits

**Table 4.3 Emission Limits (FCC:15.107 (CISPR); IC: RSS-Gen, 7.2.2 T2).**

Frequency (MHz)	Class A (dB $\mu$ V)		Class B (dB $\mu$ V)	
	Quasi-peak	Average	Quasi-peak	Average
.150 - 0.50	79	66	66 - 56*	56 - 46*
0.50 - 5	73	60	56	46
5 - 30	73	60	60	50

Notes:

1. The lower limit shall apply at the transition frequency
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15-0.50 MHz:  
 \*Class B Quasi-peak:  $\text{dB}\mu\text{V} = 50.25 - 19.12 \cdot \log(f)$   
 \*Class B Average:  $\text{dB}\mu\text{V} = 40.25 - 19.12 \cdot \log(f)$
3. 9 kHz RBW

### 4.3 Antenna Power Conduction Limits

Ref: FCC 15.111(a). P<sub>max</sub> = 2 nW; for frequency range see Table 4.1.

## 5. Measurement Procedures

### 5.1 Semi-Anechoic Chamber Radiated Emissions

To become familiar with the radiated emission behavior of the DUT, the device is first studied and measured in our shielded semi-anechoic chamber. In the chamber there is a set-up similar to that of an outdoor 3-meter site, with a turntable, an antenna mast, and a ground plane. Instrumentation includes spectrum analyzers and other equipment as needed.

The DUT is laid on the test table as shown in the included block diagram and/or photographs. A shielded loop antenna is employed when studying emissions from 9 kHz to 30 MHz. Above 30 MHz and below 250 MHz a biconical antenna is employed. Above 250 MHz a ridge or standard gain horn antennas are used. The spectrum analyzer resolution and video bandwidths are set so as to measure the DUT emission without decreasing the emission bandwidth (EBW) of the device. Emissions are studied for all orientations (3-axes) of the DUT and all test antenna polarizations. In the chamber, spectrum and modulation characteristics of intentional carriers are recorded. Receiver spurious emissions are measured with an appropriate carrier signal applied. Associated test data is presented in subsequent sections.

## **5.2 Outdoor Radiated Emissions**

After measurements are performed indoors, emissions on our outdoor 3-meter Open Area Test Site (OATS) are made, when applicable. If the DUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in ANSI C63.4 are employed. Alternatively, an on-table layout more representative of actual use may be employed if the resulting emissions appear to be worst-case in such a configuration. Any intentionally radiating elements are placed on the test table flat, on their side, and on their end (3-axes) and worst case emissions are recorded. For each configuration the DUT is rotated 360 degrees about its azimuth and the receive antenna is raised and lowered between 1 and 4 meters to maximize radiated emissions from the device. Receiver spurious emissions are measured with an appropriate carrier signal applied. For devices with intentional emissions below 30 MHz, our shielded loop antenna at a 1 meter receive height is used. Low frequency field extrapolation to the regulatory limit distance is employed as needed. Emissions between 30 MHz and 1 GHz are measured using tuned dipoles and/or biconical antennas. Care is taken to ensure that the RBW and VBW used meet the regulatory requirements, and that the EBW of the DUT is not reduced. The Photographs included in this report show the Test Setup.

## **5.3 Radiated Field Computations**

To convert the dBm values measured on the spectrum analyzer to dB( $\mu$ V/m), we use expression

$$E3(\text{dB}\mu\text{V/m}) = 107 + \text{PR} + \text{KA} - \text{KG} + \text{KE} - \text{CF}$$

where      PR = power recorded on spectrum analyzer, dBm, measured at 3 m  
              KA = antenna factor, dB/m  
              KG = pre-amplifier gain, including cable loss, dB  
              KE = duty correction factor, dB  
              CF = distance conversion (employed only if limits are specified at alternate distance), dB

When presenting the data at each frequency, the highest measured emission under all of the possible DUT orientations (3-axes) is given.

## **5.4 Indoor Power Line Conducted Emissions**

When applicable, power line conducted emissions are measured in our semi-anechoic chamber. If the DUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in ANSI C63.4 are employed. Alternatively, an on-table layout more representative of actual use may be employed if the resulting emissions appear to be worst-case in such a configuration.

The conducted emissions measured with the spectrum analyzer and recorded (in dB $\mu$ V) from 0-2 MHz and 2-30 MHz for both the ungrounded (Hi) and grounded (Lo) conductors. The spectrum analyzer is set to peak-hold mode in order to record the highest peak throughout the course of functional operation. Only when the emission exceeds or is near the limit are quasi-peak and average detection used.

## **5.5 Supply Voltage Variation**

Measurements of the variation in the fundamental radiated emission were performed with the supply voltage varied by no less than 85% and 115% of the nominal rated value. For battery operated equipment, tests were performed using a new battery, and worst case emissions are re-checked employing a new battery.

## **6. Test Results : Radiated Emissions**

### **6.1.1 Emission Spectrum**

The only detectable RF emission occurs at the LO or  $2 \times \text{LO} = \text{VCO}$ . The relative DUT emission spectrum is recorded and is shown in Figures 6.1 through 6.3.

### **6.1.2 Supply Voltage and Supply Voltage Variation**

The DUT has been designed to be powered by a 12 VDC battery. For this test, relative radiated power was measured at the fundamental as the voltage was varied from 4.0 to 18.0 volts. The emission variation is shown in Figure 6.4.

Supply Voltage	V	=	13.3 V
Current	I	=	11.8 mA (pulsed)

### **6.1.3 Antenna Conducted Emissions**

These measurements are made by connecting the DUT antenna terminal directly to the spectrum analyzer 50  $\Omega$  input and recording all spurious signals. The following worst case emissions from the sample tested are:

Frequency (MHz)	Power (pW)
48.5	0.20
80.7	0.20
253.5	0.20
651.8	0.18

RBW 120 kHz, Peak Detection

**Table 6.1 Highest Emissions Measured**

<b>Radiated Emission - RF</b>											Lear Ford Rx; FCC, IC
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3 dBμV/m	E3lim dBμV/m	Pass dB	Comments
1	<b>Interior &amp; Exterior Antenna Modules</b>										
2	325.7	Sbic	H	-78.6	Pk	19.2	20.8	26.8	46.0	19.2	max. of all, noise
3	325.7	Sbic	V	-80.8	Pk	19.2	20.8	24.6	46.0	21.4	max. of all, noise
4	651.4	Sbic	H	-76.8	Pk	25.5	17.7	38.0	46.0	<b>8.0</b>	max. of all, noise
5	651.4	Sbic	V	-77.8	Pk	25.5	17.7	37.0	46.0	9.0	max. of all, noise
6	977.1	Sbic	H	-79.2	Pk	29.2	15.7	41.3	54.0	12.7	max. of all, noise
7	977.1	Sbic	V	-80.5	Pk	29.2	15.7	40.0	54.0	14.0	max. of all, noise
8	1001.0	Horn	H	-62.2	Pk	20.6	28.0	37.4	54.0	16.6	max. of all, noise
9	1100.0	Horn	H	-62.4	Pk	21.0	28.1	37.5	54.0	16.5	max. of all, noise
10	1200.0	Horn	H	-60.8	Pk	21.3	28.1	39.4	54.0	14.6	max. of all, noise;
11	1300.0	Horn	H	-61.8	Pk	21.4	28.1	38.5	54.0	15.5	max. of all, noise
12	1400.0	Horn	H	-62.0	Pk	21.8	28.1	38.7	54.0	15.3	max. of all, noise
13	1500.0	Horn	H	-62.1	Pk	22.2	28.1	39.0	54.0	15.0	max. of all, noise
14	1600.0	Horn	H	-62.4	Pk	22.4	28.1	38.9	54.0	15.1	max. of all, noise
15											
16											
17											
18											
19											
20											
21											
22											
23											
24											
25											
26											
27											
<b>Digital Radiated Emissions*</b>											
#	Freq. kHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3 dBμV/m	E3lim dBμV/m	Pass dB	Comments
1											
2											
3											
4	Digital emissions more than 20 dB below FCC/IC Class B Limit.										
5											
6											
7											
8											
9	* For devices used in transportation vehicles, digital emissions are exempt from FCC regulations per FCC 15.103(a)										

Meas.10/08/09; U of Mich.






Figure 6.1. Emissions measured at 3 meters in chamber, 0-1000 MHz.




Figure 6.2. Emissions measured at 3 meters in chamber, 1000-2000 MHz. (emission at marker is background)




Figure 6.3. Relative receiver emission(s).





Figure 6.4. Relative emission vs. supply voltage.



**Photograph 6.5. DUT on OATS (one of three axes tested)**



**Photograph 6.6. Close-up of DUT on OATS (one of three axes tested)**