Y2283

Technical Specification

806-960 MHz 6dB Gain

High Performance: These antennas provide 6dBd, wide band performance.

Rugged and weatherproof: The construction of our standard duty yagis feature 1/2" aluminum U channel with 1/4" solid elements. All exposed areas are coated with UV polyester. The balun assembly is filled and sealed with elastomeric thermoplastic.

Lightweight and Durable: These antennas are easily installed by one person.

Termination Options:

Type A: 12" Teflon pigtail with N connector. **Type B:** Direct TNC connection to the balun.

ELECTRICAL SPECIFICATIONS:

GAIN: 6dBd F/B 15dB

FREQUENCY: -06 806-896MHz <2:1 VSWR

-25 825-896MHz <2:1 VSWR -96 896-960MHz <2:1 VSWR -915 900-930MHz <2:1 VSWR

VERT BEAMWIDTH: 70° **HORIZ BEAM WIDTH:** 90°

RATING: 150 watts, 50 ohms impedance

MECHANICAL SPECIFICATIONS:

MATERIAL: ½" aluminum U channel boom

1/4" solid elements

FINISH: UV inhibited polyester coat

LENGTH: 15" **WEIGHT:** <2 lbs.


MOUNT: 1 5/8" mast, stainless hardware

FLAT PLATE AREA: .08 ft²
WIND RATING: 125 MPH
WIND LOAD: 4.7 lbs.

YAGI ANTENNA



Horizontal Pattern



Vertical Pattern

