

TABLE OF CONTENTS

APPLICANT: SIEMENS AG

FCC ID: KR5FBS2BHASH

REPORT CONTAINING:

PAGE 1.....TEST PROCEDURE
PAGE 2.....CIRCUIT DESCRIPTION
PAGE 3-4.....125KHz Tx RADIATION INTERFERENCE TEST DATA
PAGE 5.....OCCUPIED BANDWIDTH

EXHIBITS CONTAINING:

EXHIBIT 1.....POWER OF ATTORNEY LETTER
EXHIBIT 2.....FCC ID LABEL SAMPLE
EXHIBIT 3.....SKETCH OF FCC ID LABEL LOCATION
EXHIBIT 4.....BLOCK DIAGRAM
EXHIBIT 5.....SCHEMATIC
EXHIBIT 6A-6C.....PARTS LIST
EXHIBIT 7A-7B.....INSTRUCTION MANUAL
EXHIBIT 8A.....EXTERNAL FRONT VIEW PHOTOGRAPH
EXHIBIT 8B.....EXTERNAL REAR VIEW PHOTOGRAH
EXHIBIT 8C.....INTERNAL COMPONENT VIEW PHOTOGRAPH
EXHIBIT 8D.....INTERNAL SOLDER SIDE PHOTOGRAPH
EXHIBIT 8E.....CONNECTOR PHOTOGRAPH
EXHIBIT 8F-8G.....PHOTOGRAPH
EXHIBIT 9.....OCCUPIED BANDWIDTH PLOT

APPLICANT: SIEMENS AG
FCC ID: KR5FBS2BHASH
REPORT #: F:\CUS\S\SIEMENS\SIE112A9.RPT
TABLE OF CONTENTS LIST

APPLICANT: SIEMENS AG

TEST EQUIPMENT LIST

1. Spectrum Analyzer: Hewlett Packard 8566B - Opt 462, w/ preselector 85685A, & Quasi-Peak Adapter HP 85650A, & HP 8449B - OPT H02 Cal. 6/26/98
2. Signal Generator, Hewlett Packard 8640B, cal. 10/1/98
3. Eaton Biconnical Antenna Model 94455-1 20-200 MHz Serial No. 0997 Cal. 5/15/98
4. Electro-Metric Dipole Kit, 20-1000 MHz, Model TDA-30 10/15/98
5. Electro-Metric Horn 1-18 GHz, Model RGA-180, Cal. 8/15/98
6. Electro-Metric Antennas Model TDA-30/1-4, Cal. 10/15/98
7. Electro-Metric Line Impedance Stabilization Network Model No. EM-7821, Serial No. 101; 100KHz-30MHz 50uH. Cal. 11/19/98
8. Electro-Metric Line Impedance Stabilization Network Model No. EM-7820, Serial No. 2682; 10KHz-30MHz 50uH. Cal. 11/19/98
9. Special low loss cable was used above 1 GHz
10. Tenney Temperature Chamber

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. In the frequency range 10KHz to 30MHz the RBW was 10KHz and from 30-1000MHz the RBW of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was &temp& with a humidity of &humr&.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

APPLICANT: SIEMENS AG
FCC ID: KR5FBS2BHASH
REPORT #: F:\CUS\S\SIEMENS\SIE112A9.RPT
PAGE #: 1

APPLICANT: SIEMENS AG

FCC ID: KR5FBS2BHASH

CIRCUIT DESCRIPTION:

The sensor detects the transponder which causes the frequency to vary. This device will detect its own transponder.

ANTENNA_AND_GROUND_CIRCUITRY

This unit makes use of a short, helical antenna. The antenna is inductively coupled to the wiring on the automobile. The antenna is self contained, no provision is made for an external antenna. This unit is powered from a 12.0V battery.

No ground connection is provided. The unit relies on the ground track of the printed circuit board.

APPLICANT: SIEMENS AG
FCC ID: KR5FBS2BHASH
REPORT #: F:\CUS\S\SIEMENS\SIE112A9.RPT
PAGE #: 2

APPLICANT: SIEMENS AG
 FCC ID: KR5FBS2BHASH
 NAME OF TEST: RADIATION INTERFERENCE
 RULES PART NO.15.109(a) and 15.209
 REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 2400/F(KHz) AT 300 Meters.
 OUT-OF-BAND EMISSIONS SHALL NOT EXCEED THE LEVEL OF THE FUNDAMENTAL.

9 to 490 KHz: 2400/F(KHz) uV/m @ 300 METERS
 @125KHz Limit is 25.66dBuV/m @300Meters
 490 to 1705 KHz: 24000/F(KHz) uV/m @ 30 METERS
 1705 to 30 MHz: 29.54 dBuV/M @ 30 METERS
 30 to 88 MHz: 40.00 dBuV/M @ 3 METERS
 88 to 216 MHz: 43.50 dBuV/M
 216 to 960 MHz: 46.02 dBuV/M
 ABOVE 960 MHz: 54.00 dBuV/M

TEST

CONFIGURATION: The INTENTIONAL RADIATOR was connected to an ignition switch and a harness simulator cable box. The device was tested in both transmitting modes.

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR dB	FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT. POL.
125.00	7.29	0.80	11.35	8.50	17.16	V
375.00	3.23	1.40	16.27	5.00	20.66	V
625.00	2.08	1.60	20.65	4.30	21.36	V

SAMPLE CALCULATION: $FSdBuV/m = MR(dBuV) + ACFdB.$

APPLICANT: SIEMENS AG
 FCC ID: KR5FBS2BHASH
 REPORT #: F:\CUS\S\SIEMENS\SIE112A9.RPT
 PAGE #: 3

APPLICANT: SIEMENS AG
FCC ID: KR5FBS2BHASH
NAME OF TEST: RADIATION INTERFERENCE

TEST PROCEDURE: ANSI C63.4-1992 Section 8.2.1. The EUT was placed on a non-conducting table 80CM above the ground plane with the EUT located in the center of the table. With the antenna vertical a preliminary scan was done at 3 meters distance, the EUT was moved to a appropriate distance and the antenna height varied and also placed in a horizontal position. The frequency was scanned from 9.0KHz to 1.0GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The EUT was measured in three(3) orthogonal planes. The unit was measured at TIMCO ENGINEERING, INC. located at 6051 N.W. 19th Lane Gainesville, Florida 32605.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: S. S. SANDERS DATE: MARCH 12, 1999

APPLICANT: SIEMENS AG
FCC ID: KR5FBS2BHASH
REPORT #: F:\CUS\S\SIEMENS\SIE112A9.RPT
PAGE #: 4

APPLICANT: SIEMENS AG
FCC ID: KR5FBS2BHASH
NAME OF TEST: Occupied Bandwidth
RULES PART NO.: 15.209
REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPH IN EXHIBIT 9 REPRESENTS THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the above photo was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: S. S. SANDERS MARCH 12, 1999

APPLICANT: SIEMENS AG
FCC ID: KR5FBS2BHASH
REPORT #: F:\CUS\S\SIEMENS\SIE112A9.RPT
PAGE #: 5