

CCSEM-TRF-001 Rev. 02 Sep 01, 2023 Report No.: KSCR240600110702

Page: 1 of 7

1 Cover Page

RF Exposure Evaluation Report

Application No.: KSCR2406001107AU

FCC ID: KR5H6315

Applicant: Continental Automotive Technologies GmbH **Address of Applicant:** Siemensstrasse 12 Regensburg Germany

Manufacturer: Continental Automotive Changchun Co., Ltd. Jingyue Branch

Address of Manufacturer: 5800 Shengtai Street 130000Changchun China

Equipment Under Test (EUT):

EUT Name: IBC (Integrated Body Controller)

Model No.: H6315 Trade Mark: Continental

FCC Rules 47 CFR §2.1091

Standard(s): KDB 447498 D04 interim General RF Exposure Guidance v01

Date of Receipt: 2024-06-18

Date of Test: 2024-06-24 to 2024-07-15

Date of Issue: 2024-07-17

Test Result: Pass*

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240600110702

Page: 2 of 7

Revision Record			
Version	Description	Date	Remark
00	Original	2024-07-17	/

Authorized for issue by:	
Tested By	Maker_Qi/Project Engineer
Approved By	Terry Hou /Reviewer



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240600110702

Page: 3 of 7

2 Contents

		P	age	
1	Cov	er Page	1	
2	Contents			
3	Gen	eral Information	4	
	3.1	General Description of E.U.T.	4	
	3.2	Technical Specifications	4	
	3.3	Separation Distance	4	
	3.4	Test Location	5	
	3.5	Test Facility	5	
4	RF E	Exposure Test Exemptions	6	
	4.1	RF Exposure Test Exemptions for single RF sources	6	
5	Mea	surement and Calculation	7	
	5.1	Maximum transmit power	7	
	5.2	RF Exposure Calculation	7	



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240600110702

Page: 4 of 7

3 General Information

3.1 General Description of E.U.T.

Power supply:	Voltage 12V, Static current ≤ 3mA
Test voltage:	DC 12V
	☐ Portable device
Product Type:	☐ Mobile device
	☐ Fixed device

3.2 Technical Specifications

125kHz

Operation Frequency:	125kHz
Modulation Type:	ASK
Number of Channels:	1
Number of Antennas	6
Antenna Type:	External antenna

3.3 Separation Distance

Separation distance between the antenna to person (R):	>20cm		
Remark: This minimum test separation distance is determined by the smallest distance from the antenna			
and radiating structures or outer surface of the device, according to the host form factor, exposure			
conditions and platform requirements, to any part of the body or extremity of a user or bystander. R has			
been stated in user manual			



CCSEM-TRF-001 Rev. 02 Sep 01, 2023 Report No.: KSCR240600110702

Page: 5 of 7

3.4 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

- 1.SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
- 2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
- 3. Sample source: sent by customer.

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

A2LA

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

• FCC

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

• ISED

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 2324E

VCCI

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240600110702

Page: 6 of 7

4 RF Exposure Test Exemptions

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.1 RF Exposure Test Exemptions for single RF sources

4.1.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240600110702

Page: 7 of 7

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report KSCR240600110701

Freq. (kHz)	Result Level (dBµV/m@3m)	Result Level (mW)
125	72.11	0.005

5.2 RF Exposure Calculation

For single RF source:

	Evaluation method	Exempt Limit(mW)	Verdict
\boxtimes	Blanket 1 mW Blanket Exemption	1mW	Pass

The max power is 72.11dBuV/m@3m=0.005mW<1mW

So the device is exclusion from SAR test.

-- End of the Report--