

FCC ID: KR5S122736001

Date of issue: 2006-05-16



Test Report
acc. to the relevant standard
47 CFR Part 15 C – Intentional Radiators
Measurement Procedure:
ANSI C63.4 - 1992
relating to
Siemens AG
Siemens VDO Automotive
S122736001
with antennas 5WK4 8774
&
antennas 5WK4 8775

Measurement of Radio- Noise Emissions
from Low- Voltage Electrical and Electronic Equipment
Technical characteristics and test methods for radio equipment
in the frequency range 9 kHz to 40 GHz

FCC ID: KR5S122736001

Date of issue: 2006-05-16

| Manufacturer's details | |
|-------------------------------|--|
| Manufacturer | Siemens AG Siemens VDO Automotive |
| Manufacturer's grantee code | KR5 |
| Manufacturer's address | Siemens AG Siemens VDO Automotive |
| | Siemensstrasse 12 |
| | D-93005 Regensburg |
| | Germany |
| | Phone: +49 0941 790 6699 |
| | Fax: +49 0941 790 136699 |
| | E-mail: dagmar.kolar@siemens.com |
| Relevant standard used | 47 CFR Part 15C - Intentional Radiators |
| | ANSI C63.4-1992 |

| Test report prepared by | |
|--------------------------------|--|
| Technical engineer | Ralf Trepper |
| | m.dudde hochfrequenz-technik (laboratory) |
| | Rottland 5a |
| | D-51429 Bergisch Gladbach |
| | Germany |
| | Phone: +49 2207 96890 |
| | Fax : +49 2207 968920 |
| | E-mail: m.duddelabor@t-online.de |

| Equipment Under Test (EUT) | |
|-----------------------------------|-------------------------|
| Equipment category | Inductive system |
| Trade name | Siemens VDO |
| Type designation | S122736001 |
| Serial no. | none |
| Variants | with antennas 5WK4 8774 |
| | with antennas 5WK4 8775 |
| | |
| | |

FCC ID: KR5S122736001

Date of issue: 2006-05-16

0 Test result

| CFR Section | Report Chapter | Requirements Headline | Test result | | |
|------------------|----------------|-----------------------------|-------------|-----------------|---------------|
| | | | OK | fail | na |
| 15.203 | 10.1 | Antenna Requirement | pass | fail | na |
| 15.205 15.209 | 10.2 | Radiated spurious emissions | pass | fail | na |
| | | | | | |

| | |
|-------------------------------|--------------------------|
| Test requirements kept | yes no |
|-------------------------------|--------------------------|

Signature test personnel



.....
Ralf Trepper

Signature of the company official



.....
Manfried Dudde

FCC ID: KR5S122736001

Date of issue: 2006-05-16

| List of contents | Page |
|--|-------------|
| 0 Test result | 3 |
| 1 Testing laboratory | 5 |
| 2 Introduction | 5 |
| 3 Product | 6 |
| 4 Test schedule | 6 |
| 5 Product and measurement documentation..... | 7 |
| 6 Observations and comments..... | 7 |
| 7 Summary | 7 |
| 8 Conclusions | 8 |
| 9 Operation description..... | 9 |
| 10.1 Antenna Requirement..... | 11 |
| 10.1.1 Regulation | 11 |
| 10.1.2 Result | 11 |
| 10.2 Radiated emission..... | 12 |
| 10.2.1 Regulation | 12 |
| 10.2.2 Test equipment | 13 |
| 10.2.3 Test procedures..... | 14 |
| 10.2.4 Calculation of field strength Section 15.209 below 30 MHz..... | 15 |
| 10.2.5 Calculation of field strength Section 15.209 above 30 MHz | 15 |
| 10.2.6 Calculation of the field strength..... | 16 |
| 10.2.7 Calculation of Average Correction Factor..... | 16 |
| 11 Additional information to this test report | 21 |

FCC ID: KR5S122736001

Date of issue: 2006-05-16

1 Testing laboratory

Company name: m.dudde high frequency technology
Street: Rottland 5a
City: 51429 Bergisch Gladbach
Country: Germany
Laboratory:
FCC Registration Number: 699717
This site has been fully described in a report submitted to the FCC and was
accepted with letter dated _____ Registration Number .699717
Phone: +49-2207-9689-0
Fax: +49-2207-9689-20
E-mail: manfred.dudde@t-online.de
Web: <http://www.dudde.com>

2 Introduction

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of m. dudde hochfrequenz - technik.

This report contains the result of tests performed by m. dudde hochfrequenz - technik for the purpose of a type approval. The order for carrying out these tests had been placed by:

Manufacturer

Company name : Siemens AG
Siemens VDO Automotive
Address : Siemensstrasse 12
Postcode : D-93055
City/town : Regensburg
Country : Germany
Telephone : +49 941 790 6699
Telefax : +49 941 790 136699
E-mail : dagmar.kolar@siemens.com
Date of order : 2006-04-22
References : Mrs. Kolar

FCC ID: KR5S122736001

Date of issue: 2006-05-16

3 Product

Samples of the following apparatus were submitted for testing:

| | |
|-------------------------------|---|
| Type of equipment | : Inductive system |
| Trademark | : Siemens VDO |
| Type designation | : S122736001 |
| Hardware version | : S122736001 |
| with | : antennas 5WK4 8774 & antennas 5WK4 8775 |
| Serial number | : --- |
| Software release | : --- |
| Power used | : 12.00 VDC |
| Frequency used | : 125 kHz |
| Generated or used frequencies | : 8.00 MHz / 125 Khz |
| ITU emission class | : 00H0 A1D |
| FCC ID | : KR5S122736001 |

4 Test schedule

Tests were carried out in accordance with the specifications detailed in chapter 7 “Summary“ of this report.

Tests were carried out at:

- m. dudde hochfrequenz - technik, D-51429 Bergisch Gladbach

The test sample was received on:

- 2005-06-10

The tests were carried out in the following period of time:

- 2005-06-13

FCC ID: KR5S122736001

Date of issue: 2006-05-16

5 Product and measurement documentation

For issuing this report the following product documentation was used and the following annexes were created:

| Description: | Date: | Identifications: |
|--|--------------|-------------------------|
| External photographs of the Equipment Under Test (EUT) | 2006-05-05 | Annex no. 1 |
| Internal photographs of the Equipment Under Test (EUT) | 2006-05-05 | Annex no. 2 |
| Occupied bandwidth plot | 2006-05-05 | Annex no. 3 |
| Label sample | 2006-05-15 | Annex no. 4 |
| User Manual | 2006-05-02 | Annex no. 5 |
| Test setup photos | 2006-05-05 | Annex no. 6 |
| Block diagram | 2006-05-02 | Annex no. 7 |
| Schematics | 2006-01-11 | Annex no. 8 |
| Technical description | 2006-05-02 | Annex no. 9 |

The above mentioned documentation will be filed at m. dudde hochfrequenz - technik for a period of 10 years following the issue of this test report.

6 Observations and comments

7 Summary

The product is intended for the use in the following areas of application:
Radio- Noise Emissions from Low- Voltage Electrical and Electronic Equipment
in the frequency range 9 kHz to 40 GHz

The samples were tested according to the following specification:

47 CFR Part 15C – Intentional Radiators, ANSI C63.4 - 1992

FCC ID: KR5S122736001

Date of issue: 2006-05-16

8 Conclusions

Samples of the apparatus were found to **CONFORM WITH** the specifications stated in chapter 7 "Summary" of this report.

In the opinion of m. dudde hochfrequenz - technik, the samples satisfied all applicable requirements relating to the network interface types specified in chapter 7 "Summary".

The results of the type tests as stated in this report are exclusively applicable to the product item as identified in this report. m. dudde hochfrequenz - technik does not accept any responsibility for the results stated in this report, with respect to the properties of product items not involved in these tests.

This report consists of a main module, modules with test results and annexes listed in chapter 5: "Product documentation". All pages have been numbered consecutively and bear the m. dudde hochfrequenz - technik logo, the report number and sub numbers.
The total number of pages in this report is **22**.

Tester:

Date : 2006-05-16


Name : Ralf Trepper

Signature : 

Technical responsibility for area of testing:

Date : 2006-05-16

Name : Manfred Dudde

Signature : 

FCC ID: KR5S122736001


Date of issue: 2006-05-16

9 Operation description

9.1 EUT details

Inductive System, Passive entry, Vehicle Immobilizer

9.2 EUT configuration



FCC ID: KR5S122736001

Date of issue: 2006-05-16

9.3 EUT measurement description

The **S122736001** was tested in a typical fashion. During primary emission tests there had been examined all orthogonal adjustments of the EUT. In the final measurement there was chosen the adjustment in which there had been established before the highest level.

FCC ID: KR5S122736001

Date of issue: 2006-05-16

10.1 Antenna Requirement

10.1.1 Regulation

15.203 An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of Part 15C. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31 (d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

10.1.2 Result

| | | | |
|--------------------------------------|-----|----|-----------------|
| The equipment meets the requirements | yes | no | n.a. |
|--------------------------------------|-----|----|-----------------|

| | | | |
|-----------------------------------|----------------|----|----------|
| Further test results are attached | yes | no | page no: |
|-----------------------------------|----------------|----|----------|

n.a^x see page no. 21

FCC ID: KR5S122736001

Date of issue: 2006-05-16

10.2 Radiated emission

10.2.1 Regulation

Test Requirement: FCC CFR47, Part 15B Test Procedure: ANSI C63.4:1992

15.109(a) Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurements distance (meters) |
|-----------------|-----------------------------------|--------------------------------|
| 30 - 88 | 100 | 3 |
| 88 - 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |

(c) In the emission tables above, the tighter limits applies at the band edges. Section 15.33 and 15.35 which specify the frequency range over which radiated emissions are to be measured and the detector functions and other measurement standards apply.

(f) For a receiver which employs terminals for the connection of an external receiving antenna, the receiver shall be tested to demonstrate compliance with the provisions of this Section with an antenna connected to the antenna terminals unless the antenna conducted power is measured as specified in Section 15.111(a). If a permanently attached receiving antenna is used, the receiver shall be tested to demonstrate compliance with the provisions of this Section.

Test Requirement: FCC CFR47, Part 15C Test Procedure: ANSI C63.4:1992

Section 15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

(b) In the emission table above, the tighter limit applies at the band edges.

FCC ID: KR5S122736001

Date of issue: 2006-05-16

(c) The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission. For intentional radiators which operate under the provisions of other sections within this part and which are required to reduce their unwanted emissions to the limits specified in this table, the limits in this table are based on the frequency of the unwanted emission and not the fundamental frequency. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.

(d) The emission limits shown in the above table are based on measurements employing a CISPR quasi peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

(e) The provisions in §§ 15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

(f) In accordance with Section 15.33(a), in some cases the emissions from an intentional radiator must be measured to beyond the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator because of the incorporation of a digital device. If measurements above the tenth harmonic are so required, the radiated emissions above the tenth harmonic shall comply with the general radiated emission limits applicable to the incorporated digital device, as shown in Section 15.109 and as based on the frequency of the emission being measured, or, except for emissions contained in the restricted frequency bands shown in Section 15.205, the limit on spurious emissions specified for the intentional radiator, whichever is the higher limit. Emissions which must be measured above the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator and which fall within the restricted bands shall comply with the general radiated emission limits in Section 15.109 that are applicable to the incorporated digital device.

10.2.2 Test equipment

| Type | Manufacturer/ Model no. | Serial no. | Last calibration | Next calibration |
|------------------------------------|---|------------|------------------|------------------|
| Receiver (9 kHz –26.5 GHz) | Hewlett Packard Spectrum Analyzer 8593E (171) | 3528U00990 | 2006/03 | 2008/03 |
| Pre-amplifier (100kHz - 1.3GHz) | Hewlett Packard 8447 E (166a) | 1726A00705 | 2006/03 | 2008/03 |
| Magnetic antenna (9.0-30 MHz) | Schwarzbeck FMZB 1516 (23) | --- | 2004/04 | 2008/04 |
| Bilog antenna (30-1000 MHz) | CHASE CBL611A (167) | 1517 | 2004/04 | 2008/04 |
| Horn antenna (0.86-8.5 GHz) | Schwarzbeck BBHA 9120 A (284) | 236 | 1998/01 | 2008/01 |
| | | | | |

FCC ID: KR5S122736001

Date of issue: 2006-05-16

10.2.3 Test procedures

The EUT and this peripheral (when additional equipment exist) are placed on a turn table which is 0.8 m above the ground. The turn table would be allowed to rotate 360 degrees to determine the position of the maximum emission level. The test distance between the EUT and the receiving antenna are 3m. To find the maximum emission, the polarization of the receiving antenna is changed in horizontal and vertical polarization, the position of the EUT was changed in different orthogonal determinations.

ANSI C63.4: 1992 Section 8 “Radiated Emissions Testing”

| Radiated emissions test characteristics | |
|---|---|
| Frequency range | 30 MHz - 4,000 MHz |
| Test distance | 10m, 3 m* |
| Test instrumentation resolution bandwidth | 9 kHz (20 kHz – 30 MHz) |
| | 120 kHz (30 MHz - 1,000 MHz) |
| | 1 MHz (1000 MHz - 12,000 MHz) |
| Receive antenna height | 1 m (20 kHz – 30 MHz) |
| Receive antenna polarization | 0° - 90° (20 kHz – 30 MHz) |
| Receive antenna scan height | 1 m - 4 m (30 MHz - 12,000 MHz) |
| Receive antenna polarization | vertical/horizontal (30 MHz - 12,000 MHz) |

* According to Section 15.31 (f)(1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

FCC ID: KR5S122736001

Date of issue: 2006-05-16

10.2.4 Calculation of field strength Section 15.209 below 30 MHz

The Receiver reading gives not directly the field strength result in (dB μ V/m). The antenna factors of the loop antenna and cable losses must be added to find the correct result.

For frequencies below 30 MHz and for an test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f) (2) the field strength is calculated by adding additionally an extrapolation factor of 40 dB/decade (inverse linear distance for field strength measurements).

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor

Corrected Level = Receiver Level + Correction Factor – Pre-amplifier (with the use of an Pre-amplifier)

Receiver Level : Receiver reading without correction factors

Correction Factor : Loop Antenna factor + cable loss

$$FS = 40.7 - 40 = 0.7 \text{ [dB}\mu\text{V/m]}$$

Level in μ V/m Common Antilogarithm $(0.7/20) = 1.1$

10.2.5 Calculation of field strength Section 15.209 above 30 MHz

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of an Pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-amplifier (with the use of an Pre-amplifier)

Receiver Level : Receiver reading without correction factors

Correction Factor : Antenna factor + cable loss

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f)(1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

FCC ID: KR5S122736001

Date of issue: 2006-05-16

10.2.6 Calculation of the field strength

The field strength is calculated by the following calculation:

Corrected Level = Receiver Level + Correction Factor (without the use of an Pre-amplifier)

Corrected Level = Receiver Level + Correction Factor – Pre-amplifier (with the use of an Pre-amplifier)

Receiver Level : Receiver reading without correction factors

Correction Factor : Antenna factor + cable loss

For example:

The receiver reading is 32.7 dB μ V. The antenna factor for the measured frequency is +2.5 dB(1/m) and the cable factor for the measured frequency is 0.71 dB, giving a field strength of 35.91dB μ V/m.

The 35.91dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

Level in μ V/m = Common Antilogarithm (35.91/20) = 39.8

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f)(1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements).

10.2.7 Calculation of Average Correction Factor

The average correction factor is computed by analyzing the "worst case" on time in any 100msec time period and using the formula: Corrections Factor + 20*Log (worst case on time/100msec) Analysis of the remote transmitter worst case on time in any 100msec time period is an on time of 50msec, there for the correction factor is 20*Log(50/100) = - 6 dB. The maximum correction factor to be applied is 20 dB per section 15.35 of the FCC rules.

FCC ID: KR5S122736001

Date of issue: 2006-05-16

| TRANSMITTER SPURIOUS RADIATION BELOW 30 MHz (Section 15.209) | | | | | | | | | |
|---|-----------------------------------|---------------------------|-----------------|----------------------|------------------------------|------------------------|--------------|---------------|--|
| f (MHz) | Bandwidth (kHz), Type of detector | Noted receiver level dBµV | Test distance m | Correction factor dB | Distance extrapol. factor dB | Level corrected dBµV/m | Limit dBµV/m | Margin dBµV/m | Polarisation EUT / antenna orientation |
| 0.1200 | QPK/0.2kHz | < 4.0 | 10 | 20.2 | -59.1 | -34.90 | AV26.0 @ 300 | 80.90 | V, H/0-360° |
| 0.5000 | QPK/0.2kHz | < 4.0 | 10 | 20.2 | -19.1 | 5.10 | AV33.6 @ 30 | 28.5 | V, H/0-360° |
| 1.5000 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | 5.10 | AV24.1 @ 30 | 19.00 | V, H/0-360° |
| 3.0000 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | 5.10 | AV29.5 @ 30 | 24.4 | V, H/0-360° |
| 5.0000 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | 5.10 | AV29.5 @ 30 | 24.4 | V, H/0-360° |
| 8.0000 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | 5.10 | AV29.5 @ 30 | 24.4 | V, H/0-360° |
| 10.0000 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | 5.10 | AV29.5 @ 30 | 24.4 | V, H/0-360° |
| 20.0000 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | 5.10 | AV29.5 @ 30 | 24.4 | V, H/0-360° |
| 30.0000 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | 5.10 | AV29.5 @ 30 | 24.4 | V, H/0-360° |
| No emissions detected | | | | | | | | | |
| Measurement uncertainty | | | 4 dB | | | | | | |

Remark: *¹ Noise level of the measuring instrument ≤ 4.0dBµV @ 10m distance (0.009 MHz –30 MHz)
 Remark: * Peak Limit according to Section 15.35 (b).

| | | | |
|--------------------------------------|------------|-----------|-------------|
| The equipment meets the requirements | yes | no | n.a. |
|--------------------------------------|------------|-----------|-------------|

| | | | |
|-----------------------------------|------------|-----------|----------|
| Further test results are attached | yes | no | page no: |
|-----------------------------------|------------|-----------|----------|

n.a^x see page no. 21

FCC ID: KR5S122736001

Date of issue: 2006-05-16

TRANSMITTER SPURIOUS RADIATION ABOVE 30 MHz (Section 15.209)

| f (MHz) | Bandwidth (kHz)/Type of detector | Noted receiver level dBμV | Test distance m | Correction factor dB | Distance extrapol. factor dB | AV Correction factor dB | Level corrected dBμV/m | Limit dBμV/m | Margin dBμV/m | Polaris. EUT / antenna | Antenna height cm |
|------------------------------|----------------------------------|---------------------------|-----------------|---------------------------------|------------------------------|-------------------------|------------------------|--------------|---------------|------------------------|-------------------|
| 30.0000 | 100, QPK | ≤ 3.5 | 3 | -2.60 | 0 | 0 | 0.90 | 40.00 | 39.10 | H,V/H,V | 100-400 |
| 88.0000 | 100, QPK | ≤ 3.5 | 3 | -10.80 | 0 | 0 | -7.30 | 40.00 | 47.30 | H,V/H,V | 100-400 |
| 216.0000 | 100, QPK | ≤ 3.5 | 3 | -10.30 | 0 | 0 | -6.80 | 43.50 | 50.30 | H,V/H,V | 100-400 |
| 960.0000 | 100, QPK | ≤ 3.5 | 3 | 8.50 | 0 | 0 | 12.00 | 43.50 | 31.50 | H,V/H,V | 100-400 |
| 1700.0000 | 1000, AV | ≤ 4.5 | 3 | 3.80 | 0 | 0 | 8.30 | 54.00 | 45.70 | H,V/H,V | 100-400 |
| 2250.0000 | 1000, AV | ≤ 10 | 3 | 8.00 | 0 | 0 | 18.00 | 54.00 | 36.00 | H,V/H,V | 100-400 |
| 4000.0000 | 1000, AV | ≤ 10 | 3 | 8.40* ⁶ | 0 | 0 | 18.40 | 54.00 | 35.60 | H,V/H,V | 100-400 |
| 5000.0000 | 1000, AV | ≤ 10 | 3 | 9.10* ⁶ | 0 | 0 | 19.40 | 54.00 | 34.60 | H,V/H,V | 100-400 |
| 7500.0000 | 1000, AV | ≤ 14 | 3 | 12.9* ⁶ ₀ | 0 | 0 | 26.90 | 54.00 | 27.10 | H,V/H,V | 100-400 |
| 8300.0000 | 1000, AV | ≤ 14 | 3 | 14.80* ⁶ | 0 | 0 | 28.80 | 54.00 | 25.20 | H,V/H,V | 100-400 |
| 9400.0000 | 1000, AV | ≤ 14 | 3 | 16.00* ⁶ | 0 | 0 | 30.00 | 54.00 | 24.00 | H,V/H,V | 100-400 |
| 11000.0000 | 1000, AV | ≤ 14 | 3 | 18.25* ⁶ | 0 | 0 | 32.25 | 54.00 | 21.75 | H,V/H,V | 100-400 |
| No emissions detected | | | | | | | | | | | |
| Measurement uncertainty | | | 4 dB | | | | | | | | |

* Bandwidth = the measuring receiver bandwidth

- Remark: *¹ noise floor noise level of the measuring instrument ≤ 3.5dBμV @ 3m distance (30 – 1,000 MHz)
- Remark: *² noise floor noise level of the measuring instrument ≤ 4.5 dBμV @ 3m distance (1,000 – 2,000 MHz)
- Remark: *³ noise floor noise level of the measuring instrument ≤ 10 dBμV @ 3m distance (2,000 – 5,500 MHz)
- Remark: *⁴ noise floor noise level of the measuring instrument ≤ 14 dBμV @ 3m distance (5,500 – 14,500 MHz)
- Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz
- Remark: *⁶ for using a pre-amplifier in the range between 4.0 GHz and 18.0 GHz

| | | | |
|--------------------------------------|------------|---------------|-----------------|
| The equipment meets the requirements | yes | no | n.a. |
|--------------------------------------|------------|---------------|-----------------|

| | | | |
|-----------------------------------|----------------|-----------|----------|
| Further test results are attached | yes | no | page no: |
|-----------------------------------|----------------|-----------|----------|

n.a^x see page no. 21

FCC ID: KR5S122736001

Date of issue: 2006-05-16

antenna 5WK4 8774

| INTENTIONAL RADIATOR SPURIOUS RADIATION (Section 15.209(a)) | | | | | | | | | |
|---|-----------------------------------|---------------------------|-----------------|----------------------|------------------------------|------------------------|--------------|---------------|--|
| f (MHz) | Bandwidth (kHz), Type of detector | Noted receiver level dBμV | Test distance m | Correction factor dB | Distance extrapol. factor dB | Level corrected dBμV/m | Limit dBμV/m | Margin dBμV/m | Polarisation EUT / antenna orientation |
| 0.125 | QPK/0.2kHz | 49.7 | 10 | 20.2 | -59.1 | 10.8 | AV19.2 @ 300 | 8.4 | V / 90° |
| 0.250 | QPK/0.2kHz | < 4.0 | 10 | 20.2 | -59.1 | < -34.9 | AV9.6 @ 300 | 44.5 | V, H/0-360° |
| 0.375 | QPK/0.2kHz | < 4.0 | 10 | 20.2 | -59.1 | < -34.9 | AV6.4 @ 300 | 41.3 | V, H/0-360° |
| 0.500 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV48.0 @ 30 | 42.9 | V, H/0-360° |
| 0.750 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV38.4 @ 30 | 33.3 | V, H/0-360° |
| 1.000 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV32.0 @ 30 | 26.9 | V, H/0-360° |
| 1.250 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV27.4 @ 30 | 22.3 | V, H/0-360° |
| 1.375 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV24.0 @ 30 | 18.9 | V, H/0-360° |
| 1.500 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV21.3 @ 30 | 16.2 | V, H/0-360° |
| 1.750 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV19.2 @ 30 | 14.1 | V, H/0-360° |
| Measurement uncertainty | | | 4 dB | | | | | | |

- Remark: *¹ noise floor noise level of the measuring instrument ≤ 4.0dBμV @ 10m distance (0.009 – 30 MHz)
 Remark: *² noise floor noise level of the measuring instrument ≤ 6.5dBμV @ 3m distance (30 – 1,000 MHz)
 Remark: *³ noise floor noise level of the measuring instrument ≤ 10 dBμV @ 3m distance (1,000 – 2,000 MHz)
 Remark: *⁴ noise floor noise level of the measuring instrument ≤ 17 dBμV @ 3m distance (2,000 – 5,500 MHz)
 Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz

| | | | |
|--------------------------------------|-----|----|------|
| The equipment meets the requirements | yes | no | n.a. |
|--------------------------------------|-----|----|------|

| | | | |
|-----------------------------------|-----|----|----------|
| Further test results are attached | yes | no | page no: |
|-----------------------------------|-----|----|----------|

n.a^x see page no. 21

FCC ID: KR5S122736001

Date of issue: 2006-05-16

antenna 5WK4 8775

| INTENTIONAL RADIATOR SPURIOUS RADIATION (Section 15.209(a)) | | | | | | | | | |
|---|-----------------------------------|---------------------------------|-----------------|----------------------|------------------------------|------------------------------|--------------------|---------------------|--|
| f (MHz) | Bandwidth (kHz), Type of detector | Noted receiver level dB μ V | Test distance m | Correction factor dB | Distance extrapol. factor dB | Level corrected dB μ V/m | Limit dB μ V/m | Margin dB μ V/m | Polarisation EUT / antenna orientation |
| 0.125 | QPK/0.2kHz | 52.3 | 10 | 20.2 | -59.1 | 13.4 | AV19.2 @ 300 | 5.8 | V / 90° |
| 0.250 | QPK/0.2kHz | < 4.0 | 10 | 20.2 | -59.1 | < -34.9 | AV9.6 @ 300 | 44.5 | V, H/0-360° |
| 0.375 | QPK/0.2kHz | < 4.0 | 10 | 20.2 | -59.1 | < -34.9 | AV6.4 @ 300 | 41.3 | V, H/0-360° |
| 0.500 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV48.0 @ 30 | 42.9 | V, H/0-360° |
| 0.750 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV38.4 @ 30 | 33.3 | V, H/0-360° |
| 1.000 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV32.0 @ 30 | 26.9 | V, H/0-360° |
| 1.250 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV27.4 @ 30 | 22.3 | V, H/0-360° |
| 1.375 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV24.0 @ 30 | 18.9 | V, H/0-360° |
| 1.500 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV21.3 @ 30 | 16.2 | V, H/0-360° |
| 1.750 | QPK/9kHz | < 4.0 | 10 | 20.2 | -19.1 | < 5.1 | AV19.2 @ 30 | 14.1 | V, H/0-360° |
| Measurement uncertainty | | | 4 dB | | | | | | |

- Remark: *¹ noise floor noise level of the measuring instrument ≤ 4.0 dB μ V @ 10m distance (0.009 – 30 MHz)
 Remark: *² noise floor noise level of the measuring instrument ≤ 6.5 dB μ V @ 3m distance (30 – 1,000 MHz)
 Remark: *³ noise floor noise level of the measuring instrument ≤ 10 dB μ V @ 3m distance (1,000 – 2,000 MHz)
 Remark: *⁴ noise floor noise level of the measuring instrument ≤ 17 dB μ V @ 3m distance (2,000 – 5,500 MHz)
 Remark: *⁵ for using a pre-amplifier in the range between 100 kHz and 1,000 MHz

| | | | |
|--------------------------------------|-----|----|------|
| The equipment meets the requirements | yes | no | n.a. |
|--------------------------------------|-----|----|------|

| | | | |
|-----------------------------------|-----|----|----------|
| Further test results are attached | yes | no | page no: |
|-----------------------------------|-----|----|----------|

n.a^x see page no. 21

FCC ID: KR5S122736001

Date of issue: 2006-05-16

11 Additional information to this test report

Remarks

- | | |
|-------------------|---|
| n.a. ¹ | not applicable, because antenna is part of the PCB |
| n.a. ² | not applicable, because EUT is directly battery powered |

FCC ID: KR5S122736001

Date of issue: 2006-05-16

End of test report