

EMC EMISSION -- TEST REPORT

Test report file no. : T13826-1-10KG Date : May 03, 1999
of issue

Model / Type No. : VENUS

Kind of product : Immobilizer system

Applicant : Siemens AG

Manufacturer : Siemens AG

Licence holder : Siemens AG

Address : Wernerwerkstraße 2
D-93049 Regensburg

Test result accrdg.
to the regulation(s)
at page 3

: **Positive** **Negative**

Mikes Product Service is a subcontractor to TÜV Product Service, GmbH according to the principles outlined in ISO/IEC Guide 25 and EN 45001.

Mikes Product Service reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. Mikes Product Service shall have no liability for any deductions, inferences or generalizations drawn by the client or others from Mikes Product Service issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval. This report shall not be used by the client to claim product endorsement by NVLAP or any agency of the US government.

Mikes Product Service and its professional staff hold government
and professional organization certifications are members of
DAR, DaTech, KBA, FCC, VCCI, MoC, AUSTEL

This testreport with appendix consists of 62 pages.
The testresult only responds to the tested sample. It is not allowed to copy
this report even partly without the allowance of the test laboratory.

D I R E C T O R Y - E M I S S I O N S

		Page(s)
A) Documentation		
	Test report	<u>1 - 17</u>
	Directory	<u>2</u>
	Test Regulations	<u>3</u>
	Summary	<u>11</u>
	Test-setups (Photos)	<u>12-17</u>
	Test-setup (drawing)	<u>Appendix A2</u>
B) Test data		
	Conducted emissions 10/150 kHz - 30 MHz	<u>5; 9</u>
	Radiated emissions 10 kHz - 30 MHz	<u>5; 9</u>
	Radiated emissions 30 MHz - 1000 MHz	<u>6; 9</u>
	Interference power 30 MHz - 300 MHz	<u>6; 10</u>
	Equivalent Radiated emissions 1 GHz - 18 GHz	<u>7; 10</u>
C) Appendix A		
	Test Data Sheets and Test Setup Drawing(s)	<u>A1 – A21</u>
D) Appendix B		
	Constructional Data Form	<u>B1 – B4</u>
E) Appendix C		
	Measurement Protocol for FCC, VCCI and/or AUSTEL	<u>C1 - C3</u>
F) Appendix D		
	Photos of the Product	<u>D1 – D17</u>
	Photos of the untested variants	<u>--</u>

TEST REGULATIONS

The tests were performed according to following regulations :

- o - EN 50081-1 / 2.1991
- o - EN 50081-2 / 7.1993

- o - EN 55011 / 3.1991

- o - Group 1
- o - class A

- o - Group 2
- o - class B

- o - EN 55014 / 4.1993

- o - Household appliances and similar
- o - tools
- o - Semiconductor devices

- o - EN 55014 / A2:1990

- o - EN 55104 / 5.1995

Category:)

- o - EN 55015 / A1:1990

- o - EN 55015 / 12.1993

- o - EN 55022 / 5.1995

- o - class A

- o - class B

- o - prEN 55103-1 / 3.1995

- o - prEN 50121-3-2 / 3.1995

- o - EN 60601-1-2 / 4.1994

- o - VCCI

- o - class A

- o - class B

- - FCC Part 15 Subpart C Section 15.209

- o - CISPR

TEST CONDITIONS

The measurement of the conducted emissions (interference voltage) were performed in a shielded room.

- Test not applicable

Test location :

- Shielded room no. 1
- Shielded room no. 2
- Shielded room no. 3
- Shielded room no. 4
- Shielded room no. 5
- Shielded room no. 6
- Shielded room no. 7
- Anechoic chamber
- Full compact chamber

Test equipment used :

Model Number	Manufacturer	Description	Serial Number	Cal Date
--------------	--------------	-------------	---------------	----------

All used test-instruments as well as the Test-accessories are calibrated regularly.

The measurement of the radiated emissions (magnetic field) in the frequency range from 9 kHz to 30 MHz were performed

- Test not applicable

- in a shielded room
- at a non - reflecting open-site and
- in a testdistance of 3 meters.
- in a testdistance of 10 meters.
- in a testdistance of 30 meters.

Test equipment used :

Model Number	Manufacturer	Description	Serial Number	Cal Date
ESHS 30	Rohde & Schwarz	Test Receiver	828.765/003	17.3.1999
FMZB 1516	Rohde & Schwarz	Magnetic field antenna	335.4711.52	17.11.1998

The measurement of the radiated emissions (electric field) in the frequency range of 30 MHz-1000 MHz were performed in horizontal and vertical antenna polarization at a non-reflecting open-site and a test distance of:

- Test not applicable

- Open-site 1
- Open-site 2
- 3 meters
- 10 meters
- 30 meters

Test equipment used :

Model Number	Manufacturer	Description	Serial Number	Cal Date
ESVP	Rohde & Schwarz	Test Receiver	880.726/005	5.12.1998
BBA 9106	Schwarzbeck	Antenna	no Number	6.08.1998
UHALP 9107	Schwarzbeck	Antenna	no Number	7.12.1998

All used test-instruments as well as the Test-accessories are calibrated regularly.

The measurement of the interference power were performed in a shielded room by using the absorbing clamp on the mains and interface cables in the frequency range 30 MHz - 300 MHz.

- Test not applicable

Testlocation :

- Anechoic chamber
- Full compact chamber

Test equipment used :

Model Number	Manufacturer	Description	Serial Number	Cal Date
--------------	--------------	-------------	---------------	----------

All used test-instruments as well as the Test-accessories are calibrated regularly.

The measurement of the equivalent radiated emissions in the frequency range 1 GHz - 18 GHz were performed in horizontal and vertical antenna polarization at a non-reflecting test-site and a test distance of:

● - Test not applicable

Testlocation :

- - Open-site 1
- - Open-site 2
- - Anechoic chamber
- - Full compact chamber

- - 1 meters
- - 3 meters
- - 10 meters

Test equipment used :

Model Number	Manufacturer	Description	Serial Number	Cal Date
--------------	--------------	-------------	---------------	----------

All used test-instruments as well as the Test-accessories are calibrated regularly.

EQUIPMENT UNDER TEST

Operation - mode of the EUT.:

The equipment under test was operated during the measurement under following conditions:

- - Standby
- - Testprogram (H - Pattern)
- - Testprogram (color bar)
- - Testprogram (customer specific)
- - Permanent Transmit _____
- - _____

Configuration of the equipment under test:

Following peripheral devices and interface cables were connected during the measurement:

- - Vehicle _____ Type :Mercedes _____
- - _____ Type : _____
- - _____ Type : _____
- - _____ Type : _____
- - _____ Type : _____
- - unshielded power cable
- - unshielded cables
- - shielded cables for connection to the notebook
- - customer specific cables
- - _____
- - _____

TEST RESULT

Conducted emissions 10/150 kHz - 30 MHz

- Test not applicable

The requirements are - MET - NOT MET

Min. limit margin _____ dB at _____ MHz

Max. limit exceeding _____ dB at _____ MHz

Remarks: EUT is connected to the DC power supply in the car. There are.
no requirements for conducted emissions on DC input port for car
use.

Radiated emissions (magnetic field) 10 kHz - 30 MHz

- Test not applicable

The requirements are - MET - NOT MET

Min. limit margin >10 dB at 0.1249 MHz

Max. limit exceeding _____ dB at _____ MHz

Remarks: The limits are met. This was a peak and QP measurement. The
reading in average was 5 dB less than peak.

Radiated emissions (electric field) 30 MHz - 1000 MHz

- Test not applicable

The requirements are - MET - NOT MET

Min. limit margin 5.8 dB at 30 MHz

Max. limit exceeding _____ dB at _____ MHz

Remarks: The limits are met.

TEST RESULT

Interference power at the mains and interface cables 30 MHz - 300 MHz

● - Test not applicable

The requirements are	O - MET		O - NOT MET
Min. limit margin	_____	dB	at _____ MHz
Max. limit exceeding	_____	dB	at _____ MHz

Remarks: _____

Equivalent radiated emissions 1 GHz - 18 GHz

● - Test not applicable

The requirements are	O - MET		O - NOT MET
Min. limit margin	_____	dB	at _____ GHz
Max. limit exceeding	_____	dB	at _____ GHz

Remarks: Because of the used frequencies there are no requirements for
radiated emissions.

Test-Setup:
Magnetic Field 9 kHz - 30 MHz

Door Antennas:



Test-Setup:
Magnetic Field 9 kHz - 30 MHz

Bumper Antenna:



FCC ID: KR5VENUS



Test-Setup:
Radiated emission 30 MHz - 1000 MHz

Front View:



Test-Setup:
Radiated emission 30 MHz - 1000 MHz

Front View:



Test-Setup:
Radiated emission 30 MHz - 1000 MHz

Rear View:



Test-Setup:

Radiated emission 30 MHz - 1000 MHz

Rear View:

