

TEST REPORT FOR CERTIFICATION
On Behalf of
Chungear Industrial Co., Ltd.

Fan-Light Remote Controller (Transmitter)

Model : JY622CF

FCC ID : KUJ9305

Prepared for : Chungear Industrial Co., Ltd.
106 Kanho Rd., Taichung, Taiwan, R.O.C.

Prepared by : Audix Corporation
Technical Division EMC Department
No. 53-11, Tin-Fu Tsun, Lin-Kou Hsiang,
Taipei County 24443, Taiwan, R.O.C.

Tel : (02) 2609-9301, 2609-2133
Fax : (02) 2609-9303

File Number : EM930767
Report Number : EM-F930137
Date of Test : Jul. 07 ~ Sep.15, 2004
Date of Report : Jul. 22, 2004

TABLE OF CONTENTS

Description	Page
TEST REPORT CERTIFICATION	3
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT)	4
1.2. Description of Test Facility	5
1.3. Measurement Uncertainty	5
2. CONDUCTED EMISSION MEASUREMENT	6
3. RADIATED EMISSION MEASUREMENT	7
3.1. Test Equipment	7
3.2. Test Setup	7
3.3. Radiation Limit (§15.209 & 15.231)	8
3.4. EUT’s Configuration during Compliance Measurement	8
3.5. Operating Condition of EUT	9
3.6. Test Procedure	9
3.7. Radiated Emission Noise Measurement Results	10
4. EMISSION BANDWIDTH MEASUREMENT	19
4.1. Test Equipment	19
4.2. Block Diagram of Test Setup	19
4.3. Specification Limits (§15.231-(c))	19
4.4. EUT’s Configuration during Compliance Measurement	19
4.5. Emission Bandwidth Measurement Results	19
5. PERIODIC OPERATED MEASUREMENT	21
5.1. Test Equipment	21
5.2. Block Diagram of Test Setup	21
5.3. Specification Limits [§15.231-(a)-(1)]	21
5.4. EUT’s Configuration during Compliance Measurement	21
5.5. Periodic Operated Measurement Results	21
6. DEVIATION TO TEST SPECIFICATIONS	23
7. PHOTOGRAPHS	24
7.1. Photos of Radiated Measurement at Semi-Anechoic Chamber (30~1000MHz)	24
7.2. Photos of Radiated Measurement at Semi-Anechoic Chamber (Above 1GHz)	25
7.3. Photos of Emission Bandwidth Measurement	27
7.4. Photos of Periodic Operated Measurement	27

TEST REPORT CERTIFICATION

Applicant : Chungear Industrial Co., Ltd.
Manufacturer : Satellite Electronic (Zhongshan) Ltd.
EUT Description : Fan-Light Remote Controller (Transmitter)
FCC ID : KUJ9305
(A) MODEL NO. : JY622CF
(B) SERIAL NO. : N/A
(C) POWER SUPPLY : DC 6V

Measurement Procedure Used:

FCC RULES AND REGULATIONS PART 15 SUBPART C, APR. 2004
AND ANSI C63.4-2001
(FCC CFR 47 Part 15C, §15.207, §15.209 and §15.231)

The device described above was tested by Audix Corporation to determine the maximum emission levels emanating from the device. The maximum emission levels were compared to the FCC Part 15 subpart C limits both radiated and conducted emissions.

The measurement results are contained in this test report and Audix Corporation is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliant with the FCC official limits.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Corporation.

Date of Test : Jul. 07 ~ Sep.15, 2004

Prepared by : Nita Lee Sep. 20, 2004
(Nita Lee/Assistant Administrator)

Test Engineer : Ben Cheng Sep. 20, 2004
(Ben Cheng/Section Manager)

Approve & Authorized Signer : Leon Liu Sep. 20 2004
(Leon Liu/Senior Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Description	:	Fan-Light Remote Controller (Transmitter)
Model Number	:	JY622CF
FCC ID	:	KUJ9305
Applicant	:	Chungear Industrial Co., Ltd. 160 Kanho Rd., Taichung, Taiwan, R.O.C.
Manufacturer	:	Satellite Electronic (Zhongshan) Ltd. No. 15 Zhongshan Troch Hi-Tech Industrial Development Zone, Zhongshan City, Guangdong Province 528437 China.
Fundamental Frequency	:	304.3MHz
Power Supply	:	DC 6V
Date of Receipt of Sample	:	Jun. 29, 2004
Date of Test	:	Jul. 07 ~ Sep.15, 2004

- * Fan/Light Remote Controller -Receiver
 (1)Model No.: JY199, FCC by DoC
 (2)Model No.: JY326B, FCC by DoC

Remark:

Antenna requirement: This EUT's transmitter antenna is design in soldered to a printed circuit board, comply with §15.203 and inform to user that any change and modify is prohibited.

1.2. Description of Test Facility

Name of Firm : Audix Corporation
 Technical Division EMC Department
 No. 53-11, Tin-Fu Tsun, Lin-Kou Hsiang,
 Taipei County 24443, Taiwan, R.O.C.

Test Location & Facility (AC) : **Semi-Anechoic Chamber**
 No. 53-11, Tin-Fu Tsun, Lin-Kou Hsiang,
 Taipei County 24443, Taiwan, R.O.C.

May. 16, 2003 Re-File on
 Federal Communication Commission
 Registration Number: 90993

NVLAP Lab. Code : 200077-0
 (NVLAP is a NATA accredited body under Mutual Recognition Agreement)

1.3. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty (dB)
Conduction Test	150kHz~30MHz	± 1.73dB
Radiation Test (Distance: 3m)	30MHz~300MHz	± 2.91dB
	300MHz~1000MHz	± 2.94dB

Remark : Uncertainty = $ku_c(y)$

2. CONDUCTED EMISSION MEASUREMENT

【The EUT only employs battery power for operation, no conductive emissions limits are required according to FCC Part 15 Section §15.207】

3. RADIATED EMISSION MEASUREMENT

3.1. Test Equipment

The following test equipment was used during the radiated emission tests :

3.1.1. For Frequency 30MHz~1000MHz (at Semi-Anechoic Chamber)

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Spectrum Analyzer	HP	8593EM	3826A00248	Sep. 24, 03'	Sep. 23, 04'
2.	Test Receiver	R&S	ESCS30	100265	Sep. 22, 03'	Sep. 21, 04'
3.	Pre-Amplifier	HP	8447D	2944A06305	Mar. 18, 04'	Mar. 17, 05'
4.	Broadband Antenna	Schwarzbeck	BBA 9106	A3L	Feb. 21, 04'	Feb. 20, 05'
5.	Broadband Antenna	Schwarzbeck	UHALP 9108-A	0138	Feb. 21, 04'	Feb. 20, 05'

3.1.2. For Frequency above 1GHz (at Semi-Anechoic Chamber)

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Spectrum Analyzer	HP	8593EM	3826A00248	Sep. 24, 03'	Sep. 23, 04'
2.	Amplifier	HP	8449B	3008A00529	Jan. 29, 04'	Jan. 28, 05'
3.	Horn Antenna	EMCO	3115	9112-3775	May 05, 04'	May 04, 05'


3.2. Test Setup

3.2.1. Block Diagram of connection between EUT and simulators

**FAN-LIGHT REMOTE CONTROLLER (TRANSMITTER)
(EUT)**

3.2.2. Semi-Anechoic Chamber (3m) Setup Diagram

ANTENNA TOWER



3.3.Radiation Limit (§15.209 & 15.231)

3.3.1.Spurious Emission Limit (§15.209)

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMITS	
		μV/m	dBμV/m
30 - 88	3	100	40.00
88 - 216	3	150	43.50
216 - 960	3	200	46.00
Above 960	3	500	54.00

- Remarks :
- (1) Emission level (dBμV/m) = 20 log Emission level (μV/m)
 - (2) The tighter limit applies at the edge between two frequency bands.
 - (3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3.3.2.Fundamental Frequency Emission Limit (§15.231)

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMITS	
		μV/m	dBμV/m
Fundamental Frequency	3	5400.0	74.94 (Average)

- Remarks :
- (1) Emission level (dBμV/m) = 20 log Emission level (μV/m)
 - (2) The tighter limit applies at the edge between two frequency bands.
 - (3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
 - (4) Where limit of Fundamental Freq. is calculated by: $41.6667 \times 304 - 7083.3333 = 5400.0 \mu\text{V/m} = 74.94 \text{dB}\mu\text{V/m}$
 - (5) The limits in this table are based on CFR 47 Part 15.231(b).

3.4.EUT’s Configuration during Compliance Measurement

The following equipment were installed on radiated measurement to meet the commission requirement and operating in a manner which tended to maximize its emission characteristics in a normal application.

3.4.1.Fan-Light Remote Controller (Transmitter) (EUT)

Model Number : JY622CF
 Serial Number : N/A
 Manufacturer : Satellite Electronic (Zhongshan) Ltd.
 Fundamental Frequency : 304.3MHz

3.5. Operating Condition of EUT

- 3.5.1. Set up the EUT and simulator as shown on 3.2.
- 3.5.2. Turned on the power of all equipment.
- 3.5.3. The EUT (Fan-Light Remote Controller (Transmitter)) emitted the fundamental frequency with data code.
- 3.5.4. The EUT worked on maximum transmitting status (high & Light on) during all testing.
- 3.5.5. The above procedures from 3.5.3 to 3.5.4 were repeated.

3.6. Test Procedure

The EUT and its simulators were placed on a turn table which was 0.8 meter above the ground. The turn table rotated 360 degrees to determine the position of the maximum emission level. EUT was set to 3 meters away from the receiving antenna which was mounted on an antenna tower. The antenna moved up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna such as calibrated biconical and log-periodical antenna or horn antenna were used as a receiving antenna. Both horizontal and vertical polarization of the antenna were set on measurement. In order to find the maximum emission, all of the interface cables were manipulated according to FCC ANSI C63.4-2001 regulation.

The bandwidth of test receiver was set at 120kHz for frequencies below 1GHz and resolution bandwidth of spectrum analyzer was set at 1MHz for frequencies above 1GHz.

EUT with three kinds of positions (Stand、Side、Lying) was tested during radiated measurement and all the test results are listed in section 3.7.

3.7.Radiated Emission Noise Measurement Results

PASSED. All emissions not reported below are too low against the prescribed limits.

Date of Test :	<u>Sep. 15, 2004</u>	Temperature :	<u>24°C</u>
EUT :	<u>Fan-Light Remote Controller (Transmitter)</u>	Humidity :	<u>65%</u>
Test Position :	<u>EUT on Stand</u>		

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Horizontal dBμV	Emission Level Horizontal dBμV/m	Limits dBμV/m	Margin dB
Fundamental Freq. (Quasi-Peak Value)						
304.300	14.73	3.90	54.05	72.68	74.94	2.26
Spurious / Harmonic Freq. (Quasi-Peak Value)						
59.430	13.16	1.60	4.75	19.51	40.00	20.49
61.590	12.28	1.60	5.74	19.63	40.00	20.37
65.640	11.78	1.70	5.21	18.68	40.00	21.32
91.830	16.08	2.00	4.70	22.77	43.50	20.73
101.280	17.17	2.10	3.51	22.78	43.50	20.72
608.610	21.41	6.30	16.11	43.82	46.00	2.18
912.900	24.98	7.40	8.41	40.79	46.00	5.21


Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Vertical dBμV	Emission Level Vertical dBμV/m	Limits dBμV/m	Margin dB
Fundamental Freq. (Quasi-Peak Value)						
304.300	15.17	3.90	52.36	71.43	74.94	3.51
Spurious / Harmonic Freq. (Quasi-Peak Value)						
54.840	14.36	1.50	1.26	17.12	40.00	22.88
92.100	16.61	2.00	0.14	18.75	43.50	24.75
103.440	17.80	2.10	1.22	21.12	43.50	22.38
123.690	17.84	2.30	3.46	23.60	43.50	19.90
147.180	21.84	2.58	0.18	24.60	43.50	18.90
608.610	21.64	6.20	14.82	42.66	46.00	3.34
912.900	25.69	7.40	10.02	43.11	46.00	2.89

- Remarks :
1. Emission Level = Antenna Factor + Cable Loss + Meter Reading.
 2. Measurement was up to 10th harmonics (~5.5GHz), but the emission levels were too low against the official limit and not report.



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw

Data: 5 File: C:\WINDOWS\Desktop\767data\JY622CFE.emi (14) Date: 2004-07-09 Time: 22:19:06




Trace: (Discrete)

Site no. : A/C Chamber Data no. : 5
 Ant. / Dis. : 3115 3m Ant. pol. : HORIZONTAL
 Limit : FCC CLASS-B(1G-PK)
 Env. / Ins. : 8593EM 25°C/68% Engineer : henning
 EUT : Fan-Light Remote Controller M/N:JY622CF
 Power Rating : DC 6V
 Test Mode : TX---stand



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw

Data: 6 File: C:\WINDOWS\Desktop\767data\JY622CFE.emi (14) Date: 2004-07-09 Time: 22:20:47




Trace: (Discrete)

Site no. : A/C Chamber Data no. : 6
 Ant. / Dis. : 3115 3m Ant. pol. : VERTICAL
 Limit : FCC CLASS-B(1G-PK)
 Env. / Ins. : 8593EM 25°C/68% Engineer : henning
 EUT : Fan-Light Remote Controller M/N:JY622CF
 Power Rating : DC 6V
 Test Mode : TX---stand




AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)
 Site no. : A/C Chamber Data no. : 8
 Ant. / Dis. : 3115 3m Ant. pol. : HORIZONTAL
 Limit : FCC CLASS-B(1G-PK)
 Env. / Ins. : 8593EM 25°C/68% Engineer : henning
 EUT : Fan-Light Remote Controller M/N:JY622CF
 Power Rating : DC 6V
 Test Mode : TX---stand



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)
 Site no. : A/C Chamber Data no. : 7
 Ant. / Dis. : 3115 3m Ant. pol. : VERTICAL
 Limit : FCC CLASS-B(1G-PK)
 Env. / Ins. : 8593EM 25°C/68% Engineer : henning
 EUT : Fan-Light Remote Controller M/N:JY622CF
 Power Rating : DC 6V
 Test Mode : TX---stand

Date of Test : Sep. 15, 2004 Temperature : 24°C

EUT : Fan-Light Remote Controller Humidity : 65%
 (Transmitter)

Test Position : EUT on Side

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Horizontal dBμV	Emission Level Horizontal dBμV/m	Limits dBμV/m	Margin dB

Fundamental Freq. (Quasi-Peak Value)						
304.300	14.87	3.90	52.70	71.47	74.94	3.47
Spurious / Harmonic Freq. (Quasi-Peak Value)						
56.190	14.11	1.60	1.49	17.20	40.00	22.80
91.560	15.90	2.00	3.21	21.11	43.50	22.39
118.830	19.02	2.30	1.84	23.16	43.50	20.34
129.090	19.66	2.40	1.41	23.46	43.50	20.04
193.890	21.70	3.00	1.27	25.97	43.50	17.53
297.030	26.59	4.00	1.02	31.62	46.00	14.38
608.610	21.41	6.30	15.77	43.48	46.00	2.52
912.900	24.98	7.40	9.95	42.33	46.00	3.67


Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Vertical dBμV	Emission Level Vertical dBμV/m	Limits dBμV/m	Margin dB

Fundamental Freq. (Quasi-Peak Value)						
304.300	15.17	3.90	50.67	69.74	74.94	5.20
Spurious / Harmonic Freq. (Quasi-Peak Value)						
60.240	13.44	1.60	1.65	16.68	40.00	23.32
130.440	18.82	2.40	1.13	22.34	43.50	21.16
154.740	21.12	2.63	0.67	24.42	43.50	19.08
233.040	24.76	3.30	-0.16	27.90	46.00	18.10
608.610	21.57	6.23	16.41	44.21	46.00	1.79
912.900	25.69	7.40	9.65	42.74	46.00	3.26

Remarks : 1. Emission Level = Antenna Factor + Cable Loss + Meter Reading.
 2. Measurement was up to 10th harmonics (~5.5GHz), but the emission levels were too low against the official limit and not report.



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw




Trace: (Discrete)

Site no.	: A/C Chamber	Data no.	: 6
Ant. / Dis.	: 3115 3m	Ant. pol.	: HORIZONTAL
Limit	: FCC CLASS-B(1G-PK)		
Env. / Ins.	: 8593EM 25°C/68%	Engineer	: henning
EUT	: Fan-Light Remote Controller	M/N:	JY622CF
Power Rating	: DC 6V		
Test Mode	: TX---side		



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw




Trace: (Discrete)

Site no.	: A/C Chamber	Data no.	: 5
Ant. / Dis.	: 3115 3m	Ant. pol.	: VERTICAL
Limit	: FCC CLASS-B(1G-PK)		
Env. / Ins.	: 8593EM 25°C/68%	Engineer	: henning
EUT	: Fan-Light Remote Controller	M/N:	JY622CF
Power Rating	: DC 6V		
Test Mode	: TX---side		



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw

Data: 8 File: C:\WINDOWS\Desktop\767data\JY622CFsE.emi (14) Date: 2004-07-09 Time: 22:31:36




Trace: (Discrete)

Site no. : A/C Chamber Data no. : 8
 Ant. / Dis. : 3115 3m Ant. pol. : HORIZONTAL
 Limit : FCC CLASS-B(1G-PK)
 Env. / Ins. : 8593EM 25°C/68% Engineer : henning
 EUT : Fan-Light Remote Controller M/N:JY622CF
 Power Rating : DC 6V
 Test Mode : TX---side



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw

Data: 7 File: C:\WINDOWS\Desktop\767data\JY622CFsE.emi (14) Date: 2004-07-09 Time: 22:25:08



Trace: (Discrete)

Site no. : A/C Chamber Data no. : 7
 Ant. / Dis. : 3115 3m Ant. pol. : VERTICAL
 Limit : FCC CLASS-B(1G-PK)
 Env. / Ins. : 8593EM 25°C/68% Engineer : henning
 EUT : Fan-Light Remote Controller M/N:JY622CF
 Power Rating : DC 6V
 Test Mode : TX---side

Date of Test : Sep. 15, 2004 Temperature : 24°C

EUT : Fan-Light Remote Controller (Transmitter) Humidity : 65%

Test Position : EUT on Lying


Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Horizontal dBμV	Emission Level Horizontal dBμV/m	Limits dBμV/m	Margin dB
Fundamental Freq. (Quasi-Peak Value)						
304.300	14.87	3.90	53.38	72.15	74.94	2.79
Spurious / Harmonic Freq. (Quasi-Peak Value)						
60.240	13.44	1.60	1.65	16.68	40.00	23.32
130.440	18.82	2.40	1.13	22.34	43.50	21.16
154.740	21.12	2.63	0.67	24.42	43.50	19.08
233.040	24.76	3.30	-0.16	27.90	46.00	18.10
608.610	21.57	6.23	16.41	44.21	46.00	1.79
912.900	25.69	7.40	9.65	42.74	46.00	3.26

Emission Frequency MHz	Antenna Factor dB/m	Cable Loss dB	Meter Reading Vertical dBμV	Emission Level Vertical dBμV/m	Limits dBμV/m	Margin dB
Fundamental Freq. (Quasi-Peak Value)						
304.300	15.17	3.90	49.28	68.35	74.94	6.59
Spurious / Harmonic Freq. (Quasi-Peak Value)						
54.840	14.36	1.50	6.23	22.09	40.00	17.91
58.080	13.79	1.60	7.76	23.15	40.00	16.85
64.830	12.84	1.70	8.34	22.88	40.00	17.12
79.950	14.07	1.80	6.98	22.85	40.00	17.15
92.640	16.92	2.00	5.11	24.02	43.50	19.48
131.790	18.94	2.40	6.07	27.41	43.50	16.09
608.610	21.68	6.20	15.53	43.41	46.00	2.59
912.900	25.69	7.40	9.78	42.87	46.00	3.13

- Remarks : 1. Emission Level = Antenna Factor + Cable Loss + Meter Reading.
 2. Measurement was up to 10th harmonics (~5.5GHz), but the emission levels were too low against the official limit and not report.



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw




Trace: (Discrete)

Site no.	: A/C Chamber	Data no.	: 5
Ant. / Dis.	: 3115 3m	Ant. pol.	: HORIZONTAL
Limit	: FCC CLASS-B(1G-PK)		
Env. / Ins.	: 8593EM 25°C/68%	Engineer	: henning
EUT	: Fan-Light Remote Controller	M/N:	JY622CF
Power Rating	: DC 6V		
Test Mode	: TX---Lying		



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw




Trace: (Discrete)

Site no.	: A/C Chamber	Data no.	: 6
Ant. / Dis.	: 3115 3m	Ant. pol.	: VERTICAL
Limit	: FCC CLASS-B(1G-PK)		
Env. / Ins.	: 8593EM 25°C/68%	Engineer	: henning
EUT	: Fan-Light Remote Controller	M/N:	JY622CF
Power Rating	: DC 6V		
Test Mode	: TX---Lying		



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw

Data: 8 File: C:\WINDOWS\Desktop\767data\JY622CFE.emi (14) Date: 2004-07-09 Time: 22:29:35




Trace: (Discrete)
 Site no. : A/C Chamber Data no. : 8
 Ant. / Dis. : 3115 3m Ant. pol. : HORIZONTAL
 Limit : FCC CLASS-B(1G-PK)
 Env. / Ins. : 8593EM 25*C/68% Engineer : henning
 EUT : Fan-Light Remote Controller M/N:JY622CF
 Power Rating : DC 6V
 Test Mode : TX---Lying



AUDIX Corp. EMC Laboratory
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei
 County, Taiwan R.O.C. Post Code:24443
 Tel:02-26092133 Fax:02-26099303
 Email:ttemc@ttemc.com.tw

Data: 7 File: C:\WINDOWS\Desktop\767data\JY622CFE.emi (14) Date: 2004-07-09 Time: 22:23:03



Trace: (Discrete)
 Site no. : A/C Chamber Data no. : 7
 Ant. / Dis. : 3115 3m Ant. pol. : VERTICAL
 Limit : FCC CLASS-B(1G-PK)
 Env. / Ins. : 8593EM 25*C/68% Engineer : henning
 EUT : Fan-Light Remote Controller M/N:JY622CF
 Power Rating : DC 6V
 Test Mode : TX---Lying


4. EMISSION BANDWIDTH MEASUREMENT

4.1. Test Equipment

The following test equipment was used during the Emission Bandwidth Test :

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Spectrum Analyzer	HP	8465EC	3946A00249	Aug. 28, 03'	Aug. 27, 04'
2.	Antenna	DIAMOND	RH799	2944A06305	N/A'	N/A

4.2. Block Diagram of Test Setup



4.3. Specification Limits (§15.231-(c))

The bandwidth of emission shall be no wider than 0.25% of the center frequency for device operating above 70MHz and below 900MHz. Bandwidth is determined at the points 20dB down from the modulated carrier.

4.4. EUT's Configuration during Compliance Measurement

The configuration of EUT was same as section 3.4.

4.5. Emission Bandwidth Measurement Results


PASS.

Test Date: Jul. 07, 2004 Temperature: 26°C Humidity: 69%

No.	Center Frequency	Bandwidth	Tolerance (%)
1.	304MHz	0.05MHz	0.0164%

The graph of bandwidth measured is attached in next page.

Graph of Bandwidth Measurement



Note: "*" The line is 20dB from the modulated carrier.


5. PERIODIC OPERATED MEASUREMENT

5.1. Test Equipment

The following test equipment was used during the periodic operated test :

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Spectrum Analyzer	HP	8465EC	3946A00249	Aug. 28, 03'	Aug. 27, 04'
2.	Antenna	DIAMOND	RH799	2944A06305	N/A'	N/A

5.2. Block Diagram of Test Setup



5.3. Specification Limits [§15.231-(a)-(1)]

The operation of this device is manually operated transmitter that is automatically deactivated the transmitter within not more than 5 seconds of being released, Compliance with §15.231 (a)- (1).

5.4. EUT's Configuration during Compliance Measurement

The configuration of EUT was same as section 3.4.


5.5. Periodic Operated Measurement Results

PASS. T=1.725 sec. (< 5sec.)

Test Date: Jul. 07, 2004 Temperature: 26°C Humidity: 69%

The graph of testing is attached in next page.

Graph of Periodic Operated Measurement



6. DEVIATION TO TEST SPECIFICATIONS

【NONE】