

FCC 15.231 Above 70MHz Test Report

for

Chungear Industrial Co., Ltd

12 Jingke 8th Rd Nantun District Taichung 40852 Taiwan

**Product Name : Ceiling Fan Remote Controller
(Transmitter)**
Model Name : TR190C
FCC ID : KUJCE10710

**Prepared by: : AUDIX Technology Corporation,
EMC Department**



The statement is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo.
The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, TAF or any government agencies.

TABLE OF CONTENTS

Description	Page
TEST REPORT CERTIFICATION.....	4
1. REVISION RECORD OF TEST REPORT	4
2. SUMMARY OF TEST RESULTS	5
3. GENERAL INFORMATION	6
3.1. Description of Application	6
3.2. Description of EUT	6
3.3. Antenna Information	6
3.4. EUT Specifications Assessed in Current Report	6
3.5. Description of Key Components	7
3.6. Test Configuration	7
3.7. Tested Supporting System List	8
3.8. Setup Configuration	8
3.9. Operating Condition of EUT	8
3.10. Description of Test Facility	9
3.11. Measurement Uncertainty	9
4. MEASUREMENT EQUIPMENT LIST	10
4.1. Conducted Emission Measurement	10
4.2. Radiated Emission Measurement	10
4.3. RF Conducted Measurement	10
5. CONDUCTED EMISSION	11
5.1. Block Diagram of Test Setup	11
5.2. Conducted Emission Limit	11
5.3. Test Procedure	11
5.4. Test Results	11
6. RADIATED SPURIOUS EMISSION	12
6.1. Block Diagram of Test Setup	12
6.2. Radiated Emission Limits	13
6.3. Test Procedure	14
6.4. Measurement Result Explanation	15
6.5. Test Results	15
7. EMISSION BANDWIDTH MEASUREMENT	16
7.1. Block Diagram of Test Setup	16
7.2. Specification Limits	16
7.3. Test Procedure	16
7.4. Test Results	16
8. PERIODIC OPERATED MEASUREMENT	17
8.1. Block Diagram of Test Setup	17
8.2. Specification Limits	17
8.3. Test Procedure	17
8.4. Test Results	17
9. DEVIATION TO TEST SPECIFICATIONS	18
APPENDIX A TEST DATA AND PLOTS	
APPENDIX B TEST PHOTOGRAPHS	

TEST REPORT CERTIFICATION

Applicant : Chungear Industrial Co., Ltd
Manufacturer #1 : Chungear Industrial Co., Ltd
Manufacturer #2 : Satellite Electronic (Zhongshan) Ltd.
Manufacturer #3 : Zhongshan Amity Electronic Ltd.
EUT Description
(1) Product : Ceiling Fan Remote Controller (Transmitter)
(2) Model : TR190C
(3) Power Supply: (1)AC 120V, 60Hz (2)DC 12V

Applicable Standards:

47 CFR FCC Part 15 Subpart C
ANSI C63.10:2013

Audix Technology Corp. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report. **Audix Technology Corp.** does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.

Date of Report: 2018. 06. 21

Reviewed by:

Sabrina Wang

(Sabrina Wang/Administrator)

Approved by:

Ben Cheng

(Ben Cheng/Manager)

1. REVISION RECORD OF TEST REPORT

Edition No	Issued Data	Revision Summary	Report Number
0	2018. 06. 21	Original Report	EM-F180242

2. SUMMARY OF TEST RESULTS

Rule	Description	Results
15.207	Conducted Emission	PASS
15.209/15.231(b)	Radiated Spurious Emission and Fundamental Frequency	PASS
15.231(c)	Emission Bandwidth	PASS
15.231(a)(1)	Periodic Operated	PASS
15.203	Antenna Requirement	Compliance

3. GENERAL INFORMATION

3.1. Description of Application

Applicant	Chungear Industrial Co., Ltd 12 Jingke 8th Rd Nantun District Taichung 40852 Taiwan
Manufacture	#1 Chungear Industrial Co., Ltd 12 Jingke 8th Rd Nantun District Taichung 40852 Taiwan #2 Satellite Electronic (Zhongshan) Ltd. 8 CHUANG YE RD.TORCH DEVELOPMENT ZONE..ZHONGSHAN.GUANGDONG.528437 CHINA #3 Zhongshan Amity Electronic Ltd. No. 16 Torch Hi-Tech Industrial Development Zone, Zhong Shan City Guangdong Province China.
Product	Ceiling Fan Remote Controller (Transmitter)
Model	TR190C

3.2. Description of EUT

Test Model	TR190C
Serial Number	N/A
Power Rating	DC 12V
RF Features	ASK
Transmit Type	1T
Sample Status	Production
Date of Receipt	2018. 05. 18
Date of Test	2018. 05. 22 ~ 06. 20
Interface Ports of EUT	None
Accessories Supplied	None

3.3. Antenna Information

Antenna Type	Hollow Coil Antenna
--------------	---------------------

3.4. EUT Specifications Assessed in Current Report

Modulation	Fundamental Range (MHz)	Channel Number
ASK	304.25	1


3.5. Description of Key Components

None

3.6. Test Configuration

Duty Cycle

TX _{on}	TX _{on+off}	Duty Cycle Factor (dB)
$0.300 * 5 + 0.600 * 20 = 13.5$	31.80	-7.44
Duty Cycle Factor = $20 \log (TX_{on} / TX_{on+off})$		



AC Conduction	
Test Case	Normal operation

Item	Test Frequency
Radiated Spurious Emission and Fundamental Frequency	304.25MHz
Emission Bandwidth	304.25MHz
Periodic Operated	304.25MHz

Note 1: Mobile Device

Portable Device, and 3 axis were assessed. The worst scenario for Radiated Spurious Emission as follow: Lie Side Stand

3.7. Tested Supporting System List

3.7.1. Support Peripheral Unit


No.	Product	Brand	Model No.	Serial No.	Approval
1.	Lamp Load (60W)	N/A	N/A	N/A	FCC By DoC

3.7.2. Cable Lists

No.	Cable Description Of The Above Support Units
1.	Data cable x3: Unshielded, Detachable, 0.1m

3.8. Setup Configuration

3.8.1. EUT Configuration for Power Line Emission



3.8.2. EUT Configuration for Radiated Emission



3.8.3. EUT Configuration for RF Conducted Test Items



3.9. Operating Condition of EUT

To press the button of EUT is used for enabling EUT RF function under continues transmitting and choosing data rate/ channel.

3.10. Description of Test Facility

Name of Test Firm	Audix Technology Corporation / EMC Department No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan Tel: +886-2-26092133 Fax: +886-2-26099303 Website : www.audixtech.com Contact e-mail: attemc_report@audixtech.com
Accreditations	The laboratory is accredited by following organizations under ISO/IEC 17025:2005 (1) NVLAP(USA) NVLAP Lab Code 200077-0 (2) TAF(Taiwan) No. 1724 (3) FCC OET Designation No. TW1004 & TW1090 & TW1724
Test Facilities	(1) No. 8 Shielding Room (2) Semi-Anechoic Chamber (IC Test Site Registration No.: 5183B-1) (3) Fully Anechoic Chamber (IC Test Site Registration No.: 5183B-4)

3.11. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty
Conduction Test	150kHz~30MHz	±3.50dB
Radiation Test (Distance: 3m)	9kHz~30MHz	± 0.5dB
	30MHz~1000MHz	± 3.68dB
	Above 1GHz	± 5.82dB

Remark : Uncertainty = $ku_c(y)$

Test Item	Uncertainty
Emission Bandwidth (20dB)	± 0.2kHz
Periodic Operated	± 0.05s

4. MEASUREMENT EQUIPMENT LIST

4.1. Conducted Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1	Test Receiver	R&S	ESR3	101774	2018. 01. 24	1 Year
2	A.M.N.	R&S	ENV4200	100169	2017. 11. 12	1 Year
3	L.I.S.N.	Kyoritsu	KNW-407	8-855-9	2017. 12. 14	1 Year
4	Pulse Limiter	R&S	ESH3-Z2	100354	2018. 01. 16	1 Year
5	Signal Cable	Yeida	RG/58AU	CE-08	2017. 09. 22	1 Year
6	Digital Thermo- Hygro Meter	iMax	HTC-1	No.8 S/R	2018.04.20	1 Year
7	Test Software	Audix	e3	V.6.120424	N.C.R.	N.C.R.

4.2. Radiated Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1	Spectrum Analyzer	Agilent	N9010A-526	MY53400071	2017. 09. 13	1 Year
2	Spectrum Analyzer	Agilent	N9030A-526	MY53310269	2018. 01. 04	1 Year
3	Amplifier	HP	8447D	2944A06305	2018. 01. 30	1 Year
4	Amplifier	HP	8449B	3008A02678	2018. 03. 06	1 Year
5	Test Receiver	R & S	ESCS30	100338	2017. 06. 19	1 Year
6	Loop Antenna	R & S	HFH2-Z2	891847/27	2017. 12. 18	1 Year
7	Bilog Antenna	CHASE	CBL6112D	33821	2018. 01. 21	1 Year
8	Horn Antenna	ETS-Lindgren	3117	00135902	2018. 03. 08	1 Year
9	Signal Cable	MIYAZAKI	5D2W	RE-11	2018. 02. 08	1 Year
10	RF Cable	HUBER+SUHNER	SUCOFLEX 106	54602/6	2018. 02. 08	1 Year
11	Digital Thermo-Hygro Meter	iMax	HTC-1	No.1 3m A/C	2018. 04. 20	1 Year
12	Digital Thermo-Hygro Meter	iMax	E-512	RF-02	2018. 04. 20	1 Year
13	Test Software	Audix	e3	V.6.110601	N.C.R.	N.C.R.

4.3. RF Conducted Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A-544	US51350140	2017. 06. 20	1 Year
2	Wide Band Antenna	Diamond	RH799	N/A	N.C.R	N.C.R


5. CONDUCTED EMISSION

5.1. Block Diagram of Test Setup

5.1.1. Block Diagram of EUT

Indicated as section 3.8

5.1.2. Shielded Room Setup Diagram



5.2. Conducted Emission Limit

Frequency	Conducted Limit	
	Quasi-Peak Level	Average Level
150kHz ~ 500kHz	66 ~ 56 dB μ V	56 ~ 46 dB μ V
500kHz ~ 5MHz	56 dB μ V	46 dB μ V
5MHz ~ 30MHz	60 dB μ V	50 dB μ V

Remark 1.: If the average limit is met when using a Quasi-Peak detector, the measurement using the average detector is not required.

2.: The lower limit applies to the band edges.

5.3. Test Procedure

- 5.3.1. To set up the EUT as indicated in ANSI C 63.10. The EUT was placed on the table which has 80 cm height to the ground and 40 cm distance to the conducting wall.
- 5.3.2. Power supplier of the EUT was connected to the AC mains through an Artificial Mains Network (A.M.N.).
- 5.3.3. The AC power supplies to all peripheral devices must be provided through line impedance stabilization network (L.I.S.N.)
- 5.3.4. Checking frequency range from 150 kHz to 30 MHz and record the emission which does not have 20 dB below limit.

5.4. Test Results

Please refer to Appendix A.


6. RADIATED SPURIOUS EMISSION

6.1. Block Diagram of Test Setup


6.1.1. Block Diagram of EUT

Indicated as section 3.8


6.1.2. Setup Diagram for 9kHz-30MHz



6.1.3. Setup Diagram for 30MHz-1000MHz



6.1.4. Setup Diagram for above 1GHz



6.2. Radiated Emission Limits

6.2.1. General Limit

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205 must also comply with the radiated emission limits specified as below.

Frequency (MHz)	Distance (m)	Limits	
		dB μ V/m	μ V/m
0.009 - 0.490	300	67.6-20 log f(kHz)	2400/f kHz
0.490 - 1.705	30	87.6-20 log f(kHz)	24000/f kHz
1.705 - 30	30	29.5	30
30 - 88	3	40.0	100
88- 216	3	43.5	150
216- 960	3	46.0	200
Above 960	3	54.0	500
Above 1000	3	74.0 dB μ V/m (Peak) 54.0 dB μ V/m (Average)	

Remark : (1) dB μ V/m = 20 log (μ V/m)

- (2) The tighter limit applies to the edge between two frequency bands.
- (3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- (4) Fundamental and emission fall within operation band are exempted from this section.
- (5) Pursuant to ANSI C63.10: 6.6.4.3, if the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

6.2.2. Limite for Fundamental Frequency

In addition to the provisions of §15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	¹ 1,250 to 3,750	¹ 125 to 375
174-260	3,750	375
260-470	¹ 3,750 to 12,500	¹ 375 to 1,250
Above 470	12,500	1,250

¹: Linear Interpolations

Remark : (1) $\text{dB}\mu\text{V}/\text{m} = 20 \log (\mu\text{V}/\text{m})$

- (2) The tighter limit applies to the edge between two frequency bands.
- (3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- (4) Where limit of Fundamental Freq. is calculated by:
 $41.6667 \times 304.25 - 7083.3333 = 5593.760175 \mu\text{V}/\text{m} = 74.95 \text{dB}\mu\text{V}/\text{m}$
- (5) The limits in this table are based on CFR 47 Part 15.231(b).

6.3. Test Procedure

Frequency Range 9kHz~30MHz:

The EUT setup on the turn table which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

- (1) RBW = 9kHz with peak and average detector.
- (2) Detector: average and peak (9kHz-490kHz)
Q.P. (490kHz-30MHz)

Frequency Range above 30MHz to 10th harmonic:

The EUT setup on the turn table which has 80 cm (for 30-1000 MHz) and 1.5m (for above 1GHz) height to the ground. The turn table rotated 360 degrees and antenna varied from 1 m to 4 m to find the maximum emission level. Both horizontal and vertical polarization are required. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

Frequency below 1 GHz:

Spectrum Analyzer is used for pre-testing with following setting:

- (1) RBW = 120KHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.
- (7) When peak-detected value is lower than limit that the measurement using the Q.P. detector is not required, otherwise using Q.P. for final measurement.

Frequency above 1GHz to 10th harmonic:**Peak Detector:**

- (1) RBW = 1MHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.
- (7) When peak-detected value is lower than limit that the measurement using the average detector is not required, otherwise using average detector for final measurement.

Average Detector: **Option 1:**

- (1) RBW = 1MHz
- (2) VBW $\geq 1/T$.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.

 Option 2:

Average Emission Level = Peak Emission Level + D.C.C.F.

6.4. Measurement Result Explanation


- Peak Emission Level = Antenna Factor + Cable Loss + Meter Reading
- Average Emission Level = Antenna Factor + Cable Loss + Meter Reading
- Average Emission Level = Peak Emission Level + DCCF
Duty Cycle Correction Factor (DCCF) = $20 \log (TX_{on}/TX_{on+off})$ presented in section 3.6
- ERP = Peak Emission Level - 95.2dB - 2.14dB

6.5. Test Results

Please refer to Appendix A.

7. EMISSION BANDWIDTH MEASUREMENT

7.1. Block Diagram of Test Setup



7.2. Specification Limits

The bandwidth of emission shall be no wider than 0.25% of the center frequency for device operating above 70MHz and below 900MHz. Bandwidth is determined at the points 20dB down from the modulated carrier.

7.3. Test Procedure


- (1) Set RBW close to 1-5 % of OBW.
- (2) Set $VBW \geq RBW$.
- (3) Detector = Peak.
- (4) Trace mode = max hold.
- (5) Sweep = auto couple.
- (6) Allow the trace to stabilize.
- (7) Setting channel bandwidth function x dB to -20 dB to record the final bandwidth.

7.4. Test Results

Please refer to Appendix A

8. PERIODIC OPERATED MEASUREMENT

8.1. Block Diagram of Test Setup



8.2. Specification Limits

The operation of this device is manually operated transmitter that is automatically deactivated the transmitter within not more than 5 seconds of being released

8.3. Test Procedure

- (1) Span = zero
- (2) RBW \geq 100kHz
- (3) VBW \geq RBW
- (4) Sweep = 5s
- (5) Detector function = peak
- (6) Trace = single sweep

8.4. Test Results

Please refer to Appendix A

9. DEVIATION TO TEST SPECIFICATIONS

【NONE】



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

APPENDIX A

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX A

TEST DATA AND PLOTS


(Model: TR190C)

TABLE OF CONTENTS

A.1 CONDUCTED EMISSION	2
A.2 RADIATED SPURIOUS EMISSION	4
A.2.1 Emissions Applied to General Requirement.....	4
A.2.2 Fundamental Frequency	8
A.3 EMISSION BANDWIDTH MEASUREMENT	9
A.3.1 Emission Bandwidth.....	9
A.3.2 Measurement Plots	9
A.4 PERIODIC OPERATED MEASUREMENT	10
A.4.1 Periodic Operated	10
A.4.2 Measurement Plots	10

A.1 CONDUCTED EMISSION

Test Date	2018/06/20	Temp./Hum.	25°C/57%
Test Voltage	AC 120V 60Hz		



Site no. : No.8 Shielded Room Data no. : 2
 Condition : ENV4200 100169 LISN Phase : NEUTRAL
 Limit : FCC 15B-C
 Env. / Ins. : 25°C / 57% ESCI(1276) Engineer : Nick Du
 EUT : TR190C
 Power Rating : 120Vac/60Hz
 Test Mode : Operating


	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.213	10.51	0.03	9.98	2.42	22.94	63.10	40.16	QP
2	0.592	10.43	0.05	9.98	2.01	22.47	56.00	33.53	QP
3	1.602	10.45	0.06	9.99	4.30	24.80	56.00	31.20	QP
4	4.092	10.61	0.11	10.00	4.89	25.61	56.00	30.39	QP
5	9.011	11.22	0.18	10.02	4.26	25.68	60.00	34.32	QP
6	26.001	15.29	0.31	10.08	5.52	31.20	60.00	28.80	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.

Audix Technology Corp.
 No. 53-11, Dingfu, Linkou, Dist.,
 New Taipei City244, Taiwan

Tel: +886 2 26099301
 Fax: +886 2 26099303

Test Date	2018/06/20	Temp./Hum.	25°C/57%
Test Voltage	AC 120V 60Hz		



Site no. : No.8 Shielded Room Data no. : 1
 Condition : ENV4200 100169 LISN Phase : LINE
 Limit : FCC 15B-C
 Env. / Ins. : 25°C / 57% ESCI(1276) Engineer : Nick Du
 EUT : TR190C
 Power Rating : 120Vac/60Hz
 Test Mode : Operating

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.152	10.63	0.03	9.98	3.93	24.57	65.87	41.30	QP
2	0.585	10.45	0.05	9.98	10.28	30.76	46.00	15.24	Average
3	0.585	10.45	0.05	9.98	16.08	36.56	56.00	19.44	QP
4	1.296	10.45	0.06	9.99	3.53	24.03	56.00	31.97	QP
5	1.619	10.46	0.07	9.99	5.92	26.44	56.00	29.56	QP
6	7.646	11.09	0.16	10.01	4.90	26.16	60.00	33.84	QP
7	28.152	15.91	0.33	10.09	6.57	32.90	60.00	27.10	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.

A.2 RADIATED SPURIOUS EMISSION

Test Date	2018/05/30	Temp./Hum.	23°C/53%
Test Frequency	TX 304.25MHz	Test Voltage	DC 12V


A.2.1 Emissions Applied to General Requirement

A.2.1.1 Frequency 9kHz~30MHz

The emissions (9kHz~30MHz) not reported for there is no emission be found.

A.2.1.2 Frequency Below 1 GHz


Test Date	2018/05/30	Temp./Hum.	23°C/53%
Test Frequency	TX 304.25MHz	Test Voltage	DC 12V



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
42.61	11.98	2.55	1.91	16.44	40.00	23.56	Peak
101.78	11.03	3.23	7.50	21.76	43.50	21.74	Peak
396.66	15.47	5.62	2.42	23.51	46.00	22.49	Peak
608.12	18.36	6.52	1.87	26.75	46.00	19.25	Peak
912.70	20.65	7.62	12.46	40.73	46.00	5.27	Peak
991.27	21.04	8.05	1.64	30.73	54.00	23.27	Peak

Test Date	2018/05/30	Temp./Hum.	23°C/53%
Test Frequency	TX 304.25MHz	Test Voltage	DC 12V



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
39.70	13.51	2.51	2.43	18.45	40.00	21.55	Peak
101.78	11.03	3.23	7.95	22.21	43.50	21.29	Peak
458.74	16.42	6.14	3.62	26.18	46.00	19.82	Peak
608.12	18.36	6.52	1.42	26.30	46.00	19.70	Peak
912.70	20.65	7.62	5.36	33.63	46.00	12.37	Peak
993.21	21.06	8.07	1.63	30.76	54.00	23.24	Peak

A.2.1.3 Frequency Above 1 GHz

Test Date	2018/05/30	Temp./Hum.	23°C/53%
Test Frequency	TX 304.25MHz	Test Voltage	DC 12V

Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
2130.00	31.77	6.24	5.78	43.79	54.00	10.21	Peak
2738.00	32.58	7.05	10.02	49.65	54.00	4.35	Peak
3042.00	32.89	7.51	3.47	43.87	54.00	10.13	Peak
3346.00	32.83	7.96	8.97	49.76	54.00	4.24	Peak
3956.00	33.27	8.68	1.50	43.45	54.00	10.55	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
1522.00	28.24	5.36	7.56	41.16	54.00	12.84	Peak
2130.00	31.77	6.24	6.65	44.66	54.00	9.34	Peak
2738.00	32.58	7.05	12.96	52.59	54.00	1.41	Peak
3042.00	32.89	7.51	5.89	46.29	54.00	7.71	Peak
3346.00	32.83	7.96	9.00	49.79	54.00	4.21	Peak

A.2.2 Fundamental Frequency

Test Date	2018/05/30	Temp./Hum.	23°C/53%
Test Frequency	TX 304.25MHz	Test Voltage	DC 12V



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
304.27	13.25	4.71	62.00	79.96	94.95	14.99	Peak

Emission Frequency (MHz)	Peak Emission Level (dBμV/m)	DCCF (dB)	Average Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
304.27	79.96	-7.44	72.52	74.95	2.43	Average

Remark: Horizontal is the strongest polarization and peak value has complied with average limit, so vertical won't be listed in test report.


A.3 EMISSION BANDWIDTH MEASUREMENT

Test Date	2018/05/22	Temp./Hum.	25°C /58%
Test Frequency	TX 304.25MHz	Test Voltage	DC 12V

A.3.1 Emission Bandwidth

Center Frequency (MHz)	Occupied Bandwidth (MHz)	Tolerance (%)	Limit (%)
304.25	0.008685	0.003	0.25

A.3.2 Measurement Plots




A.4 PERIODIC OPERATED MEASUREMENT

Test Date	2018/05/22	Temp./Hum.	25°C /58%
Test Frequency	TX 304.25MHz	Test Voltage	DC 12V

A.4.1 Periodic Operated

Center Frequency (MHz)	Time (Sec.)	Limit (Sec.)
304.25	0.180	< 5

A.4.2 Measurement Plots





Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX B

TEST PHOTOGRAPHS

(Model: TR190C)