## GARAGE DOOR CONTROLLER MINI NOVA HUB **Quick Setup Guide**



Thank you for your purchase of the Mini Nova Hub, your Universal Garage Door Controller. Mini Nova Hub allows you to control and monitor your garage door with your smartphone, anywhere. Share access with your family members through the "Orbit Home" mobile app. With the built-in LED, it can be used as a light source in vour garage.

### Important Instructions

Step 2 - Install the Nova Hub

Ensure both wires are secured.

signal Wi-Fi et à au moins 20 cm de toute personne.)

## **WARNING**

TO REDUCE THE RISK OF SEVERE INJURY OR DEATH, READ AND FOLLOW ALL INSTRUCTIONS.

- . DO NOT enable the Mini Nova Hub Universal Garage Door Controller if operating either one-piece or swinging doors. To be enabled ONLY on a sectional door.
- The Nova is designed for unattended operation, the door could move unexpectedly.
- DO NOT install Nova on garage door openers manufacturered prior to 1993 without safety infrared sensors or photo eves
- . Install the Mini Nova Hub in a location where it can be seen and heard while standing next to the garage door with the door in the open position.

Mini Nova Hub can be installed on the ceiling of the garage, either near the garage

door opener, or near the wall control. It is suggested to install it with the best Wi-Fi

Place the mounting bracket at the desired location, secure it by the screws provided. Mark and drill pilot holes with anchors if mounting to drywall

2. Press the orange tabs down and insert 2 wires. (Polarity does not matter).

signal and at least 20cm from any person. (Il est suggéré de l'installer avec le meilleur

#### What is included



Mounting bracket

(For Mini Nova Hub)

Mini Nova Hub

Garage door

5. Slide the Mini Nova Hub

into the mounting bracket. with a click.

4. Plug the power adapter to the Mini Nova Hub.

opener

and screws accessories

Door Sensor

(AA battery

Screws and Double

(For Door Sensor)

sided tape

not included)





Power Adapter



2v Rell Wire

#### Overview





Connect the

OR

Wall button /

Wall console

wires to

@10 010 DIC

## R are registered trademarks of their respective corporations.

support@skylinkhome.com

**Customer Service** 

**System Requirements** 

Wi-Fi Router 2.4 GHz 802.11 b/g/n

(5 GHz network is not supported)

Before you begin, please ensure you have the following:

Compatible garage door opener \*

9:00 AM - 5:00 PM EST (MONDAY - FRIDAY)

with safety sensors installed


## Step 3 - Install Door Sensor 1. Remove the front cover with a flat screwdriver


Mobile device with iOS (9.0 and up)

1-800-304-1187


SKYLINKHOME.COM


or Android (4.4 and up)






3. The sensor should be mounted on the top door panel of the garage door. Clean the door where the sensor will be mounted







## NOTE

- . A clean smooth surface is required to mount the door sensor securely.
- · If the mounting surface is not smooth or clean enough for the doubled sided tape, you may screw the garage sensor onto the surface.


Battery Disposal - Dispose used battery according to local regulations.

### Step 1 - Check Wi-Fi signal in garage

Mini Nova Hub works with your home 2.4 GHz Wi-Fi router. It is important to ensure you have good Wi-Fi signal reception in the garage.

- . To check the Wi-Fi signal, place your mobile device such as smartphone next to where you plan to install the Mini Nova Hub. Make sure the Wi-Fi signal have at least 2 bars.
- . If you have less than 2 bars, please try the following:
- Relocate the Wi-Fi router closer to the Mini Nova Hub, or
- Add a Wi-Fi range extender.

For more information on Wi-Fi signal strength, please visit www.skvlinkhome.com/nova-support



# Step 4 - Download the Mobile App - Orbit Home

Download the Skylink® "Orbit Home" app, from iOS App Store or Google Play Store.

Follow the instructions on the Orbit App to complete the rest of the setup.



This device complies with Part 15 of the FCC Rules, Operation is subject to the following two conditions (1) This device may not cause harmful interference and (2) This device must accept any interference received including interference that may cause undesired operation

### WARNING

Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the ECC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following

- . Regrient or relocate the receiving antenna.
- . Increase the separation between the equipment and receiver
- . Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- . Consult the dealer or an evnerienced radio/TV technician for help


## ISED

This device complies contains licence-exempt transmitter/receiver that comply with Innovation Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions: (1) This device may not cause interference; and (2) This device must accept any interference, including interference that may cause undesired operation of the device

L'émetteur/récepteur exempt de licence contenu dans le present appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux

conditions suivantes : (1) L'appareil ne doit pas produire de brouillage; (2) L'appareil doit accepter tout brouillage radioélectrique subi, mêmesi le brouillage est susceptible d'en compromettre le fonctionnement

2019 SKYLINK GROUP P/N - 101Y629



- a. Back of the wall control (connect wire along existing wall control wires).
- b. Garage Door Opener (connect wire to the wall control terminals).
- 7. Place the warning label on wall next to the door control

6. Plug the power adapter into wall outlet. Blue LED should be on steadily.