

Report No.	:	AB0001831	Date :	January 12, 2022
Application No.	:	LA035718		
Applicant	:	Capital Prospect Ltd Rm 03, 13/F, Block B, Veri 34-36 Au Pui Wan Street, F Hong Kong		
Sample Description	:	One(1) item of submitted sa	umple stated to be:	
Sumple Description	•	Sample Description	Model No.	Serial Number
		318MHz Transmitter	MK-318-3	ES0002
		Radio Frequency	: 318MHz	<u> </u>
		Rating	: 1 x 3V CR2032 button cell	
		No. of submitted sample	: One (1) piece	
		Sample registration No.	: RA020319-001-5	
Date Received	:	Nov 1, 2021		
Test Period	:	Nov 1, 2021 – Dec 2, 2021		
Test Requested	:	FCC 47CFR Part 15 Certifie		
		ISED Canada Radio Standa	rds Specification RSS-210.	
Test Method	:	47 CFR Part 15 (10-1-20 Ec	lition)	
		ANSI C63.10 – 2013		
		RSS-210 Issue 10		
		RSS-GEN Issue 5		
Test Result	:	See attached sheet(s) from p	page 2 to 17.	
			e de la companya de l	
Additional Model	:	Model: MK318-1 and MK-3 housing	318-2 are same as MK-318-3	except the number of keys on the
Conclusion	:		elated models were found to c nd ISED Canada RSS-210 Iss	comply with requirement of FCC ue 10.

For and on behalf of CMA Industrial Development Foundation Limited

Page 1 of 17

Authorized Signature : \_

Wong Lap Pong / Andrew Deputy Technical Manager

### FCC ID: KUTMK-318

IC: 4454A-MK318X The conformity statement stated in Conclusion above is based on the decision rule agreed with applicant and listed in <u>www.cmatesting.org/qac/statement-of-conformity.pdf</u>. This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website <u>www.cmatesting.org</u>. This document shall not be reproduced except in full without written approval by CMA Testing. The results apply to the sample as received unless otherwise specified. The observations and test results in this report are relevant only to the sample tested.

**CMA Industrial Development Foundation Limited** 

Alesting CMA Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong. MAlesting CM

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatesting.org Web Site: http://www.cmatesting.org



Report No. : A

AB0001831

Date :

January 12, 2022

#### **Table of Contents**

1 G	eneral Information	
1.1	General Description	
1.2	Location of the test site	
1.3	List of measuring equipment	5
1.4	Measurement Uncertainty	6
1.5	Test Summary	6
2 D	escription of the radiated emission test	
2.1	Test Procedure	7
2.2	Test Setup	
2.3	Test Result	
3 D	escription of the Line-conducted Test	
3.1	Test Procedure	
3.2	Test Result	
3.3	Test Setup	
3.4	Graph and Table of Conducted Emission Measurement Data	
4 Su	upplementary document	
4.1	Bandwidth	
4.2	Average Factor	
4.3	Transmission time	
5 A	ppendices	

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 2 of 17



Report No. : AB0001831

Date :

January 12, 2022

### **1** General Information

1.1 General Description

The equipment under test (EUT) model MK-318-3 is a wireless transmitter. It operates at frequency 318MHz for transmitter 10kbps ASK modulation. The oscillation of radio control is generated by a 9.9375MHz crystal for RF transmitter. Model:MK-318-3 are powered by one 3V CR2032 button cell. Model:MK-318-3 contains 3 keys. The keys are used to control the corresponding receiver.

The 0dBi PCB antenna is used. The RF output power is unable to adjust.

No any firmware and software are associated with the device.

The brief circuit description is listed as follows:

Model: MK-318-3	
-SW1-3,	and its associated circuit act as the key input
-U3	and its associated circuit act as RFIC, SYN115
-Y1	and its associated circuit act as oscillation clock, 9.9375MHz
-U1	and its associated circuit act as MCU, STM32L011G4U6.
-C1,C2,C3,C14,L2,L3	and its associated circuit act as matching network

Model Difference:

Model: MK-318-1 and MK-318-2 are same as Model: MK-318-3 except the number of keys on the housing.

Model:	MK-318-1	MK-318-2	MK-318-3
No. of Keys:	1	2	3
HVIN:	MK-318-1	MK-318-2	MK-318-3
PMN:	MK-318-1	MK-318-2	MK-318-3

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 3 of 17



Report No. : AB0001831

Date : January 12, 2022

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2014. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2014. A shielded room is located at :

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

FCC Accredited Lab (Designation Number: HK0004) ISED Wireless Test Site (ISED Assigned Code: 4093A)

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 4 of 17



Report No. : AB0001831

Date :

January 12, 2022

#### 1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	Calibrati on Period
EMI Test Receiver	Rohde & Schwarz	ESCI	100152	23 Dec 2021	1Year
Spectrum Analyzer	R&S	FSV40	100964	14 Dec 2021	1Year
Log Periodic Antenna	TESEQ	UPA6109	Log Periodic Antenna	29 Nov 2022	2Years
Biconical Antenna	Rohde & Schwarz	HK116	Biconical Antenna	29 Nov 2022	2Years
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-531	02 Feb 2023	3Years
Broadband Pre- Amplifier	Schwarzbeck	BBV 9718	9718-119	02 Feb 2023	3Years
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA917044 2	14 Sep 2023	3Years
Broadband Pre- Amplifier	Schwarzbeck	BBV 9719	9719-010	14 Sep 2023	3Years
Coaxial Cable	Suhner	Sucoflex 106	N/A	03 May 2022	1Year
Coaxial Cable	Suhner	Sucoflex_104	N/A	14 Jan 2022	2Year
LISN	Rohde & Schwarz	ENV216	101323	23 Dec 2021	1Year
Coaxial Cable	Tyco Electronics	RG 58C/U	N/A	18 Oct 2022	1Year

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 5 of 17

CMA Industrial Development Foundation Limited



#### Report No. : AB0001831

Date : January 12, 2022

### 1.4 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%.

#### Radiated emissions

Radiated emissions		
Frequency	Uncertainty (U <sub>lab</sub> )	
30MHz ~ 200MHz (Horizontal)	4.59dB	
30MHz ~ 200MHz (Vertical)	4.49dB	
200MHz ~1000MHz (Horizontal)	4.94dB	
200MHz ~1000MHz (Vertical)	4.97dB	
1GHz ~ 6GHz	4.52dB	

### 1.5 Test Summary

TEST ITEM	FCC REFERANCE	IC REFERANCE	RESULT
Radiated emission	15.231(b)	RSS-210 Annex A1.2	Comply
Assigned bandwidth (20dB)	15.231(c)	-	Comply
Occupied bandwidth >0.25% of the center frequency	-	RSS-210 Annex A1.3	Comply
Transmission time after manual activation	15.231(a)	RSS-210 Issue 10 Annex A1.1.1	Comply
Frequency Stability	-	RSS-Gen, Clause 8.11	Comply

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 6 of 17

CMA Industrial Development Foundation Limited



Report No. : AB0001831

Date :

January 12, 2022

### 2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.10 - 2013.

A non-conductive turntable with dimensions of 1.5m x 0.4m x 0.8m (L x W x H) placed above the reference ground plane. The equipment under test (EUT) was placed at 0.8m height for below 1GHz measurement and 1.5m height for above 1GHz measurement. The test distance is 3m between EUT and receiving antenna. A broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated. Additional absorbing material will be placed between the EUT and receiving antenna for above 1GHz measurement.


For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

The EUT was pressed to make the continuous transmission during Radiated Emission test.

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 7 of 17





30MHz - 1GHz

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 8 of 17

CMA Industrial Development Foundation Limited


Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong. Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: <u>info@cmatesting.org</u> Web Site: <u>http://www.cmatesting.org</u>



#### Report No. : AB0001831

Date :

2.2 Test Setup



Above 1GHz

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 9 of 17



Report No. : AB0001831

Date : Januar

January 12, 2022

2.3 Test Result

Peak Detector data was measured unless otherwise stated.

The radiated emissions are measured from 9kHz to 4GHz (the tenth harmonics)

The worst case configuration is shown on the worst case configuration of test setup photo.

"#" means emissions appearing within the restricted bands of 47 CFR Part 15 section 15.205 and "\*" means emission appearing within the restricted band of RSS-GEN section 8.10.

The frequencies from fundamental up to tenth harmonics were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next pages.

The EUT has been tested in Transmission mode.

It was found that the EUT meet the FCC and RSS requirement.

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 10 of 17



Report No. : AB0001831

Date :

January 12, 2022

2.4 Radiated Emission Measurement Data

### **Radiated emission**

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	24.3	° C
Relative humidity:	49.8	%

Model: MK-318-3

Polarization	Frequency	Reading at 3m	Antenna	Field	Limit at	Margin	Detector
	(MHz)	(dBµV)	Factor and	Strength at	3m	(dB)	Туре
			Cable Loss	3m	(dBµV/m)		
			(dB/m)	(dBµV/m)			
Н	317.996	46.4	16.9	63.3	75.8	-12.5	Peak
V	317.998	42.7	16.9	59.6	75.8	-16.2	Peak
V	#1272.051	53.0	-8.2	44.8	54.0	-9.2	Peak
V	*#1589.955	50.7	-8.0	42.7	54.0	-11.3	Peak
Н	1908.050	57.6	-7.2	50.4	55.8	-5.4	Peak
V	2544.088	51.3	-4.7	46.6	55.8	-9.2	Peak
Н	*#2861.903	51.4	-4.7	46.7	54.0	-7.3	Peak
V	3179.920	46.8	-3.3	43.5	55.8	-12.3	Peak

Remark: 1) \* The emission is fall in the restricted band of FCC section 15.205.

2) # The emission is fall in the restricted band of RSS-Gen Table 6.

3) Since the Peak value of all measured frequencies are less than the average limit, the average value will be not be measured or calculated to comply the average limit.

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 11 of 17



Report No. : AB0001831

Date :

January 12, 2022

### **3** Description of the Line-conducted Test


3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.10 - 2013. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Test Setup



3.4 Graph and Table of Conducted Emission Measurement Data

Not Applicable

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 12 of 17

CMA Industrial Development Foundation Limited



Report No. : AB0001831

Date : January 12, 2022

### 4 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename	
ID Label/Location	Label Artwork and Location.pdf	
Block Diagram	Block Diagram.pdf	
Schematic Diagram	Schematic.pdf	
Users Manual	User Manual.pdf	
Operational Description	Operation Description.pdf	

#### 4.1 Bandwidth

Appendices A1 is shown the worst case fundamental emission of three models is confined in the specified band. The 20dB bandwidth is 4.479kHz and 99% bandwidth is 14.194kHz. The bandwidth requirement is 0.25% of 318MHz = 795kHz. It also shows that the EUT met the FCC Part 15.231(c) and RSS-210 Annex A1.3 bandwidth requirement and frequency stability requirement.

4.2 Average Factor

Not Applicable

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 13 of 17



Report No. : AB0001831

Date : J

January 12, 2022

4.3 Transmission time

All three keys are tested and following worst case found: Worst case: the lowest key

Duration of each transmission = 1.40s

The duration of the transmission is less than 5s after the transmission is activated by remote controller. An Appendices A3 is shown the EUT to comply with FCC part 15, section 15.231(a)(1) and RSS-210, Annex 1, section A1.1.1.

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 14 of 17



Report	No.	: AB0001831		Date :	January 12, 2022
5	Appe	ndices			
	A1. A2.	Bandwidth Plot Transmission Time Plot	1 1	page page	

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 15 of 17

CMA Industrial Development Foundation Limited Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong. Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: <u>info@cmatesting.org</u> Web Site: <u>http://www.cmatesting.org</u>




Report No.

AB0001831

:


Date :

January 12, 2022



### A1. Bandwidth Plot

#### 20dB bandwidth



99% bandwidth

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 16 of 17

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong. Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: <u>info@cmatesting.org</u> Web Site: <u>http://www.cmatesting.org</u>




Report No.

AB0001831

:

Date :

January 12, 2022



A2. Transmission Time Plot

\*\*\*\*\* End of Report \*\*\*\*\*

FCC ID: KUTMK-318 IC: 4454A-MK318X Page 17 of 17