

USER'S INSTRUCTIONS - (MODEL : SDTX)

PROGRAMMING YOUR NEW TRANSMITTER

1. Press the red learn button in your dialer.
2. When you see both red and green LED flash. Now you can add the new remote to the proper locations, 1, 2, 3, or 4.
3. Once the location is selected. The dialer will emit 3 beeps indicating you can now activate the remote control you would like to add to the dialer.
4. Once the signal is received and programmed to the dialer, the dialer will go back to step 2.
5. To quit, just press the green button until you hear a long beep and green LED steadily on, that indicates the dialer is back to standby mode.

BATTERY

1. Open up the housing with a coin.
2. Remove the circuit board from the housing.
3. Insert the lithium battery CR-2032 to the circuit board. *Pay attention on the polarity, positive side up.*
4. Snap the top and bottom housing together.

FCC

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

WARNING:

Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

SKYLINK TECHNOLOGIES INC.,

17 Sheard Avenue, Brampton, Ontario, Canada L6Y 1J3 Tel : (905) 456-8883