5.3.3 Photograph



5.4 800 MHz EO Cell Amplifier Module (AE04A-D1265-001)

5.4.1 Description

This 2Watt, 806-856 MHz, class A Power Amplifier Module provides a nominally 51 dB of gain. It has 30 dB of gain adjustment range, which can be varied electronically thru the front panel RS232 connector. Additionally, the module has an internal Automatic Level Control (ALC) circuit, which can be set to limit the maximum power level produced by the BDA. This module has an on board RISC processor that provides optional alarming/status monitoring and communications capabilities. The same module design is used for both the Downlink and Uplink amplifier.

The amplifier module contains high reliable RF parts to provide a long troublefree operating life. In the unlikely event of failure, the entire amplifier module should be replaced.

ANDREW	Wireless Innovations Group 2601 Telecom Parkway Richardson, Texas 75082	400/800 MHz Fiber Optic & RF Fed Bi-Directional Amplifier Operations / Maintenance Manual		
DWG NO: AE04B-A1669		Rev: B	Date: 06/18/2008	Page:28 of 63

5.4.2 Specification

PARAMETER	SPECIFICATION		
Operating Frequency Range	806 – 856 MHz		
Gain Typical	51 dB		
Output Gain Adjustment ¹	30 dB		
Composite Output Power	≥ +33 dBm		
Impedance	50 Ohms		
VSWR	2:1		
OIP3 ²	≥ + 47 dBm		
Noise Power max. @ 51 dB Gain	-111 dBm/Hz		
DC Power	+48 VDC		
Operating Temperature	-20°C to +60°C		

Note:

1.Via Front Panel RS232 Connector.

2.Two-Tone Intermodulation: Measure at two-output carriers of +23.5 dBm/C at 845 MHz and 845.6 MHz with 51 dB gain setting.

5.4.3 Photographs



ANDREW	Wireless Innovations Group 2601 Telecom Parkway Richardson, Texas 75082	400/800 MHz Fiber Optic & RF Fed Bi-Directional Amplifier Operations / Maintenance Manual		
DWG NO: AE04B-A1669		Rev: B	Date: 06/18/2008	Page:29 of 63



ANDREW	Wireless Innovations Group 2601 Telecom Parkway Richardson, Texas 75082	400/800 MHz Fiber Optic & RF Fed Bi-Directional Amplifier Operations / Maintenance Manual		
DWG NO: AE04B-A1669		Rev: B	Date: 06/18/2008	Page:16 of 63