

PLACE TOLERANCE OF THE PRINTING $\pm 0,3\text{mm}$
TO BE PRINTED IN PRODUCTION WITH
(600DPI) THERMAL TRANSFER PRINTER

Name:

Battery type

Type: iCube Li-Po 4,2V ===

FCC ID: KWC-ICUBE1

IC ID: 2262A-ICUBE1





Abrasion acc.
DIN 58199

Made in Austria www.phonak.com

Bar code 128,
height 3mm,
Module width 2 dots

SN: 0720H12GW(X)

M 1:1



Incremental SN, (3 characters in
use for the start phase)

SAP Number (H1 for Stäfa)

number of the current week
year (2007)

Biocompatible acc. USP class 1 - ISO 10993-1
Material must be ROHS compliant

Bar code contents
Label blanc see: AZ160-00029□

Control Characteristic				cpk >= .	Important Characteristic	
.	.	.	.	.	.	.
.	.	.	.	.	.	.
.	.	.	.	.	.	.
1	02	07.11.07	FAC-590-070547	final FCC-ID and IC-ID added	JN	
1	01	19.10.07	FAC-590-070498	first intruduction	JN	
INDEX VERSION		DATE	CHANGE NOTE	DESCRIPTION		NAME
PROJ.EUROPE		MATERIAL		TOLERANCES UNLESS OTHERWISE STATED	CUSTOMER	
UNIT		TREATMENT			PROJECT	
MM					PHONAK	
					COMMBUTTON	
SCALE		DESCRPT.		CODE		VERSION
5:1		ARTWORK LABEL TYPE WFD		AZ164-00162-1		02
		NAME DATE		STAGE		SHEET 110
		Neuwirth 05.09.2007				
PROPERTY OF		FLEXTRONICS				SH 1 OF 1
		Friesacher Str. 3 A 9330 Althofen, Austria				FORMAT A4

ALL RIGHTS STRICTLY RESERVED
REPRODUCTION OR ISSUE TO THIRD
PARTIES IN ANY FORM WHATEVER IS
NOT PERMITTED WITHOUT WRITTEN
AUTHORITY FROM THE PROPRIETORS

FLEXTRONICS
Design

