



## SAR Test exclusion documentation according to FCC KDB 447498, RSS-102

Report identification number: 1-9948/20-01-05-A Exclusion (FCC\_ISED)

contains the module with the following certification numbers	
FCC ID	KWCSE
ISED number	2262A-SE
HVIN (Hardware Version Identification Number)	Roger Earpiece V2, Roger Earpiece C V2
PMN (Product Marketing Name)	Roger Earpiece
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### Document authorised:

Alexander Hnatovskiy  
Lab Manager  
Radio Communications & EMC

Marco Scigliano  
Testing Manager  
Radio Communications & EMC

**EUT technologies:**

Technologies:	Max. rated power: (AVG)	Max. gain:	Min. pathloss:
Bluetooth LE 2.4 GHz	Declared: max 0 dBm	<0 dBi	0 dB (if applicable)

Note: Max declared by customer

**SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)**

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

(1) Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances  $\leq 50$ mm

$$(\text{Threshold}_{1\text{-g};10\text{-g}}) \times d_{\text{separation}} / f^{0.5}$$

where

Threshold<sub>1-g;10-g</sub> is 3 for 1-g; 7.5 for 10-g

$d_{\text{separation}}$  is the min. test separation distance; 5mm is used if the distance is less

$f$  is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	$d_{\text{separation}}$ [mm]	Threshold <sub>1-g</sub>	Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
				[dBm]	[mW]	
2450.00	5	3	9.58	0.00	1.00	yes

**SAR test exclusion according to RSS-102 Issue 5 Section 2.5.1/Table 1**

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	$d_{\text{separation}}$ [mm]	tissue volume	Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
				[dBm]	[mW]	
2450.00	5	1 g	4.00	0.00	1.00	yes

The limits above are defined for body worn application and therefore cover all use cases.