

Hong Kong Standards and Testing Centre

Date : 2005-08-30 No. : HM154794

Applicant:

TEST REPORT

Page 1 of 20

Supreme Toys (Hong Kong) Ltd. Rm. 1114-1115, 11F, Tower A, New Mandarin Plaza, 14 Science Museum Road, Tsim Sha Tsui East, Kowloon, Hong Kong.

Description of Samples:

 Baby Monitor 55005
N/A L2555005

Date Samples Received: 2005-07-20

Date Tested:

2005-08-16

Investigation Requested:

FCC Part 15 Subpart C

Conclusions:

The submitted product <u>COMPLIED</u> with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Remarks:

K C Lee, EMD for Chief Executive

This report shall not be reproduced unless with prior written approval from the Hong Kong Standards and Testing Centre.

香港新界大埔工業村大宏街 10號



香港新界大埔工業村大宏街 10號



香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-08-30

No. : HM154794

TEST REPORT

Page 4 of 20

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd. EMC Laboratory 10 Dai Wang Street, Taipo Industrial Estate New Territories, Hong Kong

Telephone:852 2666 1888Fax:852 2664 4353

1.2 Applicant Details Applicant

Supreme Toys (Hong Kong) Ltd. Rm. 1114-1115, 11F, Tower A, New Mandarin Plaza, 14 Science Museum Road, Tsim Sha Tsui East, Kowloon, Hong Kong.

HKSTC Code Number for Applicant

<u>SUT002</u>

Manufacturer

Jackpot Plastic & Metal Manufactory Feng Gang, Guan Jing Tou, Shui Ku District, Dongguan, China



香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-08-30

No. : HM154794

TEST REPORT

Page 5 of 20

- 1.3 Equipment Under Test [EUT] Description of Sample
 - Model Name: Manufacturer: Brand Name: Model Number: Input Voltage:

Baby Monitor Jackpot Plastic & Metal Manufactory N/A 55005 6Vd.c ("AA" size battery x 4) with jack The AC/DC Adaptor used for the tests was a "Winstar" adaptor: Model Number: NA-12, Input: 100-120/220-240Va.c. Output: 3-15Vd.c. 1200mA max.

1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is a Supreme Toys (H.K.) Ltd., Baby Monitor. The transmitter is a 3 button transmitter. The EUT continues to transmit while trigger is being pressed. It is voice transmission, modulation by microphone, and type is amplitude modulation.

1.4 Date of Order

2005-07-20

1.5 Submitted Sample(s):

2 Samples per model

1.6 Test Duration

2005-08-16

1.7 Country of Origin

China

香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-08-30

No. : HM154794

TEST REPORT

Page 6 of 20

2.0 Technical Details

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4:2003 for FCC Certification.

2.2 Test Standards and Results Summary Tables

EMISSION Results Summary								
Test Condition	Test Requirement	Test Method	Class /	Τe	est Resul	t		
			Severity	Pass	Failed	N/A		
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.235	ANSI C63.4:2003	N/A	\boxtimes				
Radiated Emissions	FCC 47CFR 15.209	ANSI C63.4:2003	Class B	\boxtimes				
Conducted Emissions on AC, 0.15MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2003	Class B	\boxtimes				

Note: N/A - Not Applicable



香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-08-30

No. : HM154794

TEST REPORT

Page 7 of 20

3.0 Test Results

3.1 Emission

3.1.1 Radiated Emissions (30 - 1000MHz)

Test Requirement: Test Method: Test Date: Mode of Operation: FCC 47CFR 15.235 ANSI C63.4:2003 2005-08-16 Tx mode

Test Method:

The sample was placed 0.8m above the ground plane on the OATS *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

OATS [Open Area Test Site] located at HKSTC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 607756.



香港新界大埔工業村大宏街 10號



TEST REPORT

Page 8 of 20

Date : 2005-08-30

No. : HM154794

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.235]:

Frequency Range of	Field Strength of	Field Strength of
Fundamental	Fundamental Emission	Spurious Emission
	[Peak]	[Average]
[MHz]	[µV/m]	[µV/m]
49.82-49.90	100,000	10,000

Results of Tx Mode (Channel A): PASS

Field Strength of Fundamental Emissions								
	Peak Value							
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field		
	Level @3m	Factor	Strength	Strength		Polarity		
MHz	dBµV/m	dBµV/m	dBµV/m	μV/m	μV/m			
49.87	56.1	10.0	66.1	2,018.4	100,000	Vertical		

Field Strength of Fundamental Emissions								
		Average						
Measured	Correction	Field	Field	Limit @3m	E-Field			
Level @3m	Factor	Strength	Strength		Polarity			
dBµV/m	dBµV/m	dBµV/m	μV/m	μV/m				
56.0	10.0	66.0	1,995.3	10,000	Vertical			
	F Measured Level @3m dBµV/m 56.0	Field StrengthMeasuredCorrectionLevel @3mFactordBµV/mdBµV/m56.010.0	Field Strength of FundameAverageMeasuredCorrectionFieldLevel @3mFactorStrengthdBµV/mdBµV/mdBµV/m56.010.066.0	Field Strength of Fundamental EmissionAverageMeasuredCorrectionFieldFieldLevel @3mFactorStrengthStrengthdBµV/mdBµV/mdBµV/mµV/m56.010.066.01,995.3	Field Strength of Fundamental Emissions AverageMeasuredCorrectionFieldFieldLimit @3mLevel @3mFactorStrengthStrengthV/mdBµV/mdBµV/mdBµV/mµV/mµV/m56.010.066.01,995.310,000			

Remarks:

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be recorded. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth =3MHz Video Bandwidth =1Hz

Correction Factor included Antenna Factor and Cable Attenuation. Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB

香港新界大埔工業村大宏街 10號



Date : 2005-08-30

No. : HM154794

TEST REPORT

Page 9 of 20

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]			
30-88	100			
88-216	150			
216-960	200			
Above960	500			

The emission limits shown in the above table are based on measurement employing a CISPR quasipeak detector and above 1000MHz are based on measurements employing an average detector.

	Radiated Emissions									
				Qı	lasi-Pea	k				
Frequency	Me	asured	Correction		Field		Field	Limit @3m	E-Field	
	Lev	el @3m	Factor	S	trength	S	trength		Polarity	
MHz	dE	3µV/m	dBµV/m	di	BµV/m	- 1	µV/m	µV/m		
99.74	<	1.0	11.0	<	12.0	<	4.0	150	Vertical	
149.61	<	1.0	9.8	<	10.8	<	3.5	150	Vertical	
199.48	<	1.0	11.5	<	12.5	<	4.2	150	Vertical	
249.35	<	1.0	15.2	<	16.2	<	6.5	200	Vertical	
299.22	<	1.0	16.9	<	17.9	<	7.9	200	Vertical	
349.09	<	1.0	19.0	<	20.0	<	10.0	200	Vertical	
398.96	<	1.0	20.6	<	21.6	<	12.0	200	Vertical	
448.83	<	1.0	19.7	<	20.7	<	10.8	200	Vertical	
498.70	<	1.0	20.6	<	21.6	<	12.0	200	Vertical	

Results of Tx Mode (Channel A): PASS

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation. Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB

香港新界大埔工業村大宏街 10號



Date : 2005-08-30

No. : HM154794

TEST REPORT

Page 10 of 20

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.235]:

Frequency Range of	Field Strength of	Field Strength of
Fundamental	Fundamental Emission	Spurious Emission
R	[Peak]	[Average]
[MHz]	[µV/m]	[µV/m]
49.82-49.90	100,000	10,000

Results of Tx Mode (Channel B): PASS

Field Strength of Fundamental Emissions							
Peak Value							
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field	
	Level @3m	Factor	Strength	Strength		Polarity	
MHz	dBµV/m	dBµV/m	dBµV/m	μV/m	μV/m	-	
49.81	55.6	10.0	65.6	1,905.5	100,000	Vertical	

Field Strength of Fundamental Emissions								
Average								
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field		
	Level @3m	Factor	Strength	Strength		Polarity		
MHz	dBµV/m	dBµV/m	dBµV/m	μV/m	μV/m			
49.81	55.5	10.0	65.5	1,883.6	10,000	Vertical		

Remarks:

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be recorded. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth	=3MHz
Video Bandwidth	=1Hz

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz

香港新界大埔工業村大宏街 10號

±4.1dB



Date : 2005-08-30

No. : HM154794

<u>TEST REPORT</u>

Page 11 of 20

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasipeak detector and above 1000MHz are based on measurements employing an average detector.

	Radiated Emissions									
				Qı	lasi-Pea	k				
Frequency	Me	asured	Correction		Field		Field	Limit @3m	E-Field	
	Lev	el @3m	Factor	S	trength	S	trength		Polarity	
MHz	dE	3μV/m	dBµV/m	di	BµV/m	- 1	μV/m	μV/m		
99.62	<	1.0	11.0	<	12.0	<	4.0	150	Vertical	
149.43	<	1.0	9.8	<	10.8	<	3.5	150	Vertical	
199.24	<	1.0	11.5	<	12.5	<	4.2	150	Vertical	
249.05	<	1.0	15.2	<	16.2	<	6.5	200	Vertical	
298.86	<	1.0	16.9	<	17.9	<	7.9	200	Vertical	
348.67	<	1.0	19.0	<	20.0	<	10.0	200	Vertical	
398.48	<	1.0	20.6	<	21.6	<	12.0	200	Vertical	
448.29	<	1.0	19.7	<	20.7	<	10.8	200	Vertical	
498.10	<	1.0	20.6	<	21.6	<	12.0	200	Vertical	

Results of Tx Mode (Channel B): PASS

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation. Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB

香港新界大埔工業村大宏街 10 號



Test Requirement: Test Method: Test Date: Mode of Operation: FCC 47CFR 15.207 ANSI C63.4:2003 2005-06-09 Tx Mode

Test Method:

The test was performed in accordance with ANSI C63.4: 2003, with the following: an initial measurement was performed in peak and average detection mode on the live line, any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.





香港新界大埔工業村大宏街 10號



TEST REPORT

Page 13 of 20

Date : 2005-08-30

No. : HM154794

Limits for Conducted Emissions (FCC 47 CFR 15.207):

Frequency Range	Quasi-Peak Limits	Average
[MHz]	[dBµV]	[dBµV]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

* Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram labelled as (QP and AV).

Results of Tx Mode (Channel A): PASS



		Quasi-peak		Ave	rage
Conductor	Frequency	Level	Limit	Level	Limit
Live or Neutral	MHz	dBµV	dBµV	dBµV	dBµV
NO EMISSION DETECTED WITHIN 20dB OF THE FCC LIMITS					

Remarks:

Calculated measurement uncertainty: ±2.8dB

-*- Emission(s) that is far below the corresponding limit line.

香港新界大埔工業村大宏街 10號



TEST REPORT

Page 14 of 20

Date : 2005-08-30

No. : HM154794

Limits for Conducted Emissions (FCC 47 CFR 15.207):

Frequency Range	Quasi-Peak Limits	Average
[MHz]	[dBµV]	[dBµV]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

* Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram labelled as (QP and AV).

Results of Tx Mode (Channel B): PASS



		Quasi-peak		Ave	rage
Conductor	Frequency	Level	Limit	Level	Limit
Live or Neutral	MHz	dBµV	dBµV	dBµV	dBµV
NO EMISSION DETECTED WITHIN 20dB OF THE FCC LIMITS					

Remarks:

Calculated measurement uncertainty: ±2.8dB

-*- Emission(s) that is far below the corresponding limit line.

香港新界大埔工業村大宏街 10 號



Hong Kong Standards and Testing Centre

Date : 2005-08-30

No. : HM154794

TEST REPORT

Page 15 of 20

3.2 20dB Bandwidth of Fundamental Emission

Test Requirement: Test Method: Test Date: Mode of Operation:

FCC 47 CFR 15.235 ANSI C63.4:2003 (Section 13.1.7) 2005-08-16 On mode

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.



香港新界大埔工業村大宏街 10號





Channel A





香港新界大埔工業村大宏街 10號



Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range	20dB Bandwidth	FCC Limits
[MHz]	[kHz]	[MHz]
49.81	15.6	within 49.82-49.90

Channel B





香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-08-30 No. : HM154794

TEST REPORT

Page 18 of 20

Appendix A

List of Measurement Equipment

		Radiated Emission	1		
EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	15/06/04
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	15/06/04
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	15/06/04
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	15/06/04
EM011	ATTENNUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	15/06/04
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	15/06/04
EM013	CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE	HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD	HP9000 HP A1097C HP9133L	6226A60314 3151J39517 2623A02468	15/06/04
EM020	HORN ANTENNA	EMCO	3115	4032	30/07/03
EM022	LOOP ANTENNA	EMCO	6502	1189-2424	30/07/03
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	N/A
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	08/02/03
EM131	PORTABLE SPECTRUM ANALYSER	HEWLETT PACKARD	8595EM	3710A00155	13/01/04
EM145	EMI TEST RECEIVER	R&S	ESCS 30	830245/021	04/10/04
EM219	BICONILOG ANTENNA	EMCO	3142C	00029071	28/10/03
EM195	ANTENNA POSITIONING MAST	EMCO	2075	2368	N/A
EM196	MULTI-DEVICE CONTROLLER	EMCO	2090	1662	N/A

Line Conducted

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	СМ
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	17/10/03
EM119	LISN	R&S	ESH3-Z5	0831.5518.52	14/10/04
EM127	ISOLATION TRANSFORMER 220 TO 300	WING SUN	N/A	N/A	СМ
EM142	PULES LIMITER	R&S	ESH3Z2	357.8810.52	04/08/04
EM181	EMI TEST RECEIVER	R&S	ESIB7	100072	06/01/04
EM154	SHIELDING ROOM	SIEMENA MATSUSHITA COMPONENTS	N/A	803-740-057- 99A	17/10/03
EM197	LISN	EMCO	4825/2	1193	05/06/04

Remarks:-

CM	Corrective Maintenance
N/A	Not Applicable or Not Available
TBD	To Be Determined

香港新界大埔工業村大宏街 10 號



香港新界大埔工業村大宏街 10號



Date : 2005-08-30 No. : HM154794

TEST REPORT

Page 20 of 20

Photographs of EUT

Measurement of Radiated Emission Test Set Up



Measurement of Radiated Emission Test Set Up



**** End of Test Report *****

60124

香港新界大埔工業村大宏街 10號