



October 07, 2019

TUV SUD BAPT  
Octagon House, Concorde Way  
Segensworth Rd N, Fareham  
PO15 5RL

Attention: Director of Certification

**RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 Mobile Portable RF Exposure v06 and RSS-102 Issue 5 March 2015.**

FCC ID: L2V-SF2RAS

IC: 3989A-SF2RAS

**1. Limits:**

Limits for General Population/Uncontrolled Exposure (Title 47 Subpart J §2.1091 and KDB 447498 D01 referring to limits under §1.1310)

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Electric Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f/1500	30
1500 - 100,000	-	-	1.0	30

*f = frequency in MHz*

*\*Plane-wave equivalent power density*



Limits for Devices Used by the General Public (Uncontrolled Environment (RSS-102 Issue 5 March 2015))

Frequency Range (MHz)	Electric Field Strength (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003 - 10 <sup>21</sup>	83	90	-	Instantaneous
0.1 - 10	-	0.73/f	-	6**
1.1 - 10	87/f <sup>0.5</sup>	-	-	6**
10 - 20	27.46	0.0728	2	6
20 - 48	-58.07/f <sup>0.25</sup>	0.1540/f <sup>0.25</sup>	8.944/f <sup>0.5</sup>	6
48 - 300	22.06	0.05852	1.291	6
300 - 6000	3.142 f <sup>0.3417</sup>	0.008335 f <sup>0.3417</sup>	0.02619 f <sup>0.6834</sup>	6
6000 - 15000	61.4	0.163	10	6
15000 - 150000	61.4	0.163	10	616000/f <sup>1.2</sup>
150000 - 300000	0.158f <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> f <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> f	616000/f <sup>1.2</sup>

*f* is frequency in MHz

\*Based on nerve stimulation (NS)

\*\* Based on specific absorption rate (SAR)

2. Mobile MPE Calculation Summary using a 20cm separation distance:

Mode	Output Power	Power Density (mW/cm <sup>2</sup> )
L-Band Mobile Satellite Service	1.37dBW EIRP	0.29291
WLAN (802.11 g)	15.20 dBm	0.01376

3. Co-Located Transmitters transmission table:

Transmitter type	Transmitter type that can transmit at the same time
L-Band Mobile Satellite Service	WLAN
WLAN	L-Band Mobile Satellite Service

4. Simultaneous Transmission MPE:

Transmitter type	MPE (mw/cm <sup>2</sup> )	FCC Limit (mW/cm <sup>2</sup> )	IC Limit (mW/cm <sup>2</sup> )	FCC MPE ratio (MPE/Limit)	ISED MPE ratio (MPE/Limit)
Mobile Satellite Service	0.29291	1.0	0.407207	0.29291	0.719315
WLAN	0.01376	1.0	0.53660	0.01376	0.025643
Sum of the ratios (should be <1.0)				0.30667	0.744958



**5. Mobile MPE Calculation using a 20cm separation distance (L-Band Mobile Satellite Service):**

Using Power Density formula:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to isotropic

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	<b>28.38</b>	(dBm)
Maximum peak output power at antenna input terminal:	<b>688.65</b>	(mW)
Antenna gain(typical):	<b>3.3</b>	(dBi)
Maximum antenna gain:	<b>2.138</b>	(numeric)
Prediction distance:	<b>20</b>	(cm)
Source Based Time Average Duty Cycle:	<b>100</b>	(%)
Prediction frequency:	<b>1610.73</b>	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	<b>1.000</b>	(mW/cm <sup>2</sup> )
ISED MPE limit for uncontrolled exposure at prediction frequency:	<b>0.407207</b>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.29291</b>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>2.929</b>	(W/m <sup>2</sup> )
FCC Margin of Compliance:	<b>-5.33</b>	(dB)
ISED Margin of Compliance:	<b>-1.43</b>	(dB)

**6. Mobile MPE Calculation using a 20cm separation distance (WLAN 802.1 b):**

Maximum peak output power at antenna input terminal:	<b>15.20</b>	(dBm)
Maximum peak output power at antenna input terminal:	<b>33.11</b>	(mW)
Antenna gain(typical):	<b>3.2</b>	(dBi)
Maximum antenna gain:	<b>2.089</b>	(numeric)
Prediction distance:	<b>20</b>	(cm)
Source Based Time Average Duty Cycle:	<b>100</b>	(%)
Prediction frequency:	<b>2412</b>	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	<b>1.000</b>	(mW/cm <sup>2</sup> )
ISED MPE limit for uncontrolled exposure at prediction frequency:	<b>0.53660</b>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.01376</b>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.138</b>	(W/m <sup>2</sup> )
FCC Margin of Compliance:	<b>-18.61</b>	(dB)
ISED Margin of Compliance:	<b>-15.91</b>	(dB)



Sincerely,

A handwritten signature in black ink, appearing to read 'Ferdie S. Custodio', written over a horizontal line.

Ferdie S. Custodio

Name

Authorized Signatory

Title: Senior EMC Test Engineer /Wireless Team Lead