







FCC Part 25, Certification









Figure 5e. 99% Occupied Bandwidth for 26 dB removal from peak signal



2.9 Spurious Emissions at Antenna Terminals (FCC Section 2.1051)

Spurious emissions appearing at the antenna terminals were measured with a spectrum analyzer by connecting the spectrum analyzer directly via a short cable to the antenna output terminals or across the antenna leads on the PCB as specified by the manufacturer. Results are shown in Figures 6a - 6p.

Protection of the radio-navigation-satellite service. Mobile earth stations operating in the 1610-1626.5 MHz band shall limit out-of- band emissions in the 1574.397-1576.443 MHz band so as not to exceed an e.i.r.p. density level of -70 dB (W/MHz) averaged over any 20 ms period. The e.i.r.p. of any discrete spurious emission (i.e., bandwidth less than 600 Hz) in the 1574.397-1576.443 MHz band shall not exceed -80 dBW.

FCC Minimum Standard (FCC Section 25.202(f))

For out-of-band emissions for frequencies removed from the midpoint of the assigned frequency segment by more than 250% of the authorized bandwidth (2.5 MHz), at least

43 + 10 log (P_{Watts}) attenuation below the mean power of the transmitter.

For Lowest Channel = $43 + 10 \log (0.153) = 34.8 \text{ dB}$ For Highest Channel = $43 + 10 \log (0.159) = 35.0 \text{ dB}$

The following plots show that all emissions were at least 50.4 dB below the fundamental.

Note:

A 10 kHz RBW was used instead. This was deemed to be comparable to 4 kHz RBW.

Additional requirement for 1574.397 - 157.443 MHz (FCC Section 25.213(b))

- 80 dBW (- 50 dBm)

Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

Figure 6a. Spurious Emissions at Antenna Terminals



NOTE: Marker shows Fundamental Frequency

FCC Part 25, Certification

Figure 6b. Spurious Emissions at Antenna Terminals



Figure 6c.

Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

FCC Part 25, Certification

15: 22 Ap REF 25	5:22:47 AUG Ø6. F 25.Ø dBm			2002 At 20 db Pg				dB	MKR 3,21Ø GH -49.6Ø dB		
PEAK _0G 1Ø dB/											
	STOP 6.ØØ	ø GHz									
WA SB SC FC CORR											
	· · · · · · · · · · · · · · · · · · ·										

Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

FCC Part 25, Certification

Figure 6d. Spurious Emissions at Antenna Terminals



Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

FCC Part 25, Certification

Figure 6e. Spurious Emissions at Antenna Terminals



Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

FCC Part 25, Certification

Figure 6f. Spurious Emissions at Antenna Terminals



Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

FCC Part 25, Certification

Figure 6g. Spurious Emissions at Antenna Terminals



FCC Part 25, Certification

Figure 6h. Spurious Emissions at Antenna Terminals

Limit = -80 dBW = -50 dBm



Figure 6i. Spurious Emissions at Antenna Terminals



NOTE: Marker shows Fundamental Frequency

FCC Part 25, Certification

Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

14:16:05 AUG 26, 2002 MKR 2.855 GHz REF 25.Ø dBm #AT 3Ø dB PG -10.0 dB -51.26 dBm PEAK LOG 10 dB/ MARKER 2.855 GHz -51.26 dBm VA SB SC FC CORR 0 START 1.900 GHz STOP 2.921 GHz #RES BW 10 KHz #VBW 10 KHz SWP 30.6 sec

Figure 6j. Spurious Emissions at Antenna Terminals

Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

FCC Part 25, Certification

Figure 6k. Spurious Emissions at Antenna Terminals



Figure 6I. Spurious Emissions at Antenna Terminals

Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

FCC Part 25, Certification

7 EF 28	5.Ø d	Bm	₩AT	3Ø d	IB PG	-1Ø.Ø	dB	MKR	7.799	GHz dBm
EAK DG										
3/	маяк	FA								
	7.79	9 GHz 57 dE	: 3m							
		_								
SB FC ORR										
			marchen	mm	mm	······	2mm	mmm	mmm	unter

Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

FCC Part 25, Certification

Figure 6m. Spurious Emissions at Antenna Terminals



Report Number:04-0017Customer:Axonn, L.L.C.Model:STU

FCC Part 25, Certification

,								
	MARK 13.9 -44.	ER 93 GH 21 dB	z m	ан российн нэл гэлтээл 19 оног арсган арсг	1	 		
SB FC DRR							*****	
						\diamond		

Figure 6n. Spurious Emissions at Antenna Terminals

Report Number:04-0017Customer:Axonn, L.L.C.Model:STU



FCC Part 25, Certification

Figure 6p. Spurious Emissions at Antenna Terminals

Limit= -80 dBW = -50 dBm

