




***EXHIBIT B***

***Test Report***

Report No.	C0915248
Specifications Test Method	FCC Part 15.109(g), Class B ANSI C63.4 1992
Applicant address	16F, No. 75 Hsin Tai Wu RD., Sec. 1 Bldg #A Hsi-Chih, Taipei Hsien, Taiwan
Applicant Items tested Model No.	CIS TECHNOLOGY INC. 5 Port 10/100 Dual Speed Ethernet Hub WS-DH05/V2 (Sample # C09248)
Results Sample received data	Compliance (As detailed within this report) 04/26/1999 (month / day / year)
Prepared by	 project engineer
Authorized by	 Vice General Manager (Jacob Lin)
Issue date	 May 28, 1999 (month / day / year)
Modifications	None
Tested by Office and Open site at	Training Research Co., Ltd. No. 15, Lane 530, Pa-Lian RD., Sec. 1, Hsi-Chih Town, Taipei Hsien, Taiwan, R.O.C.

**Conditions of issue:**

- (1) **This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.**
- (2) **This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.**

★ FCC ID: L4ODH05V2

# Contents

## Chapter 1 Introduction

Description of EUT.....	3
Configuration of Test Setup.....	4
List of Support Equipment.....	5

## Chapter 2 Conducted Emission Test

Test Condition and Setup.....	6
Conducted Test Placement.....	7

## Chapter 3 Radiated Emission Test

Test Condition and Setup.....	8
Radiated Test Placement.....	9

## Appendix A:

Conducted test result .....	10
-----------------------------	----

## Appendix B:

Radiated test result .....	11
----------------------------	----

## ***Chapter 1 Introduction***

### ***Description of EUT:***

HUB is a data transmission / receiver facility. It was connected to Lan card installed in the PC or compatible computer and makes your data equipment available to transmit / receive data via the EUT. During testing the EUT was operated at Tx or Rx mode for each emission measured. This was done in order to insure that maximum emission levels were attained.

### ***Connections of EUT:***

- (1) The power jack of EUT was connected with the AC power source via a power adapter.
- (2) UTP port 1 and UTP port 5 were each connected with a Lan card installed in a PC located remotely.
- (3) The other UTP ports were terminated.

### ***Test method:***


Pretest was found that the emission of operating mode is worse than standby mode. So, The final test is made at the operating mode.

During pretest, there were three modes testing: 10 x 10MHz, 10 x 100MHz, 100 x 100MHz.

During testing, the EUT was operated at “transmitting” and “receiving” mode simultaneously.

The test placement as the photographs showed is the worst case emission placed. (If the emission is close to the ambient, the resolution BW and view resolution will be reduced and the data will be recorded by detection of maximum hold peak mode.)

***The testing configuration of test setup is showing in the next page.***

*Configuration of test setup**Connections:****EUT:***

- \*RJ45 Cable  $\times$  2 --- 30M, Non-Shielded, Plastic Hood, No Ferrite bead.
- \*RJ45 Cable  $\times$  3 --- 3M, Non-Shielded, Plastic Hood, No Ferrite bead.
- \*Power cable --- non-shielded, 1.8 M, with ferrite core

*List of support equipment***Conducted (Radiated) test:**

**PC** : HP  
**Model** : Vectra VE 5/166 SERIES 3  
**Serial No.** : SG72450161, SG72450174  
**FCC ID** : B94VECTRAVE53  
**Power type** : 110~120 / 220~240 VAC, Switching  
**Power cord** : non-Shielded, 1.7m long, Plastic, no ferrite core

**Monitor** : HP  
**Model No.** : D2821  
**Serial No.** : TW73107071, TW73512262  
**FCC ID** : A3KM064  
**Power type** : 110~120 / 220~240 VAC, Switching  
**Power cord** : Non-Shielded, 3m long, no ferrite core  
**Data cable** : Shielded, 1.8m long, with ferrite core

**Keyboard** : Digital  
**Model No.** : KB-5923  
**Serial No.** : 9S74904768, 9S74904741  
**FCC ID** : E8HKB-5923  
**Power type** : By PC  
**Data cable** : Shielded, 1.8m long, with ferrite core

**Lan Card** : DELTA  
**Model No.** : AEF380-TX  
**Serial No.** : N/A  
**Power Type** : Powered by PC  
**Data Cable** : UTP, 7', Plastic RJ-45 hoods, No ferrite bead.

## Chapter 2 Conducted emission test

### Test condition and setup:

All the equipment is placed and setup according to the CISPR 22.

The EUT is assembled on a wooden table that is 80 cm high, is placed 40 cm from the back-wall which is a vertical conducting plane. One LISN is for EUT, the other LISN is for support equipment. They are all placed on the conductive ground. The EUT's LISN connect a line switch box for selecting L1 or L2, then connect to a preamplifier and spectrum.

The spectrum scans from 150KHz to 30MHz. Conducted emission levels are detected at max. peak mode. But if the max. peak mode failed, it will be measured by CISPR's quasi-peak detection mode.

While testing, there is the worst-emission plot printed at peak detection mode, and there are more than 6 highest emissions relative to limit recorded. The plot is kept as the original data, not included in test report.

### List of test Instrument:

Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
Spectrum analyzer	8594EM	H P	3710A00279	01/07/99	01/07/00
LISN (EUT)	3825/2	EMCO	9411-2284	05/15/98	05/15/99
LISN (Support E.)	AC3-001	TRC	-----	05/15/98	05/15/99
Preamplifier	AC3-002	TRC	-----	05/15/98	05/15/99
Line switch box	AC3-003	TRC	-----	05/15/98	05/15/99

The level of confidence of 95%, the uncertainty of measurement of conducted emission is  $\pm 2.4$  dB.

### Test Result: Pass (Appendix A)

### *Chapter 3 Radiated emission test*

#### *Test condition and setup:*

**Pretest:** Prior to the final test (OATS test), the EUT is placed in a anechoic chamber and scan from 30MHz to 1GHz. This is done to ensure the radiation exactly emits form the EUT.

**Final test:** Final radiation measurements are made on a **10 - meter**, open-field test site. The EUT is placed on a nonconductive table that is 0.8m height, the top surface is 1.0 x 1.5 meter. The placement is according to CISPR 22.

The spectrum is examined from 30 MHz to 1000 MHz measured by HP spectrum.

The EMCO whole range Antenna is used to measure frequency from 30 MHz to 1GHz. The final test is used the spectrum HP 8594EM.

Measure more than six top marked frequencies generated form pretest by computer step by step at each frequency. The EUT is rotated 360 degrees, and antenna is raised and lowered from 1 to 4 meters to find the maximum emission levels. The antenna is used with both horizontal and vertical polarization.

Appropriated preamplifier which is made by TRC is used for improving sensitivity and precautions is taken to avoid overloading. The spectrum analyzer's 6dB bandwidth is set to 120 KHz, and the EUT is measured at quasi-peak mode.

If the emission is close to the frequency band of ambient, the data will be rechecked by the tester and the corrected data will be written in the test data sheet. If the emission is just within the ambient, the data from anechoic chamber will be taken as the final data.

#### *List of test Instrument:*


#### *Calibration Date*

Instrument Name	Model No.	Brand	Serial No.	Last	Next
Spectrum analyzer	8594EM	H P	3619A00198	11/17/98	11/17/99
RF Pre-selector	AC4-001	TRC	-----	05/20/99	05/20/00
Antenna (30M-2G Hz)	3141	EMCO	9711-1076	12/17/98	12/17/99
Open test side (Antenna, Amplify, cable calibrated together)				05/20/99	05/20/00

The level of confidence of 95%, the uncertainty of measurement of radiated emission is  $\pm 4.96$  dB.

#### *Test Result: Pass (Appendix B)*

*Radiated Test Placement: (Photographs)*



## Appendix A

### Conducted Emission Test Result: ( 100 X 100 MHz )

Testing room: Temperature : 25 ° C      Humidity : 58 % RH

#### Line 1

FREQUENCY ( KHz )	READING AMPLITUDE			LIMIT		MARGIN ( dB )
	Peak (dB $\mu$ V/m)	Quasi-peak (dB $\mu$ V/m)	Average (dB $\mu$ V/m)	Quasi-Peak (dB $\mu$ V/m)	Average (dB $\mu$ V/m)	
368	32.69	*** **	*** **	59.77	49.77	-17.08
480	32.32	*** **	*** **	56.57	46.57	-14.25
538	30.10	*** **	*** **	56.00	46.00	-15.90
582	29.83	*** **	*** **	56.00	46.00	-16.17
697	29.28	*** **	*** **	56.00	46.00	-16.72
744	35.45	*** **	*** **	56.00	46.00	-10.55
808	30.17	*** **	*** **	56.00	46.00	-15.83
857	32.28	*** **	*** **	56.00	46.00	-13.72
910	31.88	*** **	*** **	56.00	46.00	-14.12
966	33.08	*** **	*** **	56.00	46.00	-12.92

#### Line 2

FREQUENCY ( KHz )	READING AMPLITUDE			LIMIT		MARGIN ( dB )
	Peak (dB $\mu$ V/m)	Quasi-peak (dB $\mu$ V/m)	Average (dB $\mu$ V/m)	Quasi-Peak (dB $\mu$ V/m)	Average (dB $\mu$ V/m)	
430	32.71	*** **	*** **	58.00	48.00	-15.29
477	33.21	*** **	*** **	56.66	46.66	-13.45
534	29.70	*** **	*** **	56.00	46.00	-16.30
697	28.84	*** **	*** **	56.00	46.00	-17.16
744	34.39	*** **	*** **	56.00	46.00	-11.61
803	32.64	*** **	*** **	56.00	46.00	-13.36
857	32.10	*** **	*** **	56.00	46.00	-13.90
910	33.90	*** **	*** **	56.00	46.00	-12.10
954	33.88	*** **	*** **	56.00	46.00	-12.12
1015	30.73	*** **	*** **	56.00	46.00	-15.27

\* The reading amplitudes are all under average limit.

**Appendix B****Radiated Emission Test Result: (Horizontal) ( 100 X 100 MHz )****Test Conditions:**

Testing room : Temperature : 26 ° C      Humidity : 61 % RH  
 Testing site : Temperature : 25 ° C      Humidity : 70 % RH

Frequency	Reading Amplitude	Ant. Height	Table	Correction Factors	Corrected Amplitude	Class B limit	Margin
MHz	dB $\mu$ V	m	degree	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB

60.780	43.74	2.50	278	-23.01	20.73	30.00	-9.27
64.190	46.92	4.00	7	-23.43	23.49	30.00	-6.51
124.980	42.38	0.99	0	-21.89	20.49	30.00	-9.51
***							

**Note:**

1. Margin = Amplitude - limit, if margin is minus means under limit.

2. Corrected Amplitude = Reading Amplitude + Correction Factors

3. Correction factor = Antenna factor + ( Cable Loss - Amplitude gain)

(For example: 30MHz correction factor = 15.5 + (-15.26) = 0.24 dB/m)

***Radiated Emission Test Result: (Vertical) ( 100 X 100 MHz )***

Frequency	Reading Amplitude	Ant. Height	Table	Correction Factors	Corrected Amplitude	Class B limit	Margin
MHz	dB $\mu$ V	m	degree	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB

42.060	46.23	0.99	300	-22.17	24.06	30.00	-5.94
47.800	49.07	0.99	277	-21.95	27.12	30.00	-2.88
50.410	43.84	4.02	340	-21.96	21.88	30.00	-8.12
55.890	43.54	4.01	342	-22.75	20.79	30.00	-9.21
62.230	43.86	2.51	140	-23.18	20.68	30.00	-9.32
64.200	48.16	0.99	10	-23.43	24.73	30.00	-5.27
125.030	49.89	4.02	22	-21.88	28.01	30.00	-1.99
250.000	54.81	0.99	93	-22.68	32.13	37.00	-4.87
***							

***Final statement:***

***This test report, measurements made by TRC are traceable to the NIST.***