




EXHIBIT B

Test Report

Report No.	C0915539
Specifications	FCC Part 15.109(g) Class B, Certification.
Test Method	ANSI C63.4 1992
Applicant address	16F, No. 75, Hsin Tai Wu Rd., Sec. 1, Bldg, #A, Hsi-Chih, Taipei Hsien, Taiwan, R.O.C.
Applicant Items tested	CIS TECHNOLOGY, INC. 56K modem card with voice
Model No.	WS-5614PVD (Sample # C09539)
Results	As detailed within this report
Sample received data	09/22/1998 (month / day / year)
Prepared by	 project engineer
Authorized by	 Vice General Manager (Jacob Lin)
Issue date	 (month / day / year)
Modifications	None
Tested by	Training Research Co., Ltd.
Office at	2F, No. 571, Chung Hsiao E. Road, Sec.7, Taipei, Taiwan
Open site at	No. 5-3, Lane 21, Yen Chiu Yuan Rd., Sec. 4, Taipei, Taiwan

Conditions of issue:

- (1) This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relates to the sample submitted for testing.**
- (2) This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.**

★FCC ID: L4OWS-5614PVD

Contents

Chapter 1 Introduction

Description of EUT	3
Configuration of Test Setup	4
List of Support Equipment	5

Chapter 2 Conducted Emission Test

Test Condition and Setup	7
Conducted Test Placement	8

Chapter 3 Radiated Emission Test

Test Condition and Setup	9
Radiated Test Placement	10

Appendix A:

Conducted test result.....	11
----------------------------	----

Appendix B:

Radiated test result.....	12
---------------------------	----

Chapter 1 Introduction

Description of EUT:

This Fax/Data modem card is a data communication device. It is designed to install in the personal computer and makes your data equipment available to transmit and receive data via the public telephone network.

Connections of EUT:

- (1) Put the EUT into a personal computer's bus and screw it.
- (2) Line jack of EUT connects with a line cable to the PABX located remotely.
- (3) Phone jack of EUT connects with a telephone set.

Test method:


Pretest was found that the emission of operating mode is worse than standby mode. So, The final test is made at the operating mode.

During testing, the EUT was operated at "transmitting" and "receiving" mode simultaneously.

While testing, the transmitting rate was set to "AUTO" which means it transmitted the test file depending on the telephone line condition, normally the operating rate is the highest speed. The test placement as the photographs showed is the worst case emission placed. (If the emission is close to the ambient, the resolution BW and view resolution will be reduced and the data will be recorded by detection of maximum hold peak mode.)

The testing configuration of test setup is showing in the next page.

Configuration of test setup



Connections:

PC:

- *Serial A port --- a external modem
 - *Serial B port --- a 76 cm shielded RS232 cable
 - *Printer port --- a Printer
 - *Keyboard port --- a Keyboard
 - *Mouse port --- a Mouse
 - *Monitor port --- a Monitor
- (Each port on PC is connected with suitable device)

EUT:

- *Line jack --- via 15 m RJ11C cable to PABX located remotely
- *Phone jack --- via a 7 feet RJ11C cable to telephone set

List of support equipment**Conducted (Radiated) test:****PC : HP**

Model : Vectra VE2

Serial No. : SG61803151 (SG61802786)

FCC ID : HCJVECTRAVL5

Power type : AC 230 VAC, switching

Power cord : Non-Shielded, 1.7m long, Plastic, no ferrite core

Monitor : HP

Model No. : D2084 (D2813)

Serial No. : KR4397004 (TW63803597)

FCC ID : CSYSC-428VSP (A3KM043)

Power type : 230VAC, Switching

Power cord : Non-Shielded, 3m long, no ferrite core

Data cable : Shielded, 1.8m long, with ferrite core

Keyboard : HP

Model No. : C3757 #ABO (C3346A #ABO)

Serial No. : C3757-60423 (C3346-60231)

FCC ID : CIGE03614

Power type : By PC

Data cable : Shielded, 1.8m long, with ferrite core

Mouse : Hewlett Packard Mouse

Model No. : C3751B

Serial No. : LCA52707170

FCC ID : DZL210582

Power type : Powered by PC

Power cable : Non – Shielded. 5.5' long, Plastic hoods, No ferrite bead

Printer : EPSON
Model No. : P78PA (P70RA)
Serial No. : 0EE0014030 (10010386)
FCC ID : BKM9A8P70RA
Power type : Linear
Power cord : Non-shielded, 2m long, no ferrite core
Data cable : Shielded, 1.84m long, no ferrite core (1.7m)

Modem : ACEEX
Model No. : XDM-9624
FCC ID : IFAXDM-9624
Power type : Linear
Power cord : Non-shielded, 1.9m long, no ferrite cord
Data cable : RS232, Shielded, 1.2m long, no ferrite core
RJ11C x 2, 7' long non-shielded, no ferrite core

PABX : King Design
Model No. : KD8705-A
Serial No. : GV101101186
Power type : 110 VAC 50/60Hz
Power cord : Non - Shielded

Chapter 2 Conducted emission test

Test condition and setup:

All the equipment is placed and setup according to the ANSI C63.4 - 1992. The EUT is assembled on a wooden table which is 80 cm high, is placed 40 cm from the back-wall which is a vertical conducting plane. One LISN is for EUT, The other LISN is for support equipment. They are all placed on the conductive ground. The EUT's LISN connect a line switch box for selecting L1 or L2, then connect to a preamplifier and spectrum.

The spectrum scans from 150KHz to 30MHz. Conducted emission levels are detected at max. peak mode. But if the max. peak mode failed or over average limit, it will be measured by average detection mode.

While testing, there is a worst-emission plot printed at peak detection mode, and there are more than 6 highest emissions relative to limit recorded. The plot is kept as the original data, not included in test report.

List of test Instrument:

Instrument Name	Model No.	Brand	Serial No.	Calibration Date	
				Last time	Next time
Spectrum analyzer	8591EM	H P	3619A00821	10/06/97	10/06/98
LISN (EUT)	3825/2	EMCO	9411-2284	05/15/98	05/15/99
LISN (Support E.)	3825/2	EMCO	9210-2007	05/15/98	05/15/99
Preamplifier	8447F	H P	2944A03706	05/15/98	05/15/99
Line switch box	AC1-003	TRC	-----	05/15/98	05/15/99
Line selector	AC1-002	TRC	-----	05/15/98	05/15/99

The level of confidence of 95%, the uncertainty of measurement of conducted emission is ± 2.4 dB.

Test Result : Pass (Appendix A)

Chapter 3 Radiated emission test

Test condition and setup:

Pretest: Prior to the final test (OATS test), the EUT is placed in a shielded closure, GTEM, and scan from 30MHz to 1GHz. This is done to ensure the radiation exactly emits from the EUT.

Final test: Final radiation measurements is made on a **10 - meter**, open-field test site. The EUT is placed on a nonconductive table which is 0.8 cm height, the top surface is 1.0 x 1.5 meter. All the placement is according to ANSI C63.4 - 1992.

The spectrum is examined from 30 MHz to 1000 MHz measured by HP spectrum.

The EMCO whole range Antenna is used to measure frequency from 30 MHz to 1GHz. The final test is used the spectrum HP 8591A.

Measure more than six top marked frequencies generated from pretest by computer step by step at each frequency. The EUT is rotated 360 degrees, and antenna is raised and lowered from 1 to 4 meters to find the maximum emission levels. The antenna is used with both horizontal and vertical polarization.

Appropriated preamplifier which is made by TRC is used for improving sensitivity and precautions is taken to avoid overloading. The spectrum analyzer's 6dB bandwidth is set to 120 KHz, and the EUT is measured at quasi-peak mode.

If the emission is close to the frequency band of ambient, the data will be rechecked by the tester and the corrected data will be written in the test data sheet. If the emission is just within the ambient, the data from GTEM will be taken as the final data.

List of test Instrument:

Instrument name	Model No.	Brand	Serial No.	Calibration Date	
				Last	Next
Spectrum analyzer	8568B	H P	3004A18617	05/15/98	05/15/99
Quasi-peak Adapter	85650A	H P	2521A00984	05/15/98	05/15/99
RF Pre-selector	85685A	H P	2947A01011	05/15/98	05/15/99
Spectrum analyzer	8591A	H P	2919A00263	01/07/98	01/07/99
Antenna (30M-2G Hz)	3142	EMCO	1296	06/10/98	06/10/99
Open test side (Antenna, Amplify, cable calibrated together)				05/15/98	05/15/99

The level of confidence of 95%, the uncertainty of measurement of radiated emission is ± 4.96 dB.

Test Result: Pass (Appendix B)

Appendix A**Conducted Emission Test Result:**

Testing room : Temperature : 25 ° C

Humidity : 60 % RH

Line 1

Frequency (KHz)	Amplitude (dBuV)	Limit (dBuV)	Margin (dB)
3240.00	30.34	46.00	-15.66
3350.00	29.99	46.00	-16.01
3540.00	33.22	46.00	-12.78
3730.00	32.48	46.00	-13.52
3840.00	32.94	46.00	-13.06
4030.00	31.73	46.00	-14.27
10590.00	35.41	50.00	-14.59
11260.00	37.85	50.00	-12.15
11930.00	37.49	50.00	-12.51
12450.00	34.79	50.00	-15.21

Line 2

Frequency (KHz)	Amplitude (dBuV)	Limit (dBuV)	Margin (dB)
198.00	41.88	54.63	-12.75
3240.00	31.84	46.00	-14.16
3540.00	32.99	46.00	-13.01
3660.00	32.93	46.00	-13.07
3860.00	33.27	46.00	-12.73
10660.00	35.31	50.00	-14.69
11040.00	38.95	50.00	-11.05
11260.00	36.65	50.00	-13.35
11930.00	37.42	50.00	-12.58
12890.00	36.39	50.00	-13.61

* The reading amplitudes are all under average limit.

Appendix B

Radiated Emission Test Result: (Horizontal)

Test Conditions:

Testing room : Temperature : 25 ° C

Humidity : 73 % RH

Testing site : Temperature : 32 ° C

Humidity : 85 % RH

Frequency	Reading Amplitude	Ant. Height	Table	Correction Factors	Corrected Amplitude	Class B limit	Margin
MHz	dBuV	m	degree	dB/m	dBuV/m	dBuV/m	dB

44.230	41.51	3.02	217	-21.27	20.24	30.00	-9.76
66.320	39.19	3.02	211	-25.03	14.16	30.00	-15.84
132.720	44.37	1.00	175	-25.15	19.22	30.00	-10.78
154.840	47.99	3.02	30	-23.36	24.63	30.00	-5.37
221.200	45.58	3.02	317	-20.18	25.40	30.00	-4.60
232.110	46.18	3.02	270	-19.56	26.62	37.00	-10.38
265.440	46.38	3.02	120	-18.37	28.01	37.00	-8.99
287.560	45.58	3.02	207	-17.38	28.20	37.00	-8.80
309.680	35.36	3.02	225	-15.65	19.71	37.00	-17.29
331.800	38.89	3.02	319	-14.64	24.25	37.00	-12.75
530.900	33.59	1.00	214	-10.39	23.20	37.00	-13.80
597.240	36.32	1.00	207	-12.94	23.38	37.00	-13.62
729.920	35.88	1.00	210	-13.23	22.65	37.00	-14.35

Note:

1. Margin = Amplitude - limit, *if margin is minus means under limit.*

2. Corrected Amplitude = Reading Amplitude + Correction factor

3. Correction factor = Antenna factor + (Cable Loss - Amplitude gain)

(For example : 30MHz correction factor = 15.5 + (-15.26) = 0.24 dB/m)

Radiated Emission Test Result: (Vertical)

Frequency	Reading Amplitude	Ant. Height	Table	Correction Factors	Corrected Amplitude	Class B limit	Margin
MHz	dBuV	m	degree	dB/m	dBuV/m	dBuV/m	dB

44.230	43.56	1.00	226	-21.27	22.29	30.00	-7.71
66.320	43.35	3.02	108	-25.03	18.32	30.00	-11.68
132.720	43.65	1.00	3	-25.15	18.50	30.00	-11.50
154.840	40.69	1.00	38	-23.36	17.33	30.00	-12.67
221.200	37.22	1.00	309	-20.18	17.04	30.00	-12.96
232.110	43.05	1.00	98	-19.56	23.49	37.00	-13.51
265.440	45.05	1.00	253	-18.37	26.68	37.00	-10.32
287.560	44.19	1.00	89	-17.38	26.81	37.00	-10.19
309.680	40.24	1.00	153	-15.65	24.59	37.00	-12.41
331.800	41.85	1.00	3	-14.64	27.21	37.00	-9.79
530.900	33.95	1.00	59	-10.39	23.56	37.00	-13.44
597.240	35.32	3.02	219	-12.94	22.38	37.00	-14.62
729.920	36.19	3.02	178	-13.23	22.96	37.00	-14.04
