



SENTON

Choose certainty.  
Add value.

September 9, 2010

## Prüfbericht / Test Report

Nr. / No. 69558-02103 (Edition 2)

Applicant: ELDAT GmbH

Type of equipment: Necklace Transmitter

Type designation: RT26/27/28 916,5 MHz FSK

Order No.: 4500004046

Test standards: FCC Code of Federal Regulations,  
CFR 47, Part 15,  
Sections 15.205, 15.207, 15.215 and 15.249

Industry Canada Radio Standards Specifications  
RSS-Gen Issue 2, Section 7.2.2 and  
RSS-210 Issue 7, Sections 2.2, A2.9 (Category I Equipment)

**Note:**

The test data of this report is related only to the individual item which has been tested. This report shall not be reproduced except in full extent without the written approval of the testing laboratory.

## Table of Contents

1	Description of the Equipment Under Test (EUT) .....	3
2	Administrative Data .....	4
3	Identification of the Test Laboratory .....	5
4	Summary .....	6
5	Operation Mode and Configuration of EUT .....	7
6	Measurement Procedures .....	8
6.1	Bandwidth Measurements .....	8
6.2	Radiated Emission Measurement 9 kHz to 30 MHz .....	9
6.3	Radiated Emission in Fully or Semi Anechoic Room .....	11
6.4	Radiated Emission at Alternative Test Site .....	13
7	Photographs Taken During Testing .....	15
8	Test Results .....	22
8.1	Occupied Bandwidth .....	24
8.2	Bandwidth of the Emission .....	28
8.3	Designation of Emissions .....	30
8.4	Restricted Bands of Operation .....	31
8.5	Radiated Emission Measurement 9 kHz to 30 MHz .....	33
8.6	Radiated Emission Measurement 30 MHz to 10 GHz .....	34
8.7	Exposure of Humans to RF Fields .....	36
9	Referenced Regulations .....	38
10	Revision History .....	40
11	Charts taken during testing .....	41

## 1 Description of the Equipment Under Test (EUT)

General data of EUT	
Type designation <sup>1</sup> :	RT26/27/28 916,5 MHz FSK
Parts <sup>2</sup> :	
Serial number(s):	DUT1
Manufacturer:	ELDAT GmbH
Type of equipment:	Necklace Transmitter
Version:	As received
FCC ID:	
Additional parts/accessories:	
Technical data of EUT	
Application frequency range:	902 MHz - 928 MHz
Frequency range:	916.5 MHz
Operating frequency:	916.5 MHz
Type of modulation:	FSK
Pulse train:	---
Pulse width:	---
Number of RF-channels:	1
Channel spacing:	---
Designation of emissions <sup>3</sup> :	196KF1D
Type of antenna:	Integrated on printed board
Size/length of antenna:	8 cm
Connection of antenna:	<input type="checkbox"/> detachable <input checked="" type="checkbox"/> not detachable
Type of power supply:	Battery supply
Specifications for power supply:	nominal voltage: 3.0 V

<sup>1</sup> Type designation of the system if EUT consists of more than one part.

<sup>2</sup> Type designations of the parts of the system, if applicable.

<sup>3</sup> Also known as "Class of Emission".

## 2 Administrative Data

### Application details

Applicant (full address):	ELDAT GmbH Im Gewerbepark 14 D-15711 Königs Wusterhausen
Contact person:	Mr. Andreas Eidam
Order number:	4500004046
Receipt of EUT:	May 26, 2010
Date(s) of test:	May 31, 2010
Note(s):	

### Report details

Report number:	69558-02103
Edition:	2
Issue date:	September 9, 2010

### 3 Identification of the Test Laboratory

Details of the Test Laboratory	
Company name:	TÜV SÜD SENTON GmbH
Address:	Aeussere Fruehlingstrasse 45 D-94315 Straubing Germany
Laboratory accreditation:	DAR-Registration No. DAT-PL-171/94-03
Contact person:	Mr. Johann Roidt
	Phone: +49 9421 5522-0 Fax: +49 9421 5522-99

## 4 Summary

### Summary of test results

The tested sample complies with the requirements set forth in the  
**Code of Federal Regulations CFR 47, Part 15, Sections 15.205, 15.215 and 15.249**  
of the Federal Communication Commission (FCC) and the  
**Radio Standards Specifications  
RSS-210 Issue 7, Sections 2.2, A2.9 (Category I Equipment)**  
of Industry Canada (IC).

### Personnel involved in this report

Laboratory Manager:



Mr. Johann Roidt

Responsible for testing:



Mr. Martin Steindl

Responsible for test report:

Mr. Martin Steindl

## 5 Operation Mode and Configuration of EUT

### Operation Mode(s)

The applicant provided a test sample with continuous transmitting mode for testing purposes.

### Configuration(s) of EUT

The EUT was configured as stand alone device. All emission-testings were performed in three orthogonal axis.

### List of ports and cables

Port	Description	Classification <sup>4</sup>	Cable type	Cable length

### List of devices connected to EUT

Item	Description	Type Designation	Serial no. or ID	Manufacturer

### List of support devices

Item	Description	Type Designation	Serial no. or ID	Manufacturer

<sup>4</sup> Ports shall be classified as ac power, dc power or signal/control port

## 6 Measurement Procedures

### 6.1 Bandwidth Measurements

<b>Measurement Procedure:</b>	
Rules and specifications:	CFR 47 Part 2, section 2.202(a) CFR 47 Part 15, section 15.215(c) IC RSS-Gen Issue 2, sections 4.6.1 and 4.6.2 IC RSS-210 Issue 7, section A1.1.3 ANSI C63.4, annex H.6
Guide:	ANSI C63.4 / IC RSS-Gen Issue 2, sections 4.6.1 and 4.6.2
Measurement setup:	<input type="checkbox"/> Conducted: See below <input checked="" type="checkbox"/> Radiated: Radiated Emission in Fully or Semi Anechoic Room (6.3)
<p>If antenna is detachable bandwidth measurements shall be performed at the antenna connector (conducted measurement) when the transmitter is adjusted in accordance with the tune-up procedure, if applicable. The RF output terminals are connected to a spectrum analyzer. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable.</p> <p>If radiated measurements are performed the same test setups and instruments are used as with radiated emission measurements for the appropriate frequency range.</p> <p>The analyzer settings are specified by the test description of the appropriate test record(s).</p>	

## 6.2 Radiated Emission Measurement 9 kHz to 30 MHz

### Measurement Procedure:

Rules and specifications: CFR 47 Part 15, sections 15.215(b) and 15.249(d)  
 IC RSS-210 Issue 7, section A2.9(b)

Guide: ANSI C63.4

Radiated emission in the frequency range 9 kHz to 30 MHz is measured using an active loop antenna. First the whole spectrum of emission caused by the equipment is recorded at a distance of 3 meters in a fully or semi anechoic room with the detector of the spectrum analyzer or EMI receiver set to peak. This configuration is also used for recording the spectrum of intentional radiators.


Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

If worst case emission of the EUT cannot be recorded with EUT in standard position and loop antenna in vertical polarization the EUT (or the radiating part of the EUT) is rotated by 90 degrees instead of changing the loop antenna to horizontal polarization. This procedure is selected to minimize the influence of the environment (e.g. effects caused by the floor especially with longer distances).

Final measurement is performed at a test distance D of 30 meters using an open field test site. In case the regulation requires testing at other distances, the result is extrapolated by either making measurements at an additional distance D of 10 meters to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). In cases of very low emissions measurements are performed at shorter distances and results are extrapolated to the required distance. The provisions of CFR 47 Part 15 sections 15.31(d) and (f)(2) apply. According to CFR 47 Part 15 section 15.209(d) final measurement is performed with detector function set to quasi-peak except for the frequency bands 9 to 90 kHz and 110 to 490 kHz where, for non-pulsed operation, average detector is employed.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.



Test instruments used:

Type	Designation	Inv.-no.	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/> Spectrum analyzer	FSP30	1666	100036	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver	ESMI	1569	839379/013 839587/006	Rohde & Schwarz
<input checked="" type="checkbox"/> Test receiver	ESHS 10	1028	860043/016	Rohde & Schwarz
<input type="checkbox"/> Preamplifier	CPA9231A	1651	3393	Schaffner
<input checked="" type="checkbox"/> Loop antenna	HFH2-Z2	1016	882964/1	Rohde & Schwarz
<input checked="" type="checkbox"/> Fully anechoic room	No. 2	1452	---	Albatross
<input type="checkbox"/> Semi anechoic room	No. 3	1453	---	Siemens
<input type="checkbox"/> Semi anechoic room	No. 8	2057	---	Albatross

### 6.3 Radiated Emission in Fully or Semi Anechoic Room

#### Measurement Procedure:

Rules and specifications: CFR 47 Part 15, sections 15.215(b) and 15.249  
IC RSS-210 Issue 7, section A2.9

Guide: ANSI C63.4

Radiated emission in fully or semi anechoic room is measured in the frequency range from 30 MHz to the maximum frequency as specified in CFR 47 Part 15 section 15.33.

Measurements are made in both the horizontal and vertical planes of polarization using a spectrum analyzer with the detector function set to peak and resolution as well as video bandwidth set to 100 kHz (below 1 GHz) or 1 MHz (above 1 GHz).

Testing up to 1 GHz is performed with a linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna"). For testing above 1 GHz horn antennas are used.


All tests below 8.2 GHz are performed at a test distance D of 3 meters. For higher frequencies the test distance may be reduced (e.g. to 1 meter) due to the sensitivity of the measuring instrument(s) and the test results are calculated according to CFR 47 Part 15 section 15.31(f)(1) using an extrapolation factor of 20 dB/decade. If required, preamplifiers are used for the whole frequency range. Special care is taken to avoid overload, using appropriate attenuators and filters, if necessary.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

During testing the EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

For final testing below 1 GHz a semi anechoic room complying with the NSA requirements of ANSI C63.4 for alternative test sites is used (see 6.4). If prescans are recorded in fully anechoic room they are indicated appropriately.




Test instruments used:

Type	Designation	Inv.-no.	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/> Spectrum analyzer	FSP30	1666	100036	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver	Cabin no. 3	2010	101018	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver		2044	100232	Rohde & Schwarz
<input type="checkbox"/> EMI test receiver		1569	839379/013 839587/006	Rohde & Schwarz
<input checked="" type="checkbox"/> Preamplifier	Cabin no. 2	1651	3393	Schaffner
<input type="checkbox"/> Preamplifier		1142	13120026	Advantest
<input checked="" type="checkbox"/> Preamplifier (1 - 8 GHz)	AFS3-00100800-32-LN	1684	847743	Miteq
<input type="checkbox"/> Preamplifier (0.5 - 8 GHz)	AMF-4D-005080-25-13P	1685	860149	Miteq
<input checked="" type="checkbox"/> Preamplifier (8 - 18 GHz)	ACO/180-3530	1484	32641	CTT
<input type="checkbox"/> External Mixer	WM782A	1576	845881/005	Tektronix
<input type="checkbox"/> Harmonic Mixer Accessories	FS-Z30	1577	624413/003	Rohde & Schwarz
<input checked="" type="checkbox"/> Trilog antenna	Cabin no. 2	2058	9163-408	Schwarzbeck
<input checked="" type="checkbox"/> Horn antenna		3115	1516	EMCO
<input type="checkbox"/> Horn antenna	3160-03	1010	9112-1003	EMCO
<input type="checkbox"/> Horn antenna	3160-04	1011	9112-1001	EMCO
<input checked="" type="checkbox"/> Horn antenna	3160-05	1012	9112-1001	EMCO
<input checked="" type="checkbox"/> Horn antenna	3160-06	1013	9112-1001	EMCO
<input checked="" type="checkbox"/> Horn antenna	3160-07	1014	9112-1008	EMCO
<input type="checkbox"/> Horn antenna	3160-08	1015	9112-1002	EMCO
<input type="checkbox"/> Horn antenna	3160-09	1265	9403-1025	EMCO
<input type="checkbox"/> Horn antenna	3160-10	1575	399185	EMCO
<input checked="" type="checkbox"/> Fully anechoic room	No. 2	1452	---	Albatross
<input type="checkbox"/> Semi anechoic room	No. 3	1453	---	Siemens
<input type="checkbox"/> Semi anechoic room	No. 8	2057	---	Albatross

## 6.4 Radiated Emission at Alternative Test Site

<b>Measurement Procedure:</b>	
Rules and specifications:	CFR 47 Part 15, sections 15.215(b) and 15.249 IC RSS-210 Issue 7, section A2.9
Guide:	ANSI C63.4
<p>Radiated emission in the frequency range 30 MHz to 1 GHz is measured within a semi-anechoic room with groundplane complying with the NSA requirements of ANSI C63.4 for alternative test sites. A linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna") is used. The measurement bandwidth of the test receiver is set to 120 kHz with quasi-peak detector selected.</p> <p>If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.</p> <p>Hand-held or body-worn devices are tested in the position producing the highest emission relative to the limit as verified by prescans in fully anechoic room.</p> <p>If no prescan in a fully anechoic room is used first a peak scan is performed in four positions to get the whole spectrum of emission caused by EUT with the measuring antenna raised and lowered from 1 to 4 m to find table position, antenna height and antenna polarization for the maximum emission levels.</p> <p>Data reduction is applied to these results to select those levels having less margin than 10 dB to or exceeding the limit using subranges and limited number of maximums. Further maximization is following.</p> <p>With detector of the test receiver set to quasi-peak final measurements are performed immediately after frequency zoom (for drifting disturbances) and maximum adjustment.</p> <p>Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.</p> <p>In cases where prescans in a fully anechoic room are taken (e. g. if EUT is operating for a short time only or battery is discharged quickly) final measurements with quasi-peak detector are performed manually at frequencies indicated by prescan with EUT rotating all around and receiving antenna raising and lowering within 1 meter to 4 meters to find the maximum levels of emission.</p> <p>Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.</p> <p>For measuring emissions of intentional radiators and receivers a test distance D of 3 meters is selected. Testing of unintentional radiators is performed at a distance of 10 meters. If limits specified for 3 meters shall be used for measurements performed at 10 meters distance the limits are calculated according to CFR 47 Part 15 section 15.31(d) and (f)(1) using an inverse linear-distance extrapolation factor of 20 dB/decade.</p>	




Alternate test site (semi anechoic room)

Test instruments used:

Type	Designation	Inv.-no.	Serial No. or ID	Manufacturer
<input checked="" type="checkbox"/> EMI test receiver	ESU8	2044	100232	Rohde & Schwarz
<input checked="" type="checkbox"/> Trilog antenna Cabin no. 8	VULB 9163	1802	9163-214	Schwarzbeck
<input checked="" type="checkbox"/> Semi anechoic room	No. 8	2057	---	Albatross

## 7      Photographs Taken During Testing

### Test setup for radiated emission measurement 9 kHz – 30 MHz



## Test setup for radiated emission measurement (fully anechoic room)



## Test setup for radiated emission measurement (alternate test site)





**Test setup for radiated emission measurement  
(alternate test site) - continued -**



**Test setup for radiated emission measurement  
(alternate test site) - continued -**



**Test setup for radiated emission measurement  
(alternate test site) - continued -**



## 8 Test Results

<b>FCC CFR 47 Parts 2 and 15</b>			
<i>Section(s)</i>	<i>Test</i>	<i>Page</i>	<i>Result</i>
2.1046(a)	Conducted output power	---	Not applicable
2.202(a)	Occupied bandwidth	24	Recorded
15.215(c)	Bandwidth of the emission	28	Test passed
2.201, 2.202	Class of emission	30	Calculated
15.35(c)	Pulse train measurement for pulsed operation	---	Not applicable
15.205(a)	Restricted bands of operation	31	Test passed
15.207	Conducted AC powerline emission 150 kHz to 30 MHz	---	Not applicable
15.205(b) 15.249	Radiated emission 9 kHz to 30 MHz	33	Test passed
15.205(b) 15.215(b) 15.249	Radiated emission 30 MHz to 10 GHz	34	Test passed

### IC RSS-Gen Issue 2

Section(s)	Test	Page	Result
4.8	Transmitter output power (conducted)	---	Not applicable
4.6.1	Occupied Bandwidth	24	Recorded
3.2(h), 8	Designation of emissions	30	Calculated
4.5	Pulsed operation	---	Not applicable
7.2.2	Transmitter AC power lines conducted emissions 150 kHz to 30 MHz	---	Not applicable
5.5	Exposure of Humans to RF Fields	36	Exempted from SAR and RF evaluation

### IC RSS-210 Issue 7

Section(s)	Test	Page	Result
2.2(a)	Restricted bands and unwanted emission frequencies	31	Test passed
2.2(b)(c), 2.6 A2.9	Unwanted emissions 9 kHz to 30 MHz	33	Test passed
2.2(b)(c), 2.6 A2.9	Unwanted emissions 30 MHz to 10 GHz	34	Test passed

## 8.1 Occupied Bandwidth

Rules and specifications:	CFR 47 Part 2, section 2.202(a) ANSI C63.4, annex H.6								
Guide:	ANSI C63.4								
Description:	<p>The occupied bandwidth according to CFR 47 Part 2, section 2.202(a), is measured as the 99% emission bandwidth, i.e. below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5% of the total mean power radiated by a given emission.</p> <p>The occupied bandwidth according to ANSI C63.4, annex H.6; is measured as the frequency range defined by the points that are 26 dB down relative to the maximum level of the modulated carrier.</p> <p>The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:</p> <table border="1"><thead><tr><th>Fundamental frequency</th><th>Minimum resolution bandwidth</th></tr></thead><tbody><tr><td>9 kHz to 30 MHz</td><td>1 kHz</td></tr><tr><td>30 MHz to 1000 MHz</td><td>10 kHz</td></tr><tr><td>1000 MHz to 40 GHz</td><td>100 kHz</td></tr></tbody></table> <p>The video bandwidth shall be at least three times greater than the resolution bandwidth.</p>	Fundamental frequency	Minimum resolution bandwidth	9 kHz to 30 MHz	1 kHz	30 MHz to 1000 MHz	10 kHz	1000 MHz to 40 GHz	100 kHz
Fundamental frequency	Minimum resolution bandwidth								
9 kHz to 30 MHz	1 kHz								
30 MHz to 1000 MHz	10 kHz								
1000 MHz to 40 GHz	100 kHz								
Measurement procedure:	Bandwidth Measurements (6.1)								

Comment:


Date of test:

Test site:

May 31, 2010

Fully anechoic room, cabin no. 2

### Occupied Bandwidth (99 %):



Date: 31.MAY.2010 13:04:08


Occupied Bandwidth (99 %): **610 kHz**

## Occupied Bandwidth (continued)

Rules and specifications:	IC RSS-Gen Issue 2, section 4.6.1
Guide:	IC RSS-Gen Issue 2, section 4.6.1
Description:	<p>If not specified in the applicable RSS the occupied bandwidth is measured as the 99% emission bandwidth.</p> <p>The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth.</p> <p>The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is also recorded. The span between the two recorded frequencies is the occupied bandwidth.</p>
Measurement procedure:	Bandwidth Measurements (6.1)

Comment:	
Date of test:	May 31, 2010
Test site:	Fully anechoic room, cabin no. 2

### Occupied Bandwidth (99 %):




Date: 31.MAY.2010 13:04:08

Occupied Bandwidth (99 %): **610 kHz**

## 8.2 Bandwidth of the Emission

Rules and specifications:	CFR 47 Part 15, section 15.215(c)								
Guide:	ANSI C63.4								
Description:	<p>The 20 dB bandwidth of the emission is measured as the frequency range defined by the points that are 20 dB down relative to the maximum level of the modulated carrier.</p> <p>For intentional radiators operating under the alternative provisions to the general emission limits the requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.</p> <p>The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:</p> <table border="1"> <thead> <tr> <th>Fundamental frequency</th> <th>Minimum resolution bandwidth</th> </tr> </thead> <tbody> <tr> <td>9 kHz to 30 MHz</td> <td>1 kHz</td> </tr> <tr> <td>30 MHz to 1000 MHz</td> <td>10 kHz</td> </tr> <tr> <td>1000 MHz to 40 GHz</td> <td>100 kHz</td> </tr> </tbody> </table> <p>The video bandwidth shall be at least three times greater than the resolution bandwidth.</p>	Fundamental frequency	Minimum resolution bandwidth	9 kHz to 30 MHz	1 kHz	30 MHz to 1000 MHz	10 kHz	1000 MHz to 40 GHz	100 kHz
Fundamental frequency	Minimum resolution bandwidth								
9 kHz to 30 MHz	1 kHz								
30 MHz to 1000 MHz	10 kHz								
1000 MHz to 40 GHz	100 kHz								
Measurement procedure:	Bandwidth Measurements (6.1)								

Comment:	
Date of test:	May 31, 2010
Test site:	Fully anechoic room, cabin no. 2



Date: 31.MAY.2010 13:02:46

Permitted frequency band:	<b>902 MHz - 928 MHz</b>	
20 dB bandwidth:	<b>196 kHz</b>	
Carrier frequency stability:	<input type="checkbox"/> specified	<input checked="" type="checkbox"/> not specified
Maximum frequency tolerances:	---	
Bandwidth of the emission:	<b>196 kHz</b>	<b>within permitted frequency band<sup>5</sup>:</b> <input checked="" type="checkbox"/> yes <input type="checkbox"/> no

Test Result: Test passed

<sup>5</sup> If a frequency stability is not specified, it is recommended that the fundamental emission is kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### 8.3 Designation of Emissions

Rules and specifications:	CFR 47 Part 2, sections 2.201 and 2.202 IC RSS-Gen Issue 2, sections 3.2(h) and 8
Guide:	ANSI C63.4 / TRC-43

Type of modulation:	Frequency Shift Keying (FSK)
---------------------	------------------------------


$B_n = \text{Necessary Bandwidth}$	$B_n = 2DK + B$
$D = \text{Peak deviation}$	$D = 90 \text{ kHz}$
$K = \text{Overall numerical factor}$	$K = 1$
$B = \text{Modulation rate}$	$B = \dots \text{ kHz}$
Calculation:	$B_n = 2 \cdot 90 \text{ kHz} \cdot 1 + 16 \text{ kHz} = 196 \text{ kHz}$

Designation of Emissions:	<b>196KF1D</b>
---------------------------	----------------

## 8.4 Restricted Bands of Operation

Rules and specifications:	CFR 47 Part 15, section 15.205(a) IC RSS-210 Issue 7, section 2.2(a)
Guide:	ANSI C63.4
Limit:	Only spurious emissions are permitted in any of the frequency bands listed in CFR 47 Part 15, section 15.205(a) or IC RSS-210 Issue 7, section 2.2(a).
Measurement procedure:	Radiated Emission in Fully or Semi Anechoic Room (6.3)

Comment:	
Date of test:	May 31, 2010
Test site:	Fully anechoic room, cabin no. 2
Test distance:	3 meters



Date: 31.MAY.2010 13:06:22

Test Result:

Test passed

## 8.5 Radiated Emission Measurement 9 kHz to 30 MHz

Rules and specifications:	CFR 47 Part 15, sections 15.215(b) and 15.249(d) IC RSS-210 Issue 7, section A2.9(b)			
Guide:	ANSI C63.4			
Limit:	Frequency of Emission (MHz)	Field Strength ( $\mu$ V/m)	Field Strength (dB $\mu$ V/m)	Measurement Distance d (meters)
	0.009 - 0.490	2400/F(kHz)	67.6 - 20 · log(F(kHz))	300
	0.490 - 1.705	24000/F(kHz)	87.6 - 20 · log(F(kHz))	30
	1.705 - 30.000	30	29.5	30
	Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.			
Measurement procedure:	Radiated Emission Measurement 9 kHz to 30 MHz (6.2)			

Comment:	
Date of test:	May 31, 2010
Test site:	Open field test site

Test Result:	Test passed
--------------	-------------

No emissions above noise level detected

### Sample calculation of final values:

$$\begin{aligned}
 \text{Extrapolation Factor (dB)} &= (\text{Log}(d) - \text{Log}(d_1)) \cdot \text{Extrapolation Factor (dB/decade)} \\
 \text{Final Value (dB}\mu\text{V/m)} &= \text{Reading Value } d_1 \text{ (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\
 &\quad + \text{Extrapolation Factor (dB)} + \text{Pulse Train Correction (dB)}
 \end{aligned}$$

Note: Extrapolation factor (dB) and final value (dB $\mu$ V/m) are relating to distance d.

## 8.6 Radiated Emission Measurement 30 MHz to 10 GHz

Rules and specifications:	CFR 47 Part 15, sections 15.215(b) and 15.249 IC RSS-210 Issue 7, section A2.9		
Guide:	ANSI C63.4		
Limit:	Frequency of Emission (MHz)	Field Strength ( $\mu$ V/m)	Field Strength (dB $\mu$ V/m)
	30 - 88	100	40.0
	88 - 216	150	43.5
	216 - 960	200	46.0
	Above 960	500	54.0
	Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.		
Measurement procedures:	Radiated Emission in Fully or Semi Anechoic Room (6.3) Radiated Emission at Alternative Test Site (6.4)		

Comment:		
Date of test:	May 31, 2010	
Test site:	Frequencies $\leq$ 1 GHz: Open field test site Frequencies $>$ 1 GHz: Fully anechoic room, cabin no. 2	
Test distance:	Frequencies $\leq$ 8.2 GHz: 3 meters Frequencies $>$ 8.2 GHz: 1 meters	

Test Result:	Test passed
--------------	-------------

Frequency (MHz)	Antenna Polarization	Detector	Receiver Reading (dB $\mu$ V)	Correction Factor (dB/m)	Pulse Train Correction (dB)	Final Value (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
916.500	horizontal	Quasi-Peak	66.0	24.7		90.7	94.0	3.3
1834.000	horizontal	Peak	10.7	31.4		42.1	54.0	11.9
2752.000	vertical	Peak	9.7	34.8		44.5	54.0	9.5
3670.000	horizontal	Peak	12.6	38.3		50.9	54.0	3.1
4584.600	horizontal	Peak	13.2	34.1		47.3	54.0	6.7
5500.400	vertical	Peak	12.0	34.9		47.0	54.0	7.1
5504.200	vertical	Peak	8.2	34.9		43.1	54.0	10.9
6414.000	horizontal	Peak	16.6	38.3		54.9	74.0	19.2
6415.220	horizontal	Average	15.5	38.3		53.7	54.0	0.3
7335.200	vertical	Peak	8.4	39.1		47.5	54.0	6.6
8246.800	horizontal	Peak	9.5	43.2		52.7	63.5	10.8
9164.800	vertical	Peak	7.7	43.8		51.5	63.5	12.0
9168.400	horizontal	Peak	9.1	43.8		52.9	63.5	10.6

**Sample calculation of final values:**

$$\text{Final Value (dB}\mu\text{V/m)} = \text{Reading Value (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ + \text{Pulse Train Correction (dB)}$$

## 8.7 Exposure of Humans to RF Fields

Rules and specifications:	IC RSS-Gen Issue 2, section 5.5
Guide:	IC RSS-102 Issue 4, section 2.5

Exposure of Humans to RF Fields		Applicable	Declared by applicant	Measured	Exemption
The antenna is					
<input type="checkbox"/> detachable <p>The conducted output power (CP in watts) is measured at the antenna connector:</p> $CP = \dots \text{ W}$ <p>The effective isotropic radiated power (EIRP in watts) is calculated using</p> <p><input type="checkbox"/> the numerical antenna gain: <math>G = \dots</math></p> $EIRP = G \cdot CP \Rightarrow EIRP = \dots \text{ W}$ <p><input type="checkbox"/> the field strength<sup>6</sup> in V/m: <math>FS = \dots \text{ V/m}</math></p> $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = \dots \text{ W}$ <p>with:</p> <p>Distance between the antennas in m: <math>D = \dots \text{ m}</math></p>					
<input checked="" type="checkbox"/> not detachable <p>A field strength measurement is used to determine the effective isotropic radiated power (EIRP in watts) given by<sup>6</sup>:</p> $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = 352.5 \mu\text{W}$ <p>with:</p> <p>Field strength in V/m: <math>FS = 34.28 \text{ mV/m}</math></p> <p>Distance between the two antennas in m: <math>D = 3 \text{ m}</math></p>					
Selection of output power					
<p>The output power TP is the higher of the conducted or effective isotropic radiated power (e.i.r.p.):</p> $TP = 352.5 \mu\text{W}$					

<sup>6</sup> The conversion formula is valid only for properly matched antennas. In other cases the transmitter output power may have to be measured by a terminated measurement when applying the exemption clauses. If an open area test site is used for field strength measurement, the effect due to the metal ground reflecting plane should be subtracted from the maximum field strength value in order to reference it to free space, before calculating TP.

Exposure of Humans to RF Fields (continued)		Applicable	Declared by applicant	Measured	Exemption
Separation distance between the user and the transmitting device is					
<input checked="" type="checkbox"/> less than or equal to 20 cm <input type="checkbox"/> greater than 20 cm			<input checked="" type="checkbox"/>		
Transmitting device is					
<input type="checkbox"/> in the vicinity of the human head <input type="checkbox"/> body-worn			<input checked="" type="checkbox"/>		
SAR evaluation					
SAR evaluation is required if the separation distance between the user and the device is less than or equal to 20 cm.					<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/> The device operates from 3 kHz up to 1 GHz inclusively and with output power (i.e. the higher of the conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 200 mW for general public use and 1000 mW for controlled use.					<input checked="" type="checkbox"/>
<input type="checkbox"/> The device operates above 1 GHz and up to 2.2 GHz inclusively and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 100 W for general public use and 500 W for controlled use.					<input type="checkbox"/>
<input type="checkbox"/> The device operates above 2.2 GHz and up to 3 GHz inclusively and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 20 mW for general public use and 100 mW for controlled use.					<input type="checkbox"/>
<input type="checkbox"/> The device operates above 3 GHz and up to 6 GHz inclusively and with output power (i.e. the higher of the conducted or radiated (e.i.r.p.) source-based, time-averaged output power) that is less than or equal to 10 mW for general public use and 50 mW for controlled use.					<input type="checkbox"/>
<input type="checkbox"/> SAR evaluation is documented in test report no. .....					
RF exposure evaluation					
RF exposure evaluation is required if the separation distance between the user and the device is greater than 20 cm.					<input type="checkbox"/>
<input type="checkbox"/> The device operates below 1.5 GHz and the maximum e.i.r.p. of the device is equal to or less than 2.5 W.					<input type="checkbox"/>
<input type="checkbox"/> The device operates at or above 1.5 GHz and the maximum e.i.r.p. of the device is equal to or less than 5 W.					<input type="checkbox"/>
<input type="checkbox"/> RF exposure evaluation is documented in test report no. .....					

## 9 Referenced Regulations

All tests were performed with reference to the following regulations and standards:

<input checked="" type="checkbox"/>	CFR 47 Part 2	Code of Federal Regulations Part 2 (Frequency allocation and radio treaty matters; General rules and regulations) of the Federal Communication Commission (FCC)	October 1, 2009
<input checked="" type="checkbox"/>	CFR 47 Part 15	Code of Federal Regulations Part 15 (Radio Frequency Devices) of the Federal Communication Commission (FCC)	October 1, 2009
<input checked="" type="checkbox"/>	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	December 11, 2003 (published on January 30, 2004)
<input checked="" type="checkbox"/>	RSS-Gen	Radio Standards Specification RSS-Gen Issue 2 containing General Requirements and Information for the Certification of Radiocommunication Equipment, published by Industry Canada	June 2007
<input checked="" type="checkbox"/>	RSS-210	Radio Standards Specification RSS-210 Issue 7 for Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, published by Industry Canada	June 2007
<input type="checkbox"/>	RSS-310	Radio Standards Specification RSS-310 Issue 2 for Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category II Equipment, published by Industry Canada	June 2007
<input checked="" type="checkbox"/>	RSS-102	Radio Standards Specification RSS-102 Issue 4: Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), published by Industry Canada	March 2010
<input type="checkbox"/>	ICES-003	Interference-Causing Equipment Standard ICES-003 Issue 4 for Digital Apparatus, published by Industry Canada	February 7, 2004
<input checked="" type="checkbox"/>	CISPR 22	Third Edition of the International Special Committee on Radio Interference (CISPR), Pub. 22, "Information Technology Equipment – Radio Disturbance Characteristics – Limits and Methods of Measurement"	1997
<input type="checkbox"/>	CAN/CSA-CEI/IEC CISPR 22	Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment	2002

TRC-43      Notes Regarding Designation of Emission (Including Necessary Bandwidth and Classification), Class of Station and Nature of Service, published by Industry Canada      October 9, 1982

## 10 Revision History

<b>Revision History</b>			
<i>Edition</i>	<i>Date</i>	<i>Issued by</i>	<i>Modifications</i>
1	01.06.10	M. Steindl (cj)	First Edition
2	09.09.10	C. Jäger (jr)	Edition 2 Table „Referenced Regulations“ updated acc. to Mr. Hampicke / E-Mail September 8, 2010

## 11 Charts taken during testing

# Radiated Emission Test 9 kHz - 30 MHz


## acc. to FCC Part 15 Subpart C (FAR)

Model:	RT262728 916,5 MHz FSK		
Serial no.:	DUT1		
Applicant:	ELDAT GmbH		
Test site:	Fully anechoic room, cabin no. 2		
Tested on:	Test distance 3 metres		
Date of test:	05/31/2010	Operator:	M. Steindl
Test performed:	by hand	File name:	default.emi

Comment:
- 3 V battery supply
- Transmitting continuously
- Position 1: EUT flat on table

Detector:	Peak
-----------	------

List of values:	
10 dB Margin	50 Subranges



Result:	Prescan
---------	---------

Project file:	69558-02103	Page	of	Pages
---------------	-------------	------	----	-------

# Radiated Emission Test 30 MHz - 1 GHz


## acc. to FCC Part 15 Subpart C (FAR)

Model:	RT262728 916,5 MHz FSK		
Serial no.:	DUT1		
Applicant:	ELDAT GmbH		
Test site:	Fully anechoic room, cabin no. 2		
Tested on:	Test distance 3 metres	Horizontal Polarization	
Date of test:	05/31/2010	Operator:	M. Steindl
Test performed:	automatically	File name:	default.emi

Comment:
- 3 V battery supply
- Transmitting continuously
- Position 1: EUT flat on table

Detector:	Peak
-----------	------

List of values:
Selected by hand



Result:	Prescan
---------	---------

Project file:	69558-02103	Page	of	Pages
---------------	-------------	------	----	-------

# Radiated Emission Test 30 MHz - 1 GHz


## acc. to FCC Part 15 Subpart C (FAR)

Model:	RT262728 916,5 MHz FSK	
Serial no.:	DUT1	
Applicant:	ELDAT GmbH	
Test site:	Fully anechoic room, cabin no. 2	
Tested on:	Test distance 3 metres	Operator:
	Vertical Polarization	M. Steindl
Date of test:	05/31/2010	File name:
Test performed:	automatically	default.emi

Comment:
- 3 V battery supply
- Transmitting continuously
- Position 1: EUT flat on table

Detector:	Peak
-----------	------

List of values:	10 dB Margin	50 Subranges
-----------------	--------------	--------------



Result:		
Prescan		


Project file:			
69558-02103	Page	of	Pages

# Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	Comment: - 3 V battery supply
Serial no.: DUT1	- Transmitting continuously
Applicant: ELDAT GmbH	- Position 1: EUT flat on table
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------


Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------

# Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	Comment: - 3 V battery supply
Serial no.: DUT1	- Transmitting continuously
Applicant: ELDAT GmbH	- Position 1: EUT flat on table
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page      of      Pages
------------------------------	-------------------------


# Radiated Emission Test 3.95 GHz - 5.85 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK
Serial no.: DUT1
Applicant: ELDAT GmbH
Test site: Fully anechoic room, cabin no. 2
Tested on: Test distance 3 metres Horizontal Polarization
Date of test: 05/31/2010      Operator: M. Steindl
Test performed: automatically      File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 1: EUT flat on table
--

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------


# Radiated Emission Test 3.95 GHz - 5.85 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 1: EUT flat on table
--

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------


Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------

# Radiated Emission Test 5.85 GHz - 8.2 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	Comment: - 3 V battery supply
Serial no.: DUT1	- Transmitting continuously
Applicant: ELDAT GmbH	- Position 1: EUT flat on table
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------


Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------

# Radiated Emission Test 5.85 GHz - 8.2 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	Comment: - 3 V battery supply
Serial no.: DUT1	- Transmitting continuously
Applicant: ELDAT GmbH	- Position 1: EUT flat on table
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------


# Radiated Emission Test 8.2 GHz - 10 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 1: EUT flat on table
--

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page of Pages
------------------------------	---------------

# Radiated Emission Test 8.2 GHz - 10 GHz acc. to FCC Part 15 Subpart C (FAR)


Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment:
- 3 V battery supply
- Transmitting continuously
- Position 1: EUT flat on table

Detector: Peak
-------------------

List of values:
10 dB Margin

Limit1: FCC 15.209 (1 m) Transducer: EMCO 3160



Result: Prescan
--------------------

Project file: 69558-02103
Page of Pages


# Radiated Emission Test 9 kHz - 30 MHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: by hand	File name: default.emi

Comment:
- 3 V battery supply
- Transmitting continuously
- Position 2: EUT in upright position

Detector: Peak
-------------------

List of values:	
10 dB Margin	50 Subranges



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------

# Radiated Emission Test 30 MHz - 1 GHz


## acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment:
- 3 V battery supply
- Transmitting continuously
- Position 2: EUT in upright position

Detector: Peak
-------------------

List of values:
10 dB Margin
50 Subranges



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------

# Radiated Emission Test 30 MHz - 1 GHz


## acc. to FCC Part 15 Subpart C (FAR)

Model:	RT262728 916,5 MHz FSK	
Serial no.:	DUT1	
Applicant:	ELDAT GmbH	
Test site:	Fully anechoic room, cabin no. 2	
Tested on:	Test distance 3 metres	Operator:
	Vertical Polarization	M. Steindl
Date of test:	05/31/2010	File name:
Test performed:	automatically	default.emi

Comment:
- 3 V battery supply
- Transmitting continuously
- Position 2: EUT in upright position

Detector:	Peak
-----------	------

List of values:
Selected by hand



Result:		
Prescan		


Project file:			
69558-02103	Page	of	Pages

# Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	Comment: - 3 V battery supply
Serial no.: DUT1	- Transmitting continuously
Applicant: ELDAT GmbH	- Position 2: EUT in upright position
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------


Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------

# Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	Comment: - 3 V battery supply
Serial no.: DUT1	- Transmitting continuously
Applicant: ELDAT GmbH	- Position 2: EUT in upright position
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------

## Radiated Emission Test 3.95 GHz - 5.85 GHz acc. to FCC Part 15 Subpart C (FAR)

Model:	RT262728 916,5 MHz FSK
Serial no.:	DUT1
Applicant:	ELDAT GmbH
Test site:	Fully anechoic room, cabin no. 2
Tested on:	Test distance 3 metres Horizontal Polarization
Date of test:	Operator:
05/31/2010	M. Steindl
Test performed:	File name:
automatically	default.emi

**Comment:**

- 3 V battery supply
- Transmitting continuously
- Position 2: EUT in upright position

Detector:  
Peak

### List of values:


10 dB Margin

## 50 Subranges

dB $\mu$ V/m

Limit1: FCC 15.209 (3 m)

Transducer: EMCO 3160



Result:  
Prescan

Project file:  
69558-02103

Page of Pages


# Radiated Emission Test 3.95 GHz - 5.85 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 2: EUT in upright position
--

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------


# Radiated Emission Test 5.85 GHz - 8.2 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 2: EUT in upright position
--

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page of Pages
------------------------------	---------------


# Radiated Emission Test 5.85 GHz - 8.2 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 2: EUT in upright position
--

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------


# Radiated Emission Test 8.2 GHz - 10 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 2: EUT in upright position
--

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page of Pages
------------------------------	---------------


# Radiated Emission Test 8.2 GHz - 10 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 2: EUT in upright position
--

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103
------------------------------

Page of Pages


# Radiated Emission Test 9 kHz - 30 MHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: by hand	File name: default.emi

Comment:
- 3 V battery supply
- Transmitting continuously
- Position 3: EUT in upright position, rotated

Detector: Peak
-------------------

List of values:	
10 dB Margin	50 Subranges



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------

# Radiated Emission Test 30 MHz - 1 GHz


## acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 3: EUT in upright position, rotated
---

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------


# Radiated Emission Test 30 MHz - 1 GHz

## acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	Comment: - 3 V battery supply
Serial no.: DUT1	- Transmitting continuously
Applicant: ELDAT GmbH	- Position 3: EUT in upright position, rotated
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------


Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------

# Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	Comment: - 3 V battery supply
Serial no.: DUT1	- Transmitting continuously
Applicant: ELDAT GmbH	- Position 3: EUT in upright position, rotated
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Detector: Peak	List of values: Selected by hand
-------------------	-------------------------------------

Limit1: FCC 15.209 (3 m) Transducer: EMCO 3115



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------


# Radiated Emission Test 1 GHz - 4 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 3: EUT in upright position, rotated
---

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page of Pages
------------------------------	---------------


# Radiated Emission Test 3.95 GHz - 5.85 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK
Serial no.: DUT1
Applicant: ELDAT GmbH
Test site: Fully anechoic room, cabin no. 2
Tested on: Test distance 3 metres Horizontal Polarization
Date of test: 05/31/2010      Operator: M. Steindl
Test performed: automatically      File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 3: EUT in upright position, rotated
---

Detector: Peak
-------------------

List of values: 10 dB Margin	50 Subranges
---------------------------------	--------------



Result: Prescan
--------------------

Project file: 69558-02103	Page      of      Pages
------------------------------	-------------------------


# Radiated Emission Test 3.95 GHz - 5.85 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK
Serial no.: DUT1
Applicant: ELDAT GmbH
Test site: Fully anechoic room, cabin no. 2
Tested on: Test distance 3 metres Vertical Polarization
Date of test: 05/31/2010      Operator: M. Steindl
Test performed: automatically      File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 3: EUT in upright position, rotated
---

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------


# Radiated Emission Test 5.85 GHz - 8.2 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 3: EUT in upright position, rotated
---

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page of Pages
------------------------------	---------------


# Radiated Emission Test 5.85 GHz - 8.2 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: by hand	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 3: EUT in upright position, rotated
---

Detector: Average
----------------------

List of values: Selected by hand
-------------------------------------



Result: Limit kept
-----------------------

Project file: 69558-02103	Page of Pages
------------------------------	---------------


# Radiated Emission Test 5.85 GHz - 8.2 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 3: EUT in upright position, rotated
---

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page	of	Pages
------------------------------	------	----	-------

# Radiated Emission Test 8.2 GHz - 10 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Horizontal Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 3: EUT in upright position, rotated
---

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103
------------------------------

Page of Pages

# Radiated Emission Test 8.2 GHz - 10 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: RT262728 916,5 MHz FSK	
Serial no.: DUT1	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 1 meter Vertical Polarization	
Date of test: 05/31/2010	Operator: M. Steindl
Test performed: automatically	File name: default.emi

Comment: - 3 V battery supply - Transmitting continuously - Position 3: EUT in upright position, rotated
---

Detector: Peak
-------------------

List of values: Selected by hand
-------------------------------------



Result: Prescan
--------------------

Project file: 69558-02103	Page of Pages
------------------------------	---------------