

11.1 TEST DATA SUMMARY

Ambient TEMPERATURE (°C) _____ 25.0
 Relative HUMIDITY (%) _____ 49.0
 Atmospheric PRESSURE (kPa) _____ 99.0

Mixture Type: _____ Brain _____

Dielectric Constant: _____ 43.4 _____

Conductivity: _____ 0.90 _____

Closest Distance (between E-Probe & Phone Antenna): _____ 1.7 cm _____

Measurement Results (AMPS)

| FREQUENCY | | Modulation | POWER (W) | EAR Position | Antenna Position | SAR (W/kg) |
|---|-----|------------|--------------|-----------------|---------------------|---------------|
| MHz | Ch. | | | | | |
| 836.49 | 383 | AMPS | 0.6 | Left | IN | 1.3158 |
| 836.49 | 383 | AMPS | 0.6 | Left | OUT | 1.2572 |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak (Brain) Uncontrolled Exposure/General Population | | | | 1.6 W/kg (mW/g) | | |

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. All modes of operation were investigated and the worst-case are reported.
2. Battery condition is fully charged for all readings.
3. Power measured: Conducted EIRP ERP



 Randy Ortanez
 President & Chief Engineer

PCTEST SEAL