

RTS RIM Testing Services	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page	1(34)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Shahriar Ninad	June 02-24, 2008	RTS-1114-0806-05	L6ARBY40GW		




SAR Compliance Test Report

Testing Lab:	RIM Testing Services (RTS) 440 Phillip Street Waterloo, Ontario Canada N2L 5R9 Phone: 519-888-7465 Fax: 519-746-0189	Applicant:	Research In Motion Limited 295 Phillip Street Waterloo, Ontario Canada N2L 3W8 Phone: 519-888-7465 Fax: 519-888-6906 Web site: www.rim.com
---------------------	---	-------------------	--

Statement of Compliance: RIM Testing Services declares under its sole responsibility that the product to which this declaration relates, is in conformity with the appropriate RF exposure standards, recommendations and guidelines. It also declares that the product was tested in accordance with the appropriate measurement standards, guidelines and recommended practices.

Device Category: This BlackBerry® Smartphone is a portable device, designed to be used in direct contact with the user's head, hand and to be carried in approved accessories when carried on the user's body.

RF exposure environment: This device has been shown to be in compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in OET Bulletin 65 Supplement C (Edition 01-01), FCC 96-326, IEEE Std. C95.1-1999, Health Canada's Safety Code 6, as reproduced in RSS-102 issue 2-2005 and has been tested in accordance with the measurement procedures specified in OET Bulletin 65 Supplement C (Edition 01-01), ANSI/IEEE Std. C95.3-1991, IEEE 1528-2003, IEC 62209-1-2005, DASY4 manual which follows draft IEC 62209 – Part 2 and Health Canada's Safety Code 6.

Tested and documented by:	Signatures	Date
Shahriar Ninad Compliance Specialist		25-June-2008
Daoud Attayi Senior Compliance Specialist		04-July-2008
Paul G. Cardinal, Ph.D. Director, RIM Testing Services		29-July-2008

RTS RIM Testing Services	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page	2(34)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Shahriar Ninad	June 02-24, 2008	RTS-1114-0806-05	L6ARBY40GW		

CONTENTS

SAR COMPLIANCE TEST REPORT	1
CONTENTS	2
1.0 OPERATING CONFIGURATIONS AND TEST CONDITIONS	4
1.2 ANTENNA DESCRIPTION	4
1.3 DEVICE DESCRIPTION	4
1.4 BODY WORN ACCESSORIES (HOLSTERS)	5
1.5 HEADSET	5
1.6 BATTERY	5
1.7 PROCEDURE USED TO ESTABLISH TEST SIGNAL	5
1.8 HIGHLIGHTS OF THE FCC OET SAR MEASUREMENT REQUIREMENTS FOR 3-6 GHZ AND	5
MEASUREMENT PROCEDURES FOR 802.11 B/G TRANSMITTER THAT WERE FOLLOWED	5
1.9 HIGHLIGHTS OF THE FCC OET SAR EVALUATION CONSIDERATIONS FOR HANDSETS WITH	5
MULTIPLE TRANSMITTERS AND ANTENNAS	7
2.0 DESCRIPTION OF THE TEST EQUIPMENT	8
2.1 SAR MEASUREMENT SYSTEM	8
2.1.1 EQUIPMENT LIST	9
2.2.1 DEVICE AND BASE STATION SIMULATOR SETUP	10
2.2.2 DASY SETUP	10
3.0 ELECTRIC FIELD PROBE CALIBRATION	10
3.1 PROBE SPECIFICATIONS	10
3.2 PROBE CALIBRATION AND MEASUREMENT ERRORS	11
4.0 SAR MEASUREMENT SYSTEM VERIFICATION	11
4.1 SYSTEM ACCURACY VERIFICATION FOR HEAD ADJACENT USE	11
5.0 PHANTOM DESCRIPTION	12
6.0 TISSUE DIELECTRIC PROPERTIES	13
6.1 COMPOSITION OF TISSUE SIMULANT	13
6.1.1 EQUIPMENT	13
6.1.2 PREPARATION PROCEDURE	13
6.2 ELECTRICAL PARAMETERS OF THE TISSUE SIMULATING LIQUID	14
6.2.1 EQUIPMENT	15
6.2.2 TEST CONFIGURATION	15
6.2.3 PROCEDURE	15
7.0 SAR SAFETY LIMITS	19
8.0 DEVICE POSITIONING	20
8.1 DEVICE HOLDER FOR SAM TWIN PHANTOM	20
8.2 DESCRIPTION OF THE TEST POSITIONING	21
8.2.1 TEST POSITIONS OF DEVICE RELATIVE TO HEAD	21
8.2.1.1 DEFINITION OF THE "CHEEK" POSITION	22
8.2.1.2 DEFINITION OF THE "TILTED" POSITION	23
8.2.2 BODY HOLSTER CONFIGURATION	23
9.0 HIGH LEVEL EVALUATION	24
9.1 MAXIMUM SEARCH	24
9.2 EXTRAPOLATION	24
9.3 BOUNDARY CORRECTION	24
9.4 PEAK SEARCH FOR 1G AND 10G CUBE AVERAGED SAR	24
10.0 MEASUREMENT UNCERTAINTY	25
11.0 TEST RESULTS	26
11.1 SAR MEASUREMENT RESULTS AT HIGHEST POWER MEASURED AGAINST THE HEAD	26
11.2 SAR MEASUREMENT RESULTS AT HIGHEST POWER MEASURED AGAINST THE BODY USING	31
ACCESSORIES	31
12.0 REFERENCES	34

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 3(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

APPENDIX A: SAR DISTRIBUTION COMPARISON FOR ACCURACY VERIFICATION

APPENDIX B: SAR DISTRIBUTION PLOTS - HEAD CONFIGURATION

APPENDIX C: SAR DISTRIBUTION PLOTS - BODY-WORN CONFIGURATION

APPENDIX D: PROBE & DIPOLE CALIBRATION DATA

APPENDIX E: PHOTOGRAPHS

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 4(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05
		FCC ID: L6ARBY40GW	

1.0 OPERATING CONFIGURATIONS AND TEST CONDITIONS

1.1 Picture of Device

Please refer to Appendix E.

Figure 1. BlackBerry Smartphone

1.2 Antenna description

Type	Internal fixed antenna
Location	Back bottom centre
Configuration	Internal fixed antenna

Table 1. Antenna description

1.3 Device description

Device Model	RBY41GW				
FCC ID	L6ARBY40GW				
PIN/Serial No.	S/N: 1016540852 (BT); PIN: 207401C8 (Wifi), 20743668(rev 3, GSM/GPRS/EDGE), 20746462 (rev 4, GSM/GPRS/EDGE)				
Prototype or Production Unit	Production				
Mode(s) of Operation in North America	1-slot GSM 850 GSM 1900	2-slots EDGE / GPRS 850 1900	Bluetooth	802.11b	802.11g
Maximum nominal conducted RF Output Power	32.5 dBm 30.5 dBm	32.5 dBm 30.5 dBm	2.67 dBm	18.00	17.00
Tolerance in Power Setting on centre channel	± 0.50 dB	± 0.50 dB	N/A	± 0.50 dB	± 0.50 dB
Duty Cycle	1:8	2:8	N/A	1:1	1:1
Tx Frequency Range (MHz)	824.2 – 848.8 1850.2 – 1909.8	824.2 – 848.8 1850.2 – 1909.8	2402-2483	2412-2462	2412-2462

Table 2. Test device description

The device supports GSM / EDGE / GPRS 900 / 1800 MHz bands that are not operational in North America, therefore no data is presented in this report for those bands.

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 5(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

1.4 Body worn accessories (holsters)

The device has been tested with the following holster which contains metal components and the separation distance between the device and the user's body is listed in the table below. The holster is designed with the intended device orientation being with the LCD facing the belt clip. Proper positioning is vital for protection of the LCD display, and to help maximize the battery life of the device. The device can also be placed in the holster with the backside facing the belt clip. Body SAR measurements were carried out with the worst-case configuration front LCD side and backside towards the belt clip.

Holster	Model / Part Number	Separation (mm)
Holster 1	HDW-18955-001	22

Table 3: Body worn holster

Please refer to Appendix E.
Figure 2. Body-worn holster

1.5 Headset

The BlackBerry device was tested with and without the following headset model numbers.

- 1) HDW-12420-003

1.6 Battery

The BlackBerry device was tested with the following Lithium Ion Battery pack.

- 1) BAT-11004-001

1.7 Procedure used to establish test signal

The device was put into test mode for SAR measurements by placing a voice call from a Rohde & Schwarz CMU 200 Communications Test Instrument. The power control level was set to command the device to transmit at full power at the specified frequency. Other parameters include: Channel type = full rate, discontinuous transmission off, frequency hopping off. A Rohde & Schwarz CBT Bluetooth Tester was used to establish a connection with the EUT's Bluetooth radio. Worst case SAR was evaluated with Bluetooth on.

A proprietary test software was used to command the device to transmit at specific 802.11 b/g WLAN band, maximum power, desired frequency and modulation type/data rate.

1.8 Highlights of the FCC OET SAR Measurement Requirements for 3-6 GHz and Measurement Procedures for 802.11 b/g Transmitter that were followed

- Maintained dielectric parameter uncertainty as close to $\pm 5.0\%$ of the target value as possible.
- Liquid depth from SAM ERP or flat phantom was kept at 15 cm.

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 6(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

- Probe Requirement: Used SPEAG probe model EX3DV4 for 2.4 – 6 GHz SAR testing specs are outlined below:

Probe tip to sensor center	1.0 mm
Probe tip diameter is	2.5 mm
Probe calibration uncertainty	< 15 % for f = 2.45 to < 6.0 GHz
Probe calibration range	± 100 MHz

Table 4: Probe specification requirements

- Frequency Channel Configuration: 802.11 b/g modes are tested on “default test channels” 1, 6 and 11.
- For each frequency band, testing at higher rates and higher modulations is not required when the maximum average output power for each of these configurations is less than ¼ dB higher than those measured at the lowest data rate.
- SAR is not required for 802.11g channels when the maximum average output power is less than ¼ dB higher than that measured on the corresponding 802.11b channels.
- SAR test was conducted on each “default test channel” and each band with the worst case modulation that resulted in maximum duty cycle of 99.5 %.
- Conducted power measurements:

802.11b @ 1Mbps		802.11g @ 6Mbps	
Chan	Cond. Power (dBm)	Chan	Cond. Power (dBm)
1	17.61	1	13.30
6	17.70	6	16.30
11	17.75	11	13.45
14	17.45	14	13.20

Table 5: 802.11 b/g channel vs. conducted power

Data Rate (Mbps)	Mod.	802.11g	Data Rate (Mbps)	Mod.	802.11b
		Channel 6			Channel 6
		Cond. Power (dBm)			Cond. Power (dBm)
6	BPSK	16.30	1	BPSK	17.70
9	BPSK	16.20	2	DQPSK	17.60
12	QPSK	14.55	5.5	CCK	17.50
18	QPSK	14.35	11	CCK	17.30
24	16-QAM	12.82			
36	16-QAM	12.40			
48	64-QAM	10.51			
54	64-QAM	10.45			

Table 6: 802.11 b/g modulation type/data rate vs. conducted power

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW	Page 7(34)	
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

1.9 Highlights of the FCC OET SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas

Unlicensed Transmitters

When there is simultaneous transmission –
Stand-alone SAR not required when

- output $\leq 2 \cdot P_{Ref}$ and antenna is > 5.0 cm from other antennas
- output $\leq P_{Ref}$ and antenna is > 2.5 cm from other antennas
- the other antenna(s), which are < 2.5 cm away, has an output $\leq P_{Ref}$ OR max 1g SAR < 1.2 W/kg

Otherwise stand-alone SAR is required

- test SAR on highest output channel for each wireless mode and exposure condition
- if SAR for highest output channel is $> 50\%$ of SAR limit, evaluate all channels according to normal procedure

Simultaneous Transmission SAR not required:

Unlicensed only

- when stand-alone 1-g SAR is not required and antenna is > 5 cm from other antennas
- when the other antenna(s), which are < 2.5 cm away, has an output $\leq P_{Ref}$ OR max 1g SAR < 1.2 W/kg

Licensed & Unlicensed

- when the sum of the 1-g SAR is < 1.6 W/kg for all simultaneous transmitting antennas which are < 5 cm from each other.
- when SAR to antenna separation ratio of simultaneous transmitting antenna pair is < 0.3

Simultaneous Transmission SAR required:

Licensed & Unlicensed

- antenna pairs with SAR to antenna separation ratio ≥ 0.3 ; test is only required for the configuration that results in the highest SAR in standalone configuration for each wireless mode and exposure condition.

	2.45	5.15 - 5.35	5.47 - 5.85	GHz
P_{Ref}	12	6	5	mW
Device output power should be rounded to the nearest mW to compare with values specified in this table.				

Table 7 – Output Power Thresholds for Unlicensed Transmitters

Mode	Configuration	Highest 1 g SAR (W/kg)
BT	Head-Right-Touch	0.01
	Head-Flat phantom	0.01
	Body-Holster 1-Back	0.01
802.11b/g	Head-Right-Touch	0.12
	Head-Flat phantom	0.18
	Body-Holster 1-Back	0.11
GSM/GPRS/EDGE	Head-Right-Touch	1.15
	Head-Flat phantom	0.96
	Body-Holster 1-Back	1.18

Table 8 – Highest SAR values for worst case configuration

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 8(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

The sum of 1-g SAR values is < 1.6 W/kg for all simultaneous transmitting antennas which are < 5 cm from each other, therefore Simultaneous Transmission SAR is not required.

SAR Tests in Mouth and Jaw Regions of the SAM Phantom:

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones.

In order to ensure there is sufficient conservativeness for ensuring compliance, the following procedures apply. The SAR required in these regions of SAM should be measured using a flat phantom. Rectangular shaped phones should be positioned with its bottom edge positioned from the flat phantom with the same distance provided by the cheek touching position using SAM. The ear reference point (ERP, as defined for SAM) of the phone should be positioned ½ cm from the flat phantom shell. Clam-shell phones should be positioned with the hinge against a smooth edge of the flat phantom where the upper half of the phone is unfolded and extended beyond the phantom side wall. The lower half of the phone is secured in the test device holder at a fixed distance below the flat phantom determined by the minimum separation along the lower edge of the phone in the cheek touching position using SAM.

These flat phantom procedures are only applicable to stand-alone SAR evaluation in tight regions of the SAM phantom, where measurement is not feasible or test results can be questionable due to probe calibration and accessibility issues.

2.0 DESCRIPTION OF THE TEST EQUIPMENT

2.1 SAR measurement system

SAR measurements were performed using a Dosimetric Assessment System (DASY4), an automated SAR measurement system manufactured by Schmid & Partner Engineering AG (SPEAG), of Zurich, Switzerland.

The DASY 4 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller and software.
- An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A DAE module that performs the signal amplification, signal multiplexing, A/D conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the Electro-optical coupler (EOC).
- A unit to operate the optical surface detector that is connected to the EOC.
- The EOC performs the conversion from an optical signal into the digital electric signal of the DAE. The EOC is connected to the PC plug-in card.
- The functions of the PC plug-in card based on a DSP is to perform the time critical tasks such as signal filtering, surveillance of the robot operation fast movement interrupts.
- A computer operating Windows 2000.
- DASY 4 software version 4.7.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 9(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

- The SAM Twin Phantom enabling testing left-hand and right-hand usage.
- The device holder for mobile phones.
- Tissue simulating liquid mixed according to the given recipes (see section 6.1).
- System validation dipoles allowing for the validation of proper functioning of the system.




Figure 3. System Description

2.1.1 Equipment List

Manufacturer	Test Equipment	Model Number	Serial Number	Cal. Due Date
SCHMID & Partner Engineering AG	E-field probe	ET3DV6	1644	11/12/2008
SCHMID & Partner Engineering AG	E-field probe	EX3DV4	3592	11/06/2008
SCHMID & Partner Engineering AG	Data Acquisition Electronics (DAE3)	DAE3 V1	472	03/05/2009
SCHMID & Partner Engineering AG	Dipole Validation Kit	D835V2	446	01/08/2009
SCHMID & Partner Engineering AG	Dipole Validation Kit	D1900V2	545	01/09/2009
SCHMID & Partner Engineering AG	Dipole Validation Kit	D2450V2	747	11/06/2009
Agilent Technologies	Signal generator	8360B	3844A00927	09/28/2008
Agilent Technologies	Power meter	E4419B	GB40202821	09/19/2008
Agilent Technologies	Power sensor	8481A	MY41095417	09/19/2008
Amplifier Research	Amplifier	5S1G4M3	300986	CNR
Agilent Technologies	Network analyzer	8753ES	US39174857	09/19/2008
Rohde & Schwarz	Base Station Simulator	CMU 200	109747	12/04/2008
Rohde & Schwarz	CBT Bluetooth Tester	CBT35	100370	12/06/2008

Table 9. Equipment list

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 10(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

2.2 Description of the test setup

Before SAR measurements are conducted, the device and the DASYS equipment are setup as follows:

2.2.1 Device and base station simulator setup

- Power up the device.
- Turn on the base station simulator and set the radio channel and power to the appropriate values.
- Connect an antenna to the RF IN/OUT of the communication test set and place it close to the device.

2.2.2 DASYS setup

- Turn the computer on and log on to Windows 2000.
- Start the DASYS4 software by clicking on the icon located on the Windows desktop.
- Mount the DAE unit and the probe. Turn on the DAE unit.
- Turn the Robot Controller on by turning the main power switch to the horizontal position
- Align the probe by clicking the ‘Align probe in light beam’ button.
- Open a file and configure the proper parameters - probe, medium, communications system etc.
- Establish a connection between the Device and the communications test instrument. Place the Device on the stand and adjust it under the phantom.
- Start SAR measurements.

3.0 ELECTRIC FIELD PROBE CALIBRATION

3.1 Probe Specifications

SAR measurements were conducted using the dosimetric probe ET3DV6 and EX3DV4, designed by Schmid & Partner Engineering AG for the measurement of SAR. The probe is constructed using the thin film technique, with printed resistive lines on ceramic substrates. It has a symmetrical design with triangular core, built-in optical fibre for the surface detection system and built-in shielding against static discharge. The probe is sensitive to E-fields and thus incorporates three small dipoles arranged so that the overall response is close to isotropic. The table below summarizes the technical data for the probe.

Property	Data
Probe model EX3DV6	
Frequency range	30 MHz – 3 GHz
Linearity	±0.1 dB
Directivity (rotation around probe axis)	≤ ±0.2 dB
Directivity (rotation normal to probe axis)	±0.4 dB
Dynamic Range	5 mW/kg – 100 W/kg
Probe positioning repeatability	±0.2 mm
Spatial resolution	< 0.125 mm ³
Probe model EX3DV4 for 2.4 – 6 GHz	
Probe tip to sensor center	1.0 mm
Probe tip diameter is	2.5 mm
Probe calibration uncertainty	< 15 % for f = 2.45 to < 6.0 GHz
Probe calibration range	± 100 MHz

Table 10. Probe specifications

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 11(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

3.2 Probe calibration and measurement errors

The probe ET3DV6 was calibrated with an accuracy better than $\pm 10\%$ and $< 15\%$ for probe EX3DV4 (2-6 GHz). The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe were tested. The probe calibration parameters are shown on Appendix D.

4.0 SAR MEASUREMENT SYSTEM VERIFICATION

Prior to conducting SAR measurements, the system was validated using the dipole validation kit and the flat section of the SAM phantom. A power level of 1.0W was applied to the dipole antenna. The verification results are in the table below with a comparison to reference values. Printouts are shown in Appendix A. All the measured parameters are within the allowed tolerances.

4.1 System accuracy verification for head adjacent use

f (MHz)	Limits / Measured	SAR (W/kg) 1 g / 10 g	Dielectric Parameters		Liquid Temp (°C)
			ϵ_r	σ [S/m]	
835	Measured (06/09/2008)	9.3 / 6.1	41.11	0.89	22.2
	Measured (06/24/2008)	9.0 / 5.9	40.77	0.86	22.6
	Recommended Limits	9.3 / 6.0	41.50	0.90	N/A
1900	Measured (06/12/2008)	38.7 / 20.2	38.42	1.44	22.4
	Measured (06/20/2008)	36.8 / 19.0	40.35	1.46	21.8
	Recommended Limits	37.0 / 19.6	40.00	1.40	N/A
2450	Measured (06/02/2008)	57.9 / 24.8	38.36	1.94	22.4
	Measured (06/10/2008)	52.6 / 24.0	37.26	1.97	21.8
	Recommended Limits	53.2 / 24.8	39.2	1.80	N/A

Table 11. System accuracy (validation for head adjacent use)

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW	Page 12(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008
		FCC ID: L6ARBY40GW

5.0 PHANTOM DESCRIPTION

The SAM Twin Phantom, manufactured by SPEAG, was used during the SAR measurements. The phantom is made of a fibreglass shell integrated with a wooden table.

The SAM Twin Phantom is a fibreglass shell phantom with 2 mm shell thickness. It has three measurement areas:

- Left side head
- Right side head
- Flat phantom

The phantom table dimensions are: 100x50x85 cm (LxWxH). The table is intended for use with freestanding robots.

The bottom shelf contains three pair of bolts for locking the device holder in place. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different solutions).

A white cover is provided to top the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on the cover are possible; however the optical surface detector does not work properly at the cover surface. Place a sheet of white paper on the cover when using optical surface detection.

Liquid depth of ≥ 15 cm is maintained in the phantom for all the measurements.



Figure 4. SAM Twin Phantom

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 13(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05
		FCC ID: L6ARBY40GW	

6.0 TISSUE DIELECTRIC PROPERTIES

6.1 Composition of tissue simulant

The composition of the brain and muscle simulating liquids for 800-900 MHz and 1800-1900 MHz are shown in the table below.

INGREDIENT	MIXTURE 800–900MHz		MIXTURE 1800–1900MHz		MIXTURE 2450 MHz	
	Brain %	Muscle %	Brain %	Muscle %	Brain %	Muscle %
Water	40.29	65.45	55.24	69.91	55.0	68.75
Sugar	57.90	34.31	0	0	0	0
Salt	1.38	0.62	0.31	0.13	0	0
HEC	0.24	0	0	0	0	0
Bactericide	0.18	0.10	0	0	0	0
DGBE	0	0	44.45	29.96	40.0	31.25
Triton X-100	0	0	0	0	5.0	0

Table 12. Tissue simulant recipe

6.1.1 Equipment

Manufacturer	Test Equipment	Model Number	Serial Number	Cal. Due Date
Pyrex, England	Graduated Cylinder	N/A	N/A	N/A
Pyrex, USA	Beaker	N/A	N/A	N/A
Acculab	Weight Scale	V1-1200	018WB2003	N/A
Control Company	Digital Thermometer	23609-234	21352860	08/14/2008
IKA Works Inc.	Hot Plate	RC Basic	3.107433	N/A

Table 13. Tissue simulant preparation equipment

6.1.2 Preparation procedure

800-900 MHz liquids

- Fill the container with **water**. Begin heating and stirring.
- Add the **Cellulose**, the **preservative substance** and the **salt**. After several hours, the liquid will become more transparent again. The container must be covered to prevent evaporation.
- Add **Sugar**. Stir it well until the sugar is sufficiently dissolved.
- Keep the liquid hot but below the boiling point for at least an hour. The container must be covered to prevent evaporation.

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 14(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

- Remove the container from, and turn the hotplate off and allow the liquid to cool off to room temperature prior to performing dielectric measurements.

1800-2450 MHz liquid

- Fill the container with water and place it on hotplate. Begin heating and stirring.
- Add the salt, Glycol/Triton X-100. The container must be covered to prevent evaporation.
- Keep the liquid hot enough to dissolve sugar for at least an hour. The container must be covered to prevent evaporation.
- Remove the container from, and turn the hotplate off and allow the liquid to cool off to room temperature prior to performing dielectric measurements.

6.2 Electrical parameters of the tissue simulating liquid

The tissue dielectric parameters shall be measured before a batch can be used for SAR measurements to ensure that the simulated tissue was properly made and will simulate the desired human characteristic. Limits and measured electrical parameters are shown in the table below.

Recommended limits are adopted from IEEE P1528-2003:

“Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, DASY 4 manual and from FCC Tissue Dielectric Properties web page at <http://www.fcc.gov/fcc-bin/dielec.sh>

f (MHz)	Tissue Type	Limits / Measured	Dielectric Parameters		Liquid Temp (°C)
			ϵ_r	σ [S/m]	
835	Head	Measured (06/09/2008)	41.11	0.89	22.2
		Measured (06/24/2008)	40.77	0.86	22.6
		Recommended Limits	41.50	0.90	N/A
	Muscle	Measured (06/09/2008)	52.72	0.94	22.6
		Measured (06/24/2008)	53.13	0.93	22.4
		Recommended Limits	55.20	0.97	N/A
1900	Head	Measured (06/12/2008)	38.42	1.44	22.4
		Measured (06/20/2008)	40.35	1.46	21.8
		Recommended Limits	40.00	1.40	N/A
	Muscle	Measured (06/13/2008)	50.79	1.55	22.1
		Measured (06/20/2008)	50.71	1.57	22.1
		Recommended Limits	53.30	1.52	N/A
2450	Head	Measured (06/02/2008)	38.36	1.94	22.4
		Measured (06/10/2008)	37.26	1.97	21.8
		Recommended Limits	39.20	1.80	N/A
	Muscle	Measured (06/02/2008)	50.66	1.97	22.7
		Measured (06/11/2008)	50.17	1.96	22.4
		Recommended Limits	52.70	1.95	N/A

Table 14. Electrical parameters of tissue simulating liquid

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW	Page 15(34)	
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

6.2.1 Equipment

Manufacturer	Test Equipment	Model Number	Serial Number	Cal. Due Date
Agilent Technologies	Network Analyzer	8753ES	US39174857	09/19/2008
Agilent Technologies	Dielectric probe kit	HP 85070C	US9936135	CNR
Dell	PC using GPIB card	GX110	347	N/A
Control Company	Digital Thermometer	15-077-21	51129471	05/12/2009

Table 15. Equipment required for electrical parameter measurements

6.2.2 Test Configuration




Figure 5. Test configuration

6.2.3 Procedure

1. Turn NWA on and allow at least 30 minutes for warm up.
2. Mount dielectric probe kit so that interconnecting cable to NWA will not be moved during measurements or calibration.
3. Pour de-ionized water and measure water temperature ($\pm 1^\circ$).
4. Set water temperature in HP-Software (Calibration Setup).
5. Perform calibration.
6. Relative permittivity $\epsilon_r = \epsilon'$ and conductivity can be calculated from ϵ''

$$\sigma = \omega \epsilon_0 \epsilon''$$
7. Measure liquid shortly after calibration.
8. Stir the liquid to be measured. Take a sample (~50ml) with a syringe from the center of the liquid container.
9. Pour the liquid into a small glass flask. Hold the syringe at the bottom of the flask to avoid air bubbles.
10. Put the dielectric probe in the glass flask. Check that there are no air bubbles in front of the opening in the dielectric probe kit.
11. Perform measurements.
12. Adjust medium parameters in DASY4 for the frequencies necessary for the measurements ('Setup Config', select medium (e.g. Head 835 MHz) and press 'Option'-button.
13. Select the current medium for the frequency of the validation (e.g. Setup Medium Brain 835 MHz).

Sample calculation for 835 MHz head tissue dielectric parameters using data from Table 16.

Relative permittivity $\epsilon_r = \epsilon' = 41.11$

Conductivity $\sigma = \omega \epsilon_0 \epsilon'' = (2\pi \times 835 \times 10^6)(8.854 \times 10^{-12})(19.20) = 0.89 \text{ S/m}$

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 16(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

Title
SubTitle
June 09, 2008 10:16 AM

Title
SubTitle
June 09, 2008 10:25 AM

Frequency	e'	e''
800.000000 MHz	41.7587	19.5716
805.000000 MHz	41.6442	19.4861
810.000000 MHz	41.5626	19.4576
815.000000 MHz	41.4917	19.4053
820.000000 MHz	41.3803	19.3382
825.000000 MHz	41.2893	19.2825
830.000000 MHz	41.1679	19.2466
835.000000 MHz	41.1092	19.2046
840.000000 MHz	41.0127	19.1738
845.000000 MHz	40.9325	19.1598
850.000000 MHz	40.8807	19.1693
855.000000 MHz	40.8096	19.1431
860.000000 MHz	40.7576	19.1632
865.000000 MHz	40.6877	19.1883
870.000000 MHz	40.6490	19.1944
875.000000 MHz	40.6045	19.2122
880.000000 MHz	40.5688	19.2577
885.000000 MHz	40.5459	19.3091
890.000000 MHz	40.4906	19.3146
895.000000 MHz	40.4571	19.3237
900.000000 MHz	40.3834	19.3447
905.000000 MHz	40.3507	19.3339
910.000000 MHz	40.2791	19.3052
915.000000 MHz	40.2318	19.2895
920.000000 MHz	40.1365	19.2736

Frequency	e'	e''
800.000000 MHz	53.4152	20.5292
805.000000 MHz	53.3377	20.5033
810.000000 MHz	53.2009	20.4483
815.000000 MHz	53.1061	20.4131
820.000000 MHz	53.0160	20.3713
825.000000 MHz	52.9209	20.3431
830.000000 MHz	52.8183	20.2743
835.000000 MHz	52.7227	20.3133
840.000000 MHz	52.6780	20.2469
845.000000 MHz	52.6158	20.2200
850.000000 MHz	52.5494	20.2381
855.000000 MHz	52.5058	20.2265
860.000000 MHz	52.4773	20.2095
865.000000 MHz	52.4515	20.2555
870.000000 MHz	52.4174	20.2616
875.000000 MHz	52.4132	20.2883
880.000000 MHz	52.4119	20.2923
885.000000 MHz	52.3802	20.2971
890.000000 MHz	52.3832	20.3357
895.000000 MHz	52.3415	20.3230
900.000000 MHz	52.3104	20.3220
905.000000 MHz	52.2639	20.3321
910.000000 MHz	52.1986	20.2775
915.000000 MHz	52.1364	20.2684
920.000000 MHz	52.0614	20.2237

Head

Muscle

Table 16. 835 MHz head and muscle tissue dielectric parameters

RTS RIM Testing Services	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page	17(34)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Shahriar Ninad	June 02-24, 2008	RTS-1114-0806-05	L6ARBY40GW		

Title
SubTitle

June 12, 2008 05:42 PM

Title
SubTitle

June 13, 2008 11:23 AM

Frequency	e'	e''	Frequency	e'	e''
1.800000000 GHz	38.8144	13.3879	1.800000000 GHz	51.0664	14.4745
1.805000000 GHz	38.7972	13.4074	1.805000000 GHz	51.0473	14.4804
1.810000000 GHz	38.7865	13.4019	1.810000000 GHz	51.0313	14.4979
1.815000000 GHz	38.7679	13.4131	1.815000000 GHz	51.0212	14.4964
1.820000000 GHz	38.7686	13.4159	1.820000000 GHz	50.9917	14.5181
1.825000000 GHz	38.7483	13.4432	1.825000000 GHz	50.9954	14.5194
1.830000000 GHz	38.7092	13.4787	1.830000000 GHz	50.9798	14.5226
1.835000000 GHz	38.6845	13.5175	1.835000000 GHz	50.9693	14.5357
1.840000000 GHz	38.6610	13.5078	1.840000000 GHz	50.9474	14.5514
1.845000000 GHz	38.6255	13.5174	1.845000000 GHz	50.9209	14.5780
1.850000000 GHz	38.5919	13.5200	1.850000000 GHz	50.9196	14.5835
1.855000000 GHz	38.5657	13.5241	1.855000000 GHz	50.9099	14.5785
1.860000000 GHz	38.5579	13.5291	1.860000000 GHz	50.9059	14.5757
1.865000000 GHz	38.5579	13.5560	1.865000000 GHz	50.8751	14.5992
1.870000000 GHz	38.5561	13.5602	1.870000000 GHz	50.8727	14.6057
1.875000000 GHz	38.5377	13.5657	1.875000000 GHz	50.8462	14.6329
1.880000000 GHz	38.5043	13.5803	1.880000000 GHz	50.8408	14.6349
1.885000000 GHz	38.4958	13.5915	1.885000000 GHz	50.8392	14.6408
1.890000000 GHz	38.4737	13.5994	1.890000000 GHz	50.8129	14.6503
1.895000000 GHz	38.4431	13.5978	1.895000000 GHz	50.7812	14.6611
1.900000000 GHz	38.4244	13.6007	1.900000000 GHz	50.7908	14.6785
1.905000000 GHz	38.4263	13.5938	1.905000000 GHz	50.7744	14.6939
1.910000000 GHz	38.4153	13.6037	1.910000000 GHz	50.7513	14.7010
1.915000000 GHz	38.3985	13.6085	1.915000000 GHz	50.7392	14.7162
1.920000000 GHz	38.3921	13.6390	1.920000000 GHz	50.7311	14.7315

Head

Muscle

Table 17. 1900 MHz head and muscle tissue dielectric parameters

RTS RIM Testing Services	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page	18(34)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Shahriar Ninad	June 02-24, 2008	RTS-1114-0806-05	L6ARBY40GW		

Title

SubTitle

June 02, 2008 12:11 PM

Title

SubTitle

June 02, 2008 10:47 PM

Frequency	e'	e''	Frequency	e'	e''
2.400000000 GHz	38.5367	14.0725	2.400000000 GHz	50.8231	14.2178
2.405000000 GHz	38.5260	14.0739	2.405000000 GHz	50.8046	14.2574
2.410000000 GHz	38.4927	14.0882	2.410000000 GHz	50.7749	14.2814
2.415000000 GHz	38.4828	14.1002	2.415000000 GHz	50.7373	14.3226
2.420000000 GHz	38.4592	14.1123	2.420000000 GHz	50.7280	14.3297
2.425000000 GHz	38.4282	14.1389	2.425000000 GHz	50.7178	14.3236
2.430000000 GHz	38.4222	14.1479	2.430000000 GHz	50.6981	14.3364
2.435000000 GHz	38.4075	14.1836	2.435000000 GHz	50.7109	14.3608
2.440000000 GHz	38.3801	14.1797	2.440000000 GHz	50.6998	14.3891
2.445000000 GHz	38.3697	14.2063	2.445000000 GHz	50.6919	14.4317
2.450000000 GHz	38.3609	14.2178	2.450000000 GHz	50.6644	14.4400
2.455000000 GHz	38.3336	14.2335	2.455000000 GHz	50.6181	14.4862
2.460000000 GHz	38.3131	14.2604	2.460000000 GHz	50.5750	14.5139
2.465000000 GHz	38.3059	14.2596	2.465000000 GHz	50.5456	14.5435
2.470000000 GHz	38.2797	14.2691	2.470000000 GHz	50.5218	14.5298
2.475000000 GHz	38.2472	14.3006	2.475000000 GHz	50.4803	14.5311
2.480000000 GHz	38.2257	14.3119	2.480000000 GHz	50.4603	14.5496
2.485000000 GHz	38.1976	14.3315	2.485000000 GHz	50.4517	14.5799
2.490000000 GHz	38.1787	14.3519	2.490000000 GHz	50.4462	14.6066
2.495000000 GHz	38.1586	14.3541	2.495000000 GHz	50.4255	14.6413
2.500000000 GHz	38.1134	14.3690	2.500000000 GHz	50.4143	14.6716

Head

Muscle

Table 18. 2450 MHz head and muscle tissue dielectric parameters

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 19(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

7.0 SAR SAFETY LIMITS

Standards/Guideline	Localized SAR Limit (W/kg) General public (uncontrolled)	Localized SAR Limits (W/kg) Workers (controlled)
ICNIRP (1998) Standard	2.0 (10g)	10.0 (10g)
IEEE C95.1 (1999) Standard	1.6 (1g)	8.0 (1g)

Table 19. SAR safety limits for Controlled / Uncontrolled environment

Human Exposure	Localized SAR Limits (W/kg) 10g, ICNIRP (1998) Standard	Localized SAR Limits (W/kg) 1g, IEEE C95.1 (1999) Standard
Spatial Average (averaged over the whole body)	0.08	0.08
Spatial Peak (averaged over any X g of tissue)	2.00	1.60
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.00	4.00 (10g)

Table 20. SAR safety limits

Uncontrolled Environments are defined as locations where there is exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW	Page 20(34)	
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

8.0 DEVICE POSITIONING

8.1 Device holder for SAM Twin Phantom

The Device was positioned for all test configurations using the DASY4 holder. The device holder facilitates the rotation of the mounted transmitter in spherical coordinates whereby the rotation point is the ear opening. The devices can be easily, accurately and with repeatability positioned according to FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).




Figure 6. Device Holder

1. Put the phone in the clamp mechanism (1) and hold it straight while tightening. (Curved phones or phones with asymmetrical ear pieces should be positioned so that the earpiece is in the symmetry plane of the clamp).
2. Adjust the sliding carriage (2) to 90°. Then adjust the phone holder angle (3) until the reference line of the phone is horizontal (parallel to the flat phantom bottom). The phone reference line is defined as the front tangential line between the earpiece and the center of the device bottom (or the center of the flip hinge). For devices with parallel front and backsides, the phone holder angle (3) is 0°.
3. Place the device holder at the desired phantom section and move it securely against the positioning pins (4). The screw in front of the turning plate can be applied for correct positioning (5). (Do not tighten it too strongly).
4. Shift the phone clamp (6) so that the earpiece is exactly below the ear marking of the phantom. The phone is now correctly positioned in the holder for all standard phantom measurements, even after changing the phantom or phantom section.

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW	Page 21(34)	
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

5. Adjust the device position angles to the desired measurement position.
6. After fixing the device angles, move the phone fixture up until the phone touches the ear marking. (The point of contact depends on the design of the device and the positioning angle).

8.2 Description of the test positioning

8.2.1 Test Positions of Device Relative to Head

The handset was tested in two test positions against the head phantom, the “cheek” position and the “tilted” position, on both left and right sides of the phantom.

The handset was tested in the above positions according to IEEE 1528- 2003 “Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques”.




Figure 7a. Handset vertical and horizontal reference lines – fixed case




Figure 7b. Handset vertical and horizontal reference lines – “clam-shell”

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW	Page 22(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008
		FCC ID: L6ARBY40GW

8.2.1.1 Definition of the “cheek” position

- 1) Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece, open the cover.
- 2) Define two imaginary lines on the handset: the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A on Figures 7a and 7b), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 7a). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output. However, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 7b), especially for clamshell handsets, handsets with flip pieces, and other irregularly shaped handsets.
- 3) Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 7), such that the plane defined by the vertical center line and the horizontal center line is in a plane approximately parallel to the sagittal plane of the phantom.
- 4) Translate the handset towards the phantom along the line passing through RE and LE until the handset touches the ear.
- 5) While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is the plane normal to MB (“mouth-back”) - NF (“neck-front”) including the line MB (reference plane).
- 6) Rotate the phone around the vertical centerline until the phone (horizontal line) is symmetrical with respect to the line NF.
- 7) While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, rotate the handset about the line NF until any point on the handset is in contact with a phantom point below the ear (cheek).




Figure 8. Phone position 1, “cheek” or “touch” position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning, are indicated. The shoulders are shown for illustration purposes only.

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW	Page 23(34)	
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

8.2.1.2 Definition of the “Tilted” Position

- 1) Repeat steps 1 to 7 of 5.4.1 (in this report 8.2.1.1) to replace the device in the “cheek position.”
- 2) While maintaining the device in the reference plane (described above) and pivoting against the ear, move the device outward away from the mouth by an angle of 15 degrees, or until the antenna touches the phantom.




Figure 9. Phone position 2, “tilted position.” The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning, are indicated. The shoulders are shown for illustration purposes only.

8.2.2 Body Holster Configuration

A body worn holster, as shown on Figure 2, was tested with the Smartphone for FCC RF exposure compliance. The EUT was positioned in the holster case and the belt clip was placed against the flat section of the phantom. A headset was then connected to the device to simulate hands-free operation in a body worn holster configuration.

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 24(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

9.0 HIGH LEVEL EVALUATION

9.1 Maximum search

The maximum search is automatically performed after each coarse scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the coarse scan measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations.

9.2 Extrapolation

The extrapolation can be used in z-axis scans with automatic surface detection. The SAR values can be extrapolated to the inner phantom surface. The extrapolation distance is the sum of the probe sensor offset, the surface detection distance and the grid offset. The extrapolation is based on fourth order polynomial functions. The extrapolation is only available for SAR values.

9.3 Boundary correction

The correction of the probe boundary effect in the vicinity of the phantom surface is done in the standard (worst case) evaluation; the boundary effect is reduced by different weights for the lowest measured points in the extrapolation routine. The result is a slight overestimation of the extrapolated SAR values (2% to 8%) depending on the SAR distribution and gradient. The advanced evaluation makes a full compensation of the boundary effect before doing the extrapolation. This is only possible for probes with specifications on the boundary effect.

9.4 Peak search for 1g and 10g cube averaged SAR

The 1g and 10g peak evaluations are only available for the predefined cube 5x5x7 / 7x7x9 scan. The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 30x30x30mm / 24x24x20 with 7.5mm / 4.0 resolution in (x,y) and 5mm / 2.5mm resolution in z axis amounts to 175 / 693 measurement points. The first procedure is an extrapolation (incl. Boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume in a 1mm grid. In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is then moved around until the highest averaged SAR is found. This last procedure is repeated for a 10 g cube. If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.

RTS RIM Testing Services	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page	25(34)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Shahriar Ninad	June 02-24, 2008	RTS-1114-0806-05		L6ARBY40GW	

10.0 MEASUREMENT UNCERTAINTY

DASY4 Uncertainty Budget According to IEEE P1528 [1]								
Error Description	Uncertainty value	Prob. Dist.	Div.	(c_i) 1g	(c_i) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(v_i) v_{eff}
Measurement System								
Probe Calibration	±4.8%	N	1	1	1	±4.8%	±4.8%	∞
Axial Isotropy	±4.7%	R	√3	0.7	0.7	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.6%	R	√3	0.7	0.7	±3.9%	±3.9%	∞
Boundary Effects	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Linearity	±4.7%	R	√3	1	1	±2.7%	±2.7%	∞
System Detection Limits	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Readout Electronics	±1.0%	N	1	1	1	±1.0%	±1.0%	∞
Response Time	±0.8%	R	√3	1	1	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	√3	1	1	±1.5%	±1.5%	∞
RF Ambient Conditions	±3.0%	R	√3	1	1	±1.7%	±1.7%	∞
Probe Positioner	±0.4%	R	√3	1	1	±0.2%	±0.2%	∞
Probe Positioning	±2.9%	R	√3	1	1	±1.7%	±1.7%	∞
Max. SAR Eval.	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Test Sample Related								
Device Positioning	±2.9%	N	1	1	1	±2.9%	±2.9%	145
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%	5
Power Drift	±5.0%	R	√3	1	1	±2.9%	±2.9%	∞
Phantom and Setup								
Phantom Uncertainty	±4.0%	R	√3	1	1	±2.3%	±2.3%	∞
Liquid Conductivity (target)	±5.0%	R	√3	0.64	0.43	±1.8%	±1.2%	∞
Liquid Conductivity (meas.)	±2.5%	N	1	0.64	0.43	±1.6%	±1.1%	∞
Liquid Permittivity (target)	±5.0%	R	√3	0.6	0.49	±1.7%	±1.4%	∞
Liquid Permittivity (meas.)	±2.5%	N	1	0.6	0.49	±1.5%	±1.2%	∞
Combined Std. Uncertainty						±10.3%	±10.0%	330
Expanded STD Uncertainty						±20.6%	±20.1%	

Table 21. Worst-Case uncertainty budget for DASY4 assessed according to IEEE P1528.
Source: Schmid & Partner Engineering AG.

[1] The budget is valid for the frequency range 300MHz - 3 GHz and represents a worst-case analysis. For specific tests and configurations, the uncertainty could be considerably smaller.

RTS RIM Testing Services	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page	26(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05	FCC ID:	L6ARBY40GW

11.0 TEST RESULTS

11.1 SAR Measurement results at highest power measured against the head

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Left Head Cheek	BT 2450 MHz	2402					
		2441	2.17	22.3	0.009	-0.441	0.01
		2483					
Left Head 15° Tilt	BT 2450 MHz	2402					
		2441	2.17	22.5	0.009	0.721	0.01
		2483					
Right Head Cheek	BT 2450 MHz	2402					
		2441	2.17	22.3	0.006	-0.188	0.01
		2483					
Right Head 15° Tilt	BT 2450 MHz	2402					
		2441	2.17	22.5	0.006	0.676	0.01
		2483					
Flat Phantom	BT 2450 MHz	2402					
		2441	2.17	22.4	0.007	0.329	0.01
		2483					
Left Head Cheek	802.11 b 2450 MHz	2412	17.61	22.3	0.176	0.157	0.18
		2437	17.70	22.0	0.175	0.124	0.18
		2462	17.75	22.1	0.135	-0.562	0.15
Left Head 15° Tilt	802.11 b 2450 MHz	2412					
		2437	17.70	22.2	0.023	0.023	0.02
		2462					
Right Head Cheek	802.11 b 2450 MHz	2412	17.61	22.2	0.115	-0.127	0.12
		2437	17.70	21.9	0.052	0.441	0.05
		2462					
Right Head 15° Tilt	802.11 b 2450 MHz	2412					
		2437	17.70	21.6	0.015	0.136	0.02
		2462					
Flat Phantom	802.11 b 2450 MHz	2412					
		2437	17.70	22.3	0.176	0.181	0.18
		2462					

Table 22. Head SAR results for BT and WiFi/WLAN/802.11b modes

* Note 1: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}|/10)}$$

RTS RIM Testing Services	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page	27(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05	FCC ID:	L6ARBY40GW

Note 2: Supplement C: Middle channel testing is sufficient only if SAR < 3dB below limit.

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	2-slots GSM/EDGE 850 MHz	824.2					
		836.8	32.3	22.6	0.620	-0.012	0.62
		848.8					
Right Head 15° Tilt	2-slots GSM/EDGE 850 MHz	824.2					
		836.8	32.3	22.6	0.093	-0.036	0.09
		848.8					
Right Head Cheek	1-slot GSM 850 MHz	824.2					
		836.8	32.3	22.7	0.360	0.030	0.36
		848.8					
Left Head Cheek	2-slots GSM/EDGE 850 MHz	824.2					
		836.8	32.3	22.3	0.660	-0.056	0.66
		848.8					
Left Head 15° Tilt	2-slots GSM/EDGE 850 MHz	824.2					
		836.8	32.3	22.2	0.091	0.052	0.09
		848.8					
Left Head Cheek	1-slot GSM 850 MHz	824.2					
		836.8	32.3	22.4	0.440	-0.179	0.44
		848.8					
Flat Phantom	2-slots GSM/EDGE 850 MHz	824.2					
		836.8	32.3	22.3	0.440	-0.101	0.44
		848.8					
Flat Phantom	1-slot GSM 850 MHz	824.2					
		836.8	32.3	22.5	0.231	-0.059	0.23
		848.8					

Table 23. SAR results for RBY41GW rev 3 (PIN: 20743668) for head configuration

* Note: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 28(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05
		FCC ID: L6ARBY40GW	

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	2-slots GSM/EDGE 1900 MHz	1850.2	30.6	22.5	1.110	0.034	1.11
		1880.0	30.4	22.7	0.975	-0.175	0.98
		1909.8	30.4	22.4	0.995	0.013	1.00
Right Head 15° Tilt	2-slots GSM/EDGE 1900 MHz	1850.2	30.6	22.2	0.189	0.026	0.19
		1880.0					
		1909.8					
Right Head Cheek	1-slot GSM 1900 MHz	1850.2	30.6	22.6	0.567	0.083	0.57
		1880.0					
		1909.8					
Left Head Cheek	2-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0	30.4	22.5	0.692	0.182	0.69
		1909.8					
Left Head 15° Tilt	2-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0	30.4	22.8	0.193	-0.105	0.19
		1909.8					
Left Head Cheek	1-slot GSM 1900 MHz	1850.2					
		1880.0	30.4	22.6	0.420	-0.114	0.42
		1909.8					
Flat Phantom	2-slots GSM/EDGE 1900 MHz	1850.2	30.6	22.1	0.897	-0.269	0.95
		1880.0					
		1909.8					

Table 24. SAR results for RBY41GW rev 3 (PIN: 20743668) for head configuration

* Note: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 29(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	2-slots GSM/EDGE 850 MHz	824.2	32.2				
		836.8	32.3	22.2	0.527	0.130	0.53
		848.8					
Right Head 15° Tilt	2-slots GSM/EDGE 850 MHz	824.2					
		836.8					
		848.8					
Right Head Cheek	1-slot GSM 850 MHz	824.2					
		836.8					
		848.8					
Left Head Cheek	2-slots GSM/EDGE 850 MHz	824.2					
		836.8	32.3	22.5	0.787	-0.012	0.79
		848.8					
Left Head 15° Tilt	2-slots GSM/EDGE 850 MHz	824.2					
		836.8					
		848.8					
Left Head Cheek	1-slot GSM 850 MHz	824.2					
		836.8					
		848.8					
Flat Phantom	2-slots GSM/EDGE 850 MHz	824.2					
		836.8					
		848.8					
Flat Phantom	1-slot GSM 850 MHz	824.2					
		836.8					
		848.8					

Table 25. SAR results for RBY41GW rev 4 (PIN: 20746462) for head configuration

* Note: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 30(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05
		FCC ID: L6ARBY40GW	

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Right Head Cheek	2-slots GSM/EDGE 1900 MHz	1850.2	30.6	21.8	1.090	-0.021	1.09
		1880.0	30.4	21.8	1.150	0.029	1.15
		1909.8	30.4	21.7	1.040	0.050	1.04
Right Head 15° Tilt	2-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0					
		1909.8					
Right Head Cheek	1-slot GSM 1900 MHz	1850.2					
		1880.0					
		1909.8					
Left Head Cheek	2-slots GSM/EDGE 1900 MHz	1850.2	30.6	22.0	0.904	-0.022	0.90
		1880.0	30.4	21.9	0.830	0.038	0.83
		1909.8	30.4	22.1	0.540	0.035	0.54
Left Head 15° Tilt	2-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0					
		1909.8					
Left Head Cheek	1-slot GSM 1900 MHz	1850.2					
		1880.0					
		1909.8					
Flat Phantom	2-slots GSM/EDGE 1900 MHz	1850.2					
		1880.0					
		1909.8					

Table 26. SAR results for RBY41GW rev 4 (PIN: 20746462) head configuration

* Note: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 31(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05
		FCC ID: L6ARBY40GW	

11.2 SAR measurement results at highest power measured against the body using accessories

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dBm)	*Extrapolated (W/kg)
802.11b/ WLAN 2450 MHz	2412	17.61	Holster 1, Back side facing	22.3	0.106	-0.138	0.11
	2437	17.70	Holster 1, Back side facing	22.2	0.076	-0.513	0.09
	2462	17.75	Holster 1, Back side facing	22.4	0.057	-0.190	0.06
	2412	17.61	Holster 1, Front side facing	22.2	0.017	-0.060	0.02
	2412	17.61	Holster 1, Headset, Back side facing	22.5	0.096	0.113	0.10
	2412	17.61	25 mm spacing, Back side facing	22.3	0.073	0.108	0.07
Bluetooth	2441	2.17	Holster 1, Back side facing	22.7	0.006	3.210	0.01
	2441	2.17	Holster 1, Front side facing	22.8	0.006	-0.131	0.01
	2441	2.17	Holster 1, Headset, Back side facing	22.9	0.006	-0.136	0.01
	2441	2.17	25 mm spacing, Back side facing	22.6	0.005	0.427	0.01

Table 27. SAR results for RBY41GW body-worn configurations

* Note: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 32(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05
		FCC ID: L6ARBY40GW	

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
2-slots GPRS 850 MHz	824.2	32.2	Holster 1, back side facing	22.5	1.180	-0.125	1.18
	836.8	32.3	Holster 1, back side facing	22.6	1.040	-0.029	1.04
	848.8	32.3	Holster 1, back side facing	22.4	0.710	0.005	0.71
	824.2	32.2	Holster 1, front side facing	22.5	0.440	-0.166	0.44
	824.2	32.2	Holster 1, headset, back side facing	22.2	0.860	0.099	0.86
	824.2	32.2	No Holster, back side 25 mm away	22.2	0.630	-0.039	0.63
2-slots GPRS 1900 MHz	1880.0	30.4	Holster 1, back side facing	22.3	0.313	-0.136	0.31
	1880.0	30.4	Holster 1, front side facing	22.4	0.179	0.034	0.18
	1880.0	30.4	Holster 1, headset, front side facing	22.5	0.342	-0.149	0.34
	1880.0	30.4	No Holster, back side 25 mm away	22.2	0.225	-0.009	0.23

Table 28. SAR results for RBY41GW rev 3 (PIN: 20743668) body-worn configurations

* Note: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 33(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05
		FCC ID: L6ARBY40GW	

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
2-slots GPRS 850 MHz	824.2	32.2	Holster 1, back side facing				
	836.8	32.3	Holster 1, back side facing	22.6	0.787	0.004	0.79
	848.8	32.3	Holster 1, back side facing				
	824.2	32.2	Holster 1, front side facing				
	824.2	32.2	Holster 1, headset, back side facing				
	824.2	32.2	No Holster, back side 25 mm away				
2-slots GPRS 1900 MHz	1880.0	30.4	Holster 1, back side facing	22.2	0.494	-0.044	0.49
	1880.0	30.4	Holster 1, front side facing				
	1880.0	30.4	Holster 1, headset, front side facing				
	1880.0	30.4	No Holster, back side 25 mm away				

Table 29. SAR results for RBY41GW rev 4 (PIN: 20746462) body-worn configurations

* Note: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

RTS RIM Testing Services	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RBY41GW		Page 34(34)
	Author Data Shahriar Ninad	Dates of Test June 02-24, 2008	Test Report No RTS-1114-0806-05
		FCC ID: L6ARBY40GW	

12.0 REFERENCES

[1] IEEE 1528-2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

[2] EN 50360: 2001, Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz – 3 GHz)

[3] EN 50361: 2001, Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz – 3 GHz)

[4] ICNIRP, International Commission on Non-Ionizing Radiation Protection (1998), Guidelines for limiting exposure in time-varying electric, magnetic, and electromagnetic fields (up to 300 GHz).

[5] Council Recommendation 1999/519/EC of July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)

[6] IEEE C95.3-1991, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave.

[7] IEEE C95.1-1999, IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[8] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields.

[9] FCC 96-326, Guidelines for Evaluating the Environmental Effects of Radio-Frequency Radiation.

[10] DASY 4 DOSIMETRIC ASSESSMENT SYSTEM SOFTWARE MANUAL V4.7 Schmid & Partner Engineering AG, June 2006 which follows draft IEC 62209 – Part 2.

[11] Health Canada, Safety Code 6, 1999: Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency range from 3 kHz to 300 GHz.

[12] RSS-102, issue 2-2005: Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields.

[13] IEC 62209-1, First Edition-2005: Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)

[14] FCC OET SAR Measurement Requirements for 3 – 6 GHz, October 16, 2006.

[15] FCC OET SAR Measurement Procedures for 802.11 a/b/g Transmitters, October 16, 2006.

[16] FCC OET SAR Evaluation Considerations for Handsets with Multiple Transmitters & Antennas, February 2008.