	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page	1(38)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Andrew Becker	September 1 - 29, 2009	RTS-2068-0909-43	L6ARCL20CW		




SAR Compliance Test Report


Testing Lab:	RIM Testing Services 440 Phillip Street Waterloo, Ontario Canada N2L 5R9 Phone: 519-888-7465 Fax: 519-746-0189	Applicant:	Research In Motion Limited 295 Phillip Street Waterloo, Ontario Canada N2L 3W8 Phone: 519-888-7465 Fax: 519-888-6906 Web site: www.rim.com
---------------------	---	-------------------	--

Statement of Compliance: RIM Testing Services declares under its sole responsibility that the product to which this declaration relates, is in conformity with the appropriate RF exposure standards, recommendations and guidelines. It also declares that the product was tested in accordance with the appropriate measurement standards, guidelines and recommended practices.

Device Category: This BlackBerry® Smartphone is a portable device, designed to be used in direct contact with the user's head, hand and to be carried in approved accessories when carried on the user's body.

RF exposure environment: This device has been shown to be in compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in OET Bulletin 65 Supplement C (Edition 01-01), FCC 96-326, IEEE Std. C95.1-1999, Health Canada's Safety Code 6, as reproduced in RSS-102 issue 3-2009 and has been tested in accordance with the measurement procedures specified in FCC OET Procedures, OET Bulletin 65 Supplement C (Edition 01-01), ANSI/IEEE Std. C95.3-1991, IEEE 1528-2003, IEC 62209-1-2005, DASY4 manual which follows draft IEC 62209 – Part 2 and Health Canada's Safety Code 6.

Tested and documented by:	Signatures	Date
Andrew Becker Compliance Specialist		16-Sep-2009
Tested and reviewed by: Daoud Attayi Senior Compliance Specialist		05-Oct-2009
Approved by: Masud S. Attayi Mgr, Regulatory Compliance		14-Oct-2009

	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page	2(38)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Andrew Becker	September 1 - 29, 2009	RTS-2068-0909-43	L6ARCL20CW		

CONTENTS

SAR COMPLIANCE TEST REPORT..... 1

 CONTENTS..... 2

1.0 OPERATING CONFIGURATIONS AND TEST CONDITIONS..... 4

 1.1 PICTURE OF DEVICE..... 4

 1.2 ANTENNA DESCRIPTION..... 4

 1.3 DEVICE DESCRIPTION..... 4

 1.4 BODY WORN ACCESSORIES (HOLSTERS)..... 5

 1.5 HEADSET..... 5

 1.6 BATTERY..... 5

 1.7 PROCEDURE USED TO ESTABLISH TEST SIGNAL..... 5

 1.8 HIGHLIGHTS OF THE FCC OET SAR MEASUREMENT REQUIREMENTS..... 5

 1.8.1 SAR MEASUREMENT REQUIREMENTS FOR 3-6 GHZ AND MEASUREMENT PROCEDURES FOR 802.11 A/B/G TRANSMITTER..... 6

 1.8.2 FCC SAR MEASUREMENT PROCEDURES FOR 3G DEVICES CDMA 2000 1X..... 7

 1.8.2.1 OUTPUT POWER VERIFICATION..... 7

 1.8.2.2 3GPP2 C.S0011/ TIA-98-E, SECTION 4.4.5.2 METHOD OF MEASUREMENT..... 8

 1.8.2.3 HEAD SAR MEASUREMENTS..... 8

 1.8.2.4 BODY SAR MEASUREMENTS..... 9

 1.8.2.5 1X EV-DO..... 9

 1.9 HIGHLIGHTS OF THE FCC OET SAR EVALUATION CONSIDERATIONS FOR HANDSETS WITH MULTIPLE TRANSMITTERS/ANTENNAS..... 12

2.0 DESCRIPTION OF THE TEST EQUIPMENT..... 13

 2.1 SAR MEASUREMENT SYSTEM..... 13

 2.1.1 EQUIPMENT LIST..... 14

 2.2 DESCRIPTION OF THE TEST SETUP..... 15

 2.2.1 DEVICE AND BASE STATION SIMULATOR SETUP..... 15

 2.2.2 DASY SETUP..... 15

3.0 ELECTRIC FIELD PROBE CALIBRATION..... 15

 3.1 PROBE SPECIFICATIONS..... 15

 3.2 PROBE CALIBRATION AND MEASUREMENT UNCERTAINTY..... 16

4.0 SAR MEASUREMENT SYSTEM VERIFICATION..... 16

 4.1 SYSTEM ACCURACY VERIFICATION FOR HEAD ADJACENT USE..... 16

5.0 PHANTOM DESCRIPTION..... 17

6.0 TISSUE DIELECTRIC PROPERTIES..... 18

 6.1 COMPOSITION OF TISSUE SIMULANT..... 18

 6.1.1 EQUIPMENT..... 18

 6.1.2 PREPARATION PROCEDURE..... 18

 6.2 ELECTRICAL PARAMETERS OF THE TISSUE SIMULATING LIQUID..... 19

 6.2.1 EQUIPMENT..... 20

 6.2.2 TEST CONFIGURATION..... 20

 6.2.3 PROCEDURE..... 20

7.0 SAR SAFETY LIMITS..... 24

8.0 DEVICE POSITIONING..... 25

 8.1 DEVICE HOLDER FOR SAM TWIN PHANTOM..... 25

 8.2 DESCRIPTION OF THE TEST POSITIONING..... 26

 8.2.1 TEST POSITIONS OF DEVICE RELATIVE TO HEAD..... 26

 8.2.1.1 DEFINITION OF THE "CHEEK" POSITION..... 27

 8.2.1.2 DEFINITION OF THE "TILTED" POSITION..... 28

 8.2.2 BODY HOLSTER CONFIGURATION..... 28

9.0 HIGH LEVEL EVALUATION..... 29

 9.1 MAXIMUM SEARCH..... 29

 9.2 EXTRAPOLATION..... 29

 9.3 BOUNDARY CORRECTION..... 29

 9.4 PEAK SEARCH FOR 1G AND 10G CUBE AVERAGED SAR..... 29


10.0 MEASUREMENT UNCERTAINTY..... 30

11.0 TEST RESULTS..... 31

 11.1 SAR MEASUREMENT RESULTS AT HIGHEST POWER MEASURED AGAINST THE HEAD..... 31

 11.2 SAR MEASUREMENT RESULTS AT HIGHEST POWER MEASURED AGAINST THE BODY USING ACCESSORIES..... 34

12.0 REFERENCES..... 37

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 3(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43


APPENDIX A: SAR DISTRIBUTION COMPARISON FOR ACCURACY VERIFICATION

APPENDIX B: SAR DISTRIBUTION PLOTS - HEAD CONFIGURATION

APPENDIX C: SAR DISTRIBUTION PLOTS - BODY-WORN CONFIGURATION

APPENDIX D: PROBE & DIPOLE CALIBRATION DATA

APPENDIX E: PHOTOGRAPHS

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 4(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

1.0 OPERATING CONFIGURATIONS AND TEST CONDITIONS

1.1 Picture of Device

Please refer to Appendix E.
Figure 1.1.1 BlackBerry Smartphone

1.2 Antenna description


Type	Internal fixed antenna
Location	Back bottom centre (main licensed transmitters)
Configuration	Internal fixed antenna

Table 1.2.1. Antenna description

1.3 Device description

Device Model	RCL21CW				
FCC ID	L6ARCL20CW				
PIN	Rev1: 30D9EC96, 30D9ECA9 (WiFi), 30D9F068 (conducted), Rev 3: 30EC2ACE				
Prototype or Production Unit	Production				
Mode(s) of Operation	CDMA2000/ 1xEvDO 800	CDMA2000/ 1xEvDO 1900	802.11b	802.11g	Bluetooth
Maximum nominal conducted RF Output Power (dBm)	24.0	23.5	18.0	16.0	8.0
Tolerance in Power Setting on centre channel (dB)	± 0.50	± 0.50	± 0.50	± 0.50	N/A
Duty Cycle	1:1	1:1	1:1	1:1	N/A
Tx Frequency Range (MHz)	824.70 – 848.52	1851.25 – 1908.50	2412-2462	2412-2462	2402-2483

Table 1.3.1. Test device description

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 5(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

1.4 Body worn accessories (holsters)

The device has been tested with the two holsters listed below, which contain belt-clip/metal components. The separation distance between the device and the user's body is listed in the table below. The holsters are designed with the intended device orientation being with the LCD facing the belt clip. Proper positioning is vital for protection of the LCD display, and to help maximize the battery life of the device. The device can also be placed in the holster with the backside facing the belt clip. Body SAR measurements were carried out with the worst-case configuration front LCD side and backside towards the belt clip.

Number	Holster Type	Part Number	Separation distance (mm)
1	Vertical Swivel Holster	HDW-24208-001	22
2	Horizontal Swivel Holster	HDW-18965-002	21

Table 1.4.1. Body worn holster

Please refer to Appendix E.

Figure 1.4.1. Body-worn holster

1.5 Headset

The device was tested with and without the following headset model numbers.

- 1) HDW-14322-003
- 2) HDW-15766-005
- 3) HDW-15765-001

1.6 Battery


The device was tested with the following Lithium Ion Battery pack.

- 1) BAT-06860-004

1.7 Procedure used to establish test signal

The device was put into test mode for SAR measurements by placing a voice call from a Rohde & Schwarz CMU 200 Communications Test Instrument. The power control level was set to command the device to transmit at full power at the specified frequency. Other parameters include: Channel type = full rate, discontinuous transmission off, frequency hopping off. A Rohde & Schwarz CBT Bluetooth Tester was used to establish a connection with the EUT's Bluetooth radio. Worst case SAR was evaluated with Bluetooth on.

1.8 Highlights of the FCC OET SAR Measurement Requirements


	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 6(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

1.8.1 Measurement Procedure for 802.11 b/g Transmitter

- Maintained dielectric parameter uncertainty as close to $\pm 5.0\%$ of the target value as possible.
- Liquid depth from SAM ERP or flat phantom was kept at 15 cm.
- Frequency Channel Configuration: 802.11 b/g modes are tested on “default test channels” 1, 6 and 11.
- For each frequency band, testing at higher rates and higher modulations is not required when the maximum average output power for each of these configurations is less than $\frac{1}{4}$ dB higher than those measured at the lowest data rate.
- SAR is not required for 802.11g channels when the maximum average output power is less than $\frac{1}{4}$ dB higher than that measured on the corresponding 802.11b channels.
- SAR test was conducted on each “default test channel” and each band with the worst case modulation that resulted in maximum duty cycle of 99.5 %.
- Conducted power measurements:

802.11b @ 1Mbps		802.11g @ 6Mbps	
Chan	Cond. Power (dBm)	Chan	Cond. Power (dBm)
1	17.60	1	13.30
6	18.00	6	16.80
11	18.05	11	13.80

Table 1.8.1. 802.11 b/g channel vs. conducted power

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 7(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43
		FCC ID: L6ARCL20CW	

Data Rate (Mbps)	Mod.	802.11g		802.11b		
		Channel 6		Data Rate (Mbps)	Mod.	Channel 6
		Cond. Power (dBm)				Cond. Power (dBm)
6	BPSK	16.80	1	BPSK	18.00	
9	BPSK	16.80	2	DQPSK	18.00	
12	QPSK	14.80	5.5	CCK	17.95	
18	QPSK	14.65	11	CCK	17.98	
24	16-QAM	13.30				
36	16-QAM	12.90				
48	64-QAM	11.10				
54	64-QAM	11.05				


Table 1.8.2. 802.11 b/g modulation type/data rate vs. conducted power

1.8.2 FCC SAR Measurement Procedures for 3G Devices CDMA1x 2000

The followings are the **FCC SAR Measurement Procedures for 3G Devices issued in Oct. 2006**, applicable to handsets operating under CDMA 2000, Release 0, with MS Protocol Revision 6 (**P_REV 6**). The default test configuration is to measure SAR in RC3 with an established radio link between the DUT and a communication test set. SAR in RC1 is selectively confirmed according to output power and exposure conditions.

1.8.2.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. Results for at least steps 3, 4 and 10 of the power measurement procedures should be tabulated in the SAR report as shown on Table 1.9.2. Steps 3 and 4 should be measured using SO55 with power control bits in “All Up” condition. TDSO / SO32 may be used instead of SO55 for step 4. Step 10 should be measured using TDSO / SO32 with power control bits in the “Bits Hold” condition (i.e. alternative Up/Down Bits).

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 8(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

1.8.2.2 3GPP2 C.S0011/ TIA-98-E, section 4.4.5.2 Method of Measurement

3. If the mobile station supports Reverse Traffic Channel Radio Configuration 1 and 7 Forward Traffic Channel Radio Configuration 1, set up a call using Fundamental 8 Channel Test Mode 1 with 9600 bps data rate only and perform steps 6 through 8.
4. If the mobile station supports the Radio Configuration 3 Reverse Fundamental 11 Channel and demodulation of Radio Configuration 3, 4, or 5, set up a call using 12 Fundamental Channel Test Mode 3 with 9600 bps data rate only and 13 perform steps 6 through 8.
6. Set the test parameters as specified in Table 1.8.3.
7. Send continuously '0' power control bits to the mobile station.
8. Measure the mobile station output power at the mobile station antenna connector.
10. If the mobile station supports the Radio Configuration 3 Reverse Fundamental Channel, Radio Configuration 3 Reverse Supplemental Channel 0 and demodulation of Radio Configuration 3, 4, or 5, set up a call using Supplemental Channel Test Mode 3 with 9600 bps Fundamental Channel and 9600 bps Supplemental Channel 0 data rate, and perform the following:
 - a) Set the test parameters as specified in Table 1.8.4.
 - b) Send alternating '0' and '1' power control bits to the mobile station using the smallest supported closed loop power control step size supported by the mobile station.
 - c) Determine the active channel configuration. If the desired channel configuration is not active, increase by 1 dB and repeat the verification. Repeat this step until the desired channel configuration becomes active.
 - d) Measure the mobile station output power at the mobile station antenna connector and record reading.

Parameter	Units	Value
\bar{I}_{or}	dBm/1.23 MHz	-104
$\frac{\text{Pilot } E_c}{I_{or}}$	dB	-7
$\frac{\text{Traffic } E_c}{I_{or}}$	dB	-7.4

Table 1.8.3


Parameter	Units	Value
\bar{I}_{or}	dBm/1.23 MHz	-86
$\frac{\text{Pilot } E_c}{I_{or}}$	dB	-7
$\frac{\text{Traffic } E_c}{I_{or}}$	dB	-7.4

Table 1.8.4

Test Parameters for Maximum RF Output Power for Spreading Rate 1

1.8.2.3 Head SAR Measurements

SAR for head exposure configurations is measured in RC3 with the DUT configured to transmit at full rate using Loopback Service Option SO55. SAR for RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.

	Document		Page
	SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		9(38)
Author Data	Dates of Test	Test Report No	FCC ID:
Andrew Becker	September 1 - 29, 2009	RTS-2068-0909-43	L6ARCL20CW


1.8.2.4 Body SAR Measurements

SAR for body exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. SAR for multiple code channels (FCH + SCH_n) is not required when the maximum average output of each RF channel is less than ¼ dB higher than that measured with FCH only. Otherwise, SAR is measured on the maximum output channel (FCH + SCH_n) with FCH at full rate and SCH₀ enabled at 9600 bps using the exposure configuration that results in the highest SAR for that channel with FCH only. When multiple code channels are enabled, the DUT output may shift by more than 0.5 dB and lead to higher SAR drifts and SCH dropouts.

Body SAR in RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1; with Loopback Service Option SO55, at full rate, using the body exposure configuration that results in the highest SAR for that channel in RC3.


1.8.2.5 1x Ev-DO

For handsets with Ev-Do capabilities, when the maximum average output of each channel in Rev. 0 is less than ¼ dB higher than that measured in RC3 (1x RTT), body SAR for Ev-Do is not required. Otherwise, SAR for Rev. 0 is measured on the maximum output channel at 153.6 kbps using the body exposure configuration that results in the highest SAR for that channel in RC3. SAR for Rev. A is not required when the maximum average output of each channel is less than that measured in Rev. 0 or less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel for Rev. A using a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations. A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in all slots should be configured in the downlink for both Rev. 0 and Rev. A.

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 10(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

Band	Channel	1x EvDO (153.6kbps)	CDMA2000 RC	SO2 Loopback	SO55 Loopback	TDSO SO32 Test Data Service
CDMA 800	1013	24.0	RC1	24.2	24.2	N/A
			RC3	24.2	24.1	24.1
	384	23.5	RC1	23.8	23.8	N/A
			RC3	23.8	23.8	23.8
	777	23.6	RC1	23.9	23.8	N/A
			RC3	23.9	23.8	23.9
Band	Channel	1x EvDO (153.6kbps)	CDMA2000 RC	SO2 Loopback	SO55 Loopback	TDSO SO32 Test Data Service
CDMA 1900	25	23.4	RC1	23.5	23.5	N/A
			RC3	23.5	23.4	23.4
	600	23.5	RC1	23.6	23.7	N/A
			RC3	23.6	23.7	23.6
	1175	23.3	RC1	23.6	23.5	N/A
			RC3	23.5	23.5	23.3

Table 1.8.5: Conducted RF output power (dBm) measured for various settings

	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page	11(38)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Andrew Becker	September 1 - 29, 2009	RTS-2068-0909-43	L6ARCL20CW		

1.9 Highlights of the FCC OET SAR Evaluation Considerations for Handsets with Multiple Transmitters/ Antennas

Unlicensed Transmitters

When there is simultaneous transmission –
Stand-alone SAR not required when

- output $\leq 2 \cdot P_{Ref}$ and antenna is > 5.0 cm from other antennas
- output $\leq P_{Ref}$ and antenna is > 2.5 cm from other antennas
- the other antenna(s), which are < 2.5 cm away, has an output $\leq P_{Ref}$ OR max 1g SAR < 1.2 W/kg

Otherwise stand-alone SAR is required

- test SAR on highest output channel for each wireless mode and exposure condition
- if SAR for highest output channel is $> 50\%$ of SAR limit, evaluate all channels according to normal procedure

Simultaneous Transmission SAR not required:

Unlicensed only

- when stand-alone 1-g SAR is not required and antenna is > 5 cm from other antennas
- when the other antenna(s), which are < 2.5 cm away, has an output $\leq P_{Ref}$ OR max 1g SAR < 1.2 W/kg

Licensed & Unlicensed

- when the sum of the 1-g SAR is < 1.6 W/kg for each pair of simultaneous transmitting antennas.
- or
- when the ratio of SAR to peak SAR separation distance of simultaneous transmitting antenna pair is < 0.3

Simultaneous Transmission SAR required:

Licensed & Unlicensed

- antenna pairs with SAR to antenna separation ratio ≥ 0.3 ; test is only required for the configuration that results in the highest SAR in standalone configuration for each wireless mode and exposure condition.

	2.45	GHz
P_{Ref}	12	mW

Device output power should be rounded to the nearest mW to compare with values specified in this table.

Table 1.9.1 – Output Power Thresholds for Unlicensed Transmitters





Figure 1.9.1. Back view of device showing closet distance between antenna pairs

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 12(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43


Mode	Configuration	Highest 1 g SAR (W/kg)	Seperation distance between two peaks (cm)	Ratio of 1 g SAR to distance (cm) between two peaks
CDMA	Head-Right-Touch	1.31	6.02	0.28
802.11 b/g	Head-Right-Touch	0.35		
CDMA	Body-Vertical Holster Back	0.66		
802.11b/g	Body- Vertical Holster Back	0.09		

Table 1.9.2. Highest SAR values for the same setup

Simultaneous Transmission SAR is not required for body SAR based on the sum of 1-g SAR values for each pair of simultaneous transmitting antennas being $< 1.6\text{W/kg}$.

Simultaneous Transmission SAR is not required for head configuration based on ratio of SAR to peak SAR separation distance of simultaneous transmitting antenna pairs being < 0.3

BT stand-alone SAR is not required since antenna is > 2.5 cm away from the other antenna has an output \leq PRef, therefore Simultaneous Transmission SAR is not required

	Document	Page	
	SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW	13(38)	
Author Data	Dates of Test	Test Report No	FCC ID:
Andrew Becker	September 1 - 29, 2009	RTS-2068-0909-43	L6ARCL20CW

2.0 DESCRIPTION OF THE TEST EQUIPMENT

2.1 SAR measurement system

SAR measurements were performed using a Dosimetric Assessment System (DASY4), an automated SAR measurement system manufactured by Schmid & Partner Engineering AG (SPEAG), of Zurich, Switzerland.

The DASY 4 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller and software.
- An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A DAE module that performs the signal amplification, signal multiplexing, A/D conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the Electro-optical coupler (EOC).
- A unit to operate the optical surface detector that is connected to the EOC.
- The EOC performs the conversion from an optical signal into the digital electric signal of the DAE. The EOC is connected to the PC plug-in card.
- The functions of the PC plug-in card based on a DSP is to perform the time critical tasks such as signal filtering, surveillance of the robot operation fast movement interrupts.
- A computer operating Windows 2000.
- DASY 4 software version 4.7.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM Twin Phantom enabling testing left-hand and right-hand usage.
- The device holder for mobile phones.
- Tissue simulating liquid mixed according to the given recipes (see section 6.1).
- System validation dipoles allowing for the validation of proper functioning of the system.






Figure 2.1.1. System Description

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 14(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

2.1.1 Equipment List

Manufacturer	Test Equipment	Model Number	Serial Number	Cal. Due Date (MM/DD/YY)
SCHMID & Partner Engineering AG	E-field probe	ET3DV6	1642	01/12/2010
SCHMID & Partner Engineering AG	Data Acquisition Electronics (DAE3)	DAE3 V1	472	03/03/2010
SCHMID & Partner Engineering AG	Dipole Validation Kit	D835V2	446	01/05/2011
SCHMID & Partner Engineering AG	Dipole Validation Kit	D1900V2	545	01/06/2011
SCHMID & Partner Engineering AG	Dipole Validation Kit	D2450V2	747	11/06/2009
Agilent Technologies	Signal generator	8648C	4037U03155	09/20/2009
Agilent Technologies	Signal generator	E8257D	MY45140527	10/09/2010
Agilent Technologies	Power meter	E4419B	GB40202821	09/19/2009
Agilent Technologies	Power sensor	8481A	MY41095417	10/30/2009
Agilent Technologies	Power sensor	N1921A	SG45240281	05/08/2010
Agilent Technologies	Power meter	N1911A	MY45100905	05/01/2011
Amplifier Research	Amplifier	5S1G4M3	300986	CNR
Agilent Technologies	Network analyzer	8753ES	US39174857	10/29/2009
Rohde & Schwarz	Base Station Simulator	CMU 200	109747	12/07/2009

Table 2.1.2. Equipment list

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 15(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

2.2 Description of the test setup

Before SAR measurements are conducted, the device and the DASYS equipment are setup as follows:

2.2.1 Device and base station simulator setup

- Power up the device.
- Turn on the base station simulator and set the radio channel and power to the appropriate values.
- Connect an antenna to the RF IN/OUT of the communication test set and place it close to the device.

2.2.2 DASYS setup

- Turn the computer on and log on to Windows 2000.
- Start the DASYS4 software by clicking on the icon located on the Windows desktop.
- Mount the DAE unit and the probe. Turn on the DAE unit.
- Turn the Robot Controller on by turning the main power switch to the horizontal position
- Align the probe by clicking the 'Align probe in light beam' button.
- Open a file and configure the proper parameters - probe, medium, communications system etc.
- Establish a connection between the Device and the communications test instrument. Place the Device on the stand and adjust it under the phantom.
- Start SAR measurements.


3.0 ELECTRIC FIELD PROBE CALIBRATION

3.1 Probe Specifications

SAR measurements were conducted using the dosimetric probe ET3DV6, designed by Schmid & Partner Engineering AG for the measurement of SAR. The probe is constructed using the thin film technique, with printed resistive lines on ceramic substrates. It has a symmetrical design with triangular core, built-in optical fibre for the surface detection system and built-in shielding against static discharge. The probe is sensitive to E-fields and thus incorporates three small dipoles arranged so that the overall response is close to isotropic. The table below summarizes the technical data for the probe.

Property	Data
Probe model ET3DV6	
Frequency range	30 MHz – 3 GHz
Linearity	±0.1 dB
Directivity (rotation around probe axis)	≤ ±0.2 dB
Directivity (rotation normal to probe axis)	±0.4 dB
Dynamic Range	5 mW/kg – 100 W/kg
Probe positioning repeatability	±0.2 mm
Spatial resolution	< 0.125 mm ³

Table 3.1.1. Probe specifications

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 16(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

3.2 Probe calibration and measurement uncertainty

The probe ET3DV6 was calibrated with an accuracy better than $\pm 10\%$. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe were tested. The probe calibration parameters are shown on Appendix D.


4.0 SAR MEASUREMENT SYSTEM VERIFICATION

Prior to conducting SAR measurements, the system was validated using the dipole validation kit and the flat section of the SAM phantom. A power level of 1.0W was applied to the dipole antenna. The verification results are in the table below with a comparison to reference values. Printouts are shown in Appendix A. All the measured parameters are within the allowed tolerances.

4.1 System accuracy verification for head adjacent use

f (MHz)	Limits / Measured (MM/DD/YY)	SAR (W/kg) 1 g/ 10 g	Dielectric Parameters		Liquid Temp (°C)
			ϵ_r	σ [S/m]	
835	Measured (09/03/2009)	8.94/5.91	39.6	0.86	22.1
	Measured (09/25/2009)	9.27/6.11	41.1	0.88	22.2
	Recommended Limits	9.50/6.27	41.5	0.90	N/A
1900	Measured (09/01/2009)	39.1/20.8	38.4	1.45	22.1
	Measured (09/24/2009)	37.0/19.4	40.7	1.40	22.0
	Recommended Limits	39.5/20.8	40.0	1.40	N/A
2450	Measured (09/03/2009)	58.4/27.1	37.5	1.88	21.9
	Measured (09/28/2009)	58.4/26.9	37.5	1.88	22.1
	Recommended Limits	53.2/24.8	39.2	1.80	N/A

Table 4.1.1. System accuracy (validation for head adjacent use)

	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page	17(38)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Andrew Becker	September 1 - 29, 2009	RTS-2068-0909-43	L6ARCL20CW		

5.0 PHANTOM DESCRIPTION

The SAM Twin Phantom, manufactured by SPEAG, was used during the SAR measurements. The phantom is made of a fibreglass shell integrated with a wooden table.

The SAM Twin Phantom is a fibreglass shell phantom with 2 mm shell thickness. It has three measurement areas:

- Left side head
- Right side head
- Flat phantom

The phantom table dimensions are: 100x50x85 cm (LxWxH). The table is intended for use with freestanding robots.


The bottom shelf contains three pair of bolts for locking the device holder in place. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different solutions).

A white cover is provided to top the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on the cover are possible; however the optical surface detector does not work properly at the cover surface. Place a sheet of white paper on the cover when using optical surface detection.

Liquid depth of ≥ 15 cm is maintained in the phantom for all the measurements.



Figure 5.0.1. SAM Twin Phantom

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 18(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43
		FCC ID: L6ARCL20CW	

6.0 TISSUE DIELECTRIC PROPERTIES

6.1 Composition of tissue simulant

The composition of the brain and muscle simulating liquids for 800-900 MHz and 1800-1900 MHz are shown in the table below.

INGREDIENT	MIXTURE 800-900MHz		MIXTURE 1800-1900MHz		MIXTURE 2450 MHz	
	Brain %	Muscle %	Brain %	Muscle %	Brain %	Muscle %
Water	40.29	65.45	55.24	69.91	55.0	68.75
Sugar	57.90	34.31	0	0	0	0
Salt	1.38	0.62	0.31	0.13	0	0
HEC	0.24	0	0	0	0	0
Bactericide	0.18	0.10	0	0	0	0
DGBE	0	0	44.45	29.96	40.0	31.25
Triton X-100	0	0	0	0	5.0	0

Table 6.1.1 Tissue simulant recipe

6.1.1 Equipment


Manufacturer	Test Equipment	Model Number	Serial Number	Cal. Due Date (MM/DD/YY)
Pyrex, England	Graduated Cylinder	N/A	N/A	N/A
Pyrex, USA	Beaker	N/A	N/A	N/A
Acculab	Weight Scale	V1-1200	018WB2003	N/A
Control Company	Digital Thermometer	15-077-21	51129471	05/01/2010
IKA Works Inc.	Hot Plate	RC Basic	3.107433	N/A

Table 6.1.2 Tissue simulant preparation equipment

6.1.2 Preparation procedure

800-900 MHz liquids

- Fill the container with **water**. Begin heating and stirring.
- Add the **Cellulose**, the **preservative substance** and the **salt**. After several hours, the liquid will become more transparent again. The container must be covered to prevent evaporation.
- Add **Sugar**. Stir it well until the sugar is sufficiently dissolved.
- Keep the liquid hot but below the boiling point for at least an hour. The container must be covered to prevent evaporation.

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 19(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

- Remove the container from, and turn the hotplate off and allow the liquid to cool off to room temperature prior to performing dielectric measurements.

1800-2450 MHz liquid

- Fill the container with water and place it on hotplate. Begin heating and stirring.
- Add the salt, Glycol/Triton X-100. The container must be covered to prevent evaporation.
- Keep the liquid hot enough to dissolve sugar for at least an hour. The container must be covered to prevent evaporation.
- Remove the container from, and turn the hotplate off and allow the liquid to cool off to room temperature prior to performing dielectric measurements.

6.2 Electrical parameters of the tissue simulating liquid


The tissue dielectric parameters shall be measured before a batch can be used for SAR measurements to ensure that the simulated tissue was properly made and will simulate the desired human characteristic. Limits and measured electrical parameters are shown in the table below.

Recommended limits are adopted from IEEE P1528-2003:

“Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, DAS4 manual and from FCC Tissue Dielectric Properties web page at <http://www.fcc.gov/fcc-bin/dielec.sh>

f (MHz)	Tissue Type	Limits / Measured	Dielectric Parameters		Liquid Temp (°C)
			ϵ_r	σ [S/m]	
835	Head	Measured (09/03/2009)	39.6	0.86	22.1
		Measured (09/25/2009)	41.1	0.88	22.2
		Recommended Limits	41.5	0.90	N/A
	Muscle	Measured (09/03/2009)	53.0	0.94	22.0
		Measured (09/25/2009)	53.3	0.93	22.2
		Recommended Limits	55.2	0.97	N/A
1900	Head	Measured (09/01/2009)	38.4	1.45	22.1
		Measured (09/24/2009)	40.7	1.40	22.0
		Recommended Limits	40.0	1.40	N/A
	Muscle	Measured (09/01/2009)	50.8	1.57	22.4
		Measured (09/24/2009)	51.0	1.58	22.0
		Recommended Limits	53.3	1.52	N/A
2450	Head	Measured (09/03/2009)	37.5	1.88	21.9
		Measured (09/28/2009)	37.5	1.88	22.1
		Recommended Limits	39.2	1.80	N/A
	Muscle	Measured (09/04/2009)	50.2	1.96	22.1
		Measured (09/29/2009)	50.5	1.99	22.1
		Recommended Limits	52.7	1.95	N/A

Table 6.2.1 Electrical parameters of tissue simulating liquid

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 20(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

6.2.1 Equipment

Manufacturer	Test Equipment	Model Number	Serial Number	Cal. Due Date (MM/DD/YY)
Agilent Technologies	Network Analyzer	8753ES	US39174857	10/29/2009
Agilent Technologies	Dielectric probe kit	HP 85070C	US9936135	CNR
Dell	PC using GPIB card	GX110	347	N/A
Control Company	Digital Thermometer	15-077-21	51129471	05/01/2010

Table 6.2.2. Equipment required for electrical parameter measurements

6.2.2 Test Configuration




Figure 6.2.1 Test configuration

6.2.3 Procedure


1. Turn NWA on and allow at least 30 minutes for warm up.
2. Mount dielectric probe kit so that interconnecting cable to NWA will not be moved during measurements or calibration.
3. Pour de-ionized water and measure water temperature ($\pm 1^\circ$).
4. Set water temperature in HP-Software (Calibration Setup).
5. Perform calibration.
6. Relative permittivity $\epsilon_r = \epsilon'$ and conductivity can be calculated from ϵ''

$$\sigma = \omega \epsilon_0 \epsilon''$$
7. Measure liquid shortly after calibration.
8. Stir the liquid to be measured. Take a sample (~50ml) with a syringe from the center of the liquid container.
9. Pour the liquid into a small glass flask. Hold the syringe at the bottom of the flask to avoid air bubbles.
10. Put the dielectric probe in the glass flask. Check that there are no air bubbles in front of the opening in the dielectric probe kit.
11. Perform measurements.
12. Adjust medium parameters in DASY4 for the frequencies necessary for the measurements ('Setup Config', select medium (e.g. Head 835 MHz) and press 'Option'-button.
13. Select the current medium for the frequency of the validation (e.g. Setup Medium Brain 835 MHz).

Sample calculation for 835 MHz head tissue dielectric parameters using data from Table 6.2.3.

Relative permittivity $\epsilon_r = \epsilon' = 39.64$

Conductivity $\sigma = \omega \epsilon_0 \epsilon'' = (2\pi \times 835 \times 10^6)(8.854 \times 10^{-12})(18.59) = 0.86 \text{ S/m}$

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 21(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

Title
SubTitle
September 02, 2009 09:53 PM

Title
SubTitle
September 03, 2009 03:13 PM


Frequency	e'	e''
800.000000 MHz	40.1313	18.6672
805.000000 MHz	40.0690	18.6523
810.000000 MHz	39.9891	18.6477
815.000000 MHz	39.9353	18.6365
820.000000 MHz	39.8478	18.6344
825.000000 MHz	39.7898	18.6196
830.000000 MHz	39.7033	18.6126
835.000000 MHz	39.6350	18.5907
840.000000 MHz	39.5948	18.5928
845.000000 MHz	39.5188	18.5736
850.000000 MHz	39.4325	18.5885
855.000000 MHz	39.3734	18.5858
860.000000 MHz	39.3238	18.5401
865.000000 MHz	39.2622	18.5589
870.000000 MHz	39.1752	18.5545
875.000000 MHz	39.1121	18.5238
880.000000 MHz	39.0340	18.5077
885.000000 MHz	38.9866	18.5629
890.000000 MHz	38.9414	18.5330
895.000000 MHz	38.9059	18.5008
900.000000 MHz	38.8586	18.5115
905.000000 MHz	38.8122	18.4877
910.000000 MHz	38.7254	18.4564
915.000000 MHz	38.6869	18.4553
920.000000 MHz	38.6071	18.4421
925.000000 MHz	38.5512	18.4416
930.000000 MHz	38.4873	18.4435
935.000000 MHz	38.4593	18.4352
940.000000 MHz	38.3908	18.4483
945.000000 MHz	38.3305	18.4214
950.000000 MHz	38.2433	18.4122

Frequency	e'	e''
800.000000 MHz	53.3887	20.1598
805.000000 MHz	53.3293	20.1408
810.000000 MHz	53.2833	20.1564
815.000000 MHz	53.2296	20.1469
820.000000 MHz	53.1952	20.1416
825.000000 MHz	53.1471	20.1413
830.000000 MHz	53.0708	20.1511
835.000000 MHz	53.0505	20.1300
840.000000 MHz	52.9862	20.1358
845.000000 MHz	52.8996	20.1064
850.000000 MHz	52.8802	20.1393
855.000000 MHz	52.8055	20.1062
860.000000 MHz	52.7329	20.1049
865.000000 MHz	52.6813	20.1280
870.000000 MHz	52.6414	20.0936
875.000000 MHz	52.5502	20.0893
880.000000 MHz	52.4834	20.1182
885.000000 MHz	52.4281	20.0905
890.000000 MHz	52.3960	20.0803
895.000000 MHz	52.3685	20.0528
900.000000 MHz	52.3109	20.0526
905.000000 MHz	52.2701	20.0667
910.000000 MHz	52.2413	20.0556
915.000000 MHz	52.1867	20.0289
920.000000 MHz	52.1439	20.0693
925.000000 MHz	52.0815	20.0563
930.000000 MHz	52.0391	20.0659
935.000000 MHz	51.9698	20.0560
940.000000 MHz	51.9276	20.0356
945.000000 MHz	51.8534	20.0583
950.000000 MHz	51.7967	20.0342

Head

Muscle

Table 6.2.3. 835 MHz head and muscle tissue dielectric parameters

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 22(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

Title

SubTitle

September 01, 2009 05:37 PM

Frequency	e'	e''
1.800000000 GHz	38.9325	13.3122
1.805000000 GHz	38.9052	13.3406
1.810000000 GHz	38.8776	13.3780
1.815000000 GHz	38.8575	13.3870
1.820000000 GHz	38.8323	13.4170
1.825000000 GHz	38.8008	13.4508
1.830000000 GHz	38.7788	13.4849
1.835000000 GHz	38.7496	13.4964
1.840000000 GHz	38.7260	13.5166
1.845000000 GHz	38.6939	13.5419
1.850000000 GHz	38.6620	13.5670
1.855000000 GHz	38.6401	13.5833
1.860000000 GHz	38.6080	13.6117
1.865000000 GHz	38.5927	13.6329
1.870000000 GHz	38.5627	13.6392
1.875000000 GHz	38.5432	13.6719
1.880000000 GHz	38.5121	13.6850
1.885000000 GHz	38.4783	13.7028
1.890000000 GHz	38.4438	13.7092
1.895000000 GHz	38.4140	13.7276
1.900000000 GHz	38.3943	13.7428
1.905000000 GHz	38.3454	13.7673
1.910000000 GHz	38.3200	13.8007
1.915000000 GHz	38.2971	13.8092
1.920000000 GHz	38.2655	13.8408

Head

Title


SubTitle

September 01, 2009 10:58 AM

Frequency	e'	e''
1.800000000 GHz	51.2604	14.4294
1.805000000 GHz	51.2252	14.4160
1.810000000 GHz	51.1994	14.4091
1.815000000 GHz	51.1416	14.4148
1.820000000 GHz	51.0669	14.3780
1.825000000 GHz	51.0163	14.3783
1.830000000 GHz	50.9500	14.3848
1.835000000 GHz	50.8894	14.3974
1.840000000 GHz	50.8078	14.3927
1.845000000 GHz	50.7557	14.4059
1.850000000 GHz	50.7062	14.4383
1.855000000 GHz	50.6849	14.4577
1.860000000 GHz	50.6665	14.4924
1.865000000 GHz	50.6426	14.5283
1.870000000 GHz	50.6577	14.5804
1.875000000 GHz	50.6635	14.6333
1.880000000 GHz	50.6993	14.6712
1.885000000 GHz	50.7014	14.7060
1.890000000 GHz	50.7314	14.7520
1.895000000 GHz	50.7549	14.7858
1.900000000 GHz	50.7619	14.8162
1.905000000 GHz	50.7865	14.8418
1.910000000 GHz	50.7979	14.8435
1.915000000 GHz	50.7977	14.8235
1.920000000 GHz	50.7740	14.8207

Muscle

Table 6.2.4 1900 MHz head and muscle tissue dielectric parameters

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 23(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

Title
SubTitle
September 03, 2009 09:20 PM


Title
SubTitle
September 04, 2009 01:50 AM

Frequency	e'	e''	Frequency	e'	e''
2.400000000 GHz	37.7113	13.6915	2.400000000 GHz	50.3098	14.2560
2.405000000 GHz	37.7120	13.6940	2.405000000 GHz	50.2570	14.2760
2.410000000 GHz	37.6907	13.7166	2.410000000 GHz	50.2307	14.2755
2.415000000 GHz	37.6616	13.7155	2.415000000 GHz	50.2163	14.2970
2.420000000 GHz	37.6460	13.7446	2.420000000 GHz	50.2114	14.3110
2.425000000 GHz	37.6263	13.7444	2.425000000 GHz	50.1928	14.3163
2.430000000 GHz	37.5980	13.7537	2.430000000 GHz	50.1886	14.3333
2.435000000 GHz	37.5673	13.7733	2.435000000 GHz	50.2023	14.3470
2.440000000 GHz	37.5508	13.7898	2.440000000 GHz	50.1970	14.3655
2.445000000 GHz	37.5367	13.7854	2.445000000 GHz	50.1913	14.3774
2.450000000 GHz	37.5078	13.7929	2.450000000 GHz	50.1806	14.4027
2.455000000 GHz	37.4895	13.8166	2.455000000 GHz	50.1673	14.3987
2.460000000 GHz	37.4646	13.8319	2.460000000 GHz	50.1195	14.3898
2.465000000 GHz	37.4571	13.8414	2.465000000 GHz	50.0706	14.4005
2.470000000 GHz	37.4233	13.8451	2.470000000 GHz	50.0478	14.4265
2.475000000 GHz	37.3952	13.8688	2.475000000 GHz	50.0366	14.4352
2.480000000 GHz	37.3657	13.8774	2.480000000 GHz	50.0220	14.4408
2.485000000 GHz	37.3504	13.8962	2.485000000 GHz	50.0037	14.4548
2.490000000 GHz	37.3358	13.9091	2.490000000 GHz	49.9764	14.4583
2.495000000 GHz	37.3003	13.9228	2.495000000 GHz	49.9530	14.4824
2.500000000 GHz	37.2737	13.9403	2.500000000 GHz	49.9335	14.4947

Head

Muscle

Table 6.2.5 2450 MHz head and muscle tissue dielectric parameters

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 24(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

7.0 SAR SAFETY LIMITS

Standards/Guideline	Localized SAR Limit (W/kg) General public (uncontrolled)	Localized SAR Limits (W/kg) Workers (controlled)
ICNIRP (1998) Standard	2.0 (10g)	10.0 (10g)
IEEE C95.1 (1999) Standard	1.6 (1g)	8.0 (1g)


Table 7.0.1. SAR safety limits for Controlled / Uncontrolled environment

Human Exposure	Localized SAR Limits (W/kg) 10g, ICNIRP (1998) Standard	Localized SAR Limits (W/kg) 1g, IEEE C95.1 (1999) Standard
Spatial Average (averaged over the whole body)	0.08	0.08
Spatial Peak (averaged over any X g of tissue)	2.00	1.60
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.00	4.00 (10g)

Table 7.0.2. SAR safety limits

Uncontrolled Environments are defined as locations where there is exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW	Page 25(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009
		FCC ID: L6ARCL20CW

8.0 DEVICE POSITIONING

8.1 Device holder for SAM Twin Phantom

The Device was positioned for all test configurations using the DASY4 holder. The device holder facilitates the rotation of the mounted transmitter in spherical coordinates whereby the rotation point is the ear opening. The devices can be easily, accurately and with repeatability positioned according to FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).





Figure 7. Device Holder

1. Put the phone in the clamp mechanism (1) and hold it straight while tightening. (Curved phones or phones with asymmetrical ear pieces should be positioned so that the earpiece is in the symmetry plane of the clamp).
2. Adjust the sliding carriage (2) to 90°. Then adjust the phone holder angle (3) until the reference line of the phone is horizontal (parallel to the flat phantom bottom). The phone reference line is defined as the front tangential line between the earpiece and the center of the device bottom (or the center of the flip hinge). For devices with parallel front and backsides, the phone holder angle (3) is 0°.
3. Place the device holder at the desired phantom section and move it securely against the positioning pins (4). The screw in front of the turning plate can be applied for correct positioning (5). (Do not tighten it too strongly).
4. Shift the phone clamp (6) so that the earpiece is exactly below the ear marking of the phantom. The phone is now correctly positioned in the holder for all standard phantom measurements, even after changing the phantom or phantom section.
5. Adjust the device position angles to the desired measurement position.

	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page	26(38)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Andrew Becker	September 1 - 29, 2009	RTS-2068-0909-43	L6ARCL20CW		

6. After fixing the device angles, move the phone fixture up until the phone touches the ear marking. (The point of contact depends on the design of the device and the positioning angle).

8.2 Description of the test positioning

8.2.1 Test Positions of Device Relative to Head

The handset was tested in two test positions against the head phantom, the “cheek” position and the “tilted” position, on both left and right sides of the phantom.

The handset was tested in the above positions according to IEEE 1528- 2003 “Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques”.




Figure 8.2.1a. Handset vertical and horizontal reference lines – fixed case





Figure 8.2.1b. Handset vertical and horizontal reference lines – “clam-shell”

	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page	27(38)
	Author Data	Dates of Test	Test Report No	FCC ID:	
Andrew Becker	September 1 - 29, 2009	RTS-2068-0909-43	L6ARCL20CW		

8.2.1.1 Definition of the “cheek” position

- 1) Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece, open the cover.
- 2) Define two imaginary lines on the handset: the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A on Figures 8.2.1a and 8.2.1b), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 8.2.1a). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output. However, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 8.2.1b), especially for clamshell handsets, handsets with flip pieces, and other irregularly shaped handsets.
- 3) Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 8.2.1), such that the plane defined by the vertical center line and the horizontal center line is in a plane approximately parallel to the sagittal plane of the phantom.
- 4) Translate the handset towards the phantom along the line passing through RE and LE until the handset touches the ear.
- 5) While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is the plane normal to MB (“mouth-back”) - NF (“neck-front”) including the line MB (reference plane).
- 6) Rotate the phone around the vertical centerline until the phone (horizontal line) is symmetrical with respect to the line NF.
- 7) While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, rotate the handset about the line NF until any point on the handset is in contact with a phantom point below the ear (cheek).





Figure 8.2.2. Phone position 1, “cheek” or “touch” position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning, are indicated. The shoulders are shown for illustration purposes only.

	Document	SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW	
	Page	28(38)	
Author Data	Dates of Test	Test Report No	FCC ID:
Andrew Becker	September 1 - 29, 2009	RTS-2068-0909-43	L6ARCL20CW

8.2.1.2 Definition of the “Tilted” Position

- 1) Repeat steps 1 to 7 of 5.4.1 (in this report 8.2.1.1) to replace the device in the “cheek position.”
- 2) While maintaining the device in the reference plane (described above) and pivoting against the ear, move the device outward away from the mouth by an angle of 15 degrees, or until the antenna touches the phantom.





Figure 8.2.3. Phone position 2, “tilted position.” The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning, are indicated. The shoulders are shown for illustration purposes only.

8.2.2 Body Holster Configuration

Body worn holsters, as shown on Figure 1.4.1, have been test with the device for FCC RF exposure compliance. The EUT was positioned in each holster case and the belt clip was placed against the flat section of the phantom. A headset was then connected to the device to simulate hands-free operation in a body worn holster configuration.

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 29(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

9.0 HIGH LEVEL EVALUATION

9.1 Maximum search

The maximum search is automatically performed after each coarse scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the coarse scan measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations.

9.2 Extrapolation

The extrapolation can be used in z-axis scans with automatic surface detection. The SAR values can be extrapolated to the inner phantom surface. The extrapolation distance is the sum of the probe sensor offset, the surface detection distance and the grid offset. The extrapolation is based on fourth order polynomial functions. The extrapolation is only available for SAR values.


9.3 Boundary correction

The correction of the probe boundary effect in the vicinity of the phantom surface is done in the standard (worst case) evaluation; the boundary effect is reduced by different weights for the lowest measured points in the extrapolation routine. The result is a slight overestimation of the extrapolated SAR values (2% to 8%) depending on the SAR distribution and gradient. The advanced evaluation makes a full compensation of the boundary effect before doing the extrapolation. This is only possible for probes with specifications on the boundary effect.

9.4 Peak search for 1g and 10g cube averaged SAR

The 1g and 10g peak evaluations are only available for the predefined cube 5x5x7 scan. The routines are verified and optimized for the grid dimensions used in these cube measurements.

The measured volume of 30x30x30mm with 7.5mm resolution in (x,y) and 5mm resolution in z axis amounts to 175 measurement points. The first procedure is an extrapolation (incl. Boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume in a 1mm grid. In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is then moved around until the highest averaged SAR is found. This last procedure is repeated for a 10 g cube. If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.


	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 30(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

10.0 MEASUREMENT UNCERTAINTY

DASY4 Uncertainty Budget According to IEEE P1528 [1]								
Error Description	Uncertainty value	Prob. Dist.	Div.	(c_1) 1g	(c_2) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(v_i) v_{eff}
Measurement System								
Probe Calibration	±4.8%	N	1	1	1	±4.8%	±4.8%	∞
Axial Isotropy	±4.7%	R	√3	0.7	0.7	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.6%	R	√3	0.7	0.7	±3.9%	±3.9%	∞
Boundary Effects	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Linearity	±4.7%	R	√3	1	1	±2.7%	±2.7%	∞
System Detection Limits	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Readout Electronics	±1.0%	N	1	1	1	±1.0%	±1.0%	∞
Response Time	±0.8%	R	√3	1	1	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	√3	1	1	±1.5%	±1.5%	∞
RF Ambient Conditions	±3.0%	R	√3	1	1	±1.7%	±1.7%	∞
Probe Positioner	±0.4%	R	√3	1	1	±0.2%	±0.2%	∞
Probe Positioning	±2.9%	R	√3	1	1	±1.7%	±1.7%	∞
Max. SAR Eval.	±1.0%	R	√3	1	1	±0.6%	±0.6%	∞
Test Sample Related								
Device Positioning	±2.9%	N	1	1	1	±2.9%	±2.9%	145
Device Holder	±3.6%	N	1	1	1	±3.6%	±3.6%	5
Power Drift	±5.0%	R	√3	1	1	±2.9%	±2.9%	∞
Phantom and Setup								
Phantom Uncertainty	±4.0%	R	√3	1	1	±2.3%	±2.3%	∞
Liquid Conductivity (target)	±5.0%	R	√3	0.64	0.43	±1.8%	±1.2%	∞
Liquid Conductivity (meas.)	±2.5%	N	1	0.64	0.43	±1.6%	±1.1%	∞
Liquid Permittivity (target)	±5.0%	R	√3	0.6	0.49	±1.7%	±1.4%	∞
Liquid Permittivity (meas.)	±2.5%	N	1	0.6	0.49	±1.5%	±1.2%	∞
Combined Std. Uncertainty						±10.3%	±10.0%	330
Expanded STD Uncertainty						±20.6%	±20.1%	

Table 10.0.1. Worst-Case uncertainty budget for DASY4 assessed according to IEEE P1528.
Source: Schmid & Partner Engineering AG.

[1] The budget is valid for the frequency range 300MHz - 3 GHz and represents a worst-case analysis. For specific tests and configurations, the uncertainty could be considerably smaller.

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 31(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43
		FCC ID: L6ARCL20CW	

11.0 TEST RESULTS

11.1 SAR Measurement results at highest power measured against the head

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Left Head Cheek	CDMA 800 MHz	824.70	24.2	22.2	1.21	-0.01	1.21
		836.52	23.8	22.3	1.01	0.00	1.01
		848.52	23.9	22.1	1.00	-0.05	1.00
Left Head 15° Tilt	CDMA 800 MHz	824.70	24.2	22.3	0.61	-0.06	0.61
		836.52	23.8				
		848.52	23.9				
Right Head Cheek	CDMA 800 MHz	824.70	24.2	22.1	1.09	-0.03	1.09
		836.52	23.8	22.1	0.94	-0.38	1.03
		848.52	23.9	22.0	0.89	-0.05	0.89
Right Head 15° Tilt	CDMA 800 MHz	824.70	24.2	21.9	0.59	0.06	0.59
		836.52	23.8				
		848.52	23.9				


Table 11.1.1. SAR results for CDMA 800 head configuration for Rev 1

* Note: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Left Head Cheek	CDMA 800 MHz	824.70	24.2	22.2	1.26	-0.18	1.26
		836.52	23.8				
		848.52	23.9				
Right Head Cheek	CDMA 800 MHz	824.70	24.2	22.2	1.11	0.08	1.11
		836.52	23.8				
		848.52	23.9				

Table 11.1.2. SAR results for CDMA 800 head configuration for Rev 3


	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 32(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Left Head Cheek	CDMA 1900 MHz	1851.25	23.5	21.2	0.92	-0.10	0.92
		1880.00	23.6	21.2	0.64	0.34	0.64
		1908.50	23.5	21.9	0.48	0.11	0.48
Left Head 15° Tilt	CDMA 1900 MHz	1851.25	23.5	22.1	0.68	0.01	0.68
		1880.00	23.6				
		1908.50	23.5				
Right Head Cheek	CDMA 1900 MHz	1851.25	23.5	22.1	1.26	-0.13	1.26
		1880.00	23.6	21.9	0.94	-0.01	0.94
		1908.50	23.5	21.8	0.59	-0.07	0.59
Right Head 15° Tilt	CDMA 1900 MHz	1851.25	23.5	21.6	0.54	-0.06	0.54
		1880.00	23.6				
		1908.50	23.5				

Table 11.1.3. SAR results for CDMA 1900 head configuration for Rev 1

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Left Head Cheek	CDMA 1900 MHz	1851.25	23.5	22.0	0.86	-0.01	0.86
		1880.00	23.6				
		1908.50	23.5				
Right Head Cheek	CDMA 1900 MHz	1851.25	23.5	22.1	1.31	0.00	1.31
		1880.00	23.6				
		1908.50	23.5				

Table 11.1.4. SAR results for CDMA 1900 head configuration for Rev 3


	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 33(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Left Head Cheek	802.11 b 2450 MHz	2412	17.60	22.6	0.20	0.20	0.20
		2437	18.00	22.5	0.24	-0.13	0.24
		2462	18.05	22.5	0.24	-0.12	0.24
Left Head 15° Tilt	802.11 b 2450 MHz	2412	17.60				
		2437	18.00	22.4	0.35	-0.27	0.37
		2462	18.05				
Right Head Cheek	802.11 b 2450 MHz	2412	17.60	22.3	0.33	-0.22	0.35
		2437	18.00	22.4	0.31	-0.16	0.31
		2462	18.05	22.3	0.33	-0.07	0.33
Right Head 15° Tilt	802.11 b 2450 MHz	2412	17.60				
		2437	18.00	22.5	0.30	-0.06	0.30
		2462	18.05				

Table 11.1.5. Head SAR results for WiFi/WLAN/802.11b head configuration for Rev 1

Test Position	Mode	f (MHz)	Cond. Output Power (dBm)	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
Left Head 15° Tilt	802.11 b 2450 MHz	2412	17.60				
		2437	18.00	22.2	0.40	-0.02	0.40
		2462	18.05				
Right Head Cheek	802.11 b 2450 MHz	2412	17.60	22.1	0.32	0.02	0.32
		2437	18.00				
		2462	18.05				

Table 11.1.6. Head SAR results for WiFi/WLAN/802.11b head configuration for Rev 3

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 34(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

11.2 SAR measurement results at highest power measured against the body using accessories

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
CDMA 800 MHz	824.70	24.2	Vertical Holster, back side facing	22.1	0.47	-0.26	0.50
	836.52	23.8	Vertical Holster, back side facing	21.9	0.32	-0.08	0.32
	848.52	23.9	Vertical Holster, back side facing	22.0	0.33	-0.01	0.33
	824.70	24.2	Horizontal Holster, back side facing	22.3	0.56	-0.20	0.59
	836.52	23.8	Horizontal Holster, back side facing	22.3	0.36	-0.17	0.36
	848.52	23.9	Horizontal Holster, back side facing	22.4	0.37	-0.03	0.37
	824.70	24.2	Horizontal Holster, front side facing	22.4	0.37	-0.21	0.39
	824.70	24.2	Horizontal Holster, back side facing, Headset #1	22.5	0.49	-0.10	0.49
	824.70	24.2	Horizontal Holster, back side facing, Headset #2	22.3	0.48	-0.08	0.48
	824.70	24.2	Horizontal Holster, back side facing, Headset #3	22.3	0.44	0.03	0.44
	824.70	24.2	No Holster, back side 25 mm away	22.4	0.55	-0.11	0.55


Table 11.2.1. SAR results for CDMA 800 body-worn configurations for Rev 1

* Note: If the power drift is ≤ -0.200 dB, the extrapolated SAR is calculated using the formula:

$$\text{Extrapolated SAR} = (\text{Measured SAR}) * 10^{(|\text{Power Drift (dB)}| / 10)}$$

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
CDMA 800 MHz	824.70	24.2	Horizontal Holster, back side facing	22.1	0.57	0.00	0.57

Table 11.2.2. SAR results for CDMA 800 body-worn configurations for Rev 3


	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 35(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
CDMA 1900 MHz	1851.25	23.5	Vertical Holster, back side facing	22.5	0.62	-0.03	0.62
	1880.00	23.6	Vertical Holster, back side facing	22.4	0.66	-0.10	0.66
	1908.50	23.5	Vertical Holster, back side facing	22.2	0.64	-0.18	0.64
	1880.00	23.6	Horizontal Holster, back side facing	22.2	0.57	-0.25	0.60
	1880.00	23.6	Vertical Holster, front side facing	21.9	0.08	-0.13	0.08
	1880.00	23.6	Vertical Holster, back side facing, Headset #1	21.8	0.56	-0.11	0.56
	1880.00	23.6	Vertical Holster, back side facing, Headset #2	21.9	0.57	-0.05	0.57
	1880.00	23.6	Vertical Holster, back side facing, Headset #3	21.8	0.58	0.11	0.58
	1880.00	23.6	No Holster, back side 25 mm away	21.8	0.41	-0.13	0.41

Table 11.2.3. SAR results for CDMA 1900 body-worn configurations for Rev 1

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
CDMA 1900 MHz	1880.00	23.6	Vertical Holster, back side facing	22.0	0.65	0.14	0.65

Table 11.2.4. SAR results for CDMA 1900 body-worn configurations for Rev 3


	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 36(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
802.11b/ WLAN 2450 MHz	2412	17.60	Vertical Holster, back side facing	22.5	0.08	-0.09	0.08
	2437	18.00	Vertical Holster, back side facing	22.5	0.09	-0.18	0.09
	2462	18.05	Vertical Holster, back side facing	22.4	0.08	-0.17	0.08
	2412	17.60	Horizontal Holster, back side facing	22.4	0.22	-0.35	0.24
	2437	18.00	Horizontal Holster, back side facing	22.4	0.26	-0.26	0.28
	2462	18.05	Horizontal Holster, back side facing	22.3	0.19	-0.21	0.20
	2437	18.00	Horizontal Holster, front side facing	22.3	0.03	0.13	0.03
	2437	18.00	Horizontal Holster, back side facing, Headset #1	22.4	0.20	-0.07	0.20
	2437	18.00	Horizontal Holster, back side facing, Headset #2	22.4	0.19	-0.20	0.20
	2437	18.00	Horizontal Holster, back side facing, Headset #3	22.4	0.19	-0.12	0.19
	2437	18.00	No Holster, back side 25 mm away	22.3	0.08	-0.32	0.09

Table 11.2.5: SAR results for WiFi/WLAN/802.11b body-worn configurations for Rev 1


Mode	Freq. (MHz)	Cond. Power (dBm)	Holster type / device configuration	Liquid Temp. (°C)	SAR, averaged over 1 g		
					Measured (W/kg)	Power Drift (dB)	*Extrapolated (W/kg)
802.11b/ WLAN 2450 MHz	2437	18.00	Horizontal Holster, back side facing	22.1	0.29	-0.22	0.30

Table 11.2.6: SAR results for WiFi/WLAN/802.11b body-worn configurations for Rev 3

	Document		Page
	SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		37(38)
Author Data	Dates of Test	Test Report No	FCC ID:
Andrew Becker	September 1 - 29, 2009	RTS-2068-0909-43	L6ARCL20CW

12.0 REFERENCES

- [1] IEEE 1528-2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [2] EN 50360: 2001, Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz – 3 GHz)
- [3] EN 50361: 2001, Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz – 3 GHz)
- [4] ICNIRP, International Commission on Non-Ionizing Radiation Protection (1998), Guidelines for limiting exposure in time-varying electric, magnetic, and electromagnetic fields (up to 300 GHz).
- [5] Council Recommendation 1999/519/EC of July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)
- [6] IEEE C95.3-1991, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave.
- [7] IEEE C95.1-1999, IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.
- [8] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields.
- [9] FCC 96-326, Guidelines for Evaluating the Environmental Effects of Radio-Frequency Radiation.
- [10] DASY 4 DOSIMETRIC ASSESSMENT SYSTEM SOFTWARE MANUAL V4.7 Schmid & Partner Engineering AG, June 2006 which follows draft IEC 62209 – Part 2.
- [11] Health Canada, Safety Code 6, 1999: Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency range from 3 kHz to 300 GHz.
- [12] RSS-102, issue 3-2009: Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada’s Safety Code 6 for Exposure of Humans to Radio Frequency Fields.
- [13] IEC 62209-1, First Edition-2005: Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)
- [14] FCC OET SAR Measurement Requirements for 3 – 6 GHz, October, 2006.
- [15] FCC OET SAR Measurement Procedures for 802.11 a/b/g Transmitters, May, 2007.

	Document SAR Compliance Test Report for the BlackBerry® Smartphone Model RCL21CW		Page 38(38)
	Author Data Andrew Becker	Dates of Test September 1 - 29, 2009	Test Report No RTS-2068-0909-43

[16] FCC OET SAR Evaluation Considerations for Handsets with Multiple Transmitters & Antennas, September, 2008.

[17] FCC OET SAR Test Reduction Procedure for GSM/GPRS/EDGE, December, 2008.

[18] FCC OET SAR Probe Calibration and System Verification Considerations for Measurements at 150 MHz – 3 GHz, January, 2007.

[19] FCC OET RF Exposure Procedures for Mobile and Portable Devices, January, 2009.

[20] FCC OET SAR Measurements Procedures for 3G Devices, October, 2007.