
	Document Appendix A for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 1(5)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09, 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

APPENDIX A: SAR DISTRIBUTION COMPARISON FOR ACCURACY VERIFICATION

	Document Appendix A for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 2(5)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09, 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/13/2010 5:22:01 PM

Test Laboratory: RIM Testing Services

DipoleValidation_835MHz_Amb_Tem_23.2_Liq_Tem_22.4C_08_13_10

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:446

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.858 \text{ mho/m}$; $\epsilon_r = 43.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(6.12, 6.12, 6.12); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (5x5x7)/Cube 0: Measurement

grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 107.1 V/m; Power Drift = -0.047 dB

Peak SAR (extrapolated) = 13.4 W/kg


SAR(1 g) = 9.01 mW/g; SAR(10 g) = 5.9 mW/g


Maximum value of SAR (measured) = 9.76 mW/g


d=15mm, Pin=1000mW/Area Scan (31x121x1): Measurement grid: $dx=15\text{mm}$,

$dy=15\text{mm}$

Maximum value of SAR (interpolated) = 9.66 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 3(5)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09, 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



	Document Appendix A for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 4(5)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09, 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW

Date/Time: 8/12/2010 6:39:04 PM

Test Laboratory: RIM Testing Services

DipoleValidation_1900MHz_Amb_Tem_22.8_Liq_Tem_22.2_C_08_12_1 0

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:545


Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1900$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 38.6$; $\rho = 1000$ kg/m³
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(5.14, 5.14, 5.14); Calibrated: 12/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/4/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm
Reference Value = 185.1 V/m; Power Drift = -0.019 dB
Peak SAR (extrapolated) = 80.9 W/kg
SAR(1 g) = 43.4 mW/g; SAR(10 g) = 22.3 mW/g
Maximum value of SAR (measured) = 49.1 mW/g

d=15mm, Pin=1000mW/Area Scan (31x61x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 49.6 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RCL22CW SAR Report			Page 5(5)
	Author Data Andrew Becker	Dates of Test August 13, Sep 09, 2010	Test Report No RTS-2068-1008-53	FCC ID: L6ARCL20CW



0 dB = 49.6mW/g